Contents

1	cipher Theory	3
	1.1 Datatypes	3
	1.2 Definitions	3
	1.3 Theorems	3
2	cryptoExercises Theory	6
	2.1 Theorems	6

1 cipher Theory

Built: 01 November 2017

Parent Theories: indexedLists, patternMatches

1.1 Datatypes

```
asymMsg = Ea ('princ pKey) ('message option) 
 digest = hash ('message option) 
 pKey = pubK 'princ | privK 'princ 
 symKey = sym num 
 symMsg = Es symKey ('message option)
```

1.2 Definitions

1.3 Theorems

```
[asymMsg_one_one]
       (Ea a_0 a_1 = Ea a_0' a_1') \iff (a_0 = a_0') \land (a_1 = a_1')
[deciphP_clauses]
 \vdash (\forall P \ text.
        (deciphP (pubK P) (Ea (privK P) (SOME text)) =
         SOME text) \wedge
        (deciphP (privK P) (Ea (pubK P) (SOME text)) =
         SOME text)) \wedge
    (\forall k \ P \ text.
        (deciphP \ k \ (Ea \ (privK \ P) \ (SOME \ text)) = SOME \ text) \iff
        (k = pubK P)) \land
    (\forall k \ P \ text.
        (deciphP \ k \ (Ea \ (pubK \ P) \ (SOME \ text)) = SOME \ text) \iff
        (k = privK P)) \land
    (\forall x \ k_2 \ k_1 \ P_2 \ P_1.
        (deciphP (pubK P_1) (Ea (pubK P_2) (SOME x)) = NONE) \wedge
        (deciphP k_1 (Ea k_2 NONE) = NONE)) \wedge
    \forall x \ P_2 \ P_1. deciphP (privK P_1) (Ea (privK P_2) (SOME x)) = NONE
```

CIPHER THEORY Theorems

```
[deciphP_def]
 \vdash (deciphP key (Ea (privK P) (SOME x)) =
     if key = pubK P then SOME x else NONE) \wedge
    (deciphP \ key \ (Ea \ (pubK \ P) \ (SOME \ x)) =
     if key = privK P then SOME x else NONE) \wedge
     (deciphP k_1 (Ea k_2 NONE) = NONE)
[deciphP_ind]
 \vdash \forall P'.
       (\forall key \ P \ x. \ P' \ key \ (\texttt{Ea} \ (\texttt{privK} \ P) \ (\texttt{SOME} \ x))) \ \land
       (\forall key \ P \ x. \ P' \ key \ (Ea \ (pubK \ P) \ (SOME \ x))) \ \land
       (\forall k_1 \ k_2. \ P' \ k_1 \ (\texttt{Ea} \ k_2 \ \texttt{NONE})) \Rightarrow
       \forall v \ v_1 . P' \ v \ v_1
[deciphP_one_one]
 \vdash (\forall P_1 \ P_2 \ text_1 \ text_2.
        (deciphP (pubK P_1) (Ea (privK P_2) (SOME text_2)) =
         SOME text_1) \iff (P_1 = P_2) \land (text_1 = text_2)) \land
     (\forall P_1 \ P_2 \ text_1 \ text_2.
        (deciphP (privK P_1) (Ea (pubK P_2) (SOME text_2)) =
         SOME text_1) \iff (P_1 = P_2) \land (text_1 = text_2)) \land
     (\forall p \ c \ P \ msg.
        (deciphP (pubK P) (Ea p c) = SOME msg) \iff
         (p = privK P) \land (c = SOME msg)) \land
     (\forall enMsg \ P \ msg.
        (deciphP (pubK P) enMsg = SOME msg) \iff
        (enMsg = Ea (privK P) (SOME msg))) \land
     (\forall p \ c \ P \ msg.
        (deciphP (privK P) (Ea p c) = SOME msg) \iff
        (p = \text{pubK } P) \land (c = \text{SOME } msg)) \land
    \forall enMsg \ P \ msg.
       (deciphP (privK P) enMsq = SOME \ msq) \iff
       (enMsg = Ea (pubK P) (SOME msg))
[deciphS_clauses]
 \vdash (\forall k \ text. \ deciphS \ k (Es k (SOME text)) = SOME text) \land
    (\forall k_1 \ k_2 \ text.
        (deciphS k_1 (Es k_2 (SOME text)) = SOME text) \iff
        (k_1 = k_2)) \wedge
     (\forall k_1 \ k_2 \ text.
        (deciphS k_1 (Es k_2 (SOME text)) = NONE) \iff k_1 \neq k_2) \land
    \forall k_1 \ k_2. deciphS k_1 (Es k_2 NONE) = NONE
[deciphS_def]
 \vdash (deciphS k_1 (Es k_2 (SOME x)) =
     if k_1 = k_2 then SOME x else NONE) \wedge
     (deciphS k_1 (Es k_2 NONE) = NONE)
```

Theorems CIPHER THEORY

```
[deciphS_ind]
 \vdash \forall P.
        (\forall k_1 \ k_2 \ x. \ P \ k_1 \ (\texttt{Es} \ k_2 \ (\texttt{SOME} \ x))) \ \land
        (\forall k_1 \ k_2. \ P \ k_1 \ (\texttt{Es} \ k_2 \ \texttt{NONE})) \Rightarrow
       \forall v \ v_1 . \ P \ v \ v_1
[deciphS_one_one]
  \vdash (\forall k_1 \ k_2 \ text_1 \ text_2.
         (deciphS k_1 (Es k_2 (SOME text_2)) = SOME text_1) \iff
         (k_1 = k_2) \wedge (text_1 = text_2)) \wedge
     \forall enMsg text key.
        (deciphS key\ enMsg = SOME text) \iff
        (enMsg = Es \ key \ (SOME \ text))
[digest_one_one]
 \vdash \forall a \ a'. (hash a = \text{hash } a') \iff (a = a')
[option_distinct]
 \vdash \forall x. NONE \neq SOME x
[option_one_one]
 \vdash \forall x \ y. (SOME x = SOME \ y) \iff (x = y)
[pKey_distinct_clauses]
 \vdash (\forall a' \ a. pubK a \neq \text{privK } a') \land \forall a' \ a. privK a' \neq \text{pubK } a
[pKey_one_one]
 \vdash (\forall a \ a'. (pubK a = pubK a') \iff (a = a')) \land
    \forall a \ a'. (privK a = \text{privK } a') \iff (a = a')
[sign_one_one]
 \vdash \forall pubKey_1 \ pubKey_2 \ m_1 \ m_2.
        (sign pubKey_1 (hash m_1) = sign pubKey_2 (hash m_2)) \iff
        (pubKey_1 = pubKey_2) \land (m_1 = m_2)
[signVerify_one_one]
 \vdash (\forall P m_1 m_2.
         signVerify (pubK P) (Ea (privK P) (SOME (hash (SOME m_1))))
            (SOME m_2) \iff (m_1 = m_2)) \land
     (\forall signature \ P \ text.
         signVerify (pubK P) signature (SOME text) \iff
         (signature = sign (privK P) (hash (SOME text)))) <math>\land
    \forall text_2 text_1 P_2 P_1.
       signVerify (pubK P_1) (sign (privK P_2) (hash (SOME text_2)))
          (SOME text_1) \iff (P_1 = P_2) \land (text_1 = text_2)
```

```
 [\operatorname{signVerifyOK}] \\ \vdash \forall P \ msg. \\ \operatorname{signVerify} \ (\operatorname{pubK} \ P) \ (\operatorname{sign} \ (\operatorname{privK} \ P) \ (\operatorname{hash} \ (\operatorname{SOME} \ msg))) \\ \operatorname{(SOME} \ msg) \\ [\operatorname{symKey\_one\_one}] \\ \vdash \forall a \ a'. \ (\operatorname{sym} \ a = \operatorname{sym} \ a') \iff (a = a') \\ [\operatorname{symMsg\_one\_one}] \\ \vdash \forall a_0 \ a_1 \ a'_0 \ a'_1. \\ \operatorname{(Es} \ a_0 \ a_1 = \operatorname{Es} \ a'_0 \ a'_1) \iff (a_0 = a'_0) \ \land \ (a_1 = a'_1) \\ \end{aligned}
```

2 cryptoExercises Theory

Built: 01 November 2017

Parent Theories: cipher, string

2.1 Theorems

```
[exercise15_6_1a_thm]
 \vdash \forall key \ enMsq \ message.
      (deciphS key \ enMsg = SOME \ message) \iff
      (enMsg = Es \ key \ (SOME \ message))
[exercise15_6_1b_thm]
 \vdash \forall keyAlice \ k \ text.
      (deciphS \ keyAlice \ (Es \ k \ (SOME \ text)) =
       SOME "This is from Alice") \iff
      (k = keyAlice) \land (text = "This is from Alice")
exercise15_6_2a_thm
 \vdash \forall P \; message.
      (deciphP (pubK P) enMsg = SOME message) \iff
      (enMsg = Ea (privK P) (SOME message))
[exercise15_6_2b_thm]
 \vdash \forall key text.
      (deciphP (pubK Alice) (Ea key (SOME text)) =
       SOME "This is from Alice") \iff
      (key = privK Alice) \land (text = "This is from Alice")
[exercise15_6_3_thm]
 \vdash \forall signature.
      signVerify (pubK Alice) signature
        (SOME "This is from Alice") ←⇒
      (signature =
       sign (privK Alice) (hash (SOME "This is from Alice")))
```

Index

```
cipher Theory, 3
    Datatypes, 3
    Definitions, 3
      sign_def, 3
      signVerify_def, 3
    Theorems, 3
      asymMsg_one_one, 3
      deciphP_clauses, 3
      deciphP_def, 4
      deciphP_ind, 4
      deciphP_one_one, 4
      deciphS_clauses, 4
      deciphS_def, 4
      deciphS_{ind}, 5
      deciphS_one_one, 5
      digest_one_one, 5
      option_distinct, 5
      option_one_one, 5
      pKey_distinct_clauses, 5
      pKey_one_one, 5
      sign_one_one, 5
      signVerify\_one\_one, 5
      signVerifyOK, 6
      symKey_one_one, 6
      symMsg_one_one, 6
cryptoExercises Theory, 6
    Theorems, 6
      exercise15_6_1a_thm, 6
      exercise15_6_1b_thm, 6
      exercise15_6_2a_thm, 6
      exercise15_6_2b_thm, 6
      exercise15_6_3_thm, 6
```