

WR502 5-Inch Dynamic Face Recognition Attendance Terminal

The WR502 binocular face-recognition terminal uses high-definition face-recognition cameras and adapts to demanding lighting conditions, including strong light and low light. It offers fast recognition, high accuracy, and a large user database.

It can be integrated with real-name construction-site management, face-based access and attendance management, visitor management, and other application systems. The WR502 is suitable for communities, campuses, hospitals, scenic areas, hotels, shopping malls, corporate offices, public service locations, construction sites, and other environments that require temperature screening, identity recognition, and access control.

Accurate recognition

Fast face verification

Remote door opening

Binocular liveness detection

5-inch wide-view touch screen

Standalone attendance management



Designed for daily access, attendance, and secure entry



Scenic area entrances



Construction sites and factories



Industrial park commuting and attendance



Campus entrances



Office building access control



Visitor management and access verification

Product Features



Accurate



Fast

- 5-inch IPS wide-view LCD touch screen
- Remote upgrade via web portal and local USB flash-drive upgrade
- Supports a 5,000-person face database with recognition accuracy above 99.99%
- Face recognition pass-through speed under 1 second
- Stores 100,000 local face-recognition attendance records; up to 1,000,000 records without images



Remote



Liveness

- API integration documentation available for customized development
- Convenient entry for unregistered visitors, improving user experience while maintaining security
- Built-in smart doorbell for easier communication and notifications
- Standalone attendance recording and management without an external network or server



Specifications

Camera

Resolution	Dual 1 MP
Type	Binocular camera
Aperture	F2.2
Focus distance	50-150 cm
White balance	Automatic
Supplementary light	LED and infrared dual fill lights

Configuration

CPU	Single-core CPU
NPU	1.0 TOPS
Operating system	Linux
Storage	EMMC 8G
Network module	Ethernet, wireless Wi-Fi, 4G network optional
Audio	2 W / 8 Ohm speaker
Card reader	IC/ID card reader optional

General Parameters

Power supply	12 V 2 A
Operating temperature	-10 C to 60 C
Storage temperature	-20 C to 70 C
Power consumption	10 W max.
Installation	Wall-mounted
Protection rating	IP54
Device dimensions	175 x 83 x 15 mm

Display

Size	5.0-inch IPS LCD
Resolution	480 x 854
Touch	Supported

System Functions

Face database	5,000 users
Password capacity	5,000 passwords
1:N face recognition	Supported
Liveness detection	Supported
Stranger detection	Supported
Recognition distance	50-150 cm
Recognition speed	< 1 second
Recognition accuracy	99.99%
UI configuration	Supported
Remote device upgrade	Supported
API interface	Device management; personnel/photo management; communication records; system settings
Deployment	Public cloud, private deployment, LAN or standalone use