

MULTI-SCALE DEFECT DETECTION NETWORK FOR TIRE X-RAY IMAGES

Ren Wang^{1,2}, Qiang Guo^{1,2}, Caiming Zhang³

¹School of Computer Science and Technology,
Shandong University of Finance and Economics, Jinan, China

²Shandong Provincial Key Laboratory of Digital Media Technology, Jinan, China

³Software College, Shandong University, Jinan, China

ABSTRACT

Though automatic detection method has been tremendous improved, with the development of deep learning. Defect detection in many industrial processes is one of the remaining challenging tasks due to the diversity of products. In this work, we focus on detection tasks in tire industry and develop a *Multi-scale Defect Detection Network (MDDN)*, which contains two parallel sub-networks to capture multi-scale defect features. Specifically, high-abstracted semantic features containing defect shapes and locations are mined via a *Semantic-aware sub-network*, simplified by an off-the-shelf fully convolutional network. Furthermore, to complement the details filtered by the deep network, a novel *Texture-aware Sub-network* is used to cover edge features and small defects as much as possible. Finally, pixel-wised detection results are obtained by fusing features with semantic and texture information. Extensive experiments demonstrate that *MDDN* can produce comparable results and achieve significantly performance improvement in small defects detection.

Index Terms— Defect detection, Fully convolutional network, Semantic segmentation, Multi-scale context

1. INTRODUCTION

Automatic defect detection, used to improve quality and accelerate production, has become an indispensable part in industrial processes [1, 2, 3]. Especially in tire manufacturing, numerous detection algorithms have been proposed [4, 5, 6] and aroused extensive attention recently. In most real-world applications, tire defect detection is first carried out by deriving the defective region from tire X-ray images, which contains various types of defects caused by unclean raw materials and undesired manufacturing facilities [7]. Then, the defective product is hierarchical processed according to the location and area of defects. Due to unique properties of the tire image, for instance complexity and low-quality, illustrated in previous study [8, 9], most inspection processes are performed by human observers, which increases the risk and reduces the efficiency. Therefore, tire defect detection remains one of the most challenging inspection tasks.




Fig. 1. (a) shows the image pyramids. (b) indicates in-network feature hierarchies. Prediction results can be derived from each layer. (c) represents multi-size tire image patches, which can increase the relative scale of small defects and backgrounds. (d) illustrates that the semantic information is more easily retained in tire image patches by comparison.

At present, existing computer vision based detection methods are mostly devoted to distinguishing difference between defective regions and background (defective-free regions). A key issue for such methods is feature extraction. Guo *et al.* [10] proposed a component decomposition based method to detect tire defects, which separated the background from the image by means of two designed filters. Then through an adaptive thresholding processing, defects were derived from the residual image. Besides, Independent component analysis was also used for defect detection tasks [11, 12]. A major disadvantage of these fundamental methods is the limitation of the information contained in low-level clues and domain features. To address the limitation, Zhang *et al.* [8, 13] introduced multi-scale wavelet and curvelet transform, in detection tasks respectively. Furthermore, optimized edge detection and total variation algorithm are used to achieve more accurate results [14]. However, the repre-

This is the ablation experiment.This is the ablation experi-
ment.This is the ablation experiment.This is the ablation ex-
periment.This is the ablation experiment. This is the ablation
experiment.This is the ablation experiment.This is the abla-
tion experiment.This is the ablation experiment.This is the

5. REFERENCES

- [1] A. Kumar, "Computer-vision-based fabric defect detection: A survey," *IEEE Trans. on Industrial Electronics*, vol. 55, no. 1, pp. 348–363, 2008.
- [2] Y. Li, W. Zhao, and J. Pan, "Deformable patterned fabric defect detection with fisher criterion-based deep learning," *IEEE Trans. on Automation Science and Engineering*, vol. 14, no. 2, pp. 1256–1264, 2016.
- [3] S. Ghorai, A. Mukherjee, M. Gangadaran, and P. K. Dutta, "Automatic defect detection on hot-rolled flat steel products," *IEEE Trans. on Instrumentation and Measurement*, vol. 62, no. 3, pp. 612–621, 2012.
- [4] C. Zhang, X. Li, Q. Guo, X. Yu, and C. Zhang, "Texture-invariant detection method for tire crack," *Journal of Computer-Aided Design & Computer Graphics*, vol. 25, no. 6, pp. 809–816, 2013.
- [5] Y. Zhang, X. Cui, Y. Liu, and B. Yu, "Tire defects classification using convolution architecture for fast feature embedding," *International Journal of Computational Intelligence Systems*, vol. 11, no. 1, pp. 1056–1066, 2018.
- [6] C.D. Jones, A.B. Smith, and E.F. Roberts, "A dictionary-based method for tire defect detection," in *ICIA*. IEEE, 2014, pp. 519–523.
- [7] Q. Guo, C. Zhang, H. Liu, and X. Zhang, "Defect detection in tire x-ray images using weighted texture dissimilarity," *Journal of Sensors*, vol. 2016, 2016.
- [8] Y. Zhang, T. Li, and Q. Li, "Defect detection for tire laser shearography image using curvelet transform based edge detector," *Optics & Laser Technology*, vol. 47, pp. 64–71, 2013.
- [9] R. Wang, Q. Guo, S. Lu, and C. Zhang, "Tire defect detection using fully convolutional network," *IEEE Access*, vol. 7, pp. 43502–43510, 2019.
- [10] Q. Guo and Z. W. Wei, "Tire defect detection using image component decomposition," *Research Journal of Applied Sciences, Engineering and Technology*, vol. 4, no. 1, pp. 41–44, 2012.
- [11] X. Cui, Y. Liu, and C. Wang, "Defect automatic detection for tire x-ray images using inverse transformation of principal component residual," in *AIPR*. IEEE, 2016, pp. 1–8.
- [12] X. H. Cui, Y. Liu, C. X. Wang, and H. Li, "A novel method for feature extraction and automatic recognition of tire defects using independent component analysis," *DEStech Transactions on Materials Science and Engineering*, no. icimm, 2016.
- [13] Y. Zhang, D. Lefebvre, and Q. Li, "Automatic detection of defects in tire radiographic images," *IEEE Trans. on Automation Science and Engineering*, vol. 14, no. 3, pp. 1378–1386, 2015.
- [14] Z. Yan, L. Tao, and L. Qing-Ling, "Detection of foreign bodies and bubble defects in tire radiography images based on total variation and edge detection," *Chinese Physics Letters*, vol. 30, no. 8, pp. 084205, 2013.
- [15] X. Cui, Y. Liu, Y. Zhang, and C. Wang, "Tire defects classification with multi-contrast convolutional neural networks," *International Journal of Pattern Recognition and Artificial Intelligence*, vol. 32, no. 04, pp. 1850011, 2018.
- [16] J. Long, E. Shelhamer, and T. Darrell, "Fully convolutional networks for semantic segmentation," in *CVPR*, 2015, pp. 3431–3440.
- [17] D. G. Lowe, "Distinctive image features from scale-invariant keypoints," *IJCV*, vol. 60, pp. 91–110, 2004.
- [18] N. Dalal and B. Triggs, "Histograms of oriented gradients for human detection," in *CVPR*, 2005.
- [19] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *CVPR*, 2016, pp. 770–778.
- [20] T. Y. Lin, P. Dollr, R. Girshick, K. He, B. Hariharan, and S. Belongie, "Feature pyramid networks for object detection," in *CVPR*, 2017, pp. 2117–2125.
- [21] W. Liu, D. Anguelov, D. Erhan, C. Szegedy, S. Reed, C. Y. Fu, and A. C. Berg, "Ssd: Single shot multibox detector," in *ECCV*. Springer, 2016, pp. 21–37.
- [22] A. Newell, K. Yang, and J. Deng, "Stacked hourglass networks for human pose estimation," in *ECCV*. Springer, 2016, pp. 483–499.
- [23] G. Ghiasi and C. C. Fowlkes, "Laplacian pyramid reconstruction and refinement for semantic segmentation," in *ECCV*. Springer, 2016, pp. 519–534.
- [24] P. Zhou, B. Ni, C. Geng, J. Hu, and Y. Xu, "Scale-transferrable object detection," in *CVPR*, 2018, pp. 528–537.
- [25] Y. Bai, Y. Zhang, M. Ding, and B. Ghanem, "Sodmtgan: Small object detection via multi-task generative adversarial network," in *ECCV*, 2018, pp. 206–221.
- [26] L. C. Chen, Y. Yang, J. Wang, W. Xu, and A. L. Yuille, "Attention to scale: Scale-aware semantic image segmentation," in *CVPR*, 2016, pp. 3640–3649.