





G-2RB

Performance curve for Vacuum pump



2RB 920

Performance curve for Compressor



The performance curves are based on air at a temperature of 15 °C and an atmospheric pressure of 1013 mbar with a tolerance of +/- 10 %. The total pressure differences are valid for suction and ambient temperatures up to 25 °C. For other conditions please confer with us.

Each G-2RB type can be applied both as vacuum pump and compressor in continuous operation over the total stated performance curve range. The motors are available as standard for the input voltage range of 50 and 60 Hz and for protection category IP 55 as well as approbated for UL and CSA.

Selection and ordering data

Type 2RB920

Curve No.	Order No.	Fre- quency	Rated power	Input voltage	Input current	Permissible total differential pressure ²⁾		Sound pressure level ³⁾	Weight ca.
		Hz	kW	V	A	Vacuum mbar	Compressor mbar	dB(A)	kg

3~ 50/60 Hz IP55 isolation material class F 1)

A 390	2RB920-7HH17	50	12.5	345D ... 415D	600Y...720Y	28.0D	16.2Y	-300	270	74	187
A 391	2RB920-7HH17	60	14.5	380D ... 480D	660Y...720Y	29.0D	16.7Y	-220	200	84	187
A 392	2RB920-7HH27	50	16.5	345D ... 415D	600Y...720Y	35.0D	20.0Y	-410	370	74	197
A 393	2RB920-7HH27	60	19.0	380D ... 480D	660Y...720Y	36.5D	21.0Y	-340	300	84	197
A 394	2RB920-7HH37	50	20.0	345D ... 415D	600Y...720Y	40.0D	23.0Y	-440	500	74	204
A 395	2RB920-7HH37	60	23.0	380D ... 480D	660Y...720Y	42.0D	24.2Y	-440	430	84	204
A 396	2RB920-7HH47	50	25.0	345D ... 415D	600Y...720Y	52.0D	30.0Y	-440	590	74	211
A 397	2RB920-7HH47	60	29.0	380D ... 480D	660Y...720Y	52.0D	30.0Y	-440	540	84	211



Other voltage ranges

2RB 920-7HH □.□

50Hz

60Hz



3~

185...225 V D/320...390 V Y

200...240 V D/345...415 V Y

345...415 V D

200...240 V D/345...415 V Y

200...275 V D/380...480 V Y

380...480 V D

H 1

H 6

H 7

500 V D

575VD

C 5

Machines according to the ATEX norm 94/4 EG are available for the whole performance range.

Following types available: Category 3 G, 3/2 G, 3 D and 3/2 D.

1~

100 / 200 V

115 / 230 V

100 / 200 V

115 / 230 V

V 4

V 5

230V

230V

A 1

Further voltage range on request; please quote in plain text.

All G-2RB achieve the standards and norms of the low voltage directive (LVD)2006/95/EC, rotating electrotechnical motor EN 60034-1-2004, electromagnetic compatibility(EMC)EN55014-1/2,EN61000-2/-3/-4/-6.

- 1) For standard UL for ELECTRIC MOTOR UL 1004-1.
- 2) Relief-valve are available for limiting differential pressure.
- 3) Measuring-surface sound-pressure level acc. to DIN EN 21680, measured at a distance of 1 m. The pump is throttled to an average suction pressure, a hose is connected to the discharge side (compressor) / suction side (vacuum pump), but is not fitted with relief valves.

The motors are designed according to the DIN EN 60 034 / DIN IEC 34-1 and temperature class F.

For the three phase machines the tolerances are +/- 10 % for fixed voltage and +/- 5 % for voltage range.

The single phase machines are designed with a +/- 5 % tolerances. If only 90 % of the maximum allowed pressure will be used for the continuous operating then the allowed voltage range add to +/- 10 %.

For all single and three phase machines which designed according to the UL and CSA norm (UL 1004-1) the maximum allowed voltage tolerances are - 10 % resp. + 6 %.

The frequency tolerance is maximum +/- 2 %.

Changes in particular the quoted performance curve, datas and weights without prior notice. The figures are without obligations.

ZHEJIANG GREENCO INDUSTRY CO.,LTD

Add:danya industrial zone.zeguo.wenling zhejiang China

P.C:317523

Tel:0086-576-86428999

Fax:0086-576-86409555

E-mail:greenco@greenco.cn

Http://www.greenco.cn