

Cryptology

Sabyasachi Karati

Assistant Professor
Cryptology and Security Research Unit (C.S.R.U)
R. C. Bose Centre for Cryptology and Security
Indian Statistical Institute (ISI)
Kolkata, India





Lecture 13

Digital Signatures



Introduction

- Achieved private communication in the public-key setting.



Introduction

- Achieved private communication in the public-key setting.
- Q. How can we preserve message integrity?



Introduction

- Achieved private communication in the public-key setting.
- Q. How can we preserve message integrity?
- The public-key counterpart of MACs are digital signatures.



Introduction

- Achieved private communication in the public-key setting.
- Q. How can we preserve message integrity?
- The public-key counterpart of MACs are digital signatures.
- Signer uses secret key sk to create a signature σ on a message m .



Introduction

- Achieved private communication in the public-key setting.
- Q. How can we preserve message integrity?
- The public-key counterpart of MACs are digital signatures.
- Signer uses secret key sk to create a signature σ on a message m .
- Verifier uses signer's public key pk to verify the signature σ on a message m .



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.



- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.
 - However, there is no public directory.



- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.
 - However, there is no public directory.
 1. Alice creates (sk, pk) .



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.
 - However, there is no public directory.
 1. Alice creates (sk, pk) .
 2. Sends pk to Certificate Authority (CA) whose pk_{CA} is known to everyone.



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.
 - However, there is no public directory.
 1. Alice creates (sk, pk) .
 2. Sends pk to Certificate Authority (CA) whose pk_{CA} is known to everyone.
 3. CA signs the message $m = "pk \text{ is public key of Alice}"$ and creates certificate $Cert := (m, \sigma_{CA})$.



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.
 - However, there is no public directory.
 1. Alice creates (sk, pk) .
 2. Sends pk to Certificate Authority (CA) whose pk_{CA} is known to everyone.
 3. CA signs the message $m = "pk \text{ is public key of Alice}"$ and creates certificate $Cert := (m, \sigma_{CA})$.
 4. CA Sends $Cert$ to Alice, and Alice can share $Cert$ with anyone.



Introduction

- Software Patch Release:
 - Company generates a key pair (sk, pk) and publishes pk .
 - Signs the patch m using sk , let the signature be σ .
 - Client can verify the patch's (i) integrity and (ii) source authentication by verifying the σ using Company's public key pk .
- Digital Certificate:
 - Assumption: public keys are obtained from a read-only public directory.
 - However, there is no public directory.
 1. Alice creates (sk, pk) .
 2. Sends pk to Certificate Authority (CA) whose pk_{CA} is known to everyone.
 3. CA signs the message $m = "pk \text{ is public key of Alice}"$ and creates certificate $Cert := (m, \sigma_{CA})$.
 4. CA Sends $Cert$ to Alice, and Alice can share $Cert$ with anyone.
 5. Anyone including Alice can verify the $Cert$.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.
- Non-repudiation.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.
- Non-repudiation.
 - Assuming a signer S widely publicizes his public key in the first place.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.
- Non-repudiation.
 - Assuming a signer S widely publicizes his public key in the first place.
 - S signs a message he cannot later deny having done so.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.
- Non-repudiation.
 - Assuming a signer S widely publicizes his public key in the first place.
 - S signs a message he cannot later deny having done so.
 - Can not be achieved by MAC.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.
- Non-repudiation.
 - Assuming a signer S widely publicizes his public key in the first place.
 - S signs a message he cannot later deny having done so.
 - Can not be achieved by MAC.
 - MAC key is private.



Digital Signature Vs. MAC

- Digital Signature is Publicly verifiable.
 - Let (m, σ) be a message-signature pair.
 - If it is a valid one, then it does not matter who verifies it.
 - Can not be achieved by MAC.
 - Signer share different key's with different receivers.
 - Therefore, One can verify the MAC specific to him, but can not guarantee for a MAC received by others.
- Public verifiability implies that signatures are transferable.
- Non-repudiation.
 - Assuming a signer S widely publicizes his public key in the first place.
 - S signs a message he cannot later deny having done so.
 - Can not be achieved by MAC.
 - MAC key is private.
 - Even if verifier provides MAC key, there is no way to prove that is the key.



Digital Signature

Definition

A signature scheme $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$ is a triple of efficient algorithms, \mathcal{G} , \mathcal{S} and \mathcal{V} , where \mathcal{G} is called a **key generation algorithm**, \mathcal{S} is called a **signing algorithm**, and \mathcal{V} is called a **verification algorithm**. Algorithm \mathcal{S} is used to generate signatures and algorithm \mathcal{V} is used to verify signatures.



Definition

A signature scheme $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$ is a triple of efficient algorithms, \mathcal{G} , \mathcal{S} and \mathcal{V} , where \mathcal{G} is called a **key generation algorithm**, \mathcal{S} is called a **signing algorithm**, and \mathcal{V} is called a **verification algorithm**. Algorithm \mathcal{S} is used to generate signatures and algorithm \mathcal{V} is used to verify signatures.

- \mathcal{G} is a **probabilistic poly-time** algorithm that takes no input. It outputs a pair (sk, pk) , where sk is called a **secret signing key** and pk is called a **public verification key**.



Digital Signature

Definition

A signature scheme $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$ is a triple of efficient algorithms, \mathcal{G} , \mathcal{S} and \mathcal{V} , where \mathcal{G} is called a **key generation algorithm**, \mathcal{S} is called a **signing algorithm**, and \mathcal{V} is called a **verification algorithm**. Algorithm \mathcal{S} is used to generate signatures and algorithm \mathcal{V} is used to verify signatures.

- \mathcal{G} is a **probabilistic poly-time** algorithm that takes no input. It outputs a pair (sk, pk) , where sk is called a **secret signing key** and pk is called a **public verification key**.
- \mathcal{S} is a **probabilistic poly-time** algorithm that is invoked as $\sigma \xleftarrow{R} \mathcal{S}(sk, m)$, where sk is a secret key (as output by \mathcal{G}) and m is a message. The algorithm **outputs a signature** σ .



Digital Signature

Definition

A signature scheme $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$ is a triple of efficient algorithms, \mathcal{G} , \mathcal{S} and \mathcal{V} , where \mathcal{G} is called a **key generation algorithm**, \mathcal{S} is called a **signing algorithm**, and \mathcal{V} is called a **verification algorithm**. Algorithm \mathcal{S} is used to generate signatures and algorithm \mathcal{V} is used to verify signatures.

- \mathcal{G} is a **probabilistic poly-time** algorithm that takes no input. It outputs a pair (sk, pk) , where sk is called a **secret signing key** and pk is called a **public verification key**.
- \mathcal{S} is a **probabilistic poly-time** algorithm that is invoked as $\sigma \xleftarrow{R} \mathcal{S}(sk, m)$, where sk is a secret key (as output by \mathcal{G}) and m is a message. The algorithm **outputs a signature**.
- \mathcal{V} is a **deterministic poly-time algorithm** invoked as $\mathcal{V}(pk, m, \sigma)$. It outputs either **accept or reject**.



Definition (Cont.)

- We require that a signature generated by \mathcal{S} is always accepted by \mathcal{V} . That is, for **all** (sk, pk) output by \mathcal{G} and **all messages** m , we have

$$\Pr[V(pk, m, S(sk, m)) = \text{accept}] = 1.$$



Definition (Cont.)


- We require that a signature generated by \mathcal{S} is always accepted by \mathcal{V} . That is, for **all** (sk, pk) output by \mathcal{G} and **all messages** m , we have

$$\Pr[V(pk, m, S(sk, m)) = \text{accept}] = 1.$$

- Messages lie in a finite **message space** \mathcal{M} , and signatures lie in some finite signature space Σ . We say that $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$ is defined over (\mathcal{M}, Σ) .



Introduction





Existentially Unforgeable under a Chosen Message Attack

A given MAC system $\mathcal{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$, defined over (\mathcal{M}, Σ) , and a given **adversary** \mathcal{A} , the attack game runs as follows:



Existentially Unforgeable under a Chosen Message Attack

A given MAC system $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$, defined over (\mathcal{M}, Σ) , and a given adversary \mathcal{A} , the attack game runs as follows:

1. The challenger runs $(sk, pk) \xleftarrow{R} \mathcal{G}$, and sends pk to adversary.



Existentially Unforgeable under a Chosen Message Attack

A given MAC system $\mathfrak{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$, defined over (\mathcal{M}, Σ) , and a given adversary \mathcal{A} , the attack game runs as follows:

1. The challenger runs $(sk, pk) \xleftarrow{R} \mathcal{G}$, and sends pk to adversary.
2. \mathcal{A} queries the challenger several times. For $i = 1, 2, \dots$, the i -th signing query is a message $m_i \in \mathcal{M}$. Given m_i , the challenger computes a signature $\sigma_i \xleftarrow{R} \mathcal{S}(sk, m_i)$, and then gives σ_i to \mathcal{A} .



Security of Digital Signature


Existentially Unforgeable under a Chosen Message Attack

A given MAC system $\mathcal{S} = (\mathcal{G}, \mathcal{S}, \mathcal{V})$, defined over (\mathcal{M}, Σ) , and a given adversary \mathcal{A} , the attack game runs as follows:

1. The challenger runs $(sk, pk) \xleftarrow{R} \mathcal{G}$, and sends pk to adversary.
2. \mathcal{A} queries the challenger several times. For $i = 1, 2, \dots$, the i -th signing query is a message $m_i \in \mathcal{M}$. Given m_i , the challenger computes a signature $\sigma_i \xleftarrow{R} \mathcal{S}(sk, m_i)$, and then gives σ_i to \mathcal{A} .
3. Eventually \mathcal{A} outputs a candidate forgery pair $(m, \sigma) \in \mathcal{M} \times \Sigma$.



Security of Digital Signature



DS Attcak Game



Advantage of \mathcal{A}

- We say that the adversary wins the game if the following two conditions hold:
 - $\mathcal{V}(pk, m, \sigma) = \text{accept}$,



Security of Digital Signature

Advantage of \mathcal{A}

- We say that the adversary wins the game if the following two conditions hold:
 - $\mathcal{V}(pk, m, \sigma) = \text{accept}$, and
 - m is new, namely $m \notin \{m_1, m_2, \dots\}$. (Extra compared to MAC.)



Advantage of \mathcal{A}

- We say that the adversary wins the game if the following two conditions hold:
 - $\mathcal{V}(pk, m, \sigma) = \text{accept}$, and
 - m is new, namely $m \notin \{m_1, m_2, \dots\}$. (Extra compared to MAC.)
- In the adversary wins the Attack Game, the pair (m, σ) that it sends to the challenger is called an **existential forgery**.



Advantage of \mathcal{A}

- We say that the adversary wins the game if the following two conditions hold:
 - $\mathcal{V}(pk, m, \sigma) = \text{accept}$, and
 - m is new, namely $m \notin \{m_1, m_2, \dots\}$. (Extra compared to MAC.)
- In the adversary wins the Attack Game, the pair (m, σ) that it sends to the challenger is called an **existential forgery**.
- We define \mathcal{A} 's advantage with respect to \mathfrak{S} , denoted $\text{SIGadv}[\mathcal{A}, \mathfrak{S}]$, as the probability that \mathcal{A} wins the game.



Security of Digital Signature

Advantage of \mathcal{A}

- We say that the adversary wins the game if the following two conditions hold:
 - $\mathcal{V}(pk, m, \sigma) = \text{accept}$, and
 - m is new, namely $m \notin \{m_1, m_2, \dots\}$. (Extra compared to MAC.)
- In the adversary wins the Attack Game, the pair (m, σ) that it sends to the challenger is called an **existential forgery**.
- We define \mathcal{A} 's **advantage** with respect to \mathfrak{S} , denoted $\text{SIGadv}[\mathcal{A}, \mathfrak{S}]$, as **the probability that \mathcal{A} wins the game**.
- We say that \mathcal{A} is a **Q -query MAC** adversary if \mathcal{A} issues **at most Q signing queries**.



Security of Digital Signature

Advantage of \mathcal{A}

- We say that the adversary wins the game if the following two conditions hold:
 - $\mathcal{V}(pk, m, \sigma) = \text{accept}$, and
 - m is new, namely $m \notin \{m_1, m_2, \dots\}$. (Extra compared to MAC.)
- In the adversary wins the Attack Game, the pair (m, σ) that it sends to the challenger is called an **existential forgery**.
- We define \mathcal{A} 's **advantage** with respect to \mathfrak{S} , denoted $\text{SIGadv}[\mathcal{A}, \mathfrak{S}]$, as **the probability that \mathcal{A} wins the game**.
- We say that \mathcal{A} is a **Q -query MAC** adversary if \mathcal{A} issues **at most Q signing queries**.

Secure Digital Signature

A digital signature system \mathfrak{S} is **secure** if for **all efficient adversaries \mathcal{A}** , the value $\text{SIGadv}[\mathcal{A}, \mathfrak{S}]$ is **negligible**.



\mathcal{G}

1. Let the security parameter be n .



\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .



Text-Book RSA

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.



\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.



Text-Book RSA

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.
5. Compute $d \equiv e^{-1} \pmod{\phi(N)}$.



\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.
5. Compute $d \equiv e^{-1} \pmod{\phi(N)}$.
6. $sk = (N, d)$ and $pk = (N, e)$.



Text-Book RSA

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.
5. Compute $d \equiv e^{-1} \pmod{\phi(N)}$.
6. $sk = (N, d)$ and $pk = (N, e)$.

$\mathcal{S}(sk, m \in \mathbb{Z}_N)$

1. Compute $\sigma \leftarrow m^d \pmod{N}$.

\mathcal{G}

1. Let the **security parameter** be n .
2. Choose two **primes** p and q of **bit-length almost** n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.
5. Compute $d \equiv e^{-1} \pmod{\phi(N)}$.
6. $sk = (N, d)$ and $pk = (N, e)$.

$\mathcal{S}(sk, m \in \mathbb{Z}_N)$

1. Compute $\sigma \leftarrow m^d \pmod{N}$.

$\mathcal{V}(pk, (m, \sigma) \in \mathbb{Z}_N \times \mathbb{Z}_N)$

1. Compute $m \stackrel{?}{=} \sigma^e \pmod{N}$.



A no-message attack

1. Based on the public key alone.



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m := \sigma^e \pmod{N}$.



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m := \sigma^e \pmod{N}$.
4. Forgery: (m, σ) is a valid pair without any query.



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m := \sigma^e \pmod{N}$.
4. Forgery: (m, σ) is a valid pair without any query.

Forging a signature on an arbitrary message

1. Obtain (m_1, σ_1) and (m_2, σ_2) .



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m := \sigma^e \pmod{N}$.
4. Forgery: (m, σ) is a valid pair without any query.

Forging a signature on an arbitrary message

1. Obtain (m_1, σ_1) and (m_2, σ_2) .
2. Set $\sigma := \sigma_1 \cdot \sigma_2 \pmod{N}$ and $m := m_1 \cdot m_2 \pmod{N}$.



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m := \sigma^e \pmod{N}$.
4. Forgery: (m, σ) is a valid pair without any query.

Forging a signature on an arbitrary message

1. Obtain (m_1, σ_1) and (m_2, σ_2) .
2. Set $\sigma := \sigma_1 \cdot \sigma_2 \pmod{N}$ and $m := m_1 \cdot m_2 \pmod{N}$.
3. Forgery: (m, σ) is a valid pair.



A no-message attack

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m := \sigma^e \pmod{N}$.
4. Forgery: (m, σ) is a valid pair without any query.

Forging a signature on an arbitrary message

1. Obtain (m_1, σ_1) and (m_2, σ_2) .
2. Set $\sigma := \sigma_1 \cdot \sigma_2 \pmod{N}$ and $m := m_1 \cdot m_2 \pmod{N}$.
3. Forgery: (m, σ) is a valid pair.

$$\sigma^e = (\sigma_1 \cdot \sigma_2)^e = (m_1^d \cdot m_2^d)^e = m_1^{ed} \cdot m_2^{ed} = m_1 \cdot m_2 = m \pmod{N}.$$



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

1. Let the security parameter be n .



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.
5. Compute $d \equiv e^{-1} \pmod{\phi(N)}$.



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

1. Let the security parameter be n .
2. Choose two primes p and q of bit-length almost n .
3. Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
4. Choose e such that $\gcd(e, \phi(N)) = 1$.
5. Compute $d \equiv e^{-1} \pmod{\phi(N)}$.
6. $sk = (N, d)$ and $pk = (N, e)$.



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

- Let the security parameter be n .
- Choose two primes p and q of bit-length almost n .
- Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
- Choose e such that $\gcd(e, \phi(N)) = 1$.
- Compute $d \equiv e^{-1} \pmod{\phi(N)}$.
- $sk = (N, d)$ and $pk = (N, e)$.

$S(sk, m)$

- Compute $\sigma \leftarrow H(m)^d \pmod{N}$.



Hashed RSA

- Let $H : \{0, 1\}^* \rightarrow \mathbb{Z}_N$ be a collision resistant hash function.

\mathcal{G}

- Let the security parameter be n .
- Choose two primes p and q of bit-length almost n .
- Compute $N = pq$ and $\phi(N) = (p-1)(q-1)$.
- Choose e such that $\gcd(e, \phi(N)) = 1$.
- Compute $d \equiv e^{-1} \pmod{\phi(N)}$.
- $sk = (N, d)$ and $pk = (N, e)$.

$\mathcal{S}(sk, m)$

- Compute $\sigma \leftarrow H(m)^d \pmod{N}$.

$\mathcal{V}(pk, (m, \sigma))$

- Compute $H(m) \stackrel{?}{=} \sigma^e \pmod{N}$.



Hashed RSA

A no-message attack **not possible**

1. Based on the public key alone.



Hashed RSA

A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.



Hashed RSA

A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.



A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.
4. Compute m such that $m^* = H(m)$.



Hashed RSA

A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.
4. Compute m such that $m^* = H(m)$.
5. H is collision Resistant.



Hashed RSA

A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.
4. Compute m such that $m^* = H(m)$.
5. H is collision Resistant.

Forging a signature on an arbitrary message **not possible**

1. Obtain (m_1, σ_1) and (m_2, σ_2) .



Hashed RSA

A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.
4. Compute m such that $m^* = H(m)$.
5. H is collision Resistant.

Forging a signature on an arbitrary message **not possible**

1. Obtain (m_1, σ_1) and (m_2, σ_2) .
2. Set $\sigma := \sigma_1 \cdot \sigma_2 \pmod{N}$.



A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.
4. Compute m such that $m^* = H(m)$.
5. H is collision Resistant.

Forging a signature on an arbitrary message **not possible**

1. Obtain (m_1, σ_1) and (m_2, σ_2) .
2. Set $\sigma := \sigma_1 \cdot \sigma_2 \pmod{N}$.
3. Find m such that $H(m) = H(m_1) \cdot H(m_2) \pmod{N}$.



A no-message attack **not possible**

1. Based on the public key alone.
2. Choose $\sigma \xleftarrow{R} \mathbb{Z}_n$.
3. Set $m^* := \sigma^e \pmod{N}$.
4. Compute m such that $m^* = H(m)$.
5. H is collision Resistant.

Forging a signature on an arbitrary message **not possible**

1. Obtain (m_1, σ_1) and (m_2, σ_2) .
2. Set $\sigma := \sigma_1 \cdot \sigma_2 \pmod{N}$.
3. Find m such that $H(m) = H(m_1) \cdot H(m_2) \pmod{N}$.
4. Again, H is collision Resistant.



Hashed RSA

Security of hashed RSA

It is possible to prove the security-of hashed RSA in an idealized model where H is a truly random function.

- Out-of-the-scope of the course.



DL based Digital Signature

- We will study the following three digital signatures whose security relies on the **hardness of discrete logarithm problem**.
 1. ElGamal Digital Signature,
 2. The Schnorr Digital Signature Algorithm, and
 3. Digital Signature Algorithm (DSA).



DL based Digital Signature

- We will study the following three digital signatures whose security relies on the **hardness of discrete logarithm problem**.
 1. ElGamal Digital Signature,
 2. The Schnorr Digital Signature Algorithm, and
 3. Digital Signature Algorithm (DSA).
- But there is **no known proof** based on the discrete logarithm (or any other) assumption.



DL based Digital Signature

- We will study the following three digital signatures whose security relies on the **hardness of discrete logarithm problem**.
 1. ElGamal Digital Signature,
 2. The Schnorr Digital Signature Algorithm, and
 3. Digital Signature Algorithm (DSA).
- But there is **no known proof** based on the discrete logarithm (or any other) assumption.
- Let H be a **collision resistant Hash function**.



ElGamal Digital Signature

- ElGamal signature scheme was introduced by Tahir Elgamal in 1985.



- ElGamal signature scheme was introduced by Tahir Elgamal in 1985.

Domain parameter

- Let G be a **cyclic multiplicative group**.



- ElGamal signature scheme was introduced by Tahir Elgamal in 1985.

Domain parameter

- Let G be a cyclic multiplicative group.
- $O(G) = n$



- ElGamal signature scheme was introduced by Tahir Elgamal in 1985.

Domain parameter

- Let G be a **cyclic multiplicative group**.
- $O(G) = n$
- $\exists g \in G$ such that $O(g) = n$.



ElGamal Digital Signature

- ElGamal signature scheme was introduced by Tahir Elgamal in 1985.

Domain parameter

- Let G be a **cyclic multiplicative group**.
- $O(G) = n$
- $\exists g \in G$ such that $O(g) = n$.

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
- Compute $Q \equiv g^d$.



ElGamal Digital Signature

- ElGamal signature scheme was introduced by Tahir Elgamal in 1985.

Domain parameter

- Let G be a cyclic multiplicative group.
- $O(G) = n$
- $\exists g \in G$ such that $O(g) = n$.

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
- Compute $Q \equiv g^d$.
- $sk = (G, g, n, d)$ and $pk = (G, g, n, Q)$.



ElGamal Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.



$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_n$.



ElGamal Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_n$.
3. Compute $s = g^k$.
4. Compute $t \equiv k^{-1} (m - ds) \pmod{n}$.



ElGamal Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_n$.
3. Compute $s = g^k$.
4. Compute $t \equiv k^{-1} (m - ds) \pmod{n}$.
5. Signature $\sigma = (s, t)$



ElGamal Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_n$.
3. Compute $s = g^k$.
4. Compute $t \equiv k^{-1} (m - ds) \pmod{n}$.
5. Signature $\sigma = (s, t)$

$\mathcal{V}(pk, (M, \sigma, pk))$

1. Compute $m = H(M) \in \mathbb{Z}_n$.



ElGamal Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_n$.
3. Compute $s = g^k$.
4. Compute $t \equiv k^{-1}(m - ds) \pmod{n}$.
5. Signature $\sigma = (s, t)$

$\mathcal{V}(pk, (M, \sigma, pk))$

1. Compute $m = H(M) \in \mathbb{Z}_n$.
2. Compute $a_1 = g^m$.
3. Compute $a_2 = Q^s s^t$.



ElGamal Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_n \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_n$.
3. Compute $s = g^k$.
4. Compute $t \equiv k^{-1} (m - ds) \pmod{n}$.
5. Signature $\sigma = (s, t)$

$\mathcal{V}(pk, (M, \sigma, pk))$

1. Compute $m = H(M) \in \mathbb{Z}_n$.
2. Compute $a_1 = g^m$.
3. Compute $a_2 = Q^s s^t$.
4. Check $a_1 \stackrel{?}{=} a_2$.
5. If yes Return accept, else Return reject.



Correctness

$$a_1 \equiv g^m \equiv g^{tk+ds} = (g^k)^t (g^d)^s \equiv s^t Q^s.$$



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures

Domain parameter

- Let G be a **cyclic multiplicative group**.



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures

Domain parameter

- Let G be a **cyclic multiplicative group**.
- $O(G) = n$.



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures

Domain parameter

- Let G be a **cyclic multiplicative group**.
- $O(G) = n$.
- $\exists g \in G$ such that $O(g) = r$.



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures

Domain parameter

- Let G be a cyclic multiplicative group.
- $O(G) = n$.
- $\exists g \in G$ such that $O(g) = r$.
- r is suitably large prime divisor of n .



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures

Domain parameter

- Let G be a **cyclic multiplicative group**.
- $O(G) = n$.
- $\exists g \in G$ such that $O(g) = r$.
- r is suitably large prime divisor of n .

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
- Compute $Q \equiv g^d$.



The Schnorr Digital Signature Algorithm

- It is a faster modification of ElGamal scheme.
- Introduced by Claus Schnorr in 1989.
- It is known for its efficiency and it generates short signatures

Domain parameter

- Let G be a **cyclic multiplicative group**.
- $O(G) = n$.
- $\exists g \in G$ such that $O(g) = r$.
- r is suitably large prime divisor of n .

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
- Compute $Q \equiv g^d$.
- $sk = (G, g, n, r, d)$ and $pk = (G, g, n, r, Q)$



The Schnorr Digital Signature Algorithm

$S(sk, M)$

1. Choose session key (d', Q') .
 - Choose $d' \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
 - Compute $Q' = g^{d'}$.



The Schnorr Digital Signature Algorithm

$S(sk, M)$

1. Choose session key (d', Q') .
 - Choose $d' \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
 - Compute $Q' = g^{d'}$.
2. Compute $s = H(M \| Q') \in \mathbb{Z}_r$.
3. Compute $t \equiv d' - ds \pmod{r}$.



The Schnorr Digital Signature Algorithm

$S(sk, M)$

1. Choose session key (d', Q') .
 - Choose $d' \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
 - Compute $Q' = g^{d'}$.
2. Compute $s = H(M \| Q') \in \mathbb{Z}_r$.
3. Compute $t \equiv d' - ds \pmod{r}$.
4. Signature $\sigma = (s, t)$.



The Schnorr Digital Signature Algorithm

$S(sk, M)$

1. Choose session key (d', Q') .
 - Choose $d' \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
 - Compute $Q' = g^{d'}$.
2. Compute $s = H(M \| Q') \in \mathbb{Z}_r$.
3. Compute $t \equiv d' - ds \pmod{r}$.
4. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $u = g^t Q^s$.



The Schnorr Digital Signature Algorithm

$S(sk, M)$

1. Choose session key (d', Q') .
 - Choose $d' \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
 - Compute $Q' = g^{d'}$.
2. Compute $s = H(M \| Q') \in \mathbb{Z}_r$.
3. Compute $t \equiv d' - ds \pmod{r}$.
4. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $u = g^t Q^s$.
2. Compute $\hat{s} = H(M \| u) \in \mathbb{Z}_r$.



The Schnorr Digital Signature Algorithm

$S(sk, M)$

1. Choose session key (d', Q') .
 - Choose $d' \xleftarrow{R} \mathbb{Z}_r \setminus \{0, 1\}$.
 - Compute $Q' = g^{d'}$.
2. Compute $s = H(M \| Q') \in \mathbb{Z}_r$.
3. Compute $t \equiv d' - ds \pmod{r}$.
4. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $u = g^t Q^s$.
2. Compute $\hat{s} = H(M \| u) \in \mathbb{Z}_r$.
3. Check $s \stackrel{?}{=} \hat{s}$.
4. If yes Return accept, else Return reject.



The Schnorr Digital Signature Algorithm

Correctness

$$u \equiv g^t Q^s \equiv g^t (g^d)^s \equiv g^{(t+ds)} \equiv g^{d'} \equiv Q'.$$



- National Institute of Standards and Technology (NIST) proposed DSA in 1991.

Domain parameter(p, q, g)

- Let $G = \mathbb{Z}_p^*$ for some prime p .



- National Institute of Standards and Technology (NIST) proposed DSA in 1991.

Domain parameter(p, q, g)

- Let $G = \mathbb{Z}_p^*$ for some prime p .
- Let $g \in G$ such that $\langle g \rangle$ is the largest prime subgroup of G .



- National Institute of Standards and Technology (NIST) proposed DSA in 1991.

Domain parameter(p, q, g)

- Let $G = \mathbb{Z}_p^*$ for some prime p .
- Let $g \in G$ such that $\langle g \rangle$ is the largest prime subgroup of G .
- Let $O(g) = q$.



- National Institute of Standards and Technology (NIST) proposed DSA in 1991.

Domain parameter(p, q, g)

- Let $G = \mathbb{Z}_p^*$ for some prime p .
- Let $g \in G$ such that $\langle g \rangle$ is the largest prime subgroup of G .
- Let $O(g) = q$.

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.



- National Institute of Standards and Technology (NIST) proposed DSA in 1991.

Domain parameter(p, q, g)

- Let $G = \mathbb{Z}_p^*$ for some prime p .
- Let $g \in G$ such that $\langle g \rangle$ is the largest prime subgroup of G .
- Let $O(g) = q$.

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
- Compute $Q \equiv g^d \pmod{p}$.



DSA Digital Signature

- National Institute of Standards and Technology (NIST) proposed DSA in 1991.

Domain parameter(p, q, g)

- Let $G = \mathbb{Z}_p^*$ for some prime p .
- Let $g \in G$ such that $\langle g \rangle$ is the largest prime subgroup of G .
- Let $O(g) = q$.

\mathcal{G}

- Choose $d \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
- Compute $Q \equiv g^d \pmod{p}$.
- $\mathcal{SK} = (G, g, p, q, d)$ and $\mathcal{PK} = (G, g, p, q, Q)$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.
5. Signature $\sigma = (s, t)$.



DSA Digital Signature

$\mathcal{S}(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p}\right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.
5. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $m = H(M) \in \mathbb{Z}_p$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.
5. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $m = H(M) \in \mathbb{Z}_p$.
2. Compute $w \equiv t^{-1} \pmod{q}$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.
5. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $m = H(M) \in \mathbb{Z}_p$.
2. Compute $w \equiv t^{-1} \pmod{q}$.
3. Compute $w_1 \equiv mw \pmod{q}$ and $w_2 \equiv sw \pmod{q}$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.
5. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $m = H(M) \in \mathbb{Z}_p$.
2. Compute $w \equiv t^{-1} \pmod{q}$.
3. Compute $w_1 \equiv mw \pmod{q}$ and $w_2 \equiv sw \pmod{q}$.
4. Compute $s' = (g^{w_1} Q^{w_2} \pmod{p}) \pmod{q}$.



DSA Digital Signature

$S(sk, M)$

1. Choose $k \xleftarrow{R} \mathbb{Z}_q \setminus \{0, 1\}$.
2. Compute $m = H(M) \in \mathbb{Z}_p$.
3. Compute $s = \left(g^k \pmod{p} \right) \pmod{q}$.
4. Compute $t = k^{-1}(m + ds) \pmod{q}$.
5. Signature $\sigma = (s, t)$.

$\mathcal{V}(pk, (M, \sigma))$

1. Compute $m = H(M) \in \mathbb{Z}_p$.
2. Compute $w \equiv t^{-1} \pmod{q}$.
3. Compute $w_1 \equiv mw \pmod{q}$ and $w_2 \equiv sw \pmod{q}$.
4. Compute $s' = (g^{w_1} Q^{w_2} \pmod{p}) \pmod{q}$.
5. Check $s' \stackrel{?}{=} s$; If yes Return accept, else Return reject.



Correctness

$$s' = g^{w_1} Q^{w_2}$$



Correctness

$$\begin{aligned} s' &= g^{w_1} Q^{w_2} \\ &= g^{w_1} g^{dw_2} \quad \text{as } Q = g^d \end{aligned}$$



Correctness

$$\begin{aligned} s' &= g^{w_1} Q^{w_2} \\ &= g^{w_1} g^{dw_2} && \text{as } Q = g^d \\ &= g^{wm} g^{dsw} && \text{as } w_1 = mw \text{ and } w_2 = sw \end{aligned}$$



Correctness

$$\begin{aligned} s' &= g^{w_1} Q^{w_2} \\ &= g^{w_1} g^{dw_2} && \text{as } Q = g^d \\ &= g^{wm} g^{dsw} && \text{as } w_1 = mw \text{ and } w_2 = sw \\ &= g^{w(m+ds)} \end{aligned}$$



Correctness

$$\begin{aligned} s' &= g^{w_1} Q^{w_2} \\ &= g^{w_1} g^{dw_2} && \text{as } Q = g^d \\ &= g^{wm} g^{dsw} && \text{as } w_1 = mw \text{ and } w_2 = sw \\ &= g^{w(m+ds)} \\ &= g^{t^{-1}(m+ds)} && \text{as } w = t^{-1} \end{aligned}$$



Correctness

$$\begin{aligned} s' &= g^{w_1} Q^{w_2} \\ &= g^{w_1} g^{dw_2} && \text{as } Q = g^d \\ &= g^{wm} g^{dsw} && \text{as } w_1 = mw \text{ and } w_2 = sw \\ &= g^{w(m+ds)} \\ &= g^{t^{-1}(m+ds)} && \text{as } w = t^{-1} \\ &= g^k && \text{as } t = k^{-1}(m+ds) \end{aligned}$$



Correctness

$$\begin{aligned} s' &= g^{w_1} Q^{w_2} \\ &= g^{w_1} g^{dw_2} && \text{as } Q = g^d \\ &= g^{wm} g^{dsw} && \text{as } w_1 = mw \text{ and } w_2 = sw \\ &= g^{w(m+ds)} \\ &= g^{t^{-1}(m+ds)} && \text{as } w = t^{-1} \\ &= g^k && \text{as } t = k^{-1}(m+ds) \\ &= s && \text{as } s = g^k. \end{aligned}$$

End