

Cryptology

Sabyasachi Karati

Assistant Professor

Cryptology and Security Research Unit (C.S.R.U)

R. C. Bose Centre for Cryptology and Security

Indian Statistical Institute (ISI)

Kolkata, India






Lecture 02

History and Classical Ciphers




Cryptographic Schemes



- \mathcal{E} : Encryption algorithm, and K_e : Encryption key.
- \mathcal{D} : Decryption algorithm, and K_d : Decryption key.
- M : Plain text or Message, and C : Cipher text or Encrypted message.



Cryptographic Schemes




- \mathcal{E} : Encryption algorithm, and K_e : Encryption key.
- \mathcal{D} : Decryption algorithm, and K_d : Decryption key.
- M : Plain text or Message, and C : Cipher text or Encrypted message.

Settings

- Symmetric Key: $K_e = K_d$.
- Asymmetric Key or Public Key: $K_e \neq K_d$.



Cryptographic Schemes





Symmetric Encryption Scheme

Definition

Symmetric Encryption scheme is a three-tuple of algorithms $(\mathcal{G}, \mathcal{E}, \mathcal{D})$ defined over a three-tuple of spaces $(\mathcal{K}, \mathcal{P}, \mathcal{C})$, where:



Symmetric Encryption Scheme

Definition

Symmetric Encryption scheme is a three-tuple of algorithms $(\mathcal{G}, \mathcal{E}, \mathcal{D})$ defined over a three-tuple of spaces $(\mathcal{K}, \mathcal{P}, \mathcal{C})$, where:

- \mathcal{P} : **Plaintext** or **Message Space**, a finite set of possible plaintexts.
- \mathcal{C} : **Cipher Space**, a finite set of possible ciphertexts.
- \mathcal{K} : **Key Space**, a finite set of possible keys.



Symmetric Encryption Scheme

Definition

Symmetric Encryption scheme is a three-tuple of algorithms $(\mathcal{G}, \mathcal{E}, \mathcal{D})$ defined over a three-tuple of spaces $(\mathcal{K}, \mathcal{P}, \mathcal{C})$, where:

- \mathcal{P} : **Plaintext** or **Message Space**, a finite set of possible plaintexts.
- \mathcal{C} : **Cipher Space**, a finite set of possible ciphertexts.
- \mathcal{K} : **Key Space**, a finite set of possible keys.
- \mathcal{G} : **The Key-Generation Algorithm**, a probabilistic algorithm that outputs a key k from \mathcal{K} chosen according to some distribution.
- \mathcal{E} : **The Encryption Algorithm**,

$$\begin{aligned}\mathcal{E} & : \mathcal{K} \times \mathcal{P} \rightarrow \mathcal{C} \\ \mathcal{E}(k, m) &= c, \text{ where } k \in \mathcal{K}, m \in \mathcal{P}, c \in \mathcal{C}.\end{aligned}$$

- \mathcal{D} : **The Decryption Algorithm**,

$$\begin{aligned}\mathcal{D} & : \mathcal{K} \times \mathcal{C} \rightarrow \mathcal{P} \\ \mathcal{D}(k, c) &= m, \text{ where } k \in \mathcal{K}, m \in \mathcal{P}, c \in \mathcal{C}.\end{aligned}$$



Symmetric Encryption Scheme

Basic **Correctness** of a Symmetric Encryption Scheme

For all key $k \in \mathcal{K}$ generated by \mathcal{G} and for all plaintext $m \in \mathcal{P}$, the following must hold:

$$\mathcal{D}(k, \mathcal{E}(k, m)) = m.$$



Symmetric Encryption Scheme

Basic **Correctness** of a Symmetric Encryption Scheme

For all key $k \in \mathcal{K}$ generated by \mathcal{G} and for all plaintext $m \in \mathcal{P}$, the following must hold:

$$\mathcal{D}(k, \mathcal{E}(k, m)) = m.$$

- Decrypting a ciphertext using the appropriate key yields the original message that was encrypted.



Kerckhoffs' Principle

- In 1883, Auguste Kerckhoffs postulates that

Definition (Kerckhoffs' Principle)

A cryptosystem should be secure even if the attacker knows all details about the system, with the exception of the secret key. In particular, the system should be secure when the attacker knows the encryption and decryption algorithms.



Kerckhoffs' Principle

- In 1883, Auguste Kerckhoffs postulates that

Definition (Kerckhoffs' Principle)

A cryptosystem should be secure even if the attacker knows all details about the system, with the exception of the secret key. In particular, the system should be secure when the attacker knows the encryption and decryption algorithms.

Arguments in favour of Kerckhoffs' Principle

1. It is easy to **maintain secrecy** of a small key or to **share** a small key.



Kerckhoffs' Principle

- In 1883, Auguste Kerckhoffs postulates that

Definition (Kerckhoffs' Principle)

A cryptosystem should be secure even if the attacker knows all details about the system, with the exception of the secret key. In particular, the system should be secure when the attacker knows the encryption and decryption algorithms.

Arguments in favour of Kerckhoffs' Principle

1. It is easy to **maintain secrecy** of a small key or to **share** a small key.
2. If key is leaked, then communicating parties can keep on using the **same algorithm** with **different key**.



Kerckhoffs' Principle

- In 1883, Auguste Kerckhoffs postulates that

Definition (Kerckhoffs' Principle)

A cryptosystem should be secure even if the attacker knows all details about the system, with the exception of the secret key. In particular, the system should be secure when the attacker knows the encryption and decryption algorithms.

Arguments in favour of Kerckhoffs' Principle

1. It is easy to **maintain secrecy** of a small key or to **share** a small key.
2. If key is leaked, then communicating parties can keep on using the **same algorithm** with **different key**.
3. In case of many pairs are communicating, it is easy to have **same algorithm for all the pairs** with different keys than **different algorithms for each pair**.



Kerckhoffs' Principle

- In 1883, Auguste Kerckhoffs postulates that

Definition (Kerckhoffs' Principle)

A cryptosystem should be secure even if the attacker knows all details about the system, with the exception of the secret key. In particular, the system should be secure when the attacker knows the encryption and decryption algorithms.

Arguments in favour of Kerckhoffs' Principle

1. It is easy to **maintain secrecy** of a small key or to **share** a small key.
2. If key is leaked, then communicating parties can keep on using the **same algorithm** with **different key**.
3. In case of many pairs are communicating, it is easy to have **same algorithm for all the pairs** with different keys than **different algorithms for each pair**.

Therefore, Kerckhoffs' principle demands that **everything (algorithm) is public except for the key**.



Kerckhoffs' Principle

Advantage of Open Cryptographic Design

1. They undergo **public scrutiny** and are therefore likely to be **stronger**.
 - it is very **difficult** to construct good cryptographic schemes.
 - if it has been extensively studied (by **experts other than the designers** of the scheme themselves) and no weaknesses have been found, then our confidence in the security of a scheme will be much higher.



Kerckhoffs' Principle

Advantage of Open Cryptographic Design

1. They undergo **public scrutiny** and are therefore likely to be **stronger**.
 - it is very **difficult** to construct good cryptographic schemes.
 - if it has been extensively studied (by **experts other than the designers** of the scheme themselves) and no weaknesses have been found, then our confidence in the security of a scheme will be much higher.
2. It is better for security flaws, if they exist, to be **revealed by “ethical hackers”** (leading, hopefully, to the system being fixed) rather than having these **flaws be known only to malicious parties**.



Kerckhoffs' Principle

Advantage of Open Cryptographic Design

1. They undergo **public scrutiny** and are therefore likely to be **stronger**.
 - it is very **difficult** to construct good cryptographic schemes.
 - if it has been extensively studied (by **experts other than the designers** of the scheme themselves) and no weaknesses have been found, then our confidence in the security of a scheme will be much higher.
2. It is better for security flaws, if they exist, to be **revealed by “ethical hackers”** (leading, hopefully, to the system being fixed) rather than having these **flaws be known only to malicious parties**.
3. If the security of the system relies on the secrecy of the algorithm, then **reverse engineering** of the code (or leakage by industrial espionage) poses a serious threat to security.



Kerckhoffs' Principle

Advantage of Open Cryptographic Design

1. They undergo **public scrutiny** and are therefore likely to be **stronger**.
 - it is very **difficult** to construct good cryptographic schemes.
 - if it has been extensively studied (by **experts other than the designers** of the scheme themselves) and no weaknesses have been found, then our confidence in the security of a scheme will be much higher.
2. It is better for security flaws, if they exist, to be **revealed by “ethical hackers”** (leading, hopefully, to the system being fixed) rather than having these **flaws be known only to malicious parties**.
3. If the security of the system relies on the secrecy of the algorithm, then **reverse engineering** of the code (or leakage by industrial espionage) poses a serious threat to security.
4. Public design enables the establishment of standards.



Kerckhoffs' Principle

Advantage of Open Cryptographic Design

1. They undergo **public scrutiny** and are therefore likely to be **stronger**.
 - it is very **difficult** to construct good cryptographic schemes.
 - if it has been extensively studied (by **experts other than the designers** of the scheme themselves) and no weaknesses have been found, then our confidence in the security of a scheme will be much higher.
2. It is better for security flaws, if they exist, to be **revealed by “ethical hackers”** (leading, hopefully, to the system being fixed) rather than having these **flaws be known only to malicious parties**.
3. If the security of the system relies on the secrecy of the algorithm, then **reverse engineering** of the code (or leakage by industrial espionage) poses a serious threat to security.
4. Public design enables the establishment of standards.

Importance of Kerckhoffs' Principle through Example

Content Scrambling System (CSS) for DVD content protection, which was broken easily once it was reverse-engineered.



Attack Scenarios Against Symmetric Encryption Scheme

Attack Models

There are four commonly considered attack models:

1. Ciphertext-only attack
2. Known-plaintext attack
3. Chosen-plaintext attack
4. Chosen-ciphertext attack



Ciphertext-only attack

- **Given:** Only Ciphertext(s): $\{c_i \mid 1 \leq i \leq n\}$ encrypted under the **same key k** .



Ciphertext-only attack

- **Given:** Only Ciphertext(s): $\{c_i \mid 1 \leq i \leq n\}$ encrypted under the same key k .
- **Goal:** Find (one of) the message(s) m^* such that corresponding $c^* \in \{c_i \mid 1 \leq i \leq n\}$ and/or the key k .



Ciphertext-only attack

- **Given:** Only Ciphertext(s): $\{c_i \mid 1 \leq i \leq n\}$ encrypted under the same key k .
- **Goal:** Find (one of) the message(s) m^* such that corresponding $c^* \in \{c_i \mid 1 \leq i \leq n\}$ and/or the key k .
- **Weaker Goal:** Find some information regarding the key k .



Known-plaintext attack

- **Given:** One or more plaintext-ciphertext pairs $\{(m_i, c_i) \mid 1 \leq i \leq n\}$ encrypted under the **same key k** .



Known-plaintext attack

- **Given:** One or more plaintext-ciphertext pairs $\{(m_i, c_i) \mid 1 \leq i \leq n\}$ encrypted under the **same key k** .
- **Goal:** Find a valid plaintext m^* for a new c^* , that is $c^* \notin \{c_i \mid 1 \leq i \leq n\}$, under **the key k** and/or the key k .



Known-plaintext attack

- **Given:** One or more plaintext-ciphertext pairs $\{(m_i, c_i) \mid 1 \leq i \leq n\}$ encrypted under the **same key k** .
- **Goal:** Find a valid plaintext m^* for a new c^* , that is $c^* \notin \{c_i \mid 1 \leq i \leq n\}$, under **the key k** and/or the key k .
- **Weaker Goal:** Find some information regarding the key k .



Chosen-plaintext attack

- **Given:**
 - Adversary has the temporary access to the $\mathcal{E}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.



Chosen-plaintext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{E}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
- Adversary chooses a set of plain texts $\{m_i \mid 1 \leq i \leq n\}$.



Chosen-plaintext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{E}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
- Adversary chooses a set of plain texts $\{m_i \mid 1 \leq i \leq n\}$.
- Receives the corresponding ciphertexts $\{c_i \mid 1 \leq i \leq n\}$ such that $c_i = \mathcal{E}(k, m_i) \forall i$.



Chosen-plaintext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{E}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
- Adversary chooses a set of plain texts $\{m_i \mid 1 \leq i \leq n\}$.
- Receives the corresponding ciphertexts $\{c_i \mid 1 \leq i \leq n\}$ such that $c_i = \mathcal{E}(k, m_i) \forall i$.

- **Goal:** Find a valid plaintext m^* for a new c^* , that is $c^* \notin \{c_i \mid 1 \leq i \leq n\}$, under the key k and/or the key k .



Chosen-plaintext attack

- **Given:**
 - Adversary has the temporary access to the $\mathcal{E}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
 - Adversary chooses a set of plain texts $\{m_i \mid 1 \leq i \leq n\}$.
 - Receives the corresponding ciphertexts $\{c_i \mid 1 \leq i \leq n\}$ such that $c_i = \mathcal{E}(k, m_i) \forall i$.
- **Goal:** Find a valid plaintext m^* for a new c^* , that is $c^* \notin \{c_i \mid 1 \leq i \leq n\}$, under the key k and/or the key k .
- **Weaker Goal:** Find some information regarding the key k .



Chosen-ciphertext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{D}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.



Chosen-ciphertext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{D}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
- Adversary chooses a set of ciphertexts $\{c_i \mid 1 \leq i \leq n\}$.



Chosen-ciphertext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{D}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
- Adversary chooses a set of ciphertexts $\{c_i \mid 1 \leq i \leq n\}$.
- Receives the corresponding plaintexts $\{m_i \mid 1 \leq i \leq n\}$ such that $m_i = \mathcal{D}(k, c_i) \forall i$.



Chosen-ciphertext attack

- **Given:**

- Adversary has the temporary access to the $\mathcal{D}(k, \cdot)$ for some unknown key $k \in \mathcal{K}$.
- Adversary chooses a set of ciphertexts $\{c_i \mid 1 \leq i \leq n\}$.
- Receives the corresponding plaintexts $\{m_i \mid 1 \leq i \leq n\}$ such that $m_i = \mathcal{D}(k, c_i) \forall i$.

- **Goal:** Find a valid plaintext m^* for a new c^* , that is $c^* \notin \{c_i \mid 1 \leq i \leq n\}$, under the key k and/or the key k .



Chosen-ciphertext attack

- **Given:**

- Adversary has the **temporary access** to the $\mathcal{D}(k, \cdot)$ for some **unknown key** $k \in \mathcal{K}$.
- Adversary chooses a set of ciphertexts $\{c_i \mid 1 \leq i \leq n\}$.
- Receives the corresponding plaintexts $\{m_i \mid 1 \leq i \leq n\}$ such that $m_i = \mathcal{D}(k, c_i) \forall i$.

- **Goal:** Find a valid plaintext m^* for a new c^* , that is $c^* \notin \{c_i \mid 1 \leq i \leq n\}$, under the key k and/or the key k .

- **Weaker Goal:** Find some information regarding the key k .



History of Classical Ciphers

- Some examples of [historical ciphers](#) and show that they are **all badly broken**.



History of Classical Ciphers

- Some examples of **historical ciphers** and show that they are **all badly broken**.
- **Goal:**
 1. To highlight the weaknesses of **ad-hoc** approaches.



History of Classical Ciphers

- Some examples of **historical ciphers** and show that they are **all badly broken**.
- **Goal:**
 1. To highlight the weaknesses of **ad-hoc** approaches.
 2. Motivation towards a more modern and rigorous approach.



History of Classical Ciphers

- Some examples of **historical ciphers** and show that they are **all badly broken**.
- **Goal:**
 1. To highlight the weaknesses of **ad-hoc** approaches.
 2. Motivation towards a more modern and rigorous approach.
 3. Demonstrate that **simple approaches** to achieving secure encryption are **unlikely to succeed**.



History of Classical Ciphers

- Some examples of **historical ciphers** and show that they are **all badly broken**.
- **Goal:**
 1. To highlight the weaknesses of **ad-hoc** approaches.
 2. Motivation towards a more modern and rigorous approach.
 3. Demonstrate that **simple approaches** to achieving secure encryption are **unlikely to succeed**.
 4. To identify/learn why that is the case.



Caesar's Cipher (100 B.C. - 44 B.C.)

- It is one of the oldest recorded ciphers.
- Is described in *De Vita Caesarum, Divus Iulius* (The Lives of the Caesars, The Deified Julius) which was written in approximately 110 C.E.:

“There are also letters of his to Cicero, as well as to his intimates on private affairs, and in the latter, if he had anything confidential to say, he wrote it in cipher, that is, by so changing the order of the letters of the alphabet, that not a word could be made out. *If anyone wishes to decipher these, and get at their meaning, he must substitute the fourth letter of the alphabet, namely D, for A, and so with the others.*”



Caesar's Cipher (100 B.C. - 44 B.C.)

Caesar's Cipher

- $\mathcal{P} = C = \{A, B, C, \dots, Z\}$ (English Alphabet)



Caesar's Cipher (100 B.C. - 44 B.C.)

Caesar's Cipher

- $\mathcal{P} = C = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \{0, 1, 2, \dots, 25\} = \mathbb{Z}_{26}$.

| | | | | | | | | |
|---|---|---|---|-----|----|----|----|----|
| A | B | C | D | ... | W | X | Y | Z |
| 0 | 1 | 2 | 3 | ... | 22 | 23 | 24 | 25 |



Caesar's Cipher (100 B.C. - 44 B.C.)

Caesar's Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \{0, 1, 2, \dots, 25\} = \mathbb{Z}_{26}$.

| | | | | | | | | |
|---|---|---|---|-----|----|----|----|----|
| A | B | C | D | ... | W | X | Y | Z |
| 0 | 1 | 2 | 3 | ... | 22 | 23 | 24 | 25 |

- $\mathcal{E} : c := (m + 3) \pmod{26}$.

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |



Caesar's Cipher (100 B.C. - 44 B.C.)

Caesar's Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \{0, 1, 2, \dots, 25\} = \mathbb{Z}_{26}$.

| | | | | | | | | |
|---|---|---|---|-----|----|----|----|----|
| A | B | C | D | ... | W | X | Y | Z |
| 0 | 1 | 2 | 3 | ... | 22 | 23 | 24 | 25 |

- $\mathcal{E} : c := (m + 3) \pmod{26}$.

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |

- $\mathcal{D} : m := (c - 3) \pmod{26}$.

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| X | Y | Z | A | ... | T | U | V | W |



Caesar's Cipher (100 B.C. - 44 B.C.)

Example

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |

- **Plaintext:** BEGIN THE ATTACK NOW.



Caesar's Cipher (100 B.C. - 44 B.C.)

Example

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |

- **Plaintext:** BEGIN THE ATTACK NOW.
- **Ciphertext:** EHJLQ WKH DWWDFN QRZ.

Drawback

- Fixed Key, in other words, The method is fixed.



Caesar's Cipher (100 B.C. - 44 B.C.)

Example

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |

- **Plaintext:** BEGIN THE ATTACK NOW.
- **Ciphertext:** EHJLQ WKH DWWDFN QRZ.

Drawback

- Fixed Key, in other words, The method is fixed.
- If the encryption scheme is made public then decryption is trivial.



Caesar's Cipher (100 B.C. - 44 B.C.)

Example

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |

- **Plaintext:** BEGIN THE ATTACK NOW.
- **Ciphertext:** EHJLQ WKH DWWDFN QRZ.

Drawback

- Fixed Key, in other words, The method is fixed.
- If the encryption scheme is made public then decryption is trivial.
- *G*: Does nothing!



Caesar's Cipher (100 B.C. - 44 B.C.)

Example

| | | | | | | | | |
|---|---|---|---|-----|---|---|---|---|
| A | B | C | D | ... | W | X | Y | Z |
| D | E | F | G | ... | Z | A | B | C |

- **Plaintext:** BEGIN THE ATTACK NOW.
- **Ciphertext:** EHJLQ WKH DWWDFN QRZ.

Drawback

- Fixed Key, in other words, The method is fixed.
- If the encryption scheme is made public then decryption is trivial.
- \mathcal{G} : Does nothing!

Does not follow Kerckhoffs' Principle.



Shift Cipher

Shift Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \mathbb{Z}_{26}$.
- $\mathcal{K} = \mathbb{Z}_{26}$.



Shift Cipher

Shift Cipher

- $\mathcal{P} = C = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \mathbb{Z}_{26}$.
- $\mathcal{K} = \mathbb{Z}_{26}$.
- $\mathcal{G} : k \xleftarrow{R} \mathbb{Z}_{26}$



Shift Cipher

Shift Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \mathbb{Z}_{26}$.
- $\mathcal{K} = \mathbb{Z}_{26}$.
- $\mathcal{G} : k \xleftarrow{R} \mathbb{Z}_{26}$
- $\mathcal{E} : c := (m + k) \pmod{26}$.



Shift Cipher

Shift Cipher

- $\mathcal{P} = C = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \mathbb{Z}_{26}$.
- $\mathcal{K} = \mathbb{Z}_{26}$.
- $\mathcal{G} : k \xleftarrow{R} \mathbb{Z}_{26}$
- $\mathcal{E} : c := (m + k) \pmod{26}$.
- $\mathcal{D} : m := (c - k) \pmod{26}$.



Shift Cipher

Shift Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet) $= \mathbb{Z}_{26}$.
- $\mathcal{K} = \mathbb{Z}_{26}$.
- $\mathcal{G} : k \xleftarrow{R} \mathbb{Z}_{26}$
- $\mathcal{E} : c := (m + k) \pmod{26}$.
- $\mathcal{D} : m := (c - k) \pmod{26}$.

Caesar's Cipher is a special case of Shift cipher with $K = 3$



Shift Cipher

Example

- Let $K = 7$

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
| H | I | J | K | L | M | N | O | P | Q | R | S | T |
| N | O | P | Q | R | S | T | U | V | W | X | Y | Z |
| U | V | W | X | Y | Z | A | B | C | D | E | F | G |



Shift Cipher

Example

- Let $K = 7$

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
| H | I | J | K | L | M | N | O | P | Q | R | S | T |
| N | O | P | Q | R | S | T | U | V | W | X | Y | Z |
| U | V | W | X | Y | Z | A | B | C | D | E | F | G |

- Plaintext:** BEGIN THE ATTACK NOW.



Shift Cipher

Example

- Let $K = 7$

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
| H | I | J | K | L | M | N | O | P | Q | R | S | T |
| N | O | P | Q | R | S | T | U | V | W | X | Y | Z |
| U | V | W | X | Y | Z | A | B | C | D | E | F | G |

- Plaintext:** BEGIN THE ATTACK NOW.
- Ciphertext:** ILNPU AOL HAAHJR UVD.



Shift Cipher

Cryptanalysis of Shift Cipher

- Is it secure? [Answer: No](#)



Shift Cipher

Cryptanalysis of Shift Cipher

- Is it secure? [Answer: No](#)
- Is it possible to decrypt a message without knowing the key? [Answer: Yes](#)



Shift Cipher

Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDFN QRZ | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDFN QRZ | No |
| 5 | DGIKP VJG CVVCEM PQY | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| <i>K</i> | Decrypted Text | Make Sense? |
|----------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDEN QRZ | No |
| 5 | DGIKP VJG CVVCEM PQY | No |
| 6 | CFHJO UIF BUUBDL OPX | No |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| K | Decrypted Text | Make Sense? |
|---|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDEN QRZ | No |
| 5 | DGIKP VJG CVVCEM PQY | No |
| 6 | CFHJO UIF BUUBDL OPX | No |
| 7 | BEGIN THE ATTACK NOW | Yes |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| K | Decrypted Text | Make Sense? |
|------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDEN QRZ | No |
| 5 | DGIKP VJG CVVCEM PQY | No |
| 6 | CFHJO UIF BUUBDL OPX | No |
| 7 | BEGIN THE ATTACK NOW | Yes |
| Stop | | |



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| K | Decrypted Text | Make Sense? |
|------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDFN QRZ | No |
| 5 | DGIKP VJG CVVCEM PQY | No |
| 6 | CFHJO UIF BUUBDL OPX | No |
| 7 | BEGIN THE ATTACK NOW | Yes |
| Stop | | |

- Maximum number of tries required?



Cryptanalysis of Shift Cipher

- Is it secure? **Answer: No**
- Is it possible to decrypt a message without knowing the key? **Answer: Yes**
- **Brute-forced Attack:**
 - Check each key one after another.
 - Stop when the text makes **some sense**.

| K | Decrypted Text | Make Sense? |
|------|----------------------|-------------|
| 0 | ILNPU AOL HAAHJR UVD | No |
| 1 | HKMOT ZNK GZZGIQ TUC | No |
| 2 | GJLNS YMJ FYYFHP STB | No |
| 3 | FIKMR XLI EXXEGO RSA | No |
| 4 | EHJLQ WKH DWWDFN QRZ | No |
| 5 | DGIKP VJG CVVCEM PQY | No |
| 6 | CFHJO UIF BUUBDL OPX | No |
| 7 | BEGIN THE ATTACK NOW | Yes |
| Stop | | |

- Maximum number of tries required? **26**



Shift Cipher

- Should not be vulnerable to such a **brute-force attack**.
- Else, it can be **completely broken**, irrespective of how **sophisticated** the encryption algorithm is.
- **Sufficient key space principle:** For secure encryption schemes the key space must not be vulnerable to exhaustive search.



Shift Cipher

- Should not be vulnerable to such a **brute-force attack**.
- Else, it can be **completely broken**, irrespective of how **sophisticated** the encryption algorithm is.
- **Sufficient key space principle:** For secure encryption schemes the key space must not be vulnerable to exhaustive search.
Note: Only true if $|\mathcal{P}| \geq |\mathcal{K}|$.



Shift Cipher

- Should not be vulnerable to such a **brute-force attack**.
- Else, it can be **completely broken**, irrespective of how **sophisticated** the encryption algorithm is.
- **Sufficient key space principle:** For secure encryption schemes the key space must not be vulnerable to exhaustive search.
Note: Only true if $|\mathcal{P}| \geq |\mathcal{K}|$.
- **Present Standard:** $|\mathcal{K}| \geq 2^{80}$.



Shift Cipher

- Should not be vulnerable to such a **brute-force attack**.
- Else, it can be **completely broken**, irrespective of how **sophisticated** the encryption algorithm is.
- **Sufficient key space principle:** For secure encryption schemes the key space must not be vulnerable to exhaustive search.
Note: Only true if $|\mathcal{P}| \geq |\mathcal{K}|$.
- **Present Standard:** $|\mathcal{K}| \geq 2^{80}$.
- **Note:** The above principle gives a **necessary condition** for security, not a **sufficient** one.



- Should not be vulnerable to such a **brute-force attack**.
- Else, it can be **completely broken**, irrespective of how **sophisticated** the encryption algorithm is.
- **Sufficient key space principle:** For secure encryption schemes the key space must not be vulnerable to exhaustive search.
Note: Only true if $|\mathcal{P}| \geq |\mathcal{K}|$.
- **Present Standard:** $|\mathcal{K}| \geq 2^{80}$.
- **Note:** The above principle gives a *necessary condition* for security, not a **sufficient** one.
- Our next scheme has a *very large key space* but is still **insecure**.



Substitute Cipher

Substitute Cipher

- $\mathcal{P} = C = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \Pi =$ All possible permutations of the symbols $\{A, B, C, \dots, Z\}$.



Substitute Cipher

Substitute Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \Pi =$ All possible permutations of the symbols $\{A, B, C, \dots, Z\}$.
- $\mathcal{G} : \pi \xleftarrow{R} \Pi$



Substitute Cipher

Substitute Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \Pi =$ All possible permutations of the symbols $\{A, B, C, \dots, Z\}$.
- $\mathcal{G} : \pi \xleftarrow{R} \Pi$
- $\mathcal{E} : c := \pi(m).$



Substitute Cipher

Substitute Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \Pi =$ All possible permutations of the symbols $\{A, B, C, \dots, Z\}$.
- $\mathcal{G} : \pi \xleftarrow{R} \Pi$
- $\mathcal{E} : c := \pi(m).$
- $\mathcal{D} : m := \pi^{-1}(c).$



Substitute Cipher

Example

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
| H | I | J | K | L | M | N | O | P | Q | R | S | T |

π :

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| N | O | P | Q | R | S | T | U | V | W | X | Y | Z |
| U | V | W | X | Y | Z | A | B | C | D | E | F | G |



Substitute Cipher

Example

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
| H | I | J | K | L | M | N | O | P | Q | R | S | T |

π :

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| N | O | P | Q | R | S | T | U | V | W | X | Y | Z |
| U | V | W | X | Y | Z | A | B | C | D | E | F | G |

- **Plaintext:** BEGIN THE ATTACK NOW.



Substitute Cipher

Example

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
| H | I | J | K | L | M | N | O | P | Q | R | S | T |

π :

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| N | O | P | Q | R | S | T | U | V | W | X | Y | Z |
| U | V | W | X | Y | Z | A | B | C | D | E | F | G |

- **Plaintext:** BEGIN THE ATTACK NOW.
- **Ciphertext:** $\pi(B)\pi(E)\pi(G)\dots = \text{ILNPU AOL HAAHJR UVD}$.



Substitute Cipher

- The Shift Cipher is a special case of the Substitution Cipher.
 - The Shift Cipher includes only 26 of the $26!$ possible permutations of 26 elements.



Substitute Cipher

- The Shift Cipher is a special case of the Substitution Cipher.
 - The Shift Cipher includes only 26 of the $26!$ possible permutations of 26 elements.
- In both the Shift Cipher and the Substitution Cipher, once a key is chosen, each alphabetic character is mapped to a unique alphabetic character. These type of cryptosystems are called **monoalphabetic cryptosystems**.



Cryptanalysis of Substitute Cipher

Assumptions

- English-language text is being encrypted.
- The text is in grammatically-correct English.



Cryptanalysis of Substitute Cipher

Assumptions

- English-language text is being encrypted.
- The text is in grammatically-correct English.

Attack Idea

- Use statistical patterns of the English language.
Note: The same attack works for any language.



Cryptanalysis of Substitute Cipher

Assumptions

- English-language text is being encrypted.
- The text is in grammatically-correct English.

Attack Idea

- Use statistical patterns of the English language.
Note: The same attack works for any language.
- The attack utilizes the following two properties of the cipher:
 1. The mapping of each letter is fixed, that is, $e \mapsto L$ for all occurrences of e in the plaintext.
 2. The probability distribution of individual letters is known.
 - The **average frequency counts** of the different English letters are quite **invariant** over different texts.



Cryptanalysis of Substitute Cipher

Statistical Properties of English Language

- Relative Frequencies of the 26 letters.
- Compiled from numerous novels, magazines and newspaper.
- The following table was obtained by [Beker and Piper](#).



Cryptanalysis of Substitute Cipher

Statistical Properties of English Language

- Relative Frequencies of the 26 letters.
- Compiled from numerous novels, magazines and newspaper.
- The following table was obtained by [Beker and Piper](#).

| Letter | Probability | Letter | Probability |
|--------|-------------|--------|-------------|
| A | 0.082 | N | 0.067 |
| B | 0.015 | O | 0.075 |
| C | 0.028 | P | 0.019 |
| D | 0.043 | Q | 0.001 |
| E | 0.127 | R | 0.060 |
| F | 0.022 | S | 0.063 |
| G | 0.020 | T | 0.091 |
| H | 0.061 | U | 0.028 |
| I | 0.070 | V | 0.010 |
| J | 0.002 | W | 0.023 |
| K | 0.008 | X | 0.001 |
| L | 0.040 | Y | 0.020 |
| M | 0.024 | Z | 0.001 |



Cryptanalysis of Substitute Cipher

Statistical Properties of English Language

- Statistical analysis gives us the following partition the 26 letters into five groups:
 - **E**: Having probability of about 0.120.
 - **T, A, O, I, N, S, H, R**: Probability between 0.06 and 0.09.
 - **D, L**: Probability around 0.04.
 - **C, U, M, W, F, G, Y, P, B**: Prob. between 0.015 and 0.028.
 - **V, K, J, X, Q, Z**: Probability less than 0.01.



Cryptanalysis of Substitute Cipher

Statistical Properties of English Language

- Statistical analysis gives us the following partition the 26 letters into five groups:
 - **E**: Having probability of about 0.120.
 - **T, A, O, I, N, S, H, R**: Probability between 0.06 and 0.09.
 - **D, L**: Probability around 0.04.
 - **C, U, M, W, F, G, Y, P, B**: Prob. between 0.015 and 0.028.
 - **V, K, J, X, Q, Z**: Probability less than 0.01.
- It is also useful to consider distributions **digrams** and **trigrams**.



Cryptanalysis of Substitute Cipher

Statistical Properties of English Language

- Statistical analysis gives us the following partition the 26 letters into five groups:
 - **E**: Having probability of about 0.120.
 - **T, A, O, I, N, S, H, R**: Probability between 0.06 and 0.09.
 - **D, L**: Probability around 0.04.
 - **C, U, M, W, F, G, Y, P, B**: Prob. between 0.015 and 0.028.
 - **V, K, J, X, Q, Z**: Probability less than 0.01.
- It is also useful to consider distributions **digrams** and **trigrams**.
- Some of the most **common digrams** (in decreasing order) are
 - TH, HE, IN, ER, AN, RE, ED, ON, ES, ST, EN, AT, TO, NT, HA, ND, OU, EA, NG, AS, OR, TI, IS, ET, IT, AR, TE, SE, HI, OF.



Cryptanalysis of Substitute Cipher

Statistical Properties of English Language

- Statistical analysis gives us the following partition the 26 letters into five groups:
 - **E**: Having probability of about 0.120.
 - **T, A, O, I, N, S, H, R**: Probability between 0.06 and 0.09.
 - **D, L**: Probability around 0.04.
 - **C, U, M, W, F, G, Y, P, B**: Prob. between 0.015 and 0.028.
 - **V, K, J, X, Q, Z**: Probability less than 0.01.
- It is also useful to consider distributions **digrams** and **trigrams**.
- Some of the most **common digrams** (in decreasing order) are
 - TH, HE, IN, ER, AN, RE, ED, ON, ES, ST, EN, AT, TO, NT, HA, ND, OU, EA, NG, AS, OR, TI, IS, ET, IT, AR, TE, SE, HI, OF.
- Some of the most **common trigrams** (in decreasing order) are
 - THE, ING, AND, HER, ERE, ENT, THE, ING, AND, HER, ERE, ENT, THA, NTH, WAS, ETH, FOR, DTH.



Cryptanalysis of Substitute Cipher

Ciphertext:

YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZCDM
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWYVZ
VYFZUMRZCRWNZDZJJXZWGCHSMRNMDHNCMFQCHZJMXJZWIEJYUCFWDJNZDIR



Cryptanalysis of Substitute Cipher

Ciphertext:

YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZCDM
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWYVZ
VYFZUMRZCRWNZDZJJXZWGCHSMRNMDHNCMFQCHZJMXJZWIEJYUCFWDJNZDIR

- **Tabulate the frequency distribution of characters:**
A appeared 0 times, B appeared 1 times, and so on
- Compare them with the known frequencies of English text.
- Guess parts of the mapping based on the observed frequencies.
Example: Guess E \mapsto most frequent character, and so on.



Cryptanalysis of Substitute Cipher

Ciphertext:

YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZCDM
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWYVZ
VYFZUMRZCRWNZDZJXZWGCHSMRNMDHNCFQCHZJMXJZWIEJYUCFWDJNZDIR

- **Tabulate the frequency distribution of characters:**
A appeared 0 times, B appeared 1 times, and so on
- Compare them with the known frequencies of English text.
- Guess parts of the mapping based on the observed frequencies.
Example: Guess E \mapsto most frequent character, and so on.
- **Note:** Some of the guesses may be **wrong**.



Cryptanalysis of Substitute Cipher

Ciphertext:

YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZCDM
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWYVZ
VYFZUMRZCRWNZDZJJXZWGCHSMRNMHDNCFQCHZJMXJZWIEJYUCFWDJNZDIR

- Tabulate the frequency distribution of characters:

A appeared 0 times, B appeared 1 times, and so on

- Compare them with the known frequencies of English text.
- Guess parts of the mapping based on the observed frequencies.
Example: Guess E \mapsto most frequent character, and so on.
- **Note:** Some of the guesses may be **wrong**.
- But enough of the guesses will be correct to enable relatively quick decryption.
- For quick decryption use other knowledge of English.
 - u generally follows q.
 - h is likely to appear between t and e.
 - The frequencies of *digrams* and *trigrams*.
 - ...



Cryptanalysis of Substitute Cipher

Empirical distribution

| Letter | Frequency | Letter | Frequency |
|--------|-----------|--------|-----------|
| A | 0 | N | 9 |
| B | 1 | O | 0 |
| C | 15 | P | 1 |
| D | 13 | Q | 4 |
| E | 7 | R | 10 |
| F | 11 | S | 3 |
| G | 1 | T | 2 |
| H | 4 | U | 5 |
| I | 5 | V | 5 |
| J | 11 | W | 8 |
| K | 1 | X | 6 |
| L | 0 | Y | 10 |
| M | 16 | Z | 20 |



Cryptanalysis of Substitute Cipher

Empirical distribution

| Letter | Frequency | Letter | Frequency |
|--------|-----------|--------|-----------|
| A | 0 | N | 9 |
| B | 1 | O | 0 |
| C | 15 | P | 1 |
| D | 13 | Q | 4 |
| E | 7 | R | 10 |
| F | 11 | S | 3 |
| G | 1 | T | 2 |
| H | 4 | U | 5 |
| I | 5 | V | 5 |
| J | 11 | W | 8 |
| K | 1 | X | 6 |
| L | 0 | Y | 10 |
| M | 16 | Z | 20 |

- Most frequencies (≥ 10).

| | |
|---------|-----------|
| Z - 20; | D - 13 |
| M - 16; | F, J - 11 |
| C - 15; | R, Y - 10 |



Cryptanalysis of Substitute Cipher

Initial guess: Let $\mathcal{E}(k, E) = Z$.

- We might expect that

C, D, F, J, M, R, Y (frequency ≥ 10 each)

are encryptions of (a subset of)

T, A, O, I, N, S, H, R.



Cryptanalysis of Substitute Cipher

Initial guess: Let $\mathcal{E}(k, E) = Z$.

- We might expect that

C, D, F, J, M, R, Y (frequency ≥ 10 each)

are encryptions of (a subset of)

T, A, O, I, N, S, H, R.

- But these frequencies really do not vary enough to tell us what the correspondence might be.



Cryptanalysis of Substitute Cipher

Initial guess: Let $\mathcal{E}(k, E) = Z$.

- So look at **diagrams** of the form $_Z$ or $Z_$.
- **DZ and ZW:** 4 times each.
NZ and ZU: 3 times each.
RZ, HZ, XZ, FZ, ZR, ZV, ZC, ZD and ZI: Twice each.



Cryptanalysis of Substitute Cipher

Initial guess: Let $\mathcal{E}(k, E) = Z$.

- So look at **diagrams** of the form $_Z$ or $Z_$.
- **DZ and ZW:** 4 times each.
NZ and ZU: 3 times each.
RZ, HZ, XZ, FZ, ZR, ZV, ZC, ZD and ZI: Twice each.
- Observations 1:
 - ZW occurs 4 times, WZ occurs 0 times.
 - W occurs less often than many other characters.
 - **Subsequent guesses:** $\mathcal{E}(k, D) = W$.



Cryptanalysis of Substitute Cipher

Initial guess: Let $\mathcal{E}(k, E) = Z$.

- So look at **diagrams** of the form $_Z$ or $Z_$.
- **DZ** and **ZW**: 4 times each.
NZ and **ZU**: 3 times each.
RZ, HZ, XZ, FZ, ZR, ZV, ZC, ZD and **ZI**: Twice each.
- Observations 1:
 - ZW occurs 4 times, WZ occurs 0 times.
 - W occurs less often than many other characters.
 - **Subsequent guesses:** $\mathcal{E}(k, D) = W$.
- Observations 2:
 - DZ occurs 4 times, ZD occurs 2 times.
 - With high probability, $\mathcal{D}(k, D) \in \{R, S, T\}$.
 - But it is not clear which of these 3 possibility is the correct one.



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W$.

- Observations 3:
 - ZRW occurs near the beginning of the ciphertext, and RW occurs again later on.
 - Since R occurs frequently in the ciphertext and ND is a common digram.
 - Subsequent guesses:

$$\mathcal{E}(k, N) = R.$$



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W$.

- Observations 3:
 - ZRW occurs near the beginning of the ciphertext, and RW occurs again later on.
 - Since R occurs frequently in the ciphertext and ND is a common digram.
 - Subsequent guesses:

$$\mathcal{E}(k, N) = R.$$

Partial Decryption:

```

-----END-----E-----NED-----E-----E-----
YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJB TXCDDUMJNDIFE FMDZCDM
-E-----N--D--EN-----E-----E-E--N-----N-----ED--E
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZW DYVZ
---E--NE-ND-E-E--ED-----N-----E-----ED-----D--
VYFZUMRZCRWNZDZJXZWGCHSMRNMDHNCMFQCHZJMXJZWIEJYUCFWDJ
-E--N
NZDIR
    
```



Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R$.

- Observations 4:
 - NZ is a common diagram and ZN is not.
 - Subsequent guesses:

$$\mathcal{E}(k, H) = N.$$



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R$.

- Observations 4:
 - NZ is a common diagram and ZN is not.
 - Subsequent guesses:

$$\mathcal{E}(k, H) = N.$$

Further Decryption:

-----END-----E-----NEDH---E-----H-----E-----
 YIFQFMZRWQFYVECFMDZPCVMRZWMDZVEJBTXCDDUMJNDIFEFMZCDM
 -E-----NH--D--EN---E-H--EHE---N-----N-----ED---E
 QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWDYVZ
 ---E--NE-NDHE-E--ED-----NH---H-----E---ED-----D--
 VYFZUMRZCRWNZDZJXZWGCHSMRNMDHNCMFQCHZJMXJZWIEJYUCFWDJ
 HE--N
 NZDIR



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = N$.

- Observations 5:
 - AND is a very common trigram.
 - **Subsequent guesses:** (from the segment NE - NDHE suggests)

$$\mathcal{E}(k, A) = C.$$



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = N$.

- Observations 5:
 - AND is a very common trigram.
 - **Subsequent guesses:** (from the segment NE - NDHE suggests)

$$\mathcal{E}(k, A) = C.$$

Further Decryption:

-----END-----E-----NEDH---E-----H-----E-----
 YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZDCDM
 -E-----NH--D--EN-----E-H--EHE---N-----N-----ED---E
 QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWVZ
 ---E--NE-NDHE-E--ED-----NH---H-----E---ED-----D--
 VYFZUMRZCRWNZDZJXZWGCHSMRNMHDNCFQCHZJMXJZWIEJYUCFWDJ
 HE--N
 NZDIR



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = N, \mathcal{E}(k, A) = C$.

Further Decryption:

-----END -----A --- E-A -- NEDH ---E ----- A ----- H -----EA ---
 YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZCDM
 - E - A --- A ---NHAD -A-EN -- A -E - H --- EHE -A - N ----- N ----- ED --- E
 QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWYVZ
 --- E -- NEANDHE - E -- ED -- A --- NH --- HA --- A - E --- ED ----- A -D ---
 VYFZUMRZCRWNZDZJXZWGCHSMRNMDHNCMFQCHZJMXJZWIEJYUCFWDJ
 HE - -N
 NZDIR



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, (H) = N, \mathcal{E}(k, A) = C$

- Observations 6: Consider M
 - Second most common ciphertext character.
 - Partial decryption of $\mathcal{D}(k, RNM) = NH-$, suggests that H- is the beginning of a word.
 - So M probably encrypts a vowel.



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, (H) = N, \mathcal{E}(k, A) = C$

- Observations 6: Consider M

- Second most common ciphertext character.
- Partial decryption of $\mathcal{D}(k, RNM) = NH-$, suggests that H- is the beginning of a word.
- So M probably encrypts a vowel.
- A and E are already accounted, then

$$\mathcal{D}(k, M) = I \text{ or } O.$$

- “AI” is a much more likely digram than “AO”
- Subsequent guesses: (from the digram CM)

$$\mathcal{E}(k, I) = M.$$



Cryptanalysis of Substitute Cipher

Guess: Let

$\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = N, \mathcal{E}(k, A) = C, \mathcal{E}(k, I) = M.$

Further Decryption:

-----IEND----- A - I - E - A - INE D H I - E ----- A ---- I - H ----- I - EA - - I
YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJB TXCDDUMJNDIFE FMDZCDM
- E - A --- A - I - -NHAD -A-EN -- A - E - H I - EHE -A - N ----- I N - I ---- ED --- E
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWDYVZ
--- E - I NEANDHE - E -- ED -- A -- I NH I -- -HA I -- A - E - I -- -ED ----- A - D --
VYFZUMRZCRWNZDZJXZWGCHSMRNMMDHNCMFQCHZJMXJZWIEJYUCFWDJ
HE - -N
NZDIR



Cryptanalysis of Substitute Cipher

Guess: Let

$\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = V, \mathcal{E}(k, A) = C, \mathcal{E}(k, I) = M.$

- O is a common plaintext character.
- Guess $\mathcal{E}(k, O) \in \{D, F, J, Y\}.$
- Y seems to be the most likely possibility.
- Otherwise,

$$\mathcal{D}(k, CFM) = \text{AOI}; \quad \text{if } \mathcal{E}(k, O) = F \text{ or}$$

$$\mathcal{D}(k, CJM) = \text{AOI}; \quad \text{if } \mathcal{E}(k, O) = J,$$

giving long strings of vowels in both cases.

- Hence, assume $\mathcal{E}(k, O) = Y.$



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = N, \mathcal{E}(k, A) = C, \mathcal{E}(k, I) = M, \mathcal{E}(k, O) = Y$.

- **Three most frequent ciphertext letters remaining:** D, F, J.
- **Conjecture:** $\{D, F, J\} = \{r, s, t\}$.
- Two occurrences of the trigram NMD suggest that

$$\mathcal{D}(k, D) = S \Rightarrow \mathcal{D}(k, NMD) = HIS.$$

- $\mathcal{D}(k, HNCMF) = -HAI-$ could be a decryption of **CHAIR**.
- Then let $\mathcal{D}(k, F) = R$ and $\mathcal{D}(k, H) = C$, which implies

$$\mathcal{D}(k, J) = T \quad [\text{By process of elimination}].$$



Cryptanalysis of Substitute Cipher

Guess: Let $\mathcal{E}(k, E) = Z, \mathcal{E}(k, D) = W, \mathcal{E}(k, N) = R, \mathcal{E}(k, H) = N, \mathcal{E}(k, A) = C, \mathcal{E}(k, I) = M, \mathcal{E}(k, O) = Y, \mathcal{E}(k, R) = F, \mathcal{E}(k, C) = H, \mathcal{E}(k, T) = J$.

Further Decryption:

O-R -R IEND - RO - -ARI SE - A - I NE D H I S E - -T - - - ASS - -ITHS -R-R I SE AS I
YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJB TXCDDUMJNDIFE FMDZCDM
- E - A -ORATIONHA DTA-EN - - ACE - H I - EHE - ASNT- OO - I N - I - O- REDSO - E
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZW DYVZ
- ORE - I NEANDHESETT- ED - -AC - I NH I SCHA I - - ACET I - -TED- -TO -ARDST
VYFZUMRZCRWNZDZJXZWGCHSMRNMMDHNCMFQCHZJMXJZWIEJYUCFWDJ
HES -N
NZDIR



Cryptanalysis of Substitute Cipher

Partially Decrypted Text

Further Decryption:

O-R -R IEND - RO - -ARI SE - A - I NE D H I S E - -T - - - ASS - -ITHS -R-R I SE AS I
YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZCDM
- E - A -ORATIONHA DTA-EN - - ACE - H I - EHE - ASNT- OO - I N - I - O- REDSO - E
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZW DYVZ
- ORE - I NEANDHESETT- ED - -AC - I NH I SCHA I - - ACET I- -TED- -TO -ARDST
VYFZUMRZCRWNZDZJXZWGCHSMRNM DHNCMFQCHZJMXJZWIEJYUCFWDJ
HES -N
NZDIR



Cryptanalysis of Substitute Cipher

Partially Decrypted Text

Further Decryption:

O-R -R IEND - RO - -ARI SE - A - I NE D H I S E - -T - - - ASS - -ITHS -R-R I SE AS I
YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJB TXCDDUMJNDIFE FMDZCDM
- E - A -ORATIONHA DTA-EN - - ACE - H I - EHE - ASNT- OO - I N - I - O- REDSO - E
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZW DYVZ
- ORE - I NEANDHESETT- ED - -AC - I NH I SCHA I - - ACET I - -TED- -TO -ARDST
VYFZUMRZCRWNZDZJXZWGCHSMRNM DHNCMFQCHZJMXJZWIEJYUCFWDJ
HES -N
NZDIR

Plaintext

Our friend from Paris examined his empty glass with surprise, as if evaporation had taken place while he wasn't looking. I poured some more wine and he settled back in his chair, face tilted up towards the sun.



Cryptanalysis of Substitute Cipher

Partially Decrypted Text

Further Decryption:

O-R -R IEND - RO - -ARI SE - A - I NE D H I S E - -T - - - ASS - -ITHS -R-R I SE AS I
YIFQFMZRWQFYVECFMDZPCVMRZWNMDZVEJBTXCDDUMJNDIFEFMZDCDM
- E - A -ORATIONHA DTA-EN - - ACE - H I - EHE - ASNT- OO - I N - I - O- REDSO - E
QZKCEYFCJMYRNCWJCSZREXCHZUNMXZNZUCDRJXYYSMRTMEYIFZWYVZ
- ORE - I NEANDHESETT- ED - -AC - I NH I SCHA I - - ACET I - -TED- -TO -ARDST
VYFZUMRZCRWNZDZJXZWGCHSMRNMMDHNCMFQCHZJMXJZWIEJYUCFWDJ
HES -N
NZDIR

Plaintext

Our friend from Paris examined his empty glass with surprise, as if evaporation had taken place while he wasn't looking. I poured some more wine and he settled back in his chair, face tilted up towards the sun.

Conclusion

Although the mono-alphabetic substitution cipher has a large key space, it is still *insecure*.



Vigenere Cipher (16'th Century, Rome)

- This cipher is named after Blaise de Vigenere.
- Poly-Alphabetic cipher.

Vigenere Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).



Vigener Cipher (16'th Century, Rome)

- This cipher is named after Blaise de Vigenere.
- Poly-Alphabetic cipher.

Vigener Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \{\text{keywords} \mid n \in \mathbb{N} \text{ and } \text{keywords} \in \{A, B, C, \dots, Z\}^n = \mathbb{Z}_{26}^n\}$.



Vigener Cipher (16'th Century, Rome)

- This cipher is named after Blaise de Vigenere.
- Poly-Alphabetic cipher.

Vigener Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \{\text{keywords} \mid n \in \mathbb{N} \text{ and } \text{keywords} \in \{A, B, C, \dots, Z\}^n = \mathbb{Z}_{26}^n\}$.
- \mathcal{E} : Let the key be a n character long keyword $k = k_0 k_1 \dots k_{n-1}$. If the plaintext is $m = m_0 m_1 m_2 \dots$, then we encrypt as

$$c_i := \left(m_i + k_{i \pmod n} \right) \pmod{26},$$

and $c = c_0 c_1 c_2 \dots$



Vigenere Cipher (16'th Century, Rome)

- This cipher is named after Blaise de Vigenere.
- Poly-Alphabetic cipher.

Vigenere Cipher

- $\mathcal{P} = \mathcal{C} = \{A, B, C, \dots, Z\}$ (English Alphabet).
- $\mathcal{K} = \{\text{keywords} \mid n \in \mathbb{N} \text{ and } \text{keywords} \in \{A, B, C, \dots, Z\}^n = \mathbb{Z}_{26}^n\}$.
- \mathcal{E} : Let the key be a n character long keyword $k = k_0 k_1 \dots k_{n-1}$. If the plaintext is $m = m_0 m_1 m_2 \dots$, then we encrypt is as

$$c_i := \left(m_i + k_{i \pmod{n}} \right) \pmod{26},$$

and $c = c_0 c_1 c_2 \dots$

- \mathcal{D} : Let the key be a n character long keyword $k = k_0 k_1 \dots k_{n-1}$. If the ciphertext is $c = c_0 c_1 c_2 \dots$, then we decrypt is as

$$m_i := \left(c_i - k_{i \pmod{n}} \right) \pmod{26},$$

and $m = m_0 m_1 m_2 \dots$



Vigener Cipher (16'th Century, Rome)

Example

- Let $n = 6$ and Keyword is $k = \text{CIPHER}$.



Vigener Cipher (16'th Century, Rome)

Example

- Let $n = 6$ and Keyword is $k = \text{CIPHER}$.
- **Plaintext:** THISCRYPTOSYSTEMISNOTSECURE.



Vigener Cipher (16'th Century, Rome)

Example

- Let $n = 6$ and Keyword is $k = \text{CIPHER}$.
- **Plaintext:** THISCRYPTOSYSTEMISNOTSECURE.

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T | H | I | S | C | R | Y | P | T | O | S | Y | S | T | E | M | I | S | N | O | T | S | E | C | U | R | E |
| C | I | P | H | E | R | C | I | P | H | E | R | C | I | P | H | E | R | C | I | P | H | E | R | C | I | P |
| V | P | X | Z | G | I | A | X | I | V | W | P | U | B | T | T | M | J | P | W | I | Z | I | T | W | Z | T |

- **Ciphertext:** VPXZGIXIVWPUBTTMJPWIZITWZT.



Cryptanalysis of Vigenere Cipher

Let n is known

- Make the matrix from the ciphertext $c = c_0c_1c_2 \dots$ as given below:

| | | | | |
|----------|------------|------------|----------|------------|
| c_0 | c_1 | c_2 | \dots | c_{n-1} |
| c_n | c_{n+1} | c_{n+2} | \dots | c_{2n-1} |
| c_{2n} | c_{2n+1} | c_{2n+2} | \dots | c_{3n-1} |
| c_{3n} | c_{3n+1} | c_{3n+2} | \dots | c_{3n-1} |
| \vdots | \vdots | \vdots | \vdots | \vdots |



Cryptanalysis of Vigenere Cipher

Let n is known

- Make the matrix from the ciphertext $c = c_0c_1c_2 \dots$ as given below:

| | | | | |
|----------|------------|------------|----------|------------|
| c_0 | c_1 | c_2 | \dots | c_{n-1} |
| c_n | c_{n+1} | c_{n+2} | \dots | c_{2n-1} |
| c_{2n} | c_{2n+1} | c_{2n+2} | \dots | c_{3n-1} |
| c_{3n} | c_{3n+1} | c_{3n+2} | \dots | c_{3n-1} |
| \vdots | \vdots | \vdots | \vdots | \vdots |

- All the ciphertext symbols of each column of the above table are encrypted by a single character.
- Find the most frequent character of each column and it most likely the encryption of E.
- For each column, the difference between most frequent character and E is the part of the key.



Cryptanalysis of Vigenere Cipher

Let n is unknown

- Repeat the above procedure for $n = 1, 2, 3, \dots$, until the decryption makes sense.



Cryptanalysis of Vigenere Cipher

Let n is unknown

- Repeat the above procedure for $n = 1, 2, 3, \dots$, until the decryption makes sense.
- More improved version: Use [Kasiski Test](#). (proposed by Friedrich Kasiski in 1863).
 - Charles Babbage discovered it in 1854.



Cryptanalysis of Vigenere Cipher

Let n is unknown

- Repeat the above procedure for $n = 1, 2, 3, \dots$, until the decryption makes sense.
- More improved version: Use [Kasiski Test](#). (proposed by Friedrich Kasiski in 1863).
 - Charles Babbage discovered it in 1854.
- Further improvement: Use of [Index of Coincidence](#) by William Friedman in 1920.

Rotor Machines (1870-1943)




Figure: The Hebern machine (Single Rotor)

Rotor Machines (1870-1943)




Figure: The Hebern machine (Single Rotor)

- Broken just using letter frequencies, diagrams and trigrams if sufficient ciphertexts are given.
- Key can be recovered.



Rotor Machines (1870-1943)



Figure: Most Famous Enigma (Three Rotor)



Figure: Example of Rotor

- Employed extensively by Nazi Germany during World War II.
- Was broken.
- **Alan Turing** was part of the team of those who broke Enigma.



Data Encryption Standard (1974)

- DES: 56 bit keys, 64-bit block size
- AES (2001)
- Salsa20 (2008) and so on.



Study At Home

- Affine cipher and its Cryptanalysis.
- Hill cipher and its Cryptanalysis.
- Permutation cipher and its Cryptanalysis.

End