

=====

PROXY ISSUANCE API - PARTNER INTEGRATION GUIDE

Version: 1.2 (Phase 1)

=====

OVERVIEW

This API lets registered partners issue and renew static-IP proxy credentials for supported brokers, check their wallet balance, look up broker pricing, look up details of a previously issued IP, and list available brokers. All endpoints are POST requests with a JSON body, and all responses are JSON.

Base URL:

UAT : <https://partners-uat.staticip.in>

Prod : <https://partners.staticip.in>

AUTHENTICATION

Every API call requires your partner credentials in the JSON body:

"partner_userid" : your partner ID (provided to you)

"partner_password" : your partner password (provided to you)

Additionally, calls must originate from your whitelisted IP address(es) on file with us. If your integration IP changes, let us know in advance or your calls will be rejected.

Every request is validated in this order. The first check that fails is the one you'll see in the "remark" field:

1. partner_userid exists
2. partner_password is correct
3. request is coming from a whitelisted IP
4. your account is active (not suspended)

HANDLING TIMEOUTS - order_id (IMPORTANT)

issue_ip and renew_ip are financial operations - if your connection drops or times out before you receive our response, you have NO WAY of knowing whether the IP was actually issued/renewed and your wallet charged, or whether it failed. To solve this:

- Every `issue_ip` and `renew_ip` call REQUIRES an "order_id" field: a string YOU generate that is unique per attempt (a UUID is fine).
- If you call `issue_ip/renew_ip` again with the SAME order_id, we will NOT re-run the transaction. We return the exact same response we computed the first time - so retrying after a timeout is always safe and can never double-issue an IP or double-charge your wallet.
- If you never got a response at all (e.g. your client timed out before reading it), call the new `/api/order_status` endpoint with that same order_id instead of blindly retrying - it returns whatever response we already computed.

Two important behaviors to understand:

- If `issue_ip/renew_ip` failed for a BUSINESS reason (invalid broker, insufficient funds, ip not available, etc.), that result is PERMANENT for that order_id. Retrying the same order_id will just replay the same failure - it will NOT re-check your balance or inventory. To try again after fixing the underlying issue (e.g. topping up your wallet), use a NEW order_id.
- If the failure was "proxy server error, please retry" (error_code 501 - an infrastructure problem on our side), that order_id is released, not locked. Retrying the SAME order_id will cause us to genuinely attempt the transaction again.
- A duplicate order_id that arrives WHILE the first attempt is still being processed (e.g. you fired two requests in parallel by mistake) gets error_code 601 - wait a moment and check `/api/order_status`.

ERROR CODES

Every failure response includes a stable numeric "error_code" alongside the human-readable "remark", for you to branch on programmatically instead of string-matching the remark text. Once assigned, a code's MEANING will never change - we'll only ever add new codes.

- 101 partnertid not found
- 102 partner password is wrong
- 103 request not received from whitelisted ip
- 104 partner is not active
- 201 brokername is not valid
- 202 validity is not permitted
- 301 ip not available
- 302 fund is not sufficient

401	ip_userid not found in database	(renew_ip)
501	proxy server error, please retry	(safe to retry same order_id)
601	order_id already in progress	(check order_status)
602	order_id not found	(order_status query)
999	unmapped/unexpected error	

COMMON RESPONSE FORMAT

Success:

```
{ "status": "success", "remark": "", ... additional fields ... }
```

Failure:

```
{ "status": "failed", "error_code": <int>, "remark": "<reason>" }
```

Some failures include extra fields for clarity (see "fund is not sufficient" under issue_ip / renew_ip below).

=====

1. ISSUE A NEW IP

=====

Endpoint: POST /api/issue_ip

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password",
  "order_id"       : "a-unique-id-you-generate-per-attempt",
  "brokername"     : "angel",
  "validity"       : 3,
  "iptype"         : "ipv4",
  "end_user_mobile" : "9999999999", (optional)
  "end_user_email"  : "enduser@x.com" (optional)
}
```

Field notes:

- order_id : REQUIRED. Your own unique ID for this attempt - see "HANDLING TIMEOUTS" above. Generate a new one for every new transaction you intend to make.
- brokername : must be one of the brokers returned by list_brokers.
- validity : number of MONTHS (integer). Each broker/iptype has a minimum required validity (e.g. 3 months) - if you

request less than the minimum, the call fails. Check current minimums and pricing via /api/broker_info.

- iptype : "ipv4" or "ipv6", depending on what's available/priced for that broker.

Successful response:

```
{
  "status": "success",
  "remark": "",
  "order_id": "a-unique-id-you-generate-per-attempt",
  "ip_details": {
    "hostname" : "dc-mum-001.staticip@in",
    "ip"       : "1.2.3.4",
    "port"     : 443,
    "ip_userid" : "partner_name_070726_angel_193356_8f5a",
    "ip_password": "DC311Qpnw46pZDxh",
    "validity"  : "07-10-2026"
  }
}
```

- Connect to the proxy using ip/port/ip_userid/ip_password. Port is always 443 for end-user connections.
- "validity" is the exact expiry date (DD-MM-YYYY) - calculated as exactly N calendar months from issue date (e.g. 3 months from 07-Jul becomes 07-Oct, not a fixed 90-day count).
- Cost = broker's per-month price x validity (months). This amount is deducted from your wallet immediately upon successful issue.
- SAVE the "ip_userid" - you will need it later to renew this IP.

Failure remarks (issue_ip):

"partnertid not found"	(error_code 101)
"partner password is wrong"	(error_code 102)
"request not received from whitelisted ip"	(error_code 103)
"partner is not active"	(error_code 104)
"brokername is not valid"	(error_code 201)
"validity is not permitted"	(error_code 202, below broker's minimum months)
"ip not available"	(error_code 301, no free IP left)
"fund is not sufficient"	(error_code 302, see below)
"order_id already in progress, check order_status"	(error_code 601)
"proxy server error, please retry"	(error_code 501,

safe to retry
same order_id -
nothing charged)

"fund is not sufficient" response includes extra fields so you know exactly how much you're short:

```
{
  "status": "failed",
  "error_code": 302,
  "remark": "fund is not sufficient",
  "order_id": "...",
  "available_fund": 400,
  "required_fund": 600
}
```

=====

2. RENEW AN EXISTING IP

=====

Endpoint: POST /api/renew_ip

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password",
  "order_id" : "a-unique-id-you-generate-per-attempt",
  "brokername" : "angel",
  "validity" : 1,
  "old_ip_userid" : "partner_name_070726_angel_193356_8f5a"
}
```

Field notes:

- order_id : REQUIRED, same rules as issue_ip - see "HANDLING TIMEOUTS" above.
- old_ip_userid : the "ip_userid" you received when this IP was originally issued (or from a previous renewal).
- validity : number of months to extend. Unlike issue_ip, there is NO minimum-month requirement for renewals - you can renew for just 1 month even if the broker's minimum for new issues is higher.
- Renewal extends from whichever is later: your current expiry date (if it hasn't passed yet) or today (if the IP already expired). You never lose remaining validity by renewing early.

Successful response:

```
{
  "status": "success",
  "remark": "",
  "order_id": "a-unique-id-you-generate-per-attempt",
  "ip_details": {
    "hostname"      : "dc-mum-001.staticip@in",
    "ip"           : "1.2.3.4",
    "updated_validity": "07-11-2026"
  }
}
```

Failure remarks (renew_ip): same auth/order_id/fund remarks as issue_ip, plus:

"ip_userid not found in database" (error_code 401 - old_ip_userid
doesn't match any issued IP)

=====

3. CHECK AN ORDER'S RESULT (order_status)

=====

Endpoint: POST /api/order_status

Use this if you called issue_ip or renew_ip and never received a response (timeout, dropped connection, etc.) - pass the SAME order_id you used on that call.

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password",
  "order_id"       : "the-order-id-you-used-earlier"
}
```

Response is whatever issue_ip/renew_ip would have returned for that order_id (see sections 1 and 2 above) - replayed exactly, including ip_userid/ip_password if it succeeded.

If the order_id was never seen for your account:

```
{
  "status": "failed",
  "error_code": 602,
```

```
"remark": "order_id not found",
"order_id": "the-order-id-you-used-earlier"
}
```

If we're still in the middle of processing it (rare - only happens in the brief window of the original call itself):

```
{
  "status": "processing",
  "remark": "order is still being processed, check again shortly",
  "order_id": "the-order-id-you-used-earlier"
}
```

=====

4. LIST AVAILABLE BROKERS

=====

Endpoint: POST /api/list_brokers

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password"
}
```

Successful response:

```
{
  "status": "success",
  "remark": "",
  "broker_list": ["angel", "alice", "zerodha"]
}
```

Failure remarks: standard auth remarks (101/102/103/104) only.

=====

5. BROKER PRICING / MINIMUM DURATION (broker_info)

=====

Endpoint: POST /api/broker_info

Returns full pricing and minimum-duration details per broker and IP type, so you can check current offerings before deciding what to request - useful during onboarding or before building your own pricing logic on top of ours.

NOTE (pricing is now TIERED by validity): the longer you commit to, the lower your per-month rate - "price_tiers" is a list of {min_month, price} entries. To find your rate for a given validity, pick the tier with the LARGEST min_month that is <= your requested validity. Example: tiers [{"min_month":1,"price":300}, {"min_month":3,"price":250}, {"min_month":6,"price":200}] means 1-2 months costs 300/mo, 3-5 months costs 250/mo, 6+ months costs 200/mo.

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password"
}
```

Successful response:

```
{
  "status": "success",
  "remark": "",
  "brokers": {
    "angel": {
      "ipv4": {"min_month": 3, "price_tiers": [{"min_month": 1, "price": 250}, {"min_month": 3, "price": 220}, {"min_month": 6, "price": 200}]},
      "ipv6": {"min_month": 1, "price_tiers": [{"min_month": 1, "price": 220}, {"min_month": 6, "price": 200}]}
    },
    "alice": { "...": "same shape" },
    "zerodha": { "...": "same shape" }
  }
}
```

- "min_month" is the minimum validity you must request on issue_ip for that broker/iptype (does NOT apply to renew_ip - see section 2).
- "price_tiers" - see the tier-selection rule above. Renewals are priced the same way, using the renewal's own validity.

Failure remarks: standard auth remarks (101/102/103/104) only.

```
=====
6. CHECK WALLET BALANCE
=====
Endpoint: POST /api/check_balance
```

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password"
}
```

Successful response:

```
{
  "status": "success",
  "remark": "",
  "balance": 400
}
```

Failure remarks:

```
"partnertid not found"                (error_code 101)
"partner password is wrong"           (error_code 102)
"request not received from whitelisted ip" (error_code 103)
```

=====

7. LOOK UP A PREVIOUSLY ISSUED IP (ip_info)

=====

Endpoint: POST /api/ip_info

Returns the details of an IP you previously issued/renewed, identified by its ip_userid - useful if you've misplaced the credentials or want to check whether it's still active.

Request body:

```
{
  "partner_userid" : "partner_id_1",
  "partner_password" : "your_password",
  "ip_userid"      : "partner_name_070726_angel_193356_8f5a"
}
```

Successful response:

```
{
  "status": "success",
  "remark": "",
  "ip_details": {
    "broker_name" : "angel",
    "ip"          : "1.2.3.4",
    "hostname"    : "dc-mum-001.staticip@in",
  }
}
```

```

    "ip_userid" : "partner_name_070726_angel_193356_8f5a",
    "ip_password" : "DC311Qpnw46pZDxh",
    "issued_date" : "2026-07-07 19:33:56",
    "validity" : "07-10-2026",
    "status" : "active",
    "last_action" : "issue"
  }
}

```

- "status" here is "active" or "expired", based on whether "validity" (the expiry date) has passed.
- "last_action" is "issue" or "renew" - whichever happened most recently for this ip_userid.
- You can only look up ip_userids that belong to YOUR account - an ip_userid issued to a different partner will return "ip_userid not found in database", the same as a genuinely unknown one.

Failure remarks:

```

"partnertid not found"                (error_code 101)
"partner password is wrong"           (error_code 102)
"request not received from whitelisted ip" (error_code 103)
"partner is not active"                (error_code 104)
"ip_userid not found in database"       (error_code 401)

```

=====

GENERAL NOTES

=====

- All dates are in DD-MM-YYYY format.
- All amounts are in your account's credit units (1 credit = 1 unit of wallet balance; pricing is per broker per month).
- ip_userid / ip_password are randomly generated per issue - do not try to construct or guess them.
- Every request you make (successful or not) is logged on our side with timestamp and source IP for audit purposes.
- Every issue_ip/renew_ip call requires a unique order_id - see "HANDLING TIMEOUTS" above before you integrate.

For any questions or to update your whitelisted IPs, contact us directly.

=====