With TF 1.0!



Lab I TensorFlow Basics

Sung Kim < hunkim+ml@gmail.com>

Code: https://github.com/hunkim/DeepLearningZeroToAll/



An open-source software library for Machine Intelligence


GET STARTED





We're excited to announce the release of TensorFlow 1.0! Check out the migration guide to upgrade your code with ease.

UPGRADE NOW



Dynamic graphs in TensorFlow

We've open-sourced TensorFlow Fold to make it easier than ever to work with input data with varying shapes and sizes.

LEARN MORE



The 2017 TensorFlow Dev Summit

Thousands of people from the TensorFlow community participated in the first flagship event. Watch the keynote and talks.

WATCH VIDEOS

https://www.tensorflow.org

Call for comments

Please feel free to add comments directly on these slides

Other slides: https://goo.gl/jPtWNt



TensorFlow

Deep learning libraries:
Accumulated GitHub metrics

100		
Aggr	egate po	pularity (30•contrib + 10•issues + 5•forks)•1e-3
#1:	172.29	tensorflow/tensorflow
#2:	89.78	BVLC/caffe
#3:	69.70	fchollet/keras
#4:	53.09	dmlc/mxnet
#5:	38.23	Theano/Theano
#6:	29.86	<pre>deeplearning4j/deeplearning4j</pre>
#7:	27.99	Microsoft/CNTK
#8:	17.36	torch/torch7
#9:	14.43	baidu/paddle
#10:	13.10	pfnet/chainer
#11:	12.37	NVIDIA/DIGITS
#12:	10.42	tflearn/tflearn
#13:	9.20	pytorch/pytorch

Deep learning libraries: growth over past three months

new	contributors	from 2016-10-09 to 2017-02-10	new	forks	from 2016-10-09 to 2017-02-10
#1:	192	tensorflow/tensorflow	#1:	6525	tensorflow/tensorflow
#2:	89	dmlc/mxnet	#2:	1822	BVLC/caffe
#3:	78	fchollet/keras	#3:	1316	fchollet/keras
#4:	42	baidu/paddle	#4:	999	dmlc/mxnet
#5:	29	Microsoft/CNTK	#5:	909	deeplearning4j/deeplearning4j
#6:	23	pfnet/chainer	#6:	887	Microsoft/CNTK
#7:	21	Theano/Theano	#7:	324	tflearn/tflearn
#8:	20	deeplearning4j/deeplearning4j	#8:	321	baidu/paddle
#9:	20	tflearn/tflearn	#9:	287	Theano/Theano
#10:	19	BVLC/caffe	#10:	257	torch/torch7
#11:	9	torch/torch7	#11:	175	NVIDIA/DIGITS
#12:	3	NVIDIA/DIGITS	#12:	142	pfnet/chainer

new	issues fr	om 2016-10-09 to 2017-02-10	aggr	egate m	metrics growth from 2016-10-09 to 2017-02-10
#1:	1563	tensorflow/tensorflow	#1:	54.01	tensorflow/tensorflow
#2:	979	fchollet/keras	#2:	18.71	fchollet/keras
#3:	871	dmlc/mxnet	#3:	16.38	dmlc/mxnet
#4:	646	baidu/paddle	#4:	12.86	BVLC/caffe
#5:	486	Microsoft/CNTK	#5:	10.17	Microsoft/CNTK
#6:	361	deeplearning4j/deeplearning4j	#6:	9.32	baidu/paddle
#7:	318	BVLC/caffe	#7:	8.75	deeplearning4j/deeplearning4j
#8:	217	NVIDIA/DIGITS	#8:	4.21	. Theano/Theano
#9:	214	Theano/Theano	#9:	3.89	tflearn/tflearn
#10:	167	tflearn/tflearn	#10:	3.14	NVIDIA/DIGITS
#11:	150	pfnet/chainer	#11:	2.90	pfnet/chainer
#12:	90	torch/torch7	#12:	2.46	torch/torch7



François Chollet Ofchollet · Feb 11

TensorFlow

 TensorFlow[™] is an open source software library for numerical computation using data flow graphs.


Python!



What is a Data Flow Graph?

5 (choler 682) 7 K
(tholer 682) 7 K

- Nodes in the graph represent mathematical operations
- Edges represent the multidimensional data arrays (tensors) communicated between them.



https://www.tensorflow.org/


Installing TensorFlow


- Linux, Max OSX, Windows
 - (sudo -H) pip install --upgrade tensorflow
 - (sudo -H) pip install --upgrade tensorflow-gpu
- From source
 - bazel ...
 - https://www.tensorflow.org/install/install sources
- Google search/Community help
 - https://www.facebook.com/groups/TensorFlowKR/

Check installation and version

```
Sungs-MacBook-Pro:hunkim$ python3
Python 3.6.0 (v3.6.0:41df79263a11, Dec 22 2016, 17:23:13)
[GCC 4.2.1 (Apple Inc. build 5666) (dot 3)] on darwin
Type "help", "copyright", "credits" or "license" for more
information.
>>> import tensorflow as tf
>>> tf. version
'1.0.0'
>>>
```

https://github.com/hunkim/DeepLearningZeroToAll/





TensorFlow Hello World!


```
# This op is added as a node to the default graph holy that.

seart a TF session

ss = tf.Session
In [2]: # Create a constant op
        # seart a TF session
sess = tf.Session() 스 설권을 하게 써진 한민 필요.
        # run the op and get result
        print(sess.run(hello)) hello 1242 427
        b) Hello, TensorFlow!'
```

b'String' 'b' indicates Bytes literals. http://stackoverflow.com/questions/6269765/

Computational Graph




```
In [4]: node1 = tf.constant(3.0, tf.float32)
        node2 = tf.constant(4.0) # also tf.float32 implicitly
        node3 = tf.add(node1, node2)
In [5]: print("node1:", node1, "node2:", node2)
        print("node3: ", node3)
        node1: Tensor "Const 1:0", shape=(), dtype=float32) node2: Tensor ("Const 2:0", shape=(), dtype
        e=float32)
        node3: Tensor / Add: 0", shape=(), dtype=float32)
                                                                     5) "YUM" 2 34421
In [6]: sess = tf.Session()
        print("sess.run(node1, node2): ", sess.run([hode1, node2]))
        print("sess.run(node3): ", sess.run(node3))
        sess.run(node1, node2): [3.0, 4.0]
        sess.run(node3): 7.0
```

https://github.com/hunkim/DeepLearningZeroToAll/blob/master/lab-01-basics.ipynb

TensorFlow Mechanics


feed data and run graph (operation) sess.run (op)

Build graph using TensorFlow operations



update variables in the graph (and return values)

Computational Graph



(1) Build graph (tensors) using TensorFlow operations

```
In [4]: node1 = tf.constant(3.0, tf.float32)
  node2 = tf.constant(4.0) # also tf.float32 implicitly
  node3 = tf.add(node1, node2)
```

(2) feed data and run graph (operation) sess.run (op)

(3) update variables in the graph (and return values)

```
In [6]: sess = tf.Session()
print("sess.run(node1, node2): ", sess.run([node1, node2]))
print("sess.run(node3): ", sess.run(node3))

sess.run(node1, node2): [3.0, 4.0]
sess.run(node3): 7.0
```

https://github.com/hunkim/DeepLearningZeroToAll/blob/master/lab-01-basics.ipynb

Placeholder

```
AND THE THE PARTY OF THE PARTY 
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       ) 电对象 对 对 数 312 34 5 312.
                                                         a = tf(placeholder(tf.float32)
In [7]:
                                                           b = tf.placeholder(tf.float32)
                                                          adder_node = a + b # + provides a shortcut for tf.add(a, b)
                                                           print(sess.run(adder node, feed dict={a: 3, b: 4.5})
                                                           print(sess.run(adder node, feed dict={a: [1,3], b: [2, 4]})
                                                          7.5
                                                                                                                                                                                                                                                                                                                到年, 那在风处水台。
                                                          [ 3. 7.]
```

TensorFlow Mechanics

feed data and run graph (operation) sess.run (op, feed_dict={x: x_data})

Build graph using TensorFlow operations



Everything is **Tensor**

```
Tensors

In [3]: 3 # a rank 0 tensor; this is a scalar with shape []
[1.,2.,3.] # a rank 1 tensor; this is a vector with shape [3]
[[1.,2.,3.], [4.,5.,6.]] # a rank 2 tensor; a matrix with shape [2, 3]
[[[1.,2.,3.]], [[7.,8.,9.]]] # a rank 3 tensor with shape [2, 1, 3]

Out[3]: [[[1.0,2.0,3.0]], [[7.0,8.0,9.0]]]
```

```
t = tf.Constant([1., 2., 3.])
```

Tensor Ranks, Shapes, and Types

```
t = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
```

Rank	Math entity	Python example
0	Scalar (magnitude only)	s = 483
1	Vector (magnitude and direction)	v = [1.1, 2.2, 3.3]
2	Matrix (table of numbers)	m = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
3	3-Tensor (cube of numbers)	t = [[[2], [4], [6]], [[8], [10], [12]], [[14], [16], [18]]]
n	n-Tensor (you get the idea)	••••

https://www.tensorflow.org/programmers_guide/dims_types

Tensor Ranks, Shapes, and Types

Rank	Shape	Dimension number	Example
0		0-D	A 0-D tensor. A scalar.
1	[D0]	1-D	A 1-D tensor with shape [5].
2	[D0, D1]	2-D	A 2-D tensor with shape [3, 4].
3	[D0, D1, D2]	3-D	A 3-D tensor with shape [1, 4, 3].
n	[D0, D1, Dn-1]	n-D	A tensor with shape [D0, D1, Dn-1].

https://www.tensorflow.org/programmers_guide/dims_types

Tensor Ranks, Shapes, and Types

```
t = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
```

Data type	Python type	Description
DT_FLOAT	tf. <mark>floa</mark> t32	32 bits floating point.
DT_DOUBLE	tf. <mark>floa</mark> t64	64 bits floating point.
DT_INT8	tf. <mark>int8</mark>	8 bits signed integer.
DT_INT16	tf. <mark>int1</mark> 6	16 bits signed integer.
DT_INT32	tf. <mark>int3</mark> 2	32 bits signed integer.
DT_INT64	tf. <mark>int6</mark> 4	64 bits signed integer.

- - -

TensorFlow Mechanics

feed data and run graph (operation)
sess.run (op, feed_dict={x: x_data})

Build graph using TensorFlow operations



update variables in the graph (and return values)