

Data Science With Python

L A Liggett

2019-12-11

Contents

1	Overview	7
2	Python	9
2.1	General	9
2.2	Numba	10
2.3	Cython	11
3	JupyterLab	13
4	Visualization	17
4.1	Color	17
4.2	Matplotlib	18
4.3	Seaborn	21
4.4	Statistics	22
4.5	Various Plot Styles	22
5	Biology	25
5.1	General	25
5.2	Biopython	25
5.3	UCSC Genome Browser	25
5.4	Ref Genome	26
5.5	Personal Information	26
5.6	GATK	27
5.7	Samtools	27

6	Data I/O	29
6.1	Reading Data Files	29
6.2	Pickles	29
7	Pandas	31
7.1	File I/O	31
7.2	Data Structure Creation	31
7.3	Selection	32
7.4	Splitting	33
7.5	Relabeling	35
7.6	Sorting and Arranging	35
7.7	Editing Data	36
7.8	Combining Data Structures	37
7.9	Summarizing	37
7.10	Arithmetic and Row/Column-wise Analysis	38
7.11	Restructuring DataFrames	39
8	Git	41
8.1	Setup	41
8.2	Manipulating Commits	42
8.3	Credential Caching	43
8.4	Errors	43
9	VIM	45
9.1	Formatting	45
9.2	Spellcheck	45
10	Web APIs	47
10.1	Ensembl	47
10.2	UCSC Genome Browser	48

<i>CONTENTS</i>	5
-----------------	---

11 Golang	49
------------------	-----------

11.1 Installation	49
11.2 Updating	49
11.3 Sample Program	50
11.4 Type conversion	50
11.5 Strings	51
11.6 Boolean Functions	52
11.7 Variables	52
11.8 Input	53
11.9 Control Structures	53
11.10Data Structures	54
11.11Functions	56
11.12While loops	58
11.13Timing a function	58
11.14Pointers	59
11.15Structures	59
11.16Methods	61
11.17Packaging	62
11.18Read/Write Files	62
11.19Math	64
11.20Concurrency	64

12 Bioinformatics Resources	67
------------------------------------	-----------

12.1 Cancer Datasets	67
12.2 Alzheimer's	68
12.3 Genome Resources	68
12.4 Genomic Datasets	68
12.5 Computing Tools	68
12.6 Microbiome Datasets	68
12.7 eQTL/RNASeq and other Tools	69
12.8 Cell Biology	69
12.9 Other Data Resources	69

Chapter 1

Overview

These are some notes that may be helpful for computational biology analysis that focuses on Python use.

Chapter 2

Python

2.1 General

Format strings are new in python 3 and are a different manner of using variables within a string.

```
name = 'Torpal'
print(f"hello, {name}!")
```

Values can also be passed to the string in a manner similar to python 2.

```
name = 'Torpal'
print("Hello {}".format(name))
```

Here is a general skeleton that can be used to start a python script that takes input.

```
#!/usr/bin/env python

def runArgparse():
    import argparse

    parser = argparse.ArgumentParser()
    parser.add_argument('--indir', '-i', type=str, nargs='*', help='Input directory containing the v')
    parser.add_argument('--loadolddata', '-o', action='store_true', help='Load previously existing da')

    args = parser.parse_args()
    indir = args.indir
    return indir
```

```
if __name__ == '__main__':  
    runArgparse()
```

2.2 Numba

Numba speeds up python code without having to switch to a different interpreter, and doesn't require static typing of variables as Cython does. Just calling Numba will increase the speed of a script (except during the compilation which will add some time). But this isn't the best way to take advantage of the speed boost.

Here is an example script that uses jit to invoke Numba.

```
#!/usr/bin/env python

from numba import jit
import numpy as np
import time

def go_slow(x):
    for i in range(14):
        x *= x

@jit(nopython=True)
def go_fast(x):
    for i in range(14):
        x *= x

# DO NOT REPORT THIS... COMPILATION TIME IS INCLUDED IN THE EXECUTION TIME!
start = time.time()
go_slow(5)
end = time.time()
print("Elapsed slow (with compilation) = %s" % (end - start))
start = time.time()
go_fast(5)
end = time.time()
print("Elapsed fast (with compilation) = %s" % (end - start))

# DO NOT REPORT THIS... COMPILATION TIME IS INCLUDED IN THE EXECUTION TIME!
start = time.time()
go_slow(5)
end = time.time()
print("Elapsed slow (after compilation) = %s" % (end - start))
```

```
start = time.time()
go_fast(5)
end = time.time()
print("Elapsed fast (after compilation) = %s" % (end - start))
```

Parallelization can be used to automatically utilize multiple cores.

```
from numba import njit, prange
@njit(parallel=True)
def prange_test(A):
    s = 0
    for i in prange(A.shape[0]):
        s += A[i]
    return s
```

2.3 Cython

Installation

```
conda install -c conda-forge cython
```

Ipython usage

```
%load_ext Cython

%%cython
def f(x):
    return 2 * x
or

def f(int x):
    return 2 * x

timeit(f(4))
```


Chapter 3

JupyterLab

By default, notebooks are not trusted, to prevent them from executing malicious code. The following code will label a notebook as trustworthy.

```
jupyter trust my_notebook.ipynb
```

Here is a simple template that I use that controls a couple useful things when starting a new notebook.

```
import sys
sys.path.append('../util')

%reload_ext autoreload
%autoreload 2

from util import *
import numpy as np
import pandas as pd
from matplotlib import pyplot as plt
import seaborn as sns

sns.set_palette('pastel')
sns.set_style('ticks')
sns.set_context('paper', font_scale=1)
```

It is often convenient to have a notebook automatically refresh the imported libraries so that they can be modified while working on a JupyterLab notebook.

```
%reload_ext autoreload
%autoreload 2
```

To allow directory organization, dependencies can be separated into different directories and imported into a jupyter notebook using the following import statement.

```
import sys
sys.path.append('../util')
```

This is a simplified way to create a table of contents.

```
# Table of Contents
1. [Introduction] (#Notebook-Setup)
2. [Parameters] (#Parameters)
3. [Sample Processing] (#Sample-Processing)
   1. [Variant Filtering] (#Variant-Filtering)
```

A table of contents can be created to refer to each of the headers throughout a notebook in html format. The code is below (Obviously needs to be simplified.)

```
<h1>Table of Contents<span class="tocSkip"></span></h1>
<div class="toc">
  <ul class="toc-item">
    <li>
      <span><a href="#Python-Setup" data-toc-modified-id="Python-Setup-1"><span class="toc-item">
        <ul class="toc-item">
          <li>
            <span><a href="#Change-the-width-of-the-page" data-toc-modified-id="Change-the-width-of-the-page-1.2">
              <ul>
                <li>
                  <span><a href="#Import-packages" data-toc-modified-id="Import-packages-1.2.1">
                    <ul>
                      <li></li>
                    </ul>
                  </li>
                <li>
                  <span><a href="#Colours" data-toc-modified-id="Colours-2"><span class="toc-item">
                    <ul class="toc-item">
                      <li></li>
                    </ul>
                  </li>
                <li><span><a href="#Colour-line-graph" data-toc-modified-id="Colour-line-graph-2.1">
                  </li>
                <li><span><a href="#Totals-for-studies" data-toc-modified-id="Totals-for-studies-3">
                <li><span><a href="#Functions-for-calculating-trinucleotide-context-specific-mutat
                  <ul class="toc-item">
                    <li><span><a href="#Calculating-mutation-rates-for-individual-variants" data-toc-modified-id="Calculating-mutation-rates-for-individual-variants-4">
                      <ul class="toc-item">
                        <li></li>
                      </ul>
                    </li>
                  </ul>
                </li>
              </ul>
            </li>
          </ul>
        </li>
      </li>
    </ul>
  </div>
```

```

<li><span><a href="#DNMT3A" data-toc-modified-id="DNMT3A-4.1.1"><span class="toc-item-num
  <li><span><a href="#TET2" data-toc-modified-id="TET2-4.1.2"><span class="toc-item-num
  <li><span><a href="#ASXL1" data-toc-modified-id="ASXL1-4.1.3"><span class="toc-item-r
  <li><span><a href="#TP53" data-toc-modified-id="TP53-4.1.4"><span class="toc-item-num
<li><span><a href="#Calculating-mutation-rates-from-a-csv-file-of-variants" data-toc-mod
  <ul class="toc-item">
    <li><span><a href="#DNMT3A" data-toc-modified-id="DNMT3A-4.2.1"><span class="toc-item
    <li><span><a href="#TET2" data-toc-modified-id="TET2-4.2.2"><span class="toc-item-num
    <li><span><a href="#ASXL1" data-toc-modified-id="ASXL1-4.2.3"><span class="toc-item-r
    <li><span><a href="#TP53" data-toc-modified-id="TP53-4.2.4"><span class="toc-item-num
<li><span><a href="#Calculating-mutation-rates-from-a-list-of-variants" data-toc-modified
  <ul class="toc-item">
    <li><span><a href="#DNMT3A" data-toc-modified-id="DNMT3A-4.3.1"><span class="toc-item
<li><span><a href="#TET2" data-toc-modified-id="TET2-4.3.2"><span class="toc-item-num">4
    <li><span><a href="#ASXL1" data-toc-modified-id="ASXL1-4.3.3"><span class="toc-item-r
    <li><span><a href="#TP53" data-toc-modified-id="TP53-4.3.4"><span class="toc-item-num
<li><span><a href="#Lists-of-variants-targeted-by-each-study" data-toc-modified-id="Lists-of-
  <li><span><a href="#Genovese-2014" data-toc-modified-id="Genovese-2014-5.2"><span class="
  <li><span><a href="#McKerrel-2015" data-toc-modified-id="McKerrel-2015-5.3"><span class="
  <li><span><a href="#Zink-2017" data-toc-modified-id="Zink-2017-5.4"><span class="toc-item
  <li><span><a href="#Coombs-2017" data-toc-modified-id="Coombs-2017-5.5"><span class="toc-
  <li><span><a href="#Young-2016-&-2019" data-toc-modified-id="Young-2016-&-2019-5
  <li><span><a href="#Desai-2018" data-toc-modified-id="Desai-2018-5.7"><span class="toc-it
  <li><span><a href="#Acuna-Hidalgo-2017" data-toc-modified-id="Acuna-Hidalgo-2017-5.8"><sp
<li><span><a href="#Lists-of-all-possible-variants-in-DNMT3A,-TET2,-ASXL1,-TP53" data-toc-mod
  <ul class="toc-item">
    <li><span><a href="#DNMT3A" data-toc-modified-id="DNMT3A-6.1"><span class="toc-item-num">
    <li><span><a href="#TET2" data-toc-modified-id="TET2-6.2"><span class="toc-item-num">6.2&
    <li><span><a href="#ASXL1" data-toc-modified-id="ASXL1-6.3"><span class="toc-item-num">6.
<li><span><a href="#TP53" data-toc-modified-id="TP53-6.4"><span class="toc-item-num">6.4&nbs
<li><span><a href="#Actual-number-of-observations-of-each-variant" data-toc-modified-id="Actu
  <ul class="toc-item">
    <li>
      <ul class="toc-item">
        <li><span><a href="#DNMT3A" data-toc-modified-id="DNMT3A-7.0.1"><span class="toc-item
        <li><span><a href="#TET2" data-toc-modified-id="TET2-7.0.2"><span class="toc-item-num
        <li><span><a href="#ASXL1" data-toc-modified-id="ASXL1-7.0.3"><span class="toc-item-num">
        <li><span><a href="#TP53" data-toc-modified-id="TP53-7.0.4"><span class="toc-item-num">7.
<li><span><a href="#Functions-for-calculating-the-expected-number-of-observations-of-a-varian
<li><span><a href="#Maximum-Likelihood-Estimation-for-s" data-toc-modified-id="Maximum-Likeli
  <ul class="toc-item"><li><span><a href="#DNMT3A-variants" data-toc-modified-id="DNMT3A-va
  <li><span><a href="#TET2-variants" data-toc-modified-id="TET2-variants-9.2"><span class="
  <li><span><a href="#ASXL1-variants" data-toc-modified-id="ASXL1-variants-9.3"><span class=
  <li><span><a href="#TP53-variants" data-toc-modified-id="TP53-variants-9.4"><span class="
</ul>

```

```
        </li>  
    </ul>  
</div>
```


Chapter 4

Visualization

4.1 Color

4.1.1 Colorschemes

Seaborn Themes

```
Pastel: {'Blue': '#a3c6ff', 'Orange': '#f7ab60', 'Green': '#60f7a9', 'Red': '#fc9d94', 'Purple': '#bea0e0'}
```

```
Deep: {'Green': '#5baf68'}
```

4.1.2 Controlling Coloration

Not all plots automatically plot with a white background, and when using something dark like jupyterlab or a presentation this can be frustrating. The background color can be set in pyplot like this.

```
fig.patch.set_facecolor('xkcd:mint green')
```

When plotting, samples will not always be colored with the same color, especially when different subsets of samples are included in different plots. Here is a manual workaround to specify the coloration of displayed data. This is a bit cumbersome so there might be a more elegant way of achieving the same outcome.

```

# here is an example where sample order is controlled from a pandas DataFrame
sample_order = all_vars.sort_values(['ID']).drop_duplicates(['Sample']).Sample

# the color order is specified here
# colors should be in the same order as the above sample_order Series, excluding sample
colors = [pastel['Brown'], pastel['Blue'],
          pastel['Orange'], pastel['Purple'],
          pastel['Green'], pastel['Red'],
          ]

plt.figure()
# this is an example of plotting that uses the sample_order and palette to control color
sns.catplot(x='Sample', y='VAF', hue='Gene', jitter=True,
            data=oncogenic[oncogenic.Location == 'Peripheral'],
            legend=False, order=sample_order, palette=sns.color_palette(colors))

# a colorscheme can be specified if desired
pastel = {'Blue': '#a3c6ff', 'Orange': '#f7ab60',
          'Green': '#60f7a9', 'Red': '#fc9d94',
          'Purple': '#bea3ff', 'Brown': '#d1b485',
          'Pink': '#f7afdf', 'Gray': '#c4c4c4',
          'Yellow': '#ffffaa', 'LBlue': '#baf6ff'}

# this controls the coloration in the legend
import matplotlib.patches as mpatches
egfr = mpatches.Patch(color=pastel['Blue'], label='EGFR')
pik3ca = mpatches.Patch(color=pastel['Orange'], label='PIK3CA')
myc = mpatches.Patch(color=pastel['Green'], label='MYC')

plt.legend(handles=[egfr,pik3ca,myc],
           loc='upper right', bbox_to_anchor=(1.5, 1),
           ncol=1) # no legend overlap

```

4.2 Matplotlib

Plot a straight line where `num_points` is the number of elements to populate the array with (default is 50).

```

x = np.linspace(x_min, x_max, num_points)
y = m * x + b
plt.plot(x, y, '-b')

```

Plotting a heatmap.

```
import matplotlib.pyplot as plt
import numpy as np
a = np.random.random((16, 16))
plt.imshow(a, cmap='RdBu', interpolation='nearest')
plt.show()
```

Possible heatmap colors are:

Accent, Accent_r, Blues, Blues_r, BrBG, BrBG_r, BuGn, BuGn_r, BuPu, BuPu_r, CMRmap, CMRmap_r, Dark2, Dark2_r, Set1, Set1_r, Set2, Set2_r, Set3, Set3_r, Spectral, Spectral_r, Wistia, Wistia_r, YlGn, YlGnBu, YlGnBu_r, gist_sern, gist_sern_r, gist_yarg, gist_yarg_r, gnuplot, gnuplot2, gnuplot2_r, gnuplot_r, gray, twilight, twilight_r, twilight_shifted, twilight_shifted_r, viridis, viridis_r, vlag, vlag_r, winter, winter_r

A simple venn diagram.

```
from matplotlib_venn import venn2
venn2(subsets = (3, 2, 1))
```

A more complicated venn diagram.

```
from matplotlib import pyplot as plt
import numpy as np
from matplotlib_venn import venn3, venn3_circles
plt.figure(figsize=(4,4))
v = venn3(subsets=(1, 1, 1, 1, 1, 1, 1), set_labels = ('A', 'B', 'C'))
v.get_patch_by_id('100').set_alpha(1.0)
v.get_patch_by_id('100').set_color('white')
v.get_label_by_id('100').set_text('Unknown')
v.get_label_by_id('A').set_text('Set "A"')
c = venn3_circles(subsets=(1, 1, 1, 1, 1, 1, 1), linestyle='dotted')
c[0].set_lw(1.0)
c[0].set_ls('dotted')
plt.title("Sample Venn diagram")
plt.annotate('Unknown set', xy=v.get_label_by_id('100').get_position() - np.array([0, 0.05]), xytext=(0.5, 0.5),
             ha='center', textcoords='offset points', bbox=dict(boxstyle='round,pad=0.5', fc='gray', lw=1),
             arrowprops=dict(arrowstyle='->', connectionstyle='arc3,rad=0.5',color='black'))
plt.show()
```

An upset plot is a nice alternative to a traditional venn diagram. The project is hosted [here](#), and this is the [documentation](#).

First install the library.

```
pip install upsetplot
```

Here is the code to create the plot.

```
import numpy as np

arrays = [[False,False,False,False,True,True,True,True],
          [False,False,True,True,False,False,True,True],
          [False,True,False,True,False,True,False,True]]
tuples = list(zip(*arrays))

def o(one=False, two=False, three=False):
    if three:
        temp = pd.merge(indels[(indels.Individual==one)], indels[(indels.Individual==three)], how='inner', on='ID')
        return len(pd.merge(temp, indels[(indels.Individual==two)], how='inner', on='ID'))
    elif two:
        return len(pd.merge(indels[(indels.Individual==one)], indels[(indels.Individual==two)], how='inner', on='ID'))
    elif one:
        return len(indels[(indels.Individual==one)])
    else:
        return 0

index = pd.MultiIndex.from_tuples(tuples, names=['Ind 1', 'Ind 2', 'Ind 3'])
s = pd.Series([o(),
               o(3),
               o(2),
               o(2,3),
               o(1),
               o(1,3),
               o(1,2),
               o(1,2,3)], index=index)

from upsetplot import plot as up
up(s)
plt.savefig("../images/indels.svg", format="svg", bbox_inches="tight")
```

Log scales seem to always be a challenge. Here is at least one solution to change ticks to log manually.

```
y_major_ticks = [np.log(100),np.log(200),np.log(300),np.log(400),np.log(500),np.log(600),
                  np.log(1000),np.log(2000),np.log(3000),np.log(4000),np.log(5000),np.log(6000),
                  np.log(10000),np.log(20000),np.log(30000),np.log(40000),np.log(50000),np.log(60000),
                  np.log(100000),np.log(200000),np.log(300000),np.log(400000),np.log(500000),np.log(600000),
                  np.log(1000000),np.log(2000000),np.log(3000000),np.log(4000000),np.log(5000000),np.log(6000000)]
```

```

np.log(10000000)]

y_major_tick_labels = ["100","", "", "", "", "", "", "", "", "", "1000","", "", "", "", "", "", "", "", "10,000", "\
                        "", "", "", "", "", "", "", "", "", "100,000","", "", "", "", "", "", "", "", "1,000,000","",
ax1.set_yticks(y_major_ticks)
ax1.set_yticklabels(y_major_tick_labels, fontsize = axisfont)
ax1.yaxis.set_tick_params(width=scale, color = grey3, length = 6)

```

4.3 Seaborn

Here is a general bar plot that includes some commonly used parameters.

```

# fits my 22 inch monitor
plt.figure(figsize=(19.17,11.98))
# order controls the display order of the samples
sns.catplot(x="Sample", y="Somatic", kind="bar", data=var_counts, order=labels);
# keeps x-axis labels, but eliminates the tick mark
plt.tick_params(labelbottom=True, bottom=False)
# trim off the x-axis
sns.despine(offset=10, trim=True, bottom=True)
# labels
plt.title('')
plt.ylabel('', fontsize=8)
plt.xlabel('', fontsize=8)
# manual control of xlabels
labels = ['Indiv_1-a', 'Indiv_2', 'Indiv_3', 'Indiv_1-b']
# control xtick order
plt.xticks(range(len(labels)), labels, rotation=45)
# control the number of x-ticks
plt.locator_params(axis='x', nbins=10)
# legend positioning
plt.legend(loc='upper right')
# log scale
plt.gca().set_yscale('log')
# this is better if neg values are needed
plt.gca().set_yscale('symlog')
# fit plot to display
plt.tight_layout()
plt.show()
# save figure with tight_layout
plt.savefig("test.svg", format="svg", bbox_inches="tight", dpi=1000)

```

Significance information can be added by including p-values and label bars using the following code.

```
x1, x2 = 0, 1 # columns to annotate on the plot
y2, y1 = 20, 15 # placement of the line and how far down the vertical legs go
plt.plot([x1,x1, x2, x2], [y1, y2, y2, y1], linewidth=1, color='k') # stats line
plt.text((x1+x2)*.5, y2+2, "p=0.09", ha='center', va='bottom', fontsize=8) # p-value o
```

Sometimes it is helpful to get the number of rows associated with a sample and plot that by sample. Here is a way to accomplish this.

```
counts = all_vars.Sample_Name.value_counts().reset_index()
counts = counts.rename(columns={'index': 'Sample_Name', 'Sample_Name': 'Var_Count'})

all_vars = pd.merge(all_vars, counts, how='inner', on=['Sample_Name'])
```

4.4 Statistics

This is a two-sided T-test for the null hypothesis that two populations have the same means. It is important to note that it assumes the population variances are the same, so this must be changed if the assumption is incorrect.

```
# ttest_ind(a, b, axis=0, equal_var=True, nan_policy='propagate')
from scipy.stats import ttest_ind
ttest_ind(df[df['sample'] == 'one']['means'], df[df['sample'] == 'two']['means'])
```

4.5 Various Plot Styles

This displays each individual datapoint overlayed on a boxplot

```
ax = sns.boxplot(x='day', y='total_bill', data=tips)
ax = sns.swarmplot(x='day', y='total_bill', data=tips, color='.25')
```

4.5.1 Countplot: Multiple Samples / Error Bars

The typical seaborn countplot appears to only perform counts for each sample or a total from multiple samples, and therefore will not group by sample and compute error over the samples. The following code will group samples by a particular column, then calculate counts for the data in another column, and then plot the counts with error bars, colored by another column.

```
# only retain somatic substitutions
substitutions = filtered[filtered.Change.str.len() == 3]
somatic = substitutions[substitutions.Group == 'Somatic']

# group mutations together by change
somatic = pd.DataFrame(somatic.groupby('Sample').Change.value_counts())
somatic.index = somatic.index.set_names(['Sample', 'Mut'])
somatic.reset_index(inplace=True)
somatic = somatic.rename(columns={'Mut': 'Change', 'Change': 'Count'})

# label data as clonal or typical
key = substitutions[['Sample', 'Clonality']].drop_duplicates('Sample')
somatic = pd.merge(somatic, key, how='left', on=['Sample'])

plt.figure()
sns.barplot(x='Change', y='Count', hue='Clonality', data=somatic)
plt.xticks(rotation=90)
pretty()
```


Chapter 5

Biology

5.1 General

Some helpful commands for genetic sequence.

```
from string import ascii_uppercase # python 3
from string import upper, lower # python 2
upper('tcga')
lower('TCGA')
title('tcga') # capitalize the first letter
```

5.2 Biopython

Reverse complement of sequence

```
from Bio.Seq import Seq
str(Seq(i).reverse_complement())
```

5.3 UCSC Genome Browser

Get sequence from UCSC genome browser

```
from subprocess import check_output, STDOUT
temp = check_output('wget -q0- http://genome.ucsc.edu/cgi-bin/das/hg19/dna?segment=%s:%s,%s' % (v
```

If the reference genome comes in the .2bit format, it is likely that it should then be converted to .fa format, and .2bittofa can accomplish this.

```
twoBitToFa refgenomes/hg19.2bit refgenomes/hg19.fa
```

The newly created .fa file will need to be indexed if it is to be used with gatk and bwa mem.

Here is an example of indexing where -a bwtsv specifies that we want to use the indexing algorithm that is capable of handling the whole human genome.

```
bwa index -a bwtsv reference.fa
```

Then create a file called reference.fa.fai, with one record per line for each of the contigs in the FASTA reference file. Each record is composed of the contig name, size, location, basesPerLine and bytesPerLine.

```
samtools faidx reference.fa
```

5.4 Ref Genome

Get sequence from reference genome

```
from subprocess import check_output, STDOUT
temp = check_output('samtools faidx %s %s:%s-%s' % (ref, vcfObj.chrom, low, high), stdout=STDOUT)

finalSeq = ''
for line in temp.decode('UTF-8').split('\n'):
    for line in temp.decode('UTF-8').split('\n'): # this is only necessary in python 3 to
        if '>' not in line:
            finalSeq += line

finalSeq = finalSeq.upper()
```

5.5 Personal Information

```
# parse vcf file with parseline
if '#' not in line and 'chr' in line: # skip the info
    # vcf handling
from parseline import VCFObj
# or
```

```
from util import VCFObj
vcfObj = VCFObj(vcfLine)
# available attributes: ao, dp, af, wt, var, chrom, location
```

5.6 GATK

The entire set of GATK software can be downloaded together [here](#).
Methods and algorithms as they are run at the Broad can be found [here](#).
The Broad also has a number of tutorials that introduce some of the software packaged within GATK.

5.6.1 Mutect2

A tutorial exists that introduces how Mutect2 can be used to call somatic mutations.
In general Mutect2 can be run as in the following.

```
../util/gatk-4.1.4.0/gatk Mutect2 -R /seq/references/Homo_sapiens_assembly38/v0/Homo_sapiens_asse
```

5.7 Samtools

Grab a single chromosomal region from a .bam file.

```
samtools view -b in.bam chr1 > in_chr1.bam
```


Chapter 6

Data I/O

6.1 Reading Data Files

Opening .gz files

```
import gzip
for line in gzip.open('myFile.gz'):
    print line
```

6.2 Pickles

Writing data in pickle format

```
import pickle
p = open('principle.pkl', 'wb')
pickle.dump(principleData, p)
p.close()
```

Reading data in pickle format

```
import pickle
p = open('principle.pkl', 'rb')
principleData = pickle.load(p)
p.close()
```


Chapter 7

Pandas

7.1 File I/O

Read a csv file into a DataFrame.

```
pd.read_csv(filepath)
```

Write a DataFrame to a file.

```
x.to_csv(path_or_buf='outputDir', sep='\n', header=False, index=False)
```

7.2 Data Structure Creation

Create a DataFrame.

```
frame = pd.DataFrame(np.random.randn(4,3), columns=list('bde'), index=['Utah','Ohio','Texas','Oregon'])
```

A DataFrame can conveniently be created from a dictionary.

```
import pandas as pd
data = {'AAA' : [4,5,6,7], 'BBB' : [10,20,30,40], 'CCC' : [100,50,-30,-50]}
df2 = pd.DataFrame(data=data, index=[1,2,3,4]) #Note index starts at 1.
df2
```

##	AAA	BBB	CCC
## 1	4	10	100
## 2	5	20	50
## 3	6	30	-30
## 4	7	40	-50

7.3 Selection

Is data within a DataFrame found within a dictionary or list? (Instead of a dictionary a series can be used and maybe another DataFrame)

```
import pandas as pd
df = pd.DataFrame({'A': [1, 2, 3], 'B': ['a', 'b', 'f']})
df.isin([1, 3, 12, 'a'])
```

```
##      A      B
## 0  True  True
## 1 False False
## 2  True False
```

```
df[df.isin([1, 3, 12, 'a'])]
```

```
##      A      B
## 0  1.0      a
## 1  NaN    NaN
## 2  3.0    NaN
```

Data within a DataFrame can be selected based on position within the DataFrame.

```
import pandas as pd
df2.iloc[1:3]
```

```
##      AAA  BBB  CCC
## 2      5   20   50
## 3      6   30  -30
```

Select data by the length of the strings in a given column.

```
df = df[df.Change.str.len() == 3]
```

Data within a DataFrame can be selected based on position within the DataFrame.

```
import pandas as pd
df2.loc[1:3]
```



```
##    AAA  BBB  CCC
## 1    4   10  100
## 2    5   20   50
## 3    6   30  -30
```

The opposite of matching data can be selected with the inverse operator.

```
df[~((df.AAA <= 6) & (df.index.isin([0,2,4])))]
```

7.4 Splitting

Concatenate two DataFrames together without dropping any values or renaming indices.

```
left = pd.concat([left, left])
```

Concatenate two DataFrames together without dropping values, but renaming index.

```
left = pd.concat([left, left], ignore_index=True)
```

Count the number of each unique value in a specified column.

```
left['key1'].value_counts()
left.key1.value_counts()
```

Value counts can also be calculated as percentages so that raw counts as percent makeup can be compared.

```
left['key1'].value_counts(normalize=True) * 100
```

Two DataFrames can be merged such that only the data containing matching keys is retained.

```
result = pd.merge(left, right, how='inner', on=['key1', 'key2'])
```

This DataFrame merge will retain all of the data in the right DataFrame.

```
result = pd.merge(left, right, how='right', on=['key1', 'key2'])
```

Filter by multiple columns.

```
df[(df.one == 1) & (df.two == 2)]
```

Filter by multiple columns but only return certain values.

```
# this just returns the data in column AAA
df = pd.DataFrame({'AAA' : [4,5,6,7], 'BBB' : [10,20,30,40], 'CCC' : [100,50,-30,-50]})
newseries = df.loc[(df['BBB'] < 25) & (df['CCC'] >= -40), 'AAA']
```

Filtering by values and using assignment will modify the original DataFrame.

```
df.loc[(df['BBB'] > 25) | (df['CCC'] >= 75), 'AAA'] = 0.1
```

Select multiple values from a particular column, where Letter is the column header.

```
df[df.Letter.isin(['a','b'])]
```

Use itertools to find combinations of data within a column of two DataFrames.

```
itertools.product(df1['a'], df2['a'])
```

Add data to a particular cell within a DataFrame.

```
df.loc[index,column]=num
```

Make a copy of a DataFrame.

```
df.copy(deep=True)
```

Iterate through a DataFrame.

```
for i in df.itertuples():
    pass
```

Change order of columns.

```
x = x.reindex(columns=['header','seq','plus','qual'])
```

Make a DataFrame from a dictionary

```
d = {'col1': [1, 2], 'col2': [3, 4]}
x = pd.DataFrame(d)
```

Sample from a DataFrame.

```
df.sample(frac=1)
df.sample(n=20, axis=1)
```

Append to a DataFrame.

```
df=df.append(newdf, ignore_index=True) # without ignore_index, the original indices will be used
```

Remove duplicates

```
x = x[~x.index.duplicated(keep='first')] # most ideal method

data = pd.DataFrame({'k1':['one','two']*3+['two'],'k2':[1,1,2,3,3,4,4]})
data.duplicated() # identify duplicate data
data['k1'].duplicated()
data['k1'].drop_duplicates()
data.drop_duplicates(['k1']) # this does the same thing as the previous line
data.drop_duplicates(['k1','k2'], keep='last') # drops unique found in k1 and k2 and keeps the last
```

Check if string is within strings in a given column

```
x[x['strLoc'].str.contains(region)]
```

7.5 Relabeling

Rename a column or group of columns can be done by passing a dictionary of the changes.

```
df = df.rename(columns={'a':'b','c':'d'})
```

7.6 Sorting and Arranging

The data in a DataFrame can be sorted in numeric or lexicographic order. The following code sorts the values within the columns a and b.

```
df.sort_values(['a', 'b'], ascending=False)
```

Set a column as the new index

```
x.set_index(['uniques'])
```

7.7 Editing Data

Drop columns from a DataFrame.

```
import numpy as np
df = pd.DataFrame(np.arange(12).reshape(3,4),
                  columns=['A', 'B', 'C', 'D'])
print(df)

df = df.drop(columns=['B', 'C']) # may not work in python 2
df = df.drop(['B', 'C'], axis=1) # this works in python 2
print(df)
```

Changing the datatype of a column of data can be done by just changing column type.

```
df.Age = df.Age.astype(str)
```

Replace values.

```
data = pd.Series([1., -999., 2., -999., -1000., 3.])
data.replace(-999, np.nan)
```

Substrings can be extracted from each row or column using the `str` functionality.

```
Series.str.slice(start=0, stop=7, step=1)
```

7.7.1 Replace Values

New data can be set within a DataFrame one subset at a time in a way that will avoid the `SettingWithCopyWarning`.

```
import pandas as pd
df = pd.DataFrame({'Trait': ['Seed_Shape', 'Seed_Shape', 'Flower_Color', 'Flower_Color'],
                  'Phenotype': ['Round', 'Wrinkled', 'Purple', 'White']})
df.loc[df.Trait == 'Seed_Shape', 'Affected_Part'] = 'Seed'
df.loc[df.Trait == 'Flower_Color', 'Affected_Part'] = 'Flower'
print(df)
```

```
##           Trait Phenotype Affected_Part
## 0    Seed_Shape    Round           Seed
## 1    Seed_Shape  Wrinkled           Seed
## 2  Flower_Color   Purple          Flower
## 3  Flower_Color   White          Flower
```

There is a more simple alternative to the above method but it may result in the `SettingWithCopyWarning`.

```
df = df.replace('pork', 'bacon')
```

7.8 Combining Data Structures

The following merges `df` and `df2` using `inner` to get the intersection on the `Sample` column, where indexes are ignored if the merging is performed on a column as in the following example. The other possible merging strategies are: `left`: use only keys from left frame, similar to a SQL left outer join; preserve key order. `right`: use only keys from right frame, similar to a SQL right outer join; preserve key order. `outer`: use union of keys from both frames, similar to a SQL full outer join; sort keys lexicographically. `inner`: use intersection of keys from both frames, similar to a SQL inner join; preserve the order of the left keys.

```
df = pd.merge(df, df2, how='inner', on=['Sample'])
```

Appending to a Dataframe attaches a DataFrame after another one.

```
df = pd.DataFrame([[1, 2], [3, 4]], columns=list('AB'))
df2 = pd.DataFrame([[5, 6], [7, 8]], columns=list('AB'))
df.append(df2)
```

7.9 Summarizing

The mean of column values can be calculated where each of the columns is grouped by the data in a specified column.

```
temp[['Sample', 'VAF', 'Var_Count']].groupby('Sample').mean()
```

7.9.1 Adding Classifier Columns

New columns can be added that describe the data in another column using some conditional statement.

```
df['Size'] = np.where(df['Height'] <= 5, 'Short', 'Tall')
```

7.10 Arithmetic and Row/Column-wise Analysis

Sometimes it is helpful to analyze the value in a particular cell in a conditional manner depending on its value and then set the result of this analysis to a corresponding cell in a new column. Here is an example where the VAF of a variant is conditionally analyzed.

```
def LOH(x):
    if x > 0.75: return 1 - x
    elif x <= 0.75 and x > 0.25: return abs(0.5 - x)
    else: return 0
all_vars['LOH'] = all_vars.VAF.transform(LOH)
max_loh = all_vars.groupby('Sample').LOH.max().reset_index().rename(columns={'LOH': 'Max_LOH'})
all_vars = pd.merge(all_vars, max_loh, how='inner', on=['Sample'])
```

Broadcasting arithmetic is an efficient method of calculating across an entire DataFrame.

```
frame = pd.DataFrame(np.arange(12.).reshape((4,3)), columns=list('bde'), index=['Utah', 'Idaho', 'Montana', 'Wyoming'])
series = frame.iloc[0]
frame - series
# the subtraction function could also be used
# frame.sub(series, axis='columns')
```

Apply a function to each row or column.

```
f = lambda x: x.max() - x.min()
frame.apply(f, axis='index')
```

Add two sets of data together, and use fill_value to avoid replacing any missing data with NaN.

```
x = pd.DataFrame([1,2,3], columns=list('0'))
y = pd.DataFrame([1,2,3], columns=list('1'))
x = x.add(y, fill_value=0)
```

Take the mean or std across specified columns and append as a new column. Below the DataFrame has columns 1-7 that will be used in computing the mean or std and this new data will be appended in a new column labeled 'Mean' or 'Std'.

```
x['Mean']=x[[1,2,3,4,5,6,7]].mean(axis=1)
x['Std']=x[[1,2,3,4,5,6,7]].std(axis=1)
```

7.11 Restructuring DataFrames

Converting between dataframes being structured to use “dummy” or “indicator” variables, and categorical variables is easy using pandas.

The following converts a DataFrame to use dummy/indicator variables.

```
df = pd.DataFrame({'A': ['a', 'b', 'a'], 'B': ['b', 'a', 'c'], 'C': [1, 2, 3]})
pd.get_dummies(df, prefix=['col1', 'col2'])
```

```
##      C  col1_a  col1_b  col2_a  col2_b  col2_c
## 0  1      1      0      0      1      0
## 1  2      0      1      1      0      0
## 2  3      1      0      0      0      1
```

The following converts a DataFrame that uses dummy/indicator variables to instead use categorical variables.

```
df = pd.DataFrame({'Blue':[1,0,0], 'Green':[0,1,1], 'Red':[0,0,0]}, index=['One', 'Two', 'Three'])
df.eq(1) @ df.columns
```

```
## One      Blue
## Two      Green
## Three    Green
## dtype: object
```


Chapter 8

Git

8.1 Setup

8.1.1 Git Setup

The username and email needs to be added after git is installed.

```
git config --global user.name "me"  
git config --global user.email "me@gmail.com"
```

After this information has been set, it can be checked.

```
git config --list
```

8.1.2 Repository Initiation

To setup a repository, create a folder with an initial file like a README and then initiate it.

```
git init  
git status
```

8.1.3 Mirror on Online Repository

Create a repository on a repository like github, gitlab, bitbucket, or sourceforge. Then the local git repository can be synched with the online repository.

```
git remote add origin url-of-online-repository-here  
git push -u origin master
```

Of course the repository could just be setup first and then cloned.

```
git clone url-of-online-repository-here
```

8.2 Manipulating Commits

8.2.1 Repository Status

The commit history of a repository can be displayed in verbose form and in summarized form.

```
git log  
git log --oneline
```

8.2.2 File Checkout

To restore a previous version of a file it can be checked out by first identifying the version to be used using the log history and then restoring the desired file.

```
git log --oneline  
git checkout <commit number> file.txt
```

8.2.3 Resetting a Repository

To discard the effect of the previous operation on a file.

```
git reset HEAD file.txt
```

The previous version of the a file can then be restored.

```
git checkout -- file.txt
```

8.2.4 Branching

Create a new branch.

```
git branch somenewfeature
```

All current branches can then be listed.

```
git branch
```

To then use the new branch, it needs to be checked out, and after checking it out, all changes will be specific to that new branch only.

```
git checkout somenewfeature
```

After committing changes to the new branch, if the branch is changed back to the master branch or another branch those changes will not longer be present as they are branch specific. If the changes should be merged back to the master branch checkout the master and then merge them in.

```
git checkout master
git merge feature
```

8.3 Credential Caching

Credential caching will allow the username and password to be stored so commits can be expedited.

```
git config credential.helper store
git push https://github.com/owner/repo.git
>>>>>> 325964ef5965c277600913d4433186ee42658f01

Username for 'https://github.com': <USERNAME>
Password for 'https://USERNAME@github.com': <PASSWORD>
```

To configure the caching to expire:

```
git config --global credential.helper 'cache --timeout 7200'
```

8.4 Errors

There is an error where objects in the repository get corrupted resulting in an error message like this: `object corrupt or missing: .git/objects/93/17fdbd6436bfaf7b0eeae2c56`.

To fix this error remove all of the corrupted objects until there are none left.

```
rm .git/objects/93/17fdbd6436bfaf7b0eeae2c56
```

There should then be plenty of remaining errors as the files are still missing, some of the errors may look like this: `dangling blob 750718546640b5b14c19cbdb9958d7bcc4b1114c`. At this point it should be possible to push/push the current repository.

```
git push origin master
```

Chapter 9

VIM

9.1 Formatting

Automatic newlines are inserted by default; this behavior can be overridden with the following.

```
:set wrap  
:set textwidth=0 wrapmargin=0
```

9.2 Spellcheck

To setup spellchecking first setup a personal dictionary file.

```
# make a directory for personal dictionary  
mkdir -p ~/.vim/spell/
```

Then refer to the dictionary file within VIM, and enable spellchecking.

```
# set personal dictionary  
:set spellfile=~/.vim/spell/en.utf-8.add  
# turn spellcheck on  
:set spell
```

Get spellcheck commands.

```
:help spell
```

Add a word to personal dictionary.

```
zg
```

Move to next and previous misspelled word.

```
]s  
[s
```

Get suggestions for misspelled word.

```
z=
```

Chapter 10

Web APIs

10.1 Ensembl

The Ensembl Rest API has a number of different genomics tools.

Here is an example where the Rest API is used to get the genomic locus and amino acid change using only the protein name and amino acid position and identities.

```
content-type=application/json
wget -q --header='Content-type:application/json' 'https://rest.ensembl.org/map/translation/ENSMUSP000000020991/878...879?'
```

Alternatively python can be used to make the same call.

```
import requests, sys

server = "https://rest.ensembl.org"
ext = "/map/translation/ENSMUSP000000020991/878...879?"

r = requests.get(server+ext, headers={ "Content-Type" : "application/json"})

if not r.ok:
    r.raise_for_status()
    sys.exit()

decoded = r.json()
print(repr(decoded))
```

Here are examples getting variant effect consequences of a particular mutation.

```
wget -q --header='Content-type:application/json' 'https://rest.ensembl.org/vep/mus_mus'
```

10.2 UCSC Genome Browser

Here is an example where human genomic regions are converted to the orthologous mouse regions. First the human sequence is obtained.

```
wget -O - http://genome.ucsc.edu/cgi-bin/das/hg38/dna?segment=%s:%s,%s >> locs\n' % (chr,
```

Then the above sequence is used in UCSC BLAT to find the orthologous region within mouse.

Chapter 11

Golang

11.1 Installation

Installation of linuxbrew

```
sh -c "$(curl -fsSL https://raw.githubusercontent.com/Linuxbrew/install/master/install.sh)"  
# Add to path  
test -d ~/.linuxbrew && eval "$(~/.linuxbrew/bin/brew shellenv)"  
test -d /home/linuxbrew/.linuxbrew && eval "$(home/linuxbrew/.linuxbrew/bin/brew shellenv)"  
test -r ~/.bash_profile && echo "eval \"\${$(brew --prefix)/bin/brew shellenv}\"" >> ~/.bash_profile  
echo "eval \"\${$(brew --prefix)/bin/brew shellenv}\"" >> ~/.profile  
# debian/ubuntu dependencies  
sudo apt-get install build-essential curl file git
```

LinuxBrew go lang installation

```
brew install go
```

The GO PATH should then be checked; it should typically exist at ~/go but it can be checked like this

```
echo $GOPATH
```

11.2 Updating

```
brew install dep
brew upgrade dep
brew cask install spotify
```

11.3 Sample Program

Create a file called hello.go

```
package main

import "fmt"

func main() {
    fmt.Printf("hello, world\n")
}
```

The program can just be run with
`go run main.go`

Then compile the program
`go build`

Importing multiple things can be done on one line separated by a semicolon
`import ("fmt"; "math")`

11.4 Type conversion

Check the type of a variable

```
import("fmt";"reflect")
i := 5
fmt.Println(reflect.TypeOf(i))
```

Convert int to float64

```
var i int = 5
j := float64(i)
```

Convert float64 to in

```
x := 4.0
int(x)
```

int to string

```
s := strconv.Itoa(97) // s == "97"
```

int64 to string

```
var n int64 = 97
s := strconv.FormatInt(n, 10) // s == "97" (decimal) in base 10
```

string to int

```
s := "97"
if n, err := strconv.Atoi(s); err == nil {
    fmt.Println(n+1)
} else {
    fmt.Println(s, "is not an integer.")
}
```

string to int64

```
s := "97"
n, err := strconv.ParseInt(s, 10, 64)
if err == nil {
    fmt.Printf("%d of type %T", n, n)
}
```

int to int64

```
var n int = 97
m := int64(n) // safe
```

11.5 Strings

Numbers can be converted to strings using strconv

```
s := strconv.FormatFloat(3.1415, 'E', -1, 64)
s := strconv.FormatInt(-42, 16)
```

Strings can be assigned with `' '` or `" "`, but only the double quotes can use escape characters like newlines or tabs

```
fmt.Println("Hello World\n")
```

Indexing returns bytes rather than strings so they must be converted if you want a string back

```
string("Hello World"[1])
```

Test if a string is a substring of another

```
import "strings"
strings.Contains("something","some") // true
```

11.6 Boolean Functions

`&&`, `||`, `!`, `true`, `false`

11.7 Variables

Variables are statically typed and therefore must be declared when assigned

```
var x string = "Hello World"
```

Type declaration can be offloaded to the compiler using the following notation, and the compiler will try to infer the correct type

```
var x = "Hello World"
x := "Hello World"
```

Constants are similar to variables, but their values cannot be reassigned

```
const x string = "Hello"
```

Multiple variables can also be declared at once, where each variable must occupy its own line

```
var (  
    a = 5  
    b = 10  
    c = 15  
)
```

Substrings

```
s := "something"  
fmt.Println(s[:len(s)-5])  
fmt.Println(s[2:6])
```

11.8 Input

User input

```
var input float64  
fmt.Scanf("%f", &input)
```

11.9 Control Structures

For loops can be written like the following

```
i := 1  
for i <= 10 {  
    fmt.Println(i)  
    i += 1  
}
```

The variables a function will return can be defined at the beginning of the functions and then implicitly returned.

```
func something(x int) (product int) {  
    product = x * x  
    return  
}
```

Probably the easier for loop is like this one

```
for i := 1; i <= 10; i++ {  
    fmt.Println(i)  
}
```

A nice for loop to iterate through a range

```
for i := range str1 {  
    if str1[i] == str2[i] { count++ }  
}  
return count
```

For loops can be used to iterate through slices too

```
for _, num := range nums {
```

If loops look gross, but it is required that the else statement is placed where it is shown here

```
if true {  
} else if false {  
}
```

Switches are also a thing

```
switch input {  
    case 1: fmt.Println("You entered one")  
    case 2: fmt.Println("You entered two")  
    case 3: fmt.Println("You entered three")  
}
```

11.10 Data Structures

A blank array

```
var x []int
```

An array with five elements

```
var x [5]int  
x[0] = 50 // the first element of the array equals 50
```

An easier way to create an array and can be multiline broken by the commas

```
x := [5]float64{ 98, 93, 77, 82, 83 }
```

Slices can have variable lengths and are typically associated with an array of fixed length. The following slice is 5 elements long, and is a segment of a 10 element-long array

```
x := make([]float64, 5, 10)
```

In a way that seems more similar to python, slicing an array can be done like this

```
arr := [5]float64{1,2,3,4,5}
x := arr[0:2]
```

Adding data to a slice

```
slice1 := []int{1,2,3}
slice2 := append(slice1,4,5)
```

Or multiple values can be added at once

```
s = append(s, 2, 3, 4)
```

A map is an unordered collection of key-value pairs (also known as a dictionary). A map is defined by assigning it to a variable and then defining the key type in brackets and the value type after the brackets

```
var x make(map[string]int)
x["key"] = 10
fmt.Println(x)
```

Creating a map with multiple items simultaneously

```
elements := map[string]string{
    "H": "Hydrogen",
    "He": "Helium",
    "Li": "Lithium",
}
```

Items can be deleted from a map using the delete function

```
delete(x, "key")
```

Go provides functionality that checks whether a key lookup from a map was successful or not

```
m,n := x["unknown"] // this key does not exist
fmt.Println(m,n) // m will equal 0 and n will equal false
```

This check can be used in an if loop to only run a chunk of code if a key exists within a map. In the below code `el` equals the value and `ok` is true or false, if the key is found, `ok` equals true and the print statement is run

```
if el, ok := elements["Li"]; ok {
    fmt.Println(el["name"], el["state"])
}
```

Iterate through a map

```
for k, v := range kmers {
    fmt.Printf("key: %s value: %d\n", k, v)
}
```

11.11 Functions

Below is a basic function that computes the mean of a map

```
func average(xs []float64) (float64) {
    total := 0.0
    for _, v := range xs {
        total += v
    }
    return total / float64(len(xs))
}
```

A function can also take multiple different types of variables

```
func lots_of_stuff(a int, b map[string]int64, c float64) (string, string, int64) {
    // do stuff
}
```

If it is desirable that a function takes maps of variable lengths a function can be designed like the one below


```
func add(args ...int) int {  
    total := 0  
    for _, v := range args {  
        total += v  
    }  
    return total  
}
```

Functions can also be placed within other functions like this

```
func main() {  
    add := func(x, y int) int {  
        return x + y  
    }  
    fmt.Println(add(1,1))  
}
```

Closure refers to functions that utilize non-local variables

```
func main() {  
    x := 0  
    increment := func() int {  
        x++  
        return x  
    }  
    fmt.Println(increment())  
    fmt.Println(increment())  
}
```

Recursion uses the same function recursively

```
// a recursive function  
func factorial(x uint) uint {  
    if x == 0 {  
        return 1  
    }  
    return x * factorial(x-1)  
}
```

Deferring essentially moves a function call to the end of a function, like the following which closes the file after it is used

```
f, _ := os.Open(filename)
defer f.Close()
```

11.12 While loops

These are not actually included in golang as in other languages but instead utilize for loops.

This is a repeat-until loop:

```
for {
    work()
    if condition {
        break
    }
}
```

or

```
for ok := true; ok; ok = !condition {
    work()
}
```

A do-while loop

```
for {
    work()
    if !condition {
        break
    }
}
```

or

```
for ok := true; ok; ok = condition {
    work()
}
```

11.13 Timing a function

```
start := time.Now()
t := time.Now()
elapsed := t.Sub(start)
fmt.Println(elapsed)
```

11.14 Pointers

Pointers can be used to access the memory location of a variable and alter the value stored in that location

```
func zero(xPtr *int) {
    *xPtr = 0 // asterisk signifies a pointer
}

func main() {
    x := 5
    zero(&x) // & finds the address of a variable
    fmt.Println(x) // using a pointer allows the value to be changed
}
```

There is a built in function called `new` that takes a type as an argument, and allocates sufficient memory to hold that type and returns a pointer to it, and unlike other languages, because go is a garbage collected language, it will delete anything created by `new` when nothing refers to it anymore

```
func one(xPtr *int) {
    *xPtr = 1
}

func main() {
    xPtr := new(int)
    one(xPtr)
    fmt.Println(*xPtr)
}
```

11.15 Structures

These seem similar to classes and allow a new ‘type’ to be created

```
type Circle struct {  
    x float64  
    y float64  
    r float64  
  
    // values of the same type can be combined like this  
    x, y, r float64  
}
```

A new structure can be created just like a typical variable

```
var c Circle
```

A structure can be created like pointers which will set all values to their zero value like 0, 0.0, "" and return a pointer

```
c := new(Circle)
```

Values for a structure can also be defined at variable creation time

```
c := Circle{x: 0, y: 0, r: 5}  
// this is possible if you remember the order vars were defined  
c := Circle{0, 0, 5}
```

Structure fields are accessed like class methods

```
fmt.Println(c.x, c.y, c.r)  
c.x = 10  
c.y = 5
```

When passing a structure to another function, its type is the name of the structure

```
func circleArea(c Circle) float64 {  
    return math.Pi * c.r * c.r  
}
```

Fields of a structure that has been defined are not altered unless a pointer is used

```
func circleArea(c *Circle) float64 {  
    c.r = 10  
    return math.Pi * c.r * c.r  
}
```

```

}

func main() {
    c:= Circle{0, 0, 5}
    fmt.Println(circleArea(&c), c)
}

```

11.16 Methods

These can be added to structures so they can be directly accessed by automatically passing a pointer to the method. The `area()` receiver can be used for other structures, and does not have to be a unique word

```

type Circle struct {
    x, y, r float64
}

func (c *Circle) area() float64 {
    return math.Pi * c.r * c.r
}

func main() {
    c:= Circle{0, 0, 5}
    fmt.Println(c.area())
}

```

Embedded Types is sort of like inheritance and gives a method access to all of the features of another structure.

Here is a person structure

```

type Person struct {
    Name string
}

func (p *Person) Talk() {
    fmt.Println("Hi, my name is", p.Name)
}

```

Here Android is defined to have the same properties as the person structure

```

type Android struct {
    Person
    Model string
}

```

```
}

a := new(Android)
a.Talk()
```

11.17 Packaging

Building code into a package is a convenient way of then accessing the same methods without having to rebuild them.

To create a package, make a folder with the same name as the package so **math** in this case. Then refer to the package name in a file within this folder like this: package math

```
func Average(xs []float64) float64 {
    total := float64(0)
    for _, x := range xs {
        total += x
    }
    return total / float64(len(xs))
}
```

Then save this file and build it from the same directory using:

```
go install
```

Finally, use this package by referring to its directory like this:

```
package main

import "fmt"
// import "chapter11/math" //this format can be used if put in ~/go/src/
import "./math"

func main() {
    xs := []float64{1,2,3,4}
    avg := math.Average(xs)
    fmt.Println(avg)
}
```

11.18 Read/Write Files

Here is how a file is opened

```
f, err := os.Open("./data/genomes/schisto_small.fa")
check(err)
f.Close() // when done

func check(e error) {
    if e != nil {
        panic(e)
    }
}
```

In Go 2.0 the `try` function can be used to open files a bit more elegantly. Instead of this:

```
f, err := os.Open(filename)
if err != nil {
    return ..., err
}
```

Opening is simplified to this:

```
f := try(os.Open(filename))
```

Read by a certain number of bytes at a time

```
b1 := make([]byte, 61)
n1, err := f.Read(b1)
check(err)
fmt.Printf("%d bytes: %s\n", n1, string(b1))
```

Peek might be more efficient with many small read calls but reads next `n` bytes without advancing the reader

```
r4 := bufio.NewReader(f)
b4, err := r4.Peek(61)
check(err)
fmt.Printf("5 bytes: %s\n", string(b4))
```

Scanners are useful ways to read newline delimited files

```
scanner := bufio.NewScanner(f)
for scanner.Scan() {
    fmt.Println(scanner.Text()) // Println retains the \n
}
```

```
if err := scanner.Err(); err != nil {
    fmt.Fprintln(os.Stderr, "reading standard input:", err)
}
```

Read from gzip file

```
import("compress/gzip")
file, err := os.Open("./data/genomes/schisto_small_2.fa.gz")
f, err := gzip.NewReader(file)
```

11.19 Math

Absolute value is pretty easy if using a float64

```
import("math")

x := -4.0
math.Abs(x)
```

Now, it seems to be super annoying to calculate the absolute value of an int.

```
import("math")

x := -5
int(math.Abs(float64(x)))
```

11.20 Concurrency

11.20.1 Goroutines

Goroutines are lightweight threads that are managed by the Go runtime, and are run concurrently in the same address space as other function calls.

```
package main

import (
    "fmt"
    "time"
)
```



```
func say(s string) {
    for i := 0; i < 5; i++ {
        time.Sleep(100 * time.Millisecond)
        fmt.Println(s)
    }
}

func main() {
    go say("world")
    say("hello")
}
```

11.20.2 Channels

Channels are a typed conduit through which values can be sent and received. They function with the `<-` operator.

```
ch <- v    // Send v to channel ch.
v := <-ch  // Receive from ch, and
           // assign value to v.
```

The default function of a channel is to block communication until both sides are ready.

In the example below, the sum of the first and last three values in an array are calculated separately and then added together when both goroutines have completed.

```
package main

import "fmt"

func sum(s []int, c chan int) {
    sum := 0
    for _, v := range s {
        sum += v
    }
    c <- sum // send sum to c
}

func main() {
    s := []int{7, 2, 8, -9, 4, 0}

    c := make(chan int)
```

```
go sum(s[:len(s)/2], c)
go sum(s[len(s)/2:], c)
x, y := <-c, <-c // receive from c

fmt.Println(x, y, x+y)
```

Unlike typical channels, buffered channels only block receiving communication when the number of slots are full.

In the below example, the buffered channel has room for two values, receives those two values and then prints them in order.

```
package main

import "fmt"

func main() {
    ch := make(chan int, 2)
    ch <- 1
    ch <- 20000

    x := <- ch
    fmt.Println(x)
    fmt.Println(<-ch)
}
```

Chapter 12

Bioinformatics Resources

12.1 Cancer Datasets

- CancerMine is a site that mines publication data to create a database of mutations labeled as drivers, oncogenes, or tumor suppressors. These classifications may help to understand the evolution of different cancers.
- The Cancer Cell Line Encyclopedia has a wealth of information from a large number of cancer cell lines.
- Project score has a number of genetic screens that may be useful in identifying pathways that are critical to cancer growth and survival
- cbiportal has information about codon changes in cancer but does not seem to have any sequence data
- dbGAP has info on genotypes and phenotypes, whatever the fuck that means
 - Here is the page with instructions on how to get dbGAP access
- TCGA
 - This page has the instructions on how to get TCGA access
- COSMIC
 - Cosmic has a project called the Cancer Gene Census in which they are trying to catalog all mutations that have been implicated in playing a causal role in cancer
 - They also have implemented convenient ways of directly downloading information and files from the database in python using the files hosted here.
- Mastermind from genomenon parsed all the articles on pubmed in order to find any and all information for each possible mutation

- GTEx has RNA-Seq, Exome Seq, WGseq, SNP arrays, gene expression arrays and more for cancer and non-cancer?
- TARGET is a dataset at the NIH that has childhood cancer data.

12.2 Alzheimer's

- The Alzheimers sequencing project is gathering data to understand late onset alzheimer's

12.3 Genome Resources

- Jax has a human to mouse gene matching list that provides gene location matching between human and mouse
- UCSC genome browser has an API for programmatic access

12.4 Genomic Datasets

- AllOfUs is sequencing and collecting other health data on a million individuals
- Color Genomics is one of three companies that will be doing the sequencing and testing for AllOfUs
- 1000 genomes
- 100,000 genomes
- TOPMed has a large number of samples spanning a number of different studies that include whole genome sequencing which can be helpful for understanding clonal dynamics in CHIP.

12.5 Computing Tools

- AWS looks like it has some healthcare and life sciences resources

12.6 Microbiome Datasets

- The Human Microbiome Project Data Portal from Michael Snyder's group has longitudinal 'omics data that includes diseased and healthy timepoints.
- Michael Snyder's iPOP Personal 'Omics Profiling has some interesting microbiome data specifically targeted to understanding diabetes.

- People respond differently to different drugs, and this appears to in part be due to the differential drug metabolism of their gut microbiome. Some of the differences can be observed when different strains of gut bacteria are isolated and directly exposed to drug to understand how the drugs are differentially metabolized (Zimmermann et al., 2019). The bacterial sequencing data is available here, and some of the extra drug screening data is available here.
- Multi-omics of Crohn's and ulcerative colitis can be found as part of the Integrative Human Microbiome Project.

12.7 eQTL/RNASEq and other Tools

- Here are a good number of general tools to check out
- Here is a good python eQTL analysis
- genenetwork2 has a great deal of data and eQTL mapping tools
- The Eske Derks lab has some hosted data that walks through how to properly run a GWAS analysis (Marees et al., 2018).

12.8 Cell Biology

- HuBMAP is a group that is organizing tissues at the single-cell scale to map tissues and organisms spatially.

12.9 Other Data Resources

- The Earth Microbiome Project already has data available, and is trying to sequence all non-eukaryotic life on earth
 - They have detailed information about the project in their PNAS paper from 2018
- Information is Beautiful has some interesting datasets

Bibliography

- Marees, A. T., de Kluiver, H., Stringer, S., Vorspan, F., Curis, E., Marie-Claire, C., and Derks, E. M. (2018). A tutorial on conducting genome-wide association studies: Quality control and statistical analysis. *Int. J. Methods Psychiatr. Res.*, 27(2):e1608.
- Zimmermann, M., Zimmermann-Kogadeeva, M., Wegmann, R., and Goodman, A. L. (2019). Mapping human microbiome drug metabolism by gut bacteria and their genes. *Nature*, page 1.