
INTERIM PROGRESS REPORT

on

A Survey of Deep Learning-Based Reconstruction Methods for Quantum Imaging Systems

Submitted by

Oishik Kar

23BCS089 B.Tech, Computer Science and Engineering

Indian Institute of Information Technology Dharwad

23bcs089@iiitdwd.ac.in


Under the guidance of

Dr. Aswath Babu H.


Assistant Professor, IIIT Dharwad



qmet.jpeg



bombay.png



OIP.png

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING
INDIAN INSTITUTE OF INFORMATION TECHNOLOGY DHARWAD

PARIMANA Summer Internship Program 2026

May 2026

Contents

1	Introduction	2
2	Work Completed	2
2.1	Literature Search and Taxonomy Development	2
2.2	Detailed Review of Ghost Imaging Methods	2
2.3	Review of Compressed Sensing and Other Domains	3
2.4	Software Framework Development	3
2.5	Preliminary Experimental Results	4
3	Survey Manuscript Status	4
4	Summary	4

1 Introduction

This document is an interim progress report for the project titled “*A Survey of Deep Learning-Based Reconstruction Methods for Quantum Imaging Systems*,” being carried out under the PARIMANA Summer Internship Program 2026 at Qmet Tech Foundation. The report provides a detailed account of the work completed so far, describes the technical approach adopted, summarises the principal findings from the literature review and software development activities, and outlines the current status of the survey manuscript.

The goal of the project is to produce a structured survey of deep learning methods that have been applied to image reconstruction in quantum optical systems. The survey covers three principal imaging modalities: quantum ghost imaging, compressed sensing with entangled photons, and sub-shot-noise imaging. It also examines hybrid classical-quantum reconstruction frameworks. The review encompasses both foundational quantum optics literature [Pittman et al., 1995, Erkmen and Shapiro, 2010] and recent deep learning contributions [Barbastathis et al., 2019].

2 Work Completed

2.1 Literature Search and Taxonomy Development

The first phase of the project involved conducting a systematic literature search across IEEE Xplore, arXiv, Google Scholar, and the Optica Publishing Group digital library. Search queries were constructed by pairing quantum imaging terminology (“ghost imaging,” “quantum imaging,” “entangled photon imaging,” “SPDC,” “sub-shot-noise”) with deep learning terms (“neural network,” “CNN,” “GAN,” “U-Net,” “image reconstruction,” “compressed sensing”). Papers were included if they applied a deep learning or neural network method to a quantum or quantum-inspired imaging reconstruction task, or if they provided essential foundational theory. This search yielded approximately 45 candidate papers spanning the period from 1995 to 2025.

To organise the collected literature, a three-axis taxonomic classification framework was developed. The first axis categorises papers by imaging modality (ghost imaging, quantum compressed sensing, sub-shot-noise, or hybrid). The second axis classifies the deep learning architecture employed (CNN, GAN, U-Net, autoencoder, fully connected, or quantum-inspired). The third axis captures the reconstruction task (compressed reconstruction, denoising, super-resolution, or phase retrieval). This taxonomy has been applied consistently throughout the survey and has been effective in revealing methodological trends and identifying gaps in existing work.

2.2 Detailed Review of Ghost Imaging Methods

The most intensive review effort has been directed at deep learning methods for quantum ghost imaging, which is the most active subfield. The review traced the evolution of the field from the foundational two-photon ghost imaging experiment of Pittman et al. [1995], through the classical and computational ghost imaging variants of Bennink et al. (2002) and Shapiro (2008), to the first application of deep learning by Lyu et al. [2017]. The Lyu et al. work demonstrated that a fully connected neural network could reconstruct ghost images at a sampling ratio of only 12.5%, compared to the near-100% ratio required by traditional correlation-based methods [Erkmen and Shapiro, 2010].

Subsequent works were reviewed in detail, including the convolutional approach of [He et al. \[2018\]](#), which improved generalisation to unseen object categories and was validated on both simulated and experimental data; the computational ghost imaging work of [Shimobaba et al. \[2018\]](#); and the end-to-end framework of [Wang et al. \[2019\]](#), which jointly optimised illumination patterns and the reconstruction network to achieve 3 to 5 dB PSNR improvement. The review also examined GAN-based ghost imaging reconstruction, noting the tension between improved perceptual quality and the risk of hallucination in scientific imaging contexts. A comparative analysis table of methods, architectures, sampling ratios, and key contributions has been compiled and is included in the survey manuscript.

2.3 Review of Compressed Sensing and Other Domains

The compressed sensing domain has been partially reviewed. The foundational compressive ghost imaging work of [Katz et al. \[2009\]](#) was studied in the context of the compressed sensing theory of Donoho (2006) and Candès and Tao (2006), with particular attention to how quantum correlations provide favourable measurement properties for compressed recovery. The area of deep unfolding networks, which parameterise iterative compressed sensing algorithms as trainable neural networks, has been identified as a key direction but requires further investigation.

Preliminary reading has also been completed on sub-shot-noise quantum imaging, based on the experimental demonstrations of [Brida et al. \[2010\]](#) and Samantaray et al. (2017), and on hybrid classical-quantum architectures, including the deep quantum neural networks of Beer et al. (2020) and the continuous-variable quantum neural networks of Killoran et al. (2019). These sections of the survey are currently in draft form and will be expanded during the remaining period.

2.4 Software Framework Development

A software framework has been developed in Python using PyTorch to complement the literature survey with empirical validation of the reviewed methods. The framework consists of the following components.

A **computational ghost imaging simulator** implements the forward measurement model as described in the survey. The simulator generates configurable illumination patterns (supporting Gaussian random, binary random, and Hadamard bases), computes bucket detector signals via inner product of the pattern with the object, supports configurable measurement noise, and performs traditional differential correlation-based reconstruction. This simulator enables controlled experimentation with different sampling ratios, noise levels, and pattern types.

Three **deep learning reconstruction models** have been implemented, corresponding to the principal architectural approaches identified in the survey. The first is a fully connected reconstruction network modelled after [Lyu et al. \[2017\]](#), which maps bucket detector signals directly to image space through dense layers with batch normalisation and dropout. The second is a convolutional architecture inspired by [He et al. \[2018\]](#), which projects bucket signals into a spatial feature map and then applies transposed convolutional layers for upsampling and refinement. The third is a U-Net variant adapted for ghost imaging [[Ronneberger et al., 2015](#)], which uses an encoder-decoder structure with skip connections to preserve fine-grained spatial information during reconstruction.

A **training and evaluation pipeline** provides automated training with validation-based model selection, standard image quality metrics (peak signal-to-noise ratio and structural similarity index), and visualisation utilities for side-by-side comparison of ground truth, traditional reconstruction, and deep learning reconstruction. The MNIST handwritten digit dataset is used as the default object set, following the convention of the reviewed literature.

2.5 Preliminary Experimental Results

Preliminary experiments have been conducted using the fully connected network at a sampling ratio of 12.5% (98 measurements for 28×28 images). The deep learning model achieved a validation PSNR of approximately 22 dB after training, compared to substantially lower quality from the traditional correlation method at the same sampling ratio. These preliminary results are consistent with the performance reported in the literature and confirm that the software framework is functioning correctly. A more comprehensive set of experiments comparing all three architectures across multiple sampling ratios will be conducted as part of the survey’s empirical analysis.

3 Survey Manuscript Status

The survey manuscript is being compiled concurrently with the literature review. The introduction, background, and ghost imaging sections are substantially complete, totalling approximately seven pages in two-column format. The compressed sensing, sub-shot-noise, hybrid architectures, discussion, and conclusion sections are in draft form with partial content. The bibliography currently contains 22 verified references spanning the foundational quantum optics literature, the deep learning for computational imaging literature, and the specific intersection of the two. The manuscript will be expanded and refined during the remaining period of the internship.

4 Summary

The project is progressing on schedule. The systematic literature review has covered the primary domains of ghost imaging and compressed sensing in depth, with sub-shot-noise imaging and hybrid architectures currently under review. A software framework has been developed and validated, producing results consistent with the published literature. The survey manuscript is approximately 60 to 70% complete and is being written in parallel with the ongoing review. The remaining work will focus on completing the reviews of the less-explored domains, conducting the full set of comparative experiments, and finalising the manuscript.

References

- George Barbastathis, Aydogan Ozcan, and Guohai Situ. On the use of deep learning for computational imaging. *Optica*, 6(8):921–943, 2019.
- Giorgio Brida, Marco Genovese, and Ivano Ruo Berchera. Experimental realization of sub-shot-noise quantum imaging. *Nature Photonics*, 4:227–230, 2010.

- Baris I. Erkmen and Jeffrey H. Shapiro. Ghost imaging: from quantum to classical to computational. *Advances in Optics and Photonics*, 2(4):405–450, 2010.
- Yurong He, Guan Wang, Guangxu Dong, Shitao Zhu, Hui Chen, Anxue Zhang, and Zhuo Xu. Ghost imaging based on deep learning. *Scientific Reports*, 8:6469, 2018.
- Ori Katz, Yaron Bromberg, and Yaron Silberberg. Compressive ghost imaging. *Applied Physics Letters*, 95:131110, 2009.
- Meng Lyu, Wei Wang, Hao Wang, Haichao Wang, Guowei Li, Ni Chen, and Guohai Situ. Deep-learning-based ghost imaging. *Scientific Reports*, 7:17865, 2017.
- T. B. Pittman, Y. H. Shih, D. V. Strekalov, and A. V. Sergienko. Optical imaging by means of two-photon quantum entanglement. *Physical Review A*, 52:R3429–R3432, 1995.
- Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *Medical Image Computing and Computer-Assisted Intervention (MICCAI)*, pages 234–241, 2015.
- Tomoyoshi Shimobaba, Yutaka Endo, Takashi Nishitsuji, Takayuki Takahashi, Yuki Nagahama, Satoki Hasegawa, Marie Sano, Ryuji Hirayama, Takashi Kakue, Tomoyoshi Ito, and Atsushi Shiraki. Computational ghost imaging using deep learning. *Optics Communications*, 413:147–151, 2018.
- Fei Wang, Hao Wang, Haichao Wang, Guowei Li, and Guohai Situ. Learning from simulation: An end-to-end deep-learning approach for computational ghost imaging. *Optics Express*, 27(18):25560–25572, 2019.