Name: Himanshu Sachdeva
Roll Number: 2021256

Description of shell

All source files are in the same folder/directory

"exit" to return from the shell

Input the commands after "$" sign

Commands Supported:

- ## Internal:
    1. cd
       Description: Changes Directory of the working shell
       Options Supported:
           -P: symbolic link shall be resolved
           -L: symbolic link shall not be resolved
       Edge Cases:
           Arguments must be present
           Incorrect use of flags handled
    2. echo
       Description: to output the argument in command line
       Options Supported:
           -n: does not add newline
           --help: prints what option does
       Edge Cases:
           Arguments must be present
           Incorrect use of flags handled

    3. pwd
       Description: prints the parent working directory
       Options Supported:
           -P: symbolic link shall be resolved
           -L: symbolic link shall not be resolved
       Edge Cases:
           Handle if extra arguments passed
           Incorrect use of flags handled

- ## External
    1. ls
       Description: Outputs all the subdirectories and files in the folder
       Options Supported:

-a: outputs all files including beginning with .
-d: list the directory only and not its content
Edge Cases:
    Invalid arguments handled
    Incorrect use of flags handled

2. cat
    Description: print the file contents
    Options Supported:
        -n: outputs along with line number
        -E: adds "$" at the end of line
    Edge Cases:
        Handled if file not exists
        Incorrect use of flags handled

3. date
    Description: prints the current date and time
    Options Supported:
        -R: output RFC 5322 format
        -u: output UTC time
    Edge Cases:
        Handle if any is argument passed other than flag
        Incorrect use of flags handled

4. rm
    Description: removes/deletes the files or folders
    Options Supported
        -i: confirm before every folder (input "yes" to confirm)
        -d: removes empty folder
    Edge Cases:
        If more than one file/folder specified
        Handled if less arguments passed
        Handled if file not exists
        Incorrect use of flags handled

5. mkdir
    Description: creates new directories
    Options Supported:
        -m: creates file with mode specified
        -v: specifies user after every operation
    Edge Cases:
        If invalid mode is specified
        Incorrect use of flags handled

- ## Multi-threading

  add "&t" after the command, eg: ls &t

- ## Test Cases

  ls -a ..

  ls &t -a ..

  date

  date -u

  date -R