# Roadkill Hotspots and Policy Advocacy (RHPA): A Multi-Layered AI and IoT Approach for Real-Time Wildlife Preservation

Lokesh Patra & Indigibilli Harshit
*Computer Science and Engineering*
*Sri Sri University*
Cuttack, India
lokesh0patra@gmail.com | harshitindigibilli@gmail.com

***Abstract*—Roadkill incidents represent a critical intersection of ecological loss and vehicular safety hazards. With rapid urbanization, the frequency of wildlife-vehicle collisions has escalated, resulting in significant biodiversity loss and danger to commuters. This research proposes a novel three-dimensional (3D) solution titled "Roadkill Hotspots and Policy Advocacy" (RHPA). Unlike traditional radar-based systems, RHPA integrates Computer Vision (YOLOv5xu), Ensemble Deep Learning (DenseNet121 + EfficientNet-B3) and the Internet of Things (IoT) to create a preventive and responsive ecosystem. The system achieves an overall accuracy of ≈95%, employing YOLOv5xu for real-time detection and a CNN ensemble for classifying subjects as "Alive" (High Risk) or "Dead" (Low Risk). Furthermore, the system integrates an ESP32-based actuation layer for real-time driver warnings and a policy-level dashboard to identify blackspots. Pilot testing indicates a potential 36% reduction in roadkill incidents.**

***Index Terms*—Road Ecology, YOLOv5xu, DenseNet121, EfficientNet, IoT, Smart Cities, Wildlife Conservation.**

## I. Introduction

The expansion of road networks acts as a double-edged sword; while it facilitates economic growth, it fragments natural habitats, forcing wildlife to navigate hazardous asphalt terrains. Personal observations over a three-year daily commute of 40 km revealed a grim reality: the daily presence of roadkill ranging from domestic vertebrates (dogs, cows) to wild species (mongooses, snakes). These incidents are not merely ecological statistics; they represent a traumatic experience for drivers and a sanitary crisis for municipal authorities.

Existing solutions often rely on passive signage or primitive radar systems that lack visual verification. This paper introduces a **3D AI-based solution**:

- **Dimension 1 (Vision):** Real-time detection and tracking.
- **Dimension 2 (Classification):** Distinguish between live threats and carcasses to automate different responses.
- **Dimension 3 (Actuation):** IoT-based warnings and automated municipal reporting.

The foundation of this research is based on the analysis of gaps in existing road ecology frameworks. Ahn and Bae proposed a "Sound Warning System for the Prevention of Roadkill" that uses radar to detect movement and emit ultrasonic frequencies [1]. Although their approach successfully deters some animals, radar systems suffer from a high false-positive rate (triggering for inanimate objects) and cannot distinguish between a living animal crossing the road and an already deceased one. Our proposed RHPA system overcomes this by replacing the radar with Computer Vision (YOLOv5xu) for granular object classification.

The research by van der Ree et al. and van Langevelde highlights the theoretical relationship between traffic flow and mammalian mortality [2]. They suggest that infrastructure modification (underpasses) is the gold standard. However, such infrastructure is expensive and slow to implement. The RHPA project proposes a "Policy Advocacy" layer, using data-driven heatmaps to identify exactly where such infrastructure is needed, bridging the gap between theoretical ecology and smart city implementation.

## II. System Architecture

The proposed methodology follows a three-tier architecture that combines Edge AI and Cloud Analytics.





Fig. 1. System Architecture Flowchart of the RHPA Pipeline

### A. D1: Object Detection (YOLOv5xu)

The first dimension utilizes the YOLOv5xu architecture. This variant is optimized for identifying small-to-medium objects (animals) in complex road backgrounds.

- **Input:** Real-time feeds from dashcams or roadside surveillance.
- **Function:** Boundary box regression and optical flow-based speed tracking.

The loss function considers the Intersection over Union (IoU) to minimize localization errors:

$$L_{IoU} = 1 - IoU + \frac{\rho^2(b, b^{gt})}{c^2} + \alpha v \tag{1}$$

Where $\rho$ is the Euclidean distance between the center points and $\alpha v$ represents the consistency of the aspect ratio.

### B. D2: Classification (Ensemble Learning)

Once an animal is detected, the Region of Interest (ROI) is passed to a classification module to determine the state: *Alive* vs. *Dead*. We employ an ensemble of two distinct CNN architectures to maximize reliability.

*1) DenseNet121:* Using dense connectivity to mitigate the problem of vanishing projects, ensuring that feature maps are preserved throughout the network. This is crucial for detecting subtle features, such as breathing or posture.

*2) EfficientNet-B3:* The compound scaling balances depth, width, and resolution, providing high accuracy with lower computational cost.

*3) Ensemble Logic:* The final classification probability $P_{final}$ is derived using a weighted average:

$$P_{final} = w_1 \cdot P_{DenseNet} + w_2 \cdot P_{EfficientNet} \tag{2}$$

Where $w_1 + w_2 = 1$. Based on validation metrics, we assign $w_1 = 0.5$ and $w_2 = 0.5$.

### C. D3: IoT and Actuation

The hardware layer is controlled by an ESP32 microcontroller.

- **Sensors:** Ultrasonic sensors for proximity verification; DHT sensors for environmental correlation (temp/humidity).
- **Actuators:** Smart signage (LED Matrices) and in-car buzzers (through TinyML integration).

**Initialize** Camera, ESP32, Models
**while** System is Active **do**
  Frame ← CaptureFrame()
  Objects ← YOLOv5xu.Detect(Frame)
  **for** each Object in Objects **do**
    **if** YOLO detects Animal **then**
      Extract bounding box coordinates
      Crop animal region from Frame
      State ← CNN_EnsembleModel.Classify(CroppedRegion)
      Movement ← OpticalFlow.Analyze(Frame, PreviousFrame)
      Speed ← CalculateSpeed(Movement, BoundingBox)
      RiskZone ← DetermineRisk(Speed, State)
      **if** State == **ALIVE** AND RiskZone == **HIGH** **then**
        **Trigger:** High Risk Alert
        **Action:** Activate Buzzer (Beep)
        **Action:** Auto-decelerate Vehicle (No sudden break)
        **Log:** Update Dynamic Danger Map
      **else if** State == **DEAD** **then**
        **Trigger:** Low Risk / Obstacle Alert
        **Action:** Notify Driver (Avoidance)
        **Action:** Send GPS to Municipal Corp (Cleanup)
        **Log:** Update Roadkill Hotspot Database
      **end if**
      SaveFrame(Frame, OutputVideo)
    **end if**
  **end for**
**end while**

## III. Implementation and Results

### A. Experimental Setup

The models were trained on a custom dataset comprising various vertebrates (cows, dogs, snakes, etc.) under diverse lighting conditions. The system was tested in a pilot in 4 locations over 1.5 months.

### B. Performance Metrics

The models were evaluated based on Precision, recall, and F1-Score.

TABLE I
Model Performance Comparison

| Model | Task | Accuracy |
|---|---|---|
| YOLOv5xu | Object Detection | 93.0% |
| DenseNet121 | Classification (State) | 98.0% |
| EfficientNet-B3 | Classification (State) | 97.0% |
| **CNN Ensemble** | **Classification (Combined)** | **97.5%** |

The overall system precision (Detection + Classification pipeline) is approximately **95%**.

### C. Impact Analysis

During the pilot phase, the system's interventions (smart signage warnings and driver alerts) resulted in an estimated **36% reduction** in traffic fatalities compared to historical data for the same route.

## IV. Policy Advocacy and Heatmaps

Beyond immediate prevention, this project serves a long-term legislative goal. By logging the GPS coordinates of every "Dead" classification, we generate high-resolution Heatmaps.

**Application for Authorities:**

1) **Hotspot Identification:** Pinpointing specific road segments (Blackspots) where animals frequently cross.

2) **Infrastructure Planning:** Data-backed recommendations for constructing underpasses or overpasses.
3) **Resource Allocation:** Optimization of routes for municipal cleanup crews based on real-time notifications.

## V. Conclusion

The RHPA project successfully bridges the gap between advanced technology and environmental ethics. Moving beyond simple detection to complex state classification (Alive vs. Dead), the system offers tailored responses that ensure passenger safety while actively preserving wildlife. Integration of these data into municipal policy frameworks ensures that the solution is not just reactive, but curative for the long-term health of our road ecosystems. Future work will focus on expanding the data set to include nocturnal species and integrating thermal imaging for night-time detection.

## References


[1] I. S. Ahn and M. J. Bae, "A Study on the Sound Warning System for Prevention of Roadkill Accident," *International Journal of Engineering Research and Technology*, vol. 11, no. 10, pp. 1605-1618, 2018.

[2] R. van der Ree, D. J. Smith, and C. Grilo, *Handbook of Road Ecology*. Chichester, UK: Wiley, 2015.

[3] A. Torres et al., "Assessing large-scale wildlife responses to human infrastructure development," *Proc. Nat. Acad. Sci.*, vol. 113, no. 30, pp. 8472–8477, 2016.

[4] F. van Langevelde and C. F. Jaarsma, "Using traffic flow theory to model traffic mortality in mammals," *Landscape Ecol*, vol. 19, no. 8, pp. 895–907, 2005.

[5] G. S. Ferrante et al., "Evaluating YOLO architectures for detecting road killed endangered Brazilian animals," *Scientific Reports*, 2023.

[6] C. Grilo et al., "Global Roadkill Data: a dataset on terrestrial vertebrate mortality caused by collision with vehicles," *Scientific Data*, 2024.

[7] L. Balčiauskas et al., "A Review of Wildlife-Vehicle Collisions: A Multidisciplinary Path to Sustainable Transportation and Wildlife Protection," *Sustainability*, 2025.

[8] J. Arca-Rubio et al., "The distribution of vertebrate roadkill varies by season, surrounding environment, and animal class," *European Journal of Wildlife Research*, 2023.

[9] I. M. F. Cassimiro et al., "How did the animal come to cross the road? Drawing insights on animal movement from existing roadkill data and expert knowledge," *Landscape Ecology*, 2023.

[10] R. T. Forman and L. E. Alexander, "Roads and their major ecological effects," *Annual Review of Ecology and Systematics*, 1998.

[11] M. Bíl et al., "Srazenazver.cz: A System for Evidence of Animal-Vehicle Collisions along Transportation Networks," *Biological Conservation*, 2017.

[12] N. P. Snow et al., "Regional-based mitigation to reduce wildlife-vehicle collisions," *Journal of Wildlife Management*, 2018.

[13] S. M. Santos et al., "How Long Do the Dead Survive on the Road? Carcass Persistence Probability and Implications for Road-Kill Monitoring Surveys," *PLoS ONE*, 2011.

[14] M. W. Fielding et al., "Roadkill islands: Carnivore extinction shifts seasonal use of roadside carrion by generalist avian scavenger," *Journal of Animal Ecology*, 2021.

[15] D. Lesbarreres and L. Fahrig, "Measures to reduce population fragmentation by roads: What has worked and how do we know?" *Trends in Ecology & Evolution*, 2012.

[16] A. W. Coffin, "From roadkill to road ecology: A review of the ecological effects of roads," *Journal of Transport Geography*, 2007.

[17] C. Grilo et al., "Conservation threats from roadkill in the global road network," *Global Ecology and Biogeography*, 2021.

[18] T. Hothorn et al., "Temporal patterns of deer–vehicle collisions consistent with deer activity pattern," *Accident Analysis & Prevention*, 2015.

[19] E. Eberhardt et al., "Road kill hotspots do not effectively indicate mitigation locations when past road kill has depressed populations," *Journal of Wildlife Management*, 2013.