Booleans, the original true-false dichotomy

Marc Coiffier

Contents

Functions on Booleans 1

```
'utils require import
```

- Required module: utils

Booleans can have two values, in any given universe. First, we define the Boolean context :

```
'Bool-context [ { Type '.Bool } { .Bool '.true } { .Bool '.false } ] def
```

In this context, the type of booleans is simply the .Bool type in context, and the 'true' and 'false' values are respectively the '.true' and '.false' hypotheses.

```
'Bool Bool-context { .Bool } prods  "Boolean" defconstr
'true Bool-context { .true } funs   "true"    defconstr
'false Bool-context { .false } funs "false"   defconstr
[ 'Bool 'true 'false ] { export } each
```

We can test that $true$ and $false$ have the correct type :

- type of $true$: $Boolean$
- type of $false$: $Boolean$
- type of $\lambda(\mathrm{b} : Boolean).\, \mu(\mathrm{b}) \;:\; \forall(\mathrm{b} : Boolean)\, (\mathrm{Bool}^P : Boolean \to Set_1), \mathrm{Bool}^P\, true \to \mathrm{Bool}^P\, false \to \mathrm{Bool}^P\, \mathrm{b}$

Functions on Booleans

Then, we can start defining first-level combinators, such as 'not', 'and' and 'or' :

```
'not { Bool 'b } Bool-context # { b ( .Bool .false .true ) } funs def
'and { Bool 'x } { Bool 'y } Bool-context # #
  { x ( .Bool y ( .Bool .true .false ) .false ) } funs def
'or { Bool 'x } { Bool 'y } Bool-context # #
  { x ( .Bool .true y ( .Bool .true .false ) ) } funs def
'implies { Bool 'x } { Bool 'y } Bool-context # #
  { x ( .Bool y ( .Bool .true .false ) .true ) } funs def
```

As always, we should verify the type of our combinators, and test whether they truly conform to their specification :

```
[ 'not 'or 'and 'implies ] { dup $ type swap "  - $%s : %l$\n" printf } each
```

- $not : Boolean \to Boolean$
  - $or : Boolean \to Boolean \to Boolean$
  - $and : Boolean \to Boolean \to Boolean$
  - $implies : Boolean \to Boolean \to Boolean$