

# Ambari后台手动关闭Kerberos

高危操作

## 备份元数据

- 需要备份的表
  - ambari.servicedesiredstate
  - ambari.hostcomponentdesiredstate
  - ambari.hostcomponentstate
  - ambari.servicecomponentdesiredstate
  - ambari.clusterservices
  - ambari.clusters
  - ambari.kkp\_mapping\_service
  - ambari.kerberos\_keytab\_principal
  - ambari.kerberos\_principal
  - ambari.kerberos\_keytab
  - ambari.clusterconfig

## 修改数据库

- 页面上启动/禁用Kerberos相关表

```
update ambari.clusters set security_type='NONE';
```

NONE:启用Kerberos按钮可用

KERBEROS:禁用Kerberos按钮可用

- 删除服务列表中显示的Kerberos组件

```
delete from ambari.servicedesiredstate where service_name='KERBEROS';
```

```
delete from ambari.hostcomponentdesiredstate where service_name='KERBEROS';
```

```
delete from ambari.hostcomponentstate where service_name='KERBEROS';
```

```
delete from ambari.servicecomponentdesiredstate where service_name='KERBEROS';
```

```
delete from ambari.clusterservices where service_name='KERBEROS';
```

- 禁用集群Kerberos配置

将ambari.clusterconfig表中type\_name="cluster-env"的行中config\_data字段中security\_enabled的值由true 改为false

- 重启ambari-server即可

## 回滚

恢复数据库，重启ambari-server