

From Generative to Embodied Intelligence: Network Evolution for Large-AI-Model Agents

INTRO

I Section I. Introduction

Research motivations

Contributions

CORE
MAP

Network-Centric Comparative Framework

GENERATIVE LAM

AGENTIC LAM

EMBODIED LAM

II Section II. From Generative to Embodied LAMs: Performance Metrics, Benchmarks, and Model Evolution

Generative LAMs

Agentic LAMs

Embodied LAMs

Development Laws and a Regression Heuristic

III Section III. From Generative to Embodied Networks for LAMs: QoS Scale and Model Emphasis

Generative Stage: Fidelity and Cost under Elastic Interaction

Agentic Stage: Long-Horizon Goodput, Memory, and Retry

Embodied Stage: Closed-Loop Timing and Physical Loss

IV Section IV. From Generative to Embodied Networks for LAMs: Architecture Evolution

Architecture for Generative-LAM Networks

Architecture for Agentic-LAM Networks

Architecture for Embodied-LAM Networks

ENABLING
TECH

V Section V. Improving Networks for LAMs: Key Enabling Technologies

Enablers for Generative-LAM Networks

Compression and token communications

Split, distributed, and speculative inference

Enablers for Agentic-LAM Networks

Reliable collaboration

Agentic Model and tool routing

Enablers for Embodied-LAM Networks

Control-loss-aware token selection

Finite-blocklength and deterministic transport

Semantic and goal-oriented communication

Communication--control co-design and dynamic model sharing

TOKEN PLANE

TRANSPORT PLANE

COORDINATION PLANE

CASE
STUDY

VI Section VI. Case Study: Two-Stage Recognition of LAM Traffic

Phase I: Passive Traffic Recognition Experiment

Phase II: Active Recognition and QoS Mapping

OUTLOOK

VII Section VII. Challenges and Future Directions

Tokenizer Compatibility

Token-Native Protocols

Benchmarking, Theory, and Standardization Gaps

CLOSING

VIII

Section VIII. Conclusions