

Unsupervised learning

Balázs Pintér

May 10, 2020

Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Supervised learning – classification

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Supervised learning – regression

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Unsupervised learning – clustering

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Unsupervised learning

Unsupervised learning

Balázs Pintér

Introduction

Clustering

- Hard clustering
 - k-means
- Soft clustering – topic models

Dimensionality reduction

- Covariance, correlation
- Principal component analysis

Autoencoders

- Supervised learning learns a function from labeled data
- Other approaches

- 1 **Unsupervised learning**
- 2 Semi-supervised learning
- 3 Reinforcement learning
- 4 Evolutionary algorithms
- 5 Neuroevolution

<http://www.youtube.com/watch?v=qv6UV0Q0F44>

Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Example – distribution-based clustering

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Example – distribution-based clustering

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Problem

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means

Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders

- Assign items to groups where similar items should belong to the same group
 - They should be as similar as possible within a group
 - They should be less similar between group
- The items are usually points in \mathbb{R}^n or nodes in a graph, like
 - Client data for market segmentation
 - Documents modeled as bag of words to determine topics or group search results
 - Contexts of words to induce word senses
 - Data about which servers are active together to optimize traffic
- A group is called a *cluster*

Hard and soft clustering

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Hard and soft clustering
 - Hard clustering: an item can belong only to a single cluster
 - Soft clustering: weights describe the degree to which an item belongs to the clusters
- Finer distinctions
 - Overlapping clustering: an item can belong to multiple clusters, but it either belongs to a cluster or not
 - Hierarchical clustering: the clusters are organized into a hierarchy. The items that belong to a child cluster also belong to the parent cluster.

Hierarchical clustering

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Naturally occurring clustering of word representations – words with the same meaning are the same color (t-SNE)

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Example

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Problem

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Given: k , the number of clusters
- Each cluster is represented by its centroid
 - the mean of the points in the cluster
- Find the k centroids and assign the points to these in a way that minimizes the squared distances of the points from the centroid of their cluster
 - Equivalent to minimizing pairwise distances within clusters
 - NP-hard, so we approximate
 - We can only find a local optimum
 - We can run it multiple times with different random initializations

k-means problem

$$\arg \min_{\mathbf{S}} \sum_{i=1}^k \sum_{\mathbf{x} \in S_i} \|\mathbf{x} - \boldsymbol{\mu}_i\|^2 = \arg \min_{\mathbf{S}} \sum_{i=1}^k \frac{1}{2|S_i|} \sum_{\mathbf{x}, \mathbf{y} \in S_i} \|\mathbf{x} - \mathbf{y}\|^2$$



Algorithm

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Given: k and the items in \mathbb{R}^n
- Initialize centroids $m_1^{(1)}, m_2^{(1)}, \dots, m_k^{(1)}$ by either
 - choosing k points randomly to be the centroids, or
 - assigning each point randomly to a cluster and computing the centroids of these clusters
- Do the following two steps until convergence
 - 1 Assign each item to the nearest centroid:

$$S_i^{(t)} = \{x_p : \|x_p - m_i^{(t)}\|^2 \leq \|x_p - m_j^{(t)}\|^2 \forall j, 1 \leq j \leq k\}$$

- 2 Compute the new centroids:

$$m_i^{(t+1)} = \frac{1}{|S_i^{(t)}|} \sum_{x_j \in S_i^{(t)}} x_j$$

Algorithm

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Algorithm

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Algorithm

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Algorithm

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Algorithm

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Algorithm

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Algorithm

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Issue – k is too small

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k -means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Issue – k is too large

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k -means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Issue – bad initialization

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Issue – the real clusters are not centroid based

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Python examples

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Color quantization:
http://scikit-learn.org/stable/auto_examples/cluster/plot_color_quantization.html
- Document clustering:
https://scikit-learn.org/stable/auto_examples/text/plot_document_clustering.html

Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means

- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation

- Principal component analysis

4 Autoencoders

Topic models

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models


Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Soft clustering example: topic models
 - What topics is a document about?
 - What words belong to a topic?
 - Example: Latent Semantic Analysis (LSA), which is a SVD



Latent Semantic Analysis

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Group-sparse regularization

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means


Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders



Example: generating odd one out puzzles

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

Words that belong together				Odd one out
cao	wei	liu	emperor	king
superman	clark	luthor	kryptonite	batman
devil	demon	hell	soul	body
egypt	egyptian	alexandria	pharaoh	bishop
singh	guru	sikh	saini	delhi
language	dialect	linguistic	spoken	sound
mass	force	motion	velocity	orbit
voice	speech	hearing	sound	view
athens	athenian	pericles	corinth	ancient
data	file	format	compression	image
function	problems	polynomial	equation	physical

Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Why dimensionality reduction?

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- The data are low dimensional in a higher dimensional space
- Data visualization
- Noise reduction
- Decrease the complexity of the learning problem (better results, smaller runtimes, . . .)
- We can conjecture new relationships on the visualized lower dimensional data
- We need a lower dimensional and/or dense representation to solve a problem

Example: Swiss roll

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Example: Rotating a letter

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Contents

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means

Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Covariance, correlation

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means






Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Covariance, correlation

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Covariance, (Pearson) correlation

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- They measure the degree to which the X , Y random variables move together
- They only show linear relationships
- $\text{Cov}(X, Y) = E[(X - E[X])(Y - E[Y])]$
- For example, if it's positive: If $X > E(X)$, then $Y > E(Y)$, if $X < E(X)$, then $Y < E(Y)$
- $\text{Cov}(X, Y) = E[XY] - E[X]E[Y]$
- Correlation: “normalized” covariance, between -1 and 1
- $\rho_{X,Y} = \text{corr}(X, Y) = \frac{\text{cov}(X,Y)}{\sigma_X \sigma_Y} = \frac{E[(X-\mu_X)(Y-\mu_Y)]}{\sigma_X \sigma_Y}$

$$\text{■ } r_{xy} = \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum_{i=1}^n (x_i - \bar{x})^2 \sum_{i=1}^n (y_i - \bar{y})^2}}$$

The correlation is 0.816 for all four datasets

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means





Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Covariance matrix

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- \mathbf{X} is a vector whose elements are random variables
- The entries of the covariance matrix are covariances between X_i, X_j

- $\Sigma_{ij} = \text{cov}(X_i, X_j) = \text{E}[(X_i - \mu_i)(X_j - \mu_j)]$

- $\mu_i = \text{E}(X_i)$

- $$\begin{bmatrix} \text{E}[(X_1 - \mu_1)(X_1 - \mu_1)] & \text{E}[(X_1 - \mu_1)(X_2 - \mu_2)] & \cdots & \text{E}[(X_1 - \mu_1)(X_n - \mu_n)] \\ \text{E}[(X_2 - \mu_2)(X_1 - \mu_1)] & \text{E}[(X_2 - \mu_2)(X_2 - \mu_2)] & \cdots & \text{E}[(X_2 - \mu_2)(X_n - \mu_n)] \\ \vdots & \vdots & \ddots & \vdots \\ \text{E}[(X_n - \mu_n)(X_1 - \mu_1)] & \text{E}[(X_n - \mu_n)(X_2 - \mu_2)] & \cdots & \text{E}[(X_n - \mu_n)(X_n - \mu_n)] \end{bmatrix}$$

- The main diagonal contains the variances
- Equivalent: $\Sigma = \text{E}(\mathbf{X}^\top \mathbf{X}) - \mu^\top \mu$

Contents

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Example – normal distribution in 2d

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Principal component analysis

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Principal component analysis (PCA)
- Demo: <http://setosa.io/ev/principal-component-analysis/>
- The dataset is transformed to a new coordinate system whose axes are orthogonal
- The projection of the dataset with the greatest variance is on the first axis (principal component)
- The projection with the second greatest variance is on the second principal component, ...
- New variables/data: we project the original variables to the principal components. These are uncorrelated.
- Dimensionality reduction: We discard the axes (and coordinates) with small variance

Principal component analysis

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- $\mathbf{X} \in \mathbb{R}^{n \times p}$: data set, one row is an item
- $\mathbf{t}_{(i)} = (t_1, \dots, t_l)_{(i)}$: the items transformed to the new coordinate system using $\mathbf{w}_{(k)} = (w_1, \dots, w_p)_{(k)}$

$$t_{k(i)} = \mathbf{x}_{(i)} \cdot \mathbf{w}_{(k)} \quad \text{for} \quad i = 1, \dots, n \quad k = 1, \dots, l$$

- Maximizing variance on the first principal component

$$\mathbf{w}_{(1)} = \arg \max_{\|\mathbf{w}\|=1} \left\{ \sum_i (t_1)_{(i)}^2 \right\} = \arg \max_{\|\mathbf{w}\|=1} \left\{ \sum_i (\mathbf{x}_{(i)} \cdot \mathbf{w})^2 \right\}$$

Principal component analysis

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- The same with a matrix:

$$\mathbf{w}_{(1)} = \arg \max_{\|\mathbf{w}\|=1} \{\|\mathbf{X}\mathbf{w}\|^2\} = \arg \max_{\|\mathbf{w}\|=1} \left\{ \mathbf{w}^T \mathbf{X}^T \mathbf{X} \mathbf{w} \right\}$$

- As \mathbf{w} is a unit vector:

$$\mathbf{w}_{(1)} = \arg \max \left\{ \frac{\mathbf{w}^T \mathbf{X}^T \mathbf{X} \mathbf{w}}{\mathbf{w}^T \mathbf{w}} \right\}$$

- This is the Rayleigh-quotient, whose largest possible value is the largest eigenvalue of $\mathbf{X}^T \mathbf{X}$, where \mathbf{w} is the corresponding eigenvector
- This is also true for the other components \rightarrow the principal components are the eigenvectors of $\mathbf{X}^T \mathbf{X}$

Principal component analysis – algorithm

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Our dataset is in the \mathbf{X} matrix
- Make the dataset zero mean (subtract the mean)
- Compute covariance matrix $\mathbf{Q} = \mathbf{X}^T \mathbf{X}$
- Determine the eigenvalues and eigenvectors of this matrix
- The eigenvectors are the principal components, the basis that consists of the eigenvectors is the new coordinate system
- The principal component that corresponds to the largest eigenvalue has the largest variance, and so on
- Dimensionality reduction: we only keep the k principal components with the largest eigenvalues

PCA and SVD

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

SVD

$$\mathbf{X} = \mathbf{U}\mathbf{\Sigma}\mathbf{W}^T$$

Computing PCA with SVD

$$\begin{aligned}\mathbf{X}^T\mathbf{X} &= \mathbf{W}\mathbf{\Sigma}^T\mathbf{U}^T\mathbf{U}\mathbf{\Sigma}\mathbf{W}^T \\ &= \mathbf{W}\mathbf{\Sigma}^T\mathbf{\Sigma}\mathbf{W}^T \\ &= \mathbf{W}\hat{\mathbf{\Sigma}}^2\mathbf{W}^T\end{aligned}$$

- \mathbf{W} contains the eigenvectors of $\mathbf{X}^T\mathbf{X}$. The singular values are the square roots of the eigenvalues.

PCA is linear too

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Python examples

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

- Importance of feature scaling:
[http://scikit-learn.org/stable/auto_examples/
preprocessing/plot_scaling_importance.html](http://scikit-learn.org/stable/auto_examples/preprocessing/plot_scaling_importance.html)

Contents

Unsupervised learning

Balázs Pintér

Introduction

Clustering

Hard clustering – k-means

Soft clustering – topic models

Dimensionality reduction

Covariance, correlation

Principal component analysis

Autoencoders

1 Introduction

2 Clustering

- Hard clustering – k-means
- Soft clustering – topic models

3 Dimensionality reduction

- Covariance, correlation
- Principal component analysis

4 Autoencoders

Autoencoders

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means


Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders



Autoencoders

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

Simple autoencoders

$$\mathcal{L}(\mathbf{x}, \mathbf{x}') = \|\mathbf{x} - \mathbf{x}'\|^2 = \|\mathbf{x} - \sigma'(\mathbf{W}'(\sigma(\mathbf{W}\mathbf{x} + \mathbf{b})) + \mathbf{b}')\|^2$$

- This simple autoencoder projects to the subspace of PCA
- Flexible, there are many variations
 - Denoising autoencoder: produces noiseless output from noisy input
 - Sparse autoencoder: the hidden representation is sparse
 - VAE: A probabilistic framework, approximates the posterior distribution
- Autoencoders can be important when pretraining a deep neural network
- <https://transcranial.github.io/keras-js/#/mnist-vaе>

Thank you for your attention!

Unsupervised
learning

Balázs Pintér

Introduction

Clustering

Hard clustering
– k-means

Soft clustering –
topic models

Dimensionality
reduction

Covariance,
correlation

Principal
component
analysis

Autoencoders

Thank you for your attention!