

Data Migration using SQL*Loader

Oracle EBS R12 | Day 15 Lab | Inbound Interface — Step-by-Step

Step 1 — Create the target table (SQL*Plus, user APPS)

```
CREATE TABLE KAWTHER_TEST
(
  ID      NUMBER,
  NAME    CHAR(50),
  COURSE  VARCHAR2(100)
);
```

```
DESC KAWTHER_TEST;
```

Make sure the parentheses are balanced, otherwise you get ORA-00907: missing right parenthesis.

Step 2 — Create the control file (Notepad)

- Local folder: C:\Users\ask13\Desktop\KAWTHER\DATA MIGRATION

```
LOAD DATA
INFILE '/u01/install/VISION/fs1/EBSapps/appl/fnd/12.0.0/reports/US/KAWTHERDATA.dat'
APPEND
INTO TABLE KAWTHER_TEST
FIELDS TERMINATED BY ','
OPTIONALLY ENCLOSED BY '"'
TRAILING NULLCOLS
(ID, NAME, COURSE)
```

- File → Save As → File name: **KAWTHERCONTROL.ctl**, Save as type: **All Files**, Encoding: **ANSI**.

Use TERMINATED BY (not SEPARATED BY). Use plain quotes only, never curly quotes copied from Word.

Step 3 — Create the data file (Notepad)

```
1, 'KAWTHER', 'ORACLE'
2, 'SUNIL', 'C++'
3, 'JOHN', 'CYBERSECURITY'
4, 'SMITH', 'JAVA'
5, 'CLARK', 'ORACLE'
```

- Save As → **KAWTHERDATA.dat**, Save as type: **All Files** (so it is not saved as .dat.txt).

Step 4 — Upload both files to the EBS server (WinSCP)

- Open WinSCP and connect to EBS.EXAMPLE.COM.
- Right panel: go to /u01/install/VISION/fs1/EBSapps/appl/fnd/12.0.0/reports/US
- Drag **KAWTHERCONTROL.ctl** and **KAWTHERDATA.dat** from the left (local) panel to the right (server) panel.

Step 5 — Run SQL*Loader on the server (PuTTY / WinSCP Terminal)

```
cd /u01/install/VISION/fs1/EBSapps/appl/fnd/12.0.0/reports/US

sed -i 's/\r$//' KAWTHERCONTROL.ctl KAWTHERDATA.dat

. /u01/install/VISION/EBSapps.env run

sqlldr userid=apps/apps control=KAWTHERCONTROL.ctl log=KAWTHERCONTROL.log
```

- **cd** — go to the folder with the files.
- **sed** — removes Windows line endings (CRLF) from files made in Notepad.
- **EBSapps.env run** — loads the EBS environment so sqlldr is found.
- **sqlldr** — loads the data file into the table using the control file.

Step 6 — Confirm the load succeeded

- Expected output:

```
Commit point reached - logical record count 5
```

- Log file: KAWTHERCONTROL.log (summary of rows loaded / rejected).
- Bad file (.bad): rows rejected because of errors. Discard file (.dsc): rows not matching selection criteria.

Step 7 — Verify the data in the table

```
sqlplus apps/apps

SELECT * FROM KAWTHER_TEST;
```

- Result: 5 rows loaded (KAWTHER, SUNIL, JOHN, SMITH, CLARK).

Errors met during the lab

Error	Cause	Fix
ORA-12154: TNS could not resolve	sqlldr run from Windows cmd; EBSDB alias not known locally	Run sqlldr on the server (Step 5)
SQL*Loader-100 / LRM-00112	Command pasted twice or broken across lines	Paste one clean command per line
ORA-00907: missing right parenthesis	Extra characters in CREATE TABLE	Re-type with balanced ()