

```

import discord
from discord.ext import commands, tasks
import yfinance as yf
import pandas as pd
import ta
import mplfinance as mpf
import datetime
import os

TOKEN = os.getenv("TOKEN")
CHANNEL_NAME = os.getenv("CHANNEL")

bot = commands.Bot(command_prefix="!", intents=discord.Intents.all())

stocks = {
    "0050": "0050.TW",
    "0056": "0056.TW",
    "00940": "00940.TW"
}

def market_ok():
    df = yf.Ticker("^TWII").history(period="6mo")
    df["ma200"] = df["Close"].rolling(200).mean()
    return df.iloc[-1]["Close"] > df.iloc[-1]["ma200"]

def analyze(stock_id):
    df = yf.Ticker(stocks[stock_id]).history(period="6mo")

    df["rsi"] = ta.momentum.RSIIndicator(df["Close"]).rsi()
    df["ma20"] = df["Close"].rolling(20).mean()
    df["ma60"] = df["Close"].rolling(60).mean()

    macd = ta.trend.MACD(df["Close"])
    df["macd"] = macd.macd()
    df["macd_signal"] = macd.macd_signal()

    latest = df.iloc[-1]
    score = 0

    if latest["rsi"] < 30: score += 2
    elif latest["rsi"] < 40: score += 1

    if latest["Close"] < latest["ma20"]: score += 1
    if latest["Close"] < latest["ma60"]: score += 1

    if latest["macd"] > latest["macd_signal"]: score += 1

    if not market_ok():

```

```
return df, latest, "❌ 大盤偏空"
```

```
if score >= 4:  
    signal = "🔥 強力進場"  
elif score >= 3:  
    signal = "🟡 分批"  
elif score >= 2:  
    signal = "🟢 試單"  
else:  
    signal = "❌ 觀望"
```

```
return df, latest, signal
```

```
def plot(df, stock_id):  
    filename = f'{stock_id}.png'  
    mpf.plot(df, type='candle', mav=(20,60), savefig=filename)  
    return filename
```

```
@tasks.loop(minutes=15)  
async def scanner():  
    channel = discord.utils.get(bot.get_all_channels(), name=CHANNEL_NAME)
```

```
    for s in stocks:  
        df, latest, signal = analyze(s)
```

```
    if "進場" in signal or "試單" in signal:  
        img = plot(df, s)
```

```
    msg = f"""\n  
    📢 訊號  
    { s }  
    價格: {latest['Close']:.2f}  
    建議: {signal}  
    """\n  
    await channel.send(msg, file=discord.File(img))
```

```
@bot.event  
async def on_ready():  
    print("Bot上線")  
    scanner.start()
```

```
bot.run(TOKEN)
```