

EXHIBIT 29


Exhibit 28C: U.S. Patent No. 12,646,735 – LGES 46950

This claim chart shows how each element of claim 1 of U.S. Patent No. 12,646,735 (“the ’735 Patent”) is met by the I [REDACTED] [REDACTED]), either literally or under the doctrine of equivalents. The materials referenced, and the citations, are merely exemplary and are not exhaustive. LGES reserves the right to rely on different or additional sources and/or different or additional citations to sources that further illustrate infringement. The evidence of infringement provided below is representative in nature and subject to change as discovery commences, including expert discovery. Further, the ALJ has not yet construed certain claim terms of the ’735 patent. Accordingly, LGES also expressly reserves the right to supplement or amend its claim charts as discovery progresses.

Claims	Exemplary Evidence of Infringement
1[a]. An electrode assembly in a jelly-roll form,	[REDACTED] includes an electrode assembly in a jelly-roll form. As shown below, the [REDACTED] [REDACTED] has an electrode assembly would into a jelly-roll form (winding indicated with blue arrows in cross-sectional view). 
1[b]. the electrode assembly having a separator disposed between a first electrode and a second electrode,	The [REDACTED] includes an electrode assembly having a separator disposed between a first electrode (negative electrode, copper-colored) and a second electrode (positive electrode, silver-colored). Te image on the left shows an unrolled portion of the electrode assembly and the “Positive Electrode (Cathode)” and a separator are labeled. Although the negative electrode is not shown in the image on the left, it is located on the opposite side of the separator. The right image shows a


¹ The [REDACTED] Domestic Industry Product meets each element of claim 1 of the ’735 patent for the same reasons as set forth herein with respect to the [REDACTED].



cross-sectional view of the electrode assembly, where the separator is deposited between the first electrode (Negative Electrode) and a second electrode (Positive Electrode).





1[c]. the electrode assembly being wound about a winding axis along a longitudinal direction,

includes an electrode assembly being wound about a winding axis along a longitudinal direction. As shown below, the electrode assembly is wound (indicated in blue arrows, right image) about a winding axis (red line and red dot, both images) along a longitudinal direction (white line, left image) of the winding (in the direction of the blue arrows).




1[d]. one of the first or second electrodes comprising: an electrode collector; and	The [REDACTED] includes an electrode having has an electrode collector. For example, the first, negative electrode (copper-colored elements and black coating) comprises an electrode collector (see red arrow, copper portions) as shown below. 
1[e]. an active material coated on a coating portion of the electrode collector,	The [REDACTED] includes an active material coated on a coating portion of the electrode collector. As shown below, the active material (black, red arrow) is coated on a coating portion of the electrode collector. 

1[f]. wherein the electrode collector comprises a notching tab part on which the active material is not coated, the notching tab part extending from one side of the coating portion in a width direction of the electrode collector perpendicular to the longitudinal direction,	The [REDACTED] includes an electrode collector comprising a notching tab part on which the active material is not coated, the notching tab part extending from one side of the coating portion in a width direction of the electrode collector perpendicular to the longitudinal direction. For example, the [REDACTED] electrode collector has a notching tab part (raised portions indicted in part with green bracket) extending from one side of the coating portion (black) in a width direction of the electrode collector (indicated by the blue line) perpendicular to the longitudinal direction of the electrode collector (indicated by the white line). 
1[g]. the notching tab part only extending from a first end region of the coating portion in the longitudinal direction located at a radially outer portion of the jelly-roll form remote from the winding axis of the jelly-roll form in a radial direction,	The [REDACTED] includes the notching tab part only extending from a first end region of the coating portion in the longitudinal direction located at a radially outer portion of the jelly-roll form remote from the winding axis of the jelly-roll form in a radial direction. For example, as shown below, the notching tab part (green bracket) only extends from a first end region of the coating portion in the longitudinal direction.

	 As further shown below, when wound, the notching tab part (indicated with green bracket) is located at a radially outer portion of the jelly-roll form remote from the winding axis (red dot) of the jelly-roll form in a radial direction (radial directions from winding axis indicated by yellow line). 
1[h]. wherein the notching tab part has a plurality of notching tabs defined by	The  includes a notching tab part that has a plurality of notching tabs defined by cut portions where the notching tab part is cut. As shown below, the notching tab part (copper portion) has a plurality of tabs defined by the cuts (see red arrow) between them where the notching tab part has been cut to form the copper tabs.



cut portions where the notching tab part is cut,




1 [i]. the plurality of notching tabs are arranged along the radially outer portion of the jelly-roll form such that they are spaced apart from one another in the longitudinal direction of the electrode collector by the cut portions but overlap one another in a radial direction of the jelly-roll form, and

The [REDACTED] includes a plurality of notching tabs arranged along the radially outer portion of the jelly-roll form such that they are spaced apart from one another in the longitudinal direction of the electrode collector by the cut portions but overlap one another in a radial direction of the jelly-roll form.

For example, as shown below, the plurality of copper notching tabs are arranged such that they are spaced apart from one another in the longitudinal direction (horizontal direction below) of the electrode collector by the cut portions (see, e.g., red arrow).




Further, as shown below, in the rolled form, the plurality of copper notching tabs (green bracket) are arranged along a radially outward portion of the jelly-roll form and overlap one another in the radial direction (yellow) of the jelly-roll form.



1[j]. each of the plurality of notching tabs is bent radially inward to define bent parts that overlap one another in an axial direction of the jelly-roll form perpendicular to the radial direction and the circumferential direction to provide welding portions.


The [REDACTED] includes that each of the plurality of notching tabs that is bent radially inward to define bent parts that overlap one another in an axial direction of the jelly-roll form perpendicular to the radial direction and the circumferential direction to provide welding portions.


For example, as shown below, the copper notching tabs are bent radially inwardly (radial direction indicated by yellow line) to define bent parts that overlap one another in the axial direction of the jelly-roll form (the direction into the page) perpendicular to the radial direction (yellow) and the circumferential direction (blue circle).



The copper bent portions (left image) provide welding portions for welding to a cap assembly (right image). As shown below, the cap assembly was removed from the electrode assembly. After removal, some of the welded portions of the copper bent portions remain joined to the cap assembly.



		
10[pre]. A secondary battery comprising:	The  is a secondary battery. For example, the  is an energy storage device that can be charged, discharged, and recharged. 	
10[a]. a can member; and	The  includes a can member, as shown below:	

	
10[b]. the electrode assembly of claim 1 accommodated in the can member,	The [REDACTED] includes the electrode assembly of claim 1 accommodated in the can member. <i>See above</i> at Claim 1. 
10[c]. wherein the bent parts are welded to the can member.	The [REDACTED] includes that the bent parts (left image) are welded to the can member (right image). As shown below, the cap assembly was removed from the electrode assembly. After removal, some of the welded portions of the copper bent portions remain joined to the cap assembly.

