

Exhibit CC-33

INTRODUCTION


DDR5 is the latest iteration of DRAM technology. It offers significant performance improvements over its predecessor, DDR4, with increased data transfer rates, higher memory densities, and lower power consumption. DDR5 DIMMs are the physical modules that contain DDR5 memory chips and are used to expand the memory capacity of a computer system. DDR5 DIMMs have larger burst lengths than DDR4, with a burst length of 16 vs. 8, which allows for a greater amount of data to be transferred between the memory and the CPU.

DDR5 DIMMs also feature improved error correction capabilities, x80 vs. x72 with DDR4, making them more reliable and less prone to data corruption. DDR5 DIMMs operate at a voltage of 1.1 volts, which is lower than the 1.2 volts required by DDR4 DIMMs. This, combined with other power-saving features, makes DDR5 DIMMs more energy-efficient than their predecessors. DDR5 RDIMM includes a Power Management Integrated Circuit (PMIC) to manage power consumption, voltage regulation, and other aspects of power delivery. This is not present in DDR4 because it is a newer technology, designed with more advanced power management features to support higher memory speeds and lower power consumption. Overall, DDR5 DRAM DIMMs represent a significant upgrade in memory technology and are expected to become the standard for high-performance computing in the years to come.


DDR5 MRDIMM (Multiplexed Rank DIMM) is specifically designed to meet the demanding needs of AI and HPC servers. By leveraging existing DDR5 DRAM memory devices, MRDIMM modules double the DRAM data rate, providing up to 2.3X better performance for HPC workloads and up to 2X better performance for AI inference workloads. This high bandwidth and low latency memory solution accelerates memory-intensive applications, making it ideal for environments that require rapid data processing and real-time analytics. Additionally, MRDIMM modules maintain the reliability and error correction capabilities of RDIMM modules, ensuring robust performance in critical computing tasks. With these advancements, DDR5 MRDIMM offers a compelling value proposition for enhancing the efficiency and speed of AI and HPC servers.

Netlist offers a wide lineup of leading-edge commercial and industrial grade DDR5 DIMMs and DDR5 MRDIMMs. All memory and storage products are 100% system tested from -40°C to +95°C for Industrial Temp Grade and from 0°C to +85°C for Commercial Temp Grade. Netlist's rigorous testing process is specifically designed to ensure these modules will operate reliably in harsh, long-life computing environments and densely configured computing applications with limited airflow.

Available in registered and unbuffered with ECC or non-ECC configurations, DIMM form factors include standard Low-Profile and Very Low Profile heights. OEMs can choose Netlist industry-standard and custom modules with confidence knowing Netlist designs, manufactures, and rigorously tests each unit.



RDIMM



VLP RDIMM



UDIMM



SODIMM



MRDIMM



DDR5 DIMMs

FEATURES

- Data rates up to 6400 Mbps
- Burst Length (BL16)
- On-Die Error Correction Coding (ECC)
- Post-Package Repair
- Refresh Management
- CRC (write & read)
- Decision Feedback Equalization (DFE)
- Temperature Sensor-ICs on DIMM
- Enhanced Training Modes
- Up to 256GB RDIMM capacity
- Reduced I/O voltage (1.1V)
- Multiple DIMM Form Factors: RDIMM, VLP RDIMM, UDIMM and SODIMM in Non-ECC and ECC

BENEFITS

- Locked BOM Support
- JEDEC Compliant
- 100% System level testing
- Technical support
- Customization

NETLIST DDR5 RDIMM ORDERING INFORMATION

	DENSITY	ORGANIZATION	MAX SPEED	PART NUMBER
RDIMM	16GB	1Rx8	4800MT/s	NLR4G0054G0748200HA
			5600MT/s	NLR4G0054G0756200HA
	32GB	1Rx4	4800MT/s	NLR5G0054G0348200HA
			5600MT/s	NLR5G0054G0356200HA
		2Rx8	4800MT/s	NLR5G0054G0748200HA
			5600MT/s	NLR5G0054G0756200HA
	48GB	1Rx4	4800MT/s	NLRFG0054G0348200HA
			5600MT/s	NLRFG0054G0356200HA
		2Rx8	4800MT/s	NLRFG0054G0748200HA
			5600MT/s	NLRFG0054G0756200HA
	64GB	2Rx4	4800MT/s	NLR6G0054G0348200HA
			5600MT/s	NLR6G0054G0356200HA
	96GB	2Rx4	4800MT/s	NLRCG0054G0348200HA
			5600MT/s	NLRCG0054G0356200HA
	128GB	4Rx4	4800MT/s	NLR7G0054G3B48209HM
			5600MT/s	NLR7G0054G3B56209HA
	128GB	4RX4	4800MT/s	NLR7G0054G3B48200HA
	16GB	1Rx8	4800MT/s	NVR4G0054G0748201HA

VLP RDIMM	16GB	1Rx8	5600MT/s	NVR4G0054G0756202HA
	32GB	2Rx8	4800MT/s	NVR5G0054G0748201HA
			5600MT/s	NVR5G0054G0756202HA
	48GB	2Rx8	4800MT/s	NVRFG0054G0748201HA
			5600MT/s	NVRFG0054G0756202HA

NETLIST DDR5 UDIMM AND SODIMM ORDERING INFORMATION

	DENSITY	ORGANIZATION	MAX SPEED	PART NUMBER
nECC UDIMM	8GB	1Rx16	4800MT/s	NLU3G0054G1548200HA
	16GB	1Rx8		NLU4G0054G0748200HA
	32GB	2Rx8		NLU5G0054G0748200HA
	48GB	2Rx8		NLUF0054G0748200HA
nECC UDIMM	8GB	1Rx16	5600MT/s	NLU3G0054G1556200HA
	16GB	1Rx8		NLU4G0054G0756200HA
	32GB	2Rx8		NLU5G0054G0756200HA
	48GB	2Rx8		NLUF0054G0756200HA
ECC UDIMM	16GB	1Rx8	4800MT/s	NLE4G0054G0748200HA
	32GB	2Rx8		NLE5G0054G0748200HA
	48GB	2Rx8		NLEFG0054G0748200HA
ECC UDIMM	16GB	1Rx8	5600MT/s	NLE4G0054G0756200HA
	32GB	2Rx8		NLE5G0054G0756200HA
	48GB	2Rx8		NLEFG0054G0756200HA
nECC SODIMM	8GB	1Rx16	4800MT/s	NLS3G0054G1548200HA
	16GB	1Rx8		NLS4G0054G0748200HA
	32GB	2Rx8		NLS5G0054G0748200HA
	48GB	2Rx8		NLSFG0054G0748200HA
nECC SODIMM	8GB	1Rx16	5600MT/s	NLS3G0054G1556200HA
	16GB	1Rx8		NLS4G0054G0756200HA
	32GB	2Rx8		NLS5G0054G0756200HA

	32GB	2Rx8		NLS5G0054G0756200HA
	48GB	2Rx8		NLSFG0054G0756200HA
ECC SODIMM	16GB	1Rx8	4800MT/s	NLT4G0054G0748200HA
	32GB	2Rx8		NLT5G0054G0748200HA
	48GB	2Rx8		NLTFG0054G0748200HA
ECC SODIMM	16GB	1Rx8	5600MT/s	NLT4G0054G0756200HA
	32GB	2Rx8		NLT5G0054G0756200HA
	48GB	2Rx8		NLTFG0054G0756200HA

APPLICATIONS

- Client PC
 - WS/Server
- AI/ML
 - HPC Workloads
- Industrial

ADDED VALUE

- Side Fill
 - Conformal Coating
- Rugged Clip
 - Heat Spreader

MARKETING COLLATERAL



Netlist DDR5 DIMMs Product Brief

MRDIMMs

FEATURES

- Parallel DRAM Activation: Enables pairs of DRAM ranks to be activated and accessed simultaneously
- Multiplexed Data Streams: Doubles the data rate per signal pin, enhancing memory bandwidth
- Increased Capacity: Supports more than two ranks of DRAM, allowing for higher memory capacity
- Backward Compatibility: Compatible with existing DDR5 RDIMMs, providing flexibility in system configurations
- High-Speed Multiplexer: Uses a high-speed multiplexer to read memory banks simultaneously
- Tall Form-Factor (TFF): Accommodates additional memory chips without requiring more physical slots

BENEFITS

- Enhanced Performance: Substantially improves memory bandwidth and capacity, supporting compute-intensive workloads like AI and HPC
- Cost-Efficiency: Increases memory capacity in a cost-effective manner
- Future-Proofing: Helps future-proof server designs against escalating demands of high-performance computing
- Optimized Power Efficiency: Delivers high current at low voltages to support more DRAM per module

without requiring more physical slots

NETLIST DDR5 MRDIMM ORDERING INFORMATION

	DENSITY	ORGANIZATION	MAX SPEED	LATENCY	PART NUMBER
MRDIMM	32GB	1Rx4	8800MT/s	36-36-36 @ 11V	NLM5G0054G0388200HC
	32GB	2Rx8	8800MT/s	36-36-36 @ 11V	NLM5G0054G0788200HC
	64GB	2Rx4	8800MT/s	36-36-36 @ 11V	NLM6G0054G0388200HC
	64GB	4Rx8	8800MT/s	36-36-36 @ 11V	NLM6G0054G0788200HC
	128GB	2Rx4	8800MT/s	36-36-36 @ 11V	NLM7G0055G0388200HM

APPLICATIONS

- Client PC
 - WS/Server
- AI/ML
 - HPC Workloads
- Industrial

ADDED VALUE

- Side Fill
 - Conformal Coating
- Rugged Clip
 - Heat Spreader

MARKETING COLLATERAL



Netlist MRDIMMs Product Brief

PRODUCTS

- Enterprise SSD
- Embedded Flash
- Memory Module
- Lightning DDR5 DIMM
- SK Hynix
- AI Server

SALES SUPPORT

- US & International
- Sales Inquiry

COMPANY

- About Netlist
- Leadership
- Contact
- Sitemap
- Privacy Policy
- Terms of Use

INVESTORS

- News
- Events and Presentations
- SEC Filings
- Financial Documents
- Management
- Gov Docs
- Responsibility
- Stock Chart
- Analyst Coverage
- Email Alerts

MRDIMM	32GB	1Rx4	8800MT/s	36-36-36 @ 11V	NLM5G0054G0388200HC
	32GB	2Rx8	8800MT/s	36-36-36 @ 11V	NLM5G0054G0788200HC
	64GB	2Rx4	8800MT/s	36-36-36 @ 11V	NLM6G0054G0388200HC
	64GB	4Rx8	8800MT/s	36-36-36 @ 11V	NLM6G0054G0788200HC
	128GB	2Rx4	8800MT/s	36-36-36 @ 11V	NLM7G0055G0388200HM

APPLICATIONS

- Client PC
 - WS/Server
- AI/ML
 - HPC Workloads
- Industrial

ADDED VALUE

- Side Fill
 - Conformal Coating
- Rugged Clip
 - Heat Spreader

MARKETING COLLATERAL



Netlist MRDIMMs Product Brief

PRODUCTS

- Enterprise SSD
- Embedded Flash
- Memory Module
- Lightning DDR5 DIMM
- SK Hynix
- AI Server

SALES SUPPORT

- US & International
- Sales Inquiry

COMPANY

- About Netlist
- Leadership
- Contact
- Sitemap
- Privacy Policy
- Terms of Use

INVESTORS

- News
- Events and Presentations
- SEC Filings
- Financial Documents
- Management
- Gov Docs
- Responsibility
- Stock Chart
- Analyst Coverage
- Email Alerts