

Exhibit 50

QC
PASSED

Spring SR112051601
Max. Load: 4000N
Stroke: 210mm Speed: 16mm/s
S/N: SR202407160020

Linear actuator

Model: SRPT

Rated Voltage: DC29V

Rated Input: 75W

Max. Duty Cycle: 2min ON and 18min OFF(10%)



E114872

CONFORMS TO UL STD.1004-1
CERTIFIED TO CSA STD.C22.2 NO.100-14



⚠ Use SR Power Supply only

⚠ Do not operate the actuator over
Max. Duty Cycle.

Spring

WARNING

DO NOT REMOVE THIS TAG
This tag is a warning label and is required to be placed on all
products in this product line. The product is a linear actuator
and is designed for use in a variety of applications. It is not
to be used in applications where it is not designed for use.
The user must read the instructions carefully and follow the
instructions to avoid injury or damage to the product.
The user must also read the safety instructions and follow the
instructions to avoid injury or damage to the product.
The user must also read the safety instructions and follow the
instructions to avoid injury or damage to the product.

NOTICE

THIS ARTICLE MEETS
FLAMMABILITY REQUIREMENTS
CALIFORNIA BUREAU
HOUSEHOLD GOODS AND
TECHNICAL BULLETIN 117
CARE SHOULD BE EXERCISED
OPEN FLAME OR WITH BURNING
CIGARETTES

The upholstery materials in this
contain added flame retardants.

UNDER PENALTY OF LAW THIS TAG
NOT TO BE REMOVED EXCEPT
BY THE CONSUMER

ALL NEW MATERIAL
CONSISTING OF

BODY

POLYURETHANE FOAM PAD	54%
POLYESTER FIBER	35%
POLYESTER FIBER BATTING	11%

REG. NO. PA 42251(VN)

Certification is made by the manufacturer
that the materials in this article are described