

PUBLIC VERSION

Exhibit 82C

REDACTED



September 25, 2025

direct dial 336 607 7475
mferrario@ktslaw.com

via UPS, Return Receipt

Zhejiang Henglin Chair Industry Co., Ltd.
No. 378 & 380 Jiayi Road
Dipu Street, Anji County
Huzhou, Zhejiang Province 313300
CHINA

Re: Infringement of Ultra-Mek's Patent Rights

Dear Sir or Madam:

We represent Ultra-Mek, Inc. I am writing to you about Zhejiang Henglin Chair Industry Co., Ltd.'s ("Henglin") infringement of Ultra-Mek's patent rights.

Henglin is [REDACTED]
[REDACTED] that infringe patents owned by Ultra-Mek, including U.S. Patent No. 7,997,644, U.S. Patent No. 8,016,348, U.S. Patent No. 8,297,693, and U.S. Patent No. 8,459,733. A copy of each of these patents is enclosed. [REDACTED]
[REDACTED]

[REDACTED]

[REDACTED]

PUBLIC VERSION

Henglin
September 25, 2025
Page 2

[REDACTED]

[REDACTED]

[REDACTED]

[REDACTED]

Sincerely,



Matias Ferrario

Enclosures

[REDACTED]

cc: Ultra-Mek, Inc.

Attachments

(12) **United States Patent**
Hoffman et al.

(10) **Patent No.:** **US 7,997,644 B2**

(45) **Date of Patent:** **Aug. 16, 2011**

(54) **GLIDING-RECLINING SEATING UNIT WITH POWER ACTUATOR**

FOREIGN PATENT DOCUMENTS

GB 2 106 777 A 4/1983

OTHER PUBLICATIONS

Lusch Brochure: "Functional Fitting and Tubular steel frames for Relaxing Chairs (11 pages), Functional Fittings for Sofabeds and Beds (10 pages), Bed Fitting (5 pages) and Upholstery joints and accessories for furniture (9 pages)", (available before Apr. 7, 2006).

(Continued)

- (75) Inventors: **D. Stephen Hoffman**, High Point, NC (US); **Marcus L. Murphy**, Lexington, NC (US)
- (73) Assignee: **Ultra-Mek, Inc.**, Denton, NC (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 275 days.

(21) Appl. No.: **12/276,567**

(22) Filed: **Nov. 24, 2008**

(65) **Prior Publication Data**

US 2010/0127555 A1 May 27, 2010

- (51) **Int. Cl.**
A47C 1/031 (2006.01)
A47C 1/00 (2006.01)
- (52) **U.S. Cl.** **297/85 M; 297/344.21**
- (58) **Field of Classification Search** **297/85 M, 297/68, 342, 330, 344.21, 344.24, 344.26**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

507,270 A	10/1893	Hirschfeld
2,526,623 A	10/1950	Maurer
2,714,922 A	8/1955	McKibban et al.
3,016,264 A	1/1962	Hughes
3,147,038 A	9/1964	Barabas
3,383,135 A	5/1968	Posh
3,622,202 A	11/1971	Brown
3,863,980 A	2/1975	Ciner
4,307,912 A	12/1981	Watt et al.

(Continued)


Primary Examiner — Milton Nelson, Jr.

(74) *Attorney, Agent, or Firm* — Myers Bigel Sibley & Sajovec

(57) **ABSTRACT**

A gliding and reclining seating unit includes: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a power actuating unit attached to the reclining mechanism. The actuating unit is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

23 Claims, 5 Drawing Sheets



PUBLIC VERSION

US 7,997,644 B2

Page 2

U.S. PATENT DOCUMENTS

4,386,803 A 6/1983 Gilderbloom
4,674,794 A 6/1987 Pine
4,681,365 A 7/1987 Pine
4,682,815 A 7/1987 Steifensand
4,691,964 A 9/1987 Morgan
4,696,512 A 9/1987 Burnett et al.
4,722,566 A 2/1988 Castellini
4,813,743 A 3/1989 Mizelle
4,915,444 A 4/1990 Rogers, Jr.
5,007,679 A 4/1991 Mizelle
5,086,769 A 2/1992 Vianello et al.
5,704,686 A * 1/1998 May 297/281
5,884,970 A 3/1999 Howard
5,931,535 A 8/1999 Sweet
6,491,342 B1 12/2002 Smith
6,540,291 B2 4/2003 Hoffman et al.

6,612,650 B1 9/2003 Ambrosio et al.
6,840,575 B2 1/2005 Hesse
6,843,531 B2 * 1/2005 Williams 297/337
6,893,085 B2 5/2005 LaPointe et al.
6,896,323 B2 * 5/2005 LaPointe et al. 297/85 M
6,948,777 B2 9/2005 Marshall et al.
7,083,235 B2 8/2006 Grimm et al.
7,188,904 B2 3/2007 Bruck et al.
7,293,834 B2 11/2007 Riach et al.
7,311,359 B2 12/2007 Smith
2006/0082195 A1 4/2006 Jiang
2011/0018331 A1 * 1/2011 Murphy et al. 297/85 R

OTHER PUBLICATIONS

“Stawett Functional Bed Mechanisms Brochure”, pp. 3-93 (2001).

* cited by examiner





FIG. 1







FIG. 3






FIG. 5

US 7,997,644 B2

1

**GLIDING-RECLINING SEATING UNIT WITH
POWER ACTUATOR****FIELD OF THE INVENTION**

This invention relates generally to seating units, and relates more particularly to reclining seating units with rocking capability.

BACKGROUND OF THE INVENTION

Recliner chairs and other reclining seating units have proven to be popular with consumers. These seating units typically move from an upright position, in which the backrest is generally upright, to one or more reclined positions, in which the backrest pivots to be less upright. The movement of the seating unit between the upright and reclined positions is typically controlled by a pair of matching reclining mechanisms that are attached to the seat, backrest and base of the chair.

In recent years, furniture designers have looked for alternatives to rocking chairs that can provide a similarly relaxing repetitive motion. One alternative has been the gliding chair, or "glider", which includes structure that enables the seat portion of the chair to "glide" forwardly and rearwardly relative to its base to mimic generally the rocking motion of a rocking chair. Often the gliding structure comprises a set of swing links (usually two at the front of the chair, and two at the rear) that are pivotally attached at their upper ends to the base and extend downwardly therefrom to attach to a structure, such as a mounting bracket, that is attached to the seat. In this configuration, the seat is suspended from the base and is free to swing forwardly and rearwardly in a double pendulum-type motion in response to a forwardly or rearwardly-directed force applied by a seated occupant. The gliding path of the chair is controlled by the configuration and mounting of the swing links. These chairs can be constructed to resemble traditional rocking chairs and thus are quite popular.

Reclining capability has been combined with gliding capability in a single unit to provide a chair that both reclines and glides. This chair includes a reclining mechanism that enables it to move between upright and one or more reclined positions, and further includes the aforementioned swing links attached between the base and the seat, armrests, or mechanism itself to enable the chair to glide. Examples of such chairs are illustrated and described in U.S. Pat. Nos. 4,536,029 and 4,544,201, both to Rogers, Jr., the disclosures of which are hereby incorporated herein by reference in their entireties.

Although they are already popular seating units, it may be desirable to provide additional functionality to glider-recliners.

SUMMARY OF THE INVENTION

As a first aspect, embodiments of the present invention are directed to a gliding and reclining seating unit. The glider-recliner comprises: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the

2

base unit along a longitudinal path responsive to a longitudinally-directed force; and a power actuating unit attached to the reclining mechanism. The actuating unit is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

As a second aspect, embodiments of the present invention are directed to a gliding and reclining seating unit, comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a linear actuator attached to the reclining mechanism. The linear actuator is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

As a third aspect, embodiments of the present invention are directed to a gliding and reclining seating unit, comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a linear actuator attached to the reclining mechanism. The linear actuator is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The reclining mechanism includes a pantographic linkage on which the ottoman is mounted. In the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position. The reclining mechanism also includes a backpost that is fixed relative to the backrest, a mounting bracket that is fixed rela-

tive to the rocker cams and pivotally attached to the backpost, and a seat adapter that is fixed relative to the seat and pivotally attached to the backpost.

As a fourth aspect, embodiments of the present invention are directed to a gliding and reclining seating unit comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a power actuating unit attached to the reclining mechanism. The actuating unit is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The reclining mechanism includes a backpost fixed relative to the backrest and a sequencer plate pivotally interconnected with the backrest and with the remainder of the reclining mechanism, and wherein the sequencer plate rotates in a first rotative direction relative to the backrest when the seating unit moves from the upright position to the TV position, and wherein the backrest rotates relative to the sequencer plate in the first rotative direction when the seating unit moves from the TV position to the fully reclined position.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view of a glider-recliner chair according to embodiments of the present invention.

FIG. 2 is a side section view of the chair of FIG. 1 with the chair in its fully upright position.

FIG. 3 is a side section view of the chair of FIG. 1 with the chair in its TV position.

FIG. 4 is a side section view of the chair of FIG. 1 with the chair in its fully reclined position.

FIG. 5 is a top cutaway view of the frame of the chair of FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The present invention now is described more fully herein after with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

Like numbers refer to like elements throughout. In the figures, the thickness of certain lines, layers, components, elements or features may be exaggerated for clarity. Broken lines illustrate optional features or operations unless specified otherwise.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items. As used herein, phrases such as "between X and Y" and "between about X and Y" should be interpreted to include X and Y. As used herein, phrases such as "between about X and Y" mean "between about X and about Y." As used herein, phrases such as "from about X to Y" mean "from about X to about Y."

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

It will be understood that when an element is referred to as being "on", "attached" to, "connected" to, "coupled" with, "contacting", etc., another element, it can be directly on, attached to, connected to, coupled with or contacting the other element or intervening elements may also be present. In contrast, when an element is referred to as being, for example, "directly on", "directly attached" to, "directly connected" to, "directly coupled" with or "directly contacting" another element, there are no intervening elements present. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed "adjacent" another feature may have portions that overlap or underlie the adjacent feature.

This invention is directed to seating units that have a stationary base, a seat portion, and a backrest. As used herein, the terms "forward", "forwardly", and "front" and derivatives thereof refer to the direction defined by a vector extending from the backrest toward the seat parallel to the underlying surface. Conversely, the terms "rearward", "rearwardly", and derivatives thereof refer to the direction directly opposite the forward direction; the rearward direction is defined by a vector that extends from the seat toward the backrest parallel to the underlying surface. The terms "lateral," "laterally", and derivatives thereof refer to the direction parallel with the floor, perpendicular to the forward and rearward directions, and extending away from a plane bisecting the seating units between their armrests. The terms "medial," "inward," "inboard," and derivatives thereof refer to the direction that is the converse of the lateral direction, i.e., the direction parallel with the floor, perpendicular to the forward direction, and extending from the periphery of the seating units toward the aforementioned bisecting plane.

The seating units illustrated and described herein comprise a plurality of pivotally interconnected links. Those skilled in this art will appreciate that the pivots between links can take a variety of configurations, such as pivot pins, rivets, bolt and nut combinations, and the like, any of which would be suitable for use with the present invention. Also, the shapes of the

US 7,997,644 B2

5

links may vary as desired, as may the locations of certain of the pivots. Moreover, in some instances combinations of pivot points may be replaced by equivalent structures, such as “slider-crank” configurations, like those described in B. Paul, *Kinematics and Dynamics of Planar Machinery* 4-21 (1979).

Referring now to the figures, a swiveling glider-recliner chair, designated broadly at **10**, is illustrated in FIGS. 1-5. The chair **10** includes a base unit **11**, a seat **13** that is generally horizontally disposed above the base unit **11**, a backrest **15** that is generally vertically and disposed substantially above a rear portion of the seat **13**, and two ottomans **17a**, **17b**, which, in the upright position of FIG. 1, are generally vertically disposed below a front portion of the seat **13**. Arms **18** are positioned on either side of the seat **13** and move in concert with the seat **13**.

A pair of mirror image reclining mechanisms **30** (only one of which is shown herein in FIGS. 2-4) are attached to the backrest **15**, the seat **13**, and the ottomans **17a**, **17b**. The reclining mechanisms **30**, which comprise a plurality of interconnected links, move the chair **10** between (a) an upright position (FIGS. 1 and 2), in which the seat **13** is generally horizontally disposed, the backrest **15** is generally vertically disposed, and the ottomans **17a**, **17b** are generally vertically disposed and positioned below the seat **13**, (b) an intermediate TV position (FIG. 3), in which the ottomans **17a**, **17b** are generally horizontally disposed in front of the seat **13** and the backrest **15** and the seat **13** substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position (FIG. 4), in which the angle between the backrest **15** and the seat **13** increases. These components are described in greater detail below.

The base unit **11** includes a circular lower base **12**. A swivel unit **14** is mounted onto the top of the lower base **12**. Cross-members **18** are mounted atop the swivel unit **14**. Those skilled in this art will recognize that the base unit **11** may take other forms that provide mounting locations for the remaining components of the chair **10**; for example, the swivel unit **14** may be omitted.

Glide foundation plates **24** are mounted to the top surfaces of the cross-members **18**. A front glide link **20** is attached at a pivot **21** to the front end of the glide foundation plate **24**, and a rear glide link **25** is attached at a pivot **26** to the rear end of the glide foundation plate **24**. The front and rear glide links **20**, **25** are suspended from the glide foundation plate **24** and together form a gliding mechanism **28** that provides a gliding motion to the chair **10** when it is in its upright position (FIG. 2). Those skilled in this art will appreciate that the gliding mechanism may take other forms; it may include glide links of different shapes, or it may include a “track”-based gliding mechanism.

Because the reclining mechanisms **30** are mirror images of each other, only one reclining mechanism will be described in detail herein, with the understanding that the discussion is equally applicable to the mirror image mechanism **30**. Also, for clarity the mechanism will be described first with reference to FIG. 4 (with the mechanism **30** in its reclined position), then will be described in its upright and TV positions.

Turning now to FIG. 4, the reclining mechanism **30** includes a generally arcuate foundation link **31**, which is attached at either end to the front and rear glide links **20**, **25** at pivots **22**, **27**, respectively. A generally crescent-shaped mounting bracket **32** is fixed to the foundation link **31**. A slot **32a** is present at the front end of the mounting bracket **32**. An L-shaped lower swing link **34** is attached to a lower region of the mounting bracket **32** at a pivot **36** and extends upwardly and rearwardly, then upwardly and forwardly therefrom. A

6

straight upper swing link **38** is attached at its lower end to the upper end of the lower swing link **34** at a pivot **40** and extends upwardly therefrom.

A backpost **48** is fixed to the backrest **15** and extends generally forwardly from the lower front end of the backrest **15**. The upper swing link **38** is attached to a forward portion of the backpost **48** at a pivot **50**. A straight coupling link **52** having a slot **52a** is attached to the backpost **48** via a pin **48a** located forwardly of the pivot **50**. The coupling link **52** extends forwardly and downwardly from the pin **48a** to attach to the front end of the mounting bracket **32** via a pin **52b** inserted into a slot **32a** in the mounting bracket **32**. A trap-ezoidal sequencer plate **54** is attached to the backpost **48** at a pivot **58**, and also interacts with the backpost **48** via a slot **54a** that receives a pin **48b**. The sequencer plate **54** is also attached to the rear end of the mounting bracket **32** at a pivot **56**.

Still referring to FIG. 4, a seat frame **62**, to which the arms **18** are mounted, underlies the seat **13**. A seat adapter **66** is fixed to the seat frame **62**. The seat adapter **66** is attached to the backpost **48** at a pivot **68** that is located just rearward of the pivot **50**. An upper ottoman swing link **72** is attached to a front region of the seat adapter **66** at a pivot **74** and extends downwardly and forwardly therefrom. A tripartite lower ottoman swing link **76** is attached to a pivot **78** that is located rearwardly and downwardly from the pivot **74**; the lower ottoman swing link **76** extends generally forwardly from the pivot **78**. An upper ottoman extension link **80** is attached to the forward end of the lower ottoman swing link **76** at a pivot **82** and extends forwardly and upwardly therefrom. Also the upper ottoman extension link **80** is attached to the upper ottoman swing link at a pivot **84**. A lower ottoman extension link **86** is attached to the forward end of the upper ottoman swing link at a pivot **88** that is positioned above and forward of the pivot **84** and extends upwardly and forwardly therefrom generally parallel with the upper ottoman extension link. An outer ottoman bracket **90** is generally horizontally disposed and is attached to the upper and lower ottoman extension links **80**, **86** at pivots **92**, **94** respectively. The ottoman **17a** is mounted on the outer ottoman bracket **90**.

An L-shaped inner ottoman bracket **96** is attached at its lower, forward end to the lower ottoman extension link **86** at a pivot **98**. At its opposite end, the inner ottoman bracket **96** supports the ottoman **17b**. The inner ottoman bracket **96** also includes a slot **96a** that receives a pin **80a** located on the upper ottoman extension link **80**.

A connecting link **100** is attached to the sequencer plate **54** at a pivot **102**. The connecting link **100** extends forwardly and slightly upwardly from the pivot **102** to a pivot **104** with the lower ottoman swing link **76**.

A locking mechanism **130** is attached to the reclining mechanism **30** to prevent gliding of the chair **10** when it is in the TV or fully reclined positions. The locking mechanism **130** includes a drive link **132** that is pivotally interconnected at one end to the sequencer plate **54** at a pivot **134**. The drive link **132** is a straight link that slopes downwardly and slightly forwardly from the pivot **134**. The opposite end of the drive link **132** is pivotally interconnected with a downwardly-extending projection **138** of a hook-shaped locking link **136** at a pivot **140**. The locking link **136** is attached to the mounting bracket **32** at a pivot **142**.

The chair **10** includes a power unit **112** that drives the chair **10** between its upright, TV and fully reclined positions. The power unit **112** includes a motor unit **114**, to which is attached a sleeve **116**. The sleeve extends rearwardly from the motor unit **114** and receives a retractable rod **118**. The motor unit

7

114 is electrically connected with an actuator (not shown), such as a toggle switch or the like, that energizes the motor unit 114 upon actuation.

The motor unit 114 is attached to a mounting bracket 110 at a pivot 120 via a mounting tab 114a (see FIG. 5). The mounting bracket 110 is then attached to a cross-member 108 that extends between the reclining mechanisms 30. A bracket 106 is fixed to each of the lower ottoman swing links 76 and to the cross-member 108.

The rod 118 of the power unit 112 is attached to a bracket 46 (FIG. 5) at a pivot 122. The bracket 46 is then attached to a cross-member 44 that extends between the reclining mechanisms 30; the cross-member 44 is fixed to a bracket 42 that is in turn fixed to the upper swing link 38 of each reclining mechanism 30.

As can be seen in FIG. 2, in the upright position, the rod 118 of the power unit 112 is retracted into the sleeve 116. As a result, a pantographic linkage formed by the upper and lower ottoman swing links 72, 76 and the upper and lower ottoman extension links 80, 86 are folded under the seat frame 62, which positions the ottoman 17b underneath a forward portion of the seat frame 62 and the ottoman 17a just forward of and below the seat frame 62 in a vertical orientation. Also, the lower and upper swing links 34, 38 are oriented such that the upper segment of the lower swing link 34 is generally horizontal, which positions the backpost 48 and, in turn, the backrest 15, in a generally upright position.

Additionally, the sequencer plate 54 is oriented such that the pivot 102 is located downwardly and rearwardly, such that the locking link 136 of the locking mechanism 130 is raised, with a pocket 137 facing downwardly and positioned above a post 139 on the rear glide link 25. In this position, the chair 10 is free to glide as the front and rear glide links 20, 25 are free to swing on the pivots 21, 26, thereby enabling the reclining mechanisms 30, the seat 13, the backrest 15 and the ottomans 17a, 17b to move fore-and-aft relative to the base unit 11. During the gliding motion, the majority of the locking mechanism 130 is stationary relative to the reclining mechanisms 30. Because the locking link 136 does not move relative to the reclining mechanism 30 as the chair 10 glides, it does not interact with the post 139.

To move the chair 10 from the upright position to the TV position of FIG. 3, an occupant of the chair 10 actuates the actuator, which causes the rod 118 to begin to extend from the sleeve 116. Extension of the rod 118 forces the upper swing link 38 to rotate slightly counterclockwise (from the vantage point of FIGS. 2 and 3) about the pivot 40. This movement draws the backpost 48 and rear end of the seat frame 62 downwardly, which causes the seat 13 to increase in pitch angle relative to the underlying surface. However, the weight of the seated occupant prevents further rotation of the upper swing link 38 at this point. Because there is little to no fore-and-aft movement of the rear end of the rod 118, the motor unit 114 moves forwardly relative to the base unit 11, thereby driving the lower ottoman swing link 76 counterclockwise about the pivot 78. Rotation of the lower ottoman swing link 76 forces the upper ottoman extension link 80 forward, which in turn draws the upper ottoman swing link 72 counterclockwise around the pivot 74. Also, the lower ottoman extension link 86 moves forwardly more than the upper ottoman extension link 80, such that the outer ottoman bracket 90 and the inner ottoman bracket 96 rotate counterclockwise (rotation of the inner ottoman bracket 96 causes the pin 80a to move in the slot 96a toward the pivot 98). The rotation of the outer and inner ottoman brackets 90, 96 induces the ottomans 17a, 17b to rotate from a vertical orientation to a horizontal orientation. Motion of the ottomans 17a, 17b ceases when a pin 72a on the

8

upper ottoman swing link 72 strikes the upper edge of the upper ottoman extension link 80.

In addition, the rotation of the lower ottoman swing link 76 draws the connecting link 100 forward. Movement of the connecting link 100 rotates the sequencer plate 54 counterclockwise about the pivot 58 with the backpost 48. The drive link 132 of the locking mechanism 130 is driven down and rotates the locking link 136 counterclockwise. The movement of the locking link 136 ceases when the pocket 137 of the locking link 136 descends sufficiently to receive the post 139 on the rear glide link 25. In this position, relative movement between the front and rear glide links 20, 25 and the reclining mechanisms is restrained, thereby preventing the reclining mechanisms 30, and in turn the chair 10, from gliding relative to the base unit 11.

To move the chair 10 from the TV position of FIG. 3 to the fully reclined position of FIG. 4, the occupant can continue to operate the actuator, which extends the rod 118 farther out of the sleeve 116. When the ottomans 17a, 17b are fully extended, the pivots 84, 88 and 94 are in a near "over-center" condition that helps to lock the ottomans 17a, 17b in an extended position. Thus, as the rod 118 continues to extend from the sleeve 116 when the chair is in the TV position, the motor unit 114 cannot move forward relative to the base unit 11 any farther, so the rear end of the rod 118 begins to move rearwardly relative to the base unit 11, resulting in clockwise rotation of the upper swing link 38 about the pivot 40. This rotation both drives the lower swing link 34 counterclockwise about the pivot 36 and drives the forward end of the backpost 48 upward. As a consequence, the backpost 48 rotates counterclockwise about the pivot 58 relative to the sequencer plate 54 (and to the seat adapter 66 and the seat frame 62). Rotation of the backpost 48 and, in turn, the backrest 15, continues until (a) the pin 48b on the backpost 48 reaches the upper end of the slot 54a in the sequencer plate 54 and the pin 52b of the coupling link 52 reaches the rear end of the slot 32a of the mounting bracket 32. In this position, the backrest 15 has reclined relative to the seat 13 at a greater angle than in the upright and TV positions.

As can also be seen in FIG. 4, the locking mechanism 130 continues to prevent the chair 10 from gliding as the chair 10 moves to the fully reclined position. It can also be seen that the seat 13 rises during movement from the TV position to the fully reclined position.

The chair 10 can be returned to its TV position from the fully reclined position by the occupant operating the actuator in the reverse direction. Because of the over-center condition of the pivots 82, 84, 88, the ottomans 17a, 17b remain extended, such that retraction of the rod 118 draws the backrest 15 to its upright position. Once the motion of the backrest 15 is complete, the over-center condition of the pivots 84, 88 and 94 can be overcome, and the ottomans 17a, 17b are able to retract to the upright position.

Those skilled in this art will recognize that other variations of the chair 10 are contemplated in connection with the present invention. For example, the power unit 112 may be reversed, such that the motor 114 is at the rear end of the power unit 112 and the rod 118 is at the front end. In such a case, the rod 118 would extend forwardly relative to the base unit 11 as the chair 10 moved from the upright position to the TV position, and the motor 114 would move rearwardly relative to the base unit 11 when the chair moved from the TV position to the fully reclined position. In either instance, the front end of the power unit 112 moves relative to the base unit 11 during the movement from the upright to the TV position,

and the rear end of the power unit moves relative to the base unit **11** during the movement from the TV to the fully reclined position.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as recited in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

That which is claimed is:

1. A gliding and reclining seating unit, comprising:
a base unit with a first bearing surface;
a generally horizontally-disposed seat positioned above the base unit;
a generally upright backrest positioned above the base unit and substantially rearward of the seat;
an extendable ottoman;
a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links;
a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and
a power actuating unit attached to the reclining mechanism, the actuating unit configured to move the seating unit between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

2. The seating unit defined in claim **1**, wherein the reclining mechanism includes a pantographic linkage on which the ottoman is mounted, and wherein in the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position.

3. The seating unit defined in claim **1**, further comprising a locking mechanism that allows the seating unit to glide while in the upright position but prevents gliding of the seating unit while in the TV and fully reclined positions.

4. The seating unit defined in claim **1**, wherein the power actuating unit includes opposed first and second ends, and wherein the first end of the power actuating unit moves forwardly as the seating unit moves from the upright position to the TV position, and wherein the second end of the power actuating unit moves rearwardly when the seating unit moves from the TV position to the fully reclined position.

5. The seating unit defined in claim **4**, wherein the reclining mechanism includes a lower swing link pivotally attached with the base unit and an upper swing link pivotally attached with the lower swing link and with the backrest, and wherein the second end of the power actuating unit is attached with the upper swing link.

6. The seating unit defined in claim **4**, wherein the power actuating unit includes a motor and an extendable member at the first and second ends.

7. The seating unit defined in claim **1**, wherein the seat rises in moving from the TV position to the fully reclined position.

8. The seating unit defined in claim **1**, wherein the base unit further comprises a swivel unit.

9. The seating unit defined in claim **1**, wherein the reclining mechanism includes a backpost that is fixed relative to the backrest, a mounting bracket that is fixed relative to the gliding mechanism and pivotally attached to the backpost, and a seat adapter that is fixed relative to the seat and pivotally attached to the backpost.

10. A gliding and reclining seating unit, comprising:

a base unit with a first bearing surface;

a generally horizontally-disposed seat positioned above the base unit;

a generally upright backrest positioned above the base unit and substantially rearward of the seat;

an extendable ottoman;

a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links;

a gliding mechanism attached to the base unit and the reclining mechanism, the gliding mechanism being configured to enable the seat, backrest and reclining mechanism to glide relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and

a linear actuator attached to the reclining mechanism, the linear actuator configured to move the seating unit between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

11. The seating unit defined in claim **10**, wherein the reclining mechanism includes a pantographic linkage on which the ottoman is mounted, and wherein in the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position.

12. The seating unit defined in claim **10**, further comprising a locking mechanism that allows the seating unit to glide on the gliding mechanism while in the upright position but prevents gliding of the seating unit while in the TV and fully reclined positions.

13. The seating unit defined in claim **10**, further comprising a swivel unit attached to the base unit.

14. The seating unit defined in claim **10**, wherein the reclining mechanism includes a backpost that is fixed relative to the backrest, a mounting bracket that is fixed relative to the gliding mechanism and pivotally attached to the backpost, and a seat adapter that is fixed relative to the seat pivotally attached to the backpost.

15. The seating unit defined in claim **10**, wherein the seat rises in moving from the TV position to the fully reclined position.

16. A gliding and reclining seating unit, comprising:

a base unit with a first bearing surface;

a generally horizontally-disposed seat positioned above the base unit;

a generally upright backrest positioned above the base unit and substantially rearward of the seat;

11

an extendable ottoman;
 a reclining mechanism attached to the seat, the backrest,
 the ottoman and the base unit, the reclining mechanism
 comprising a plurality of pivotally interconnected links;
 a gliding mechanism attached to the base unit and the
 reclining mechanism, the gliding mechanism being con-
 figured to enable the seat, backrest and reclining mecha-
 nism to glide relative to the base unit along a longitudi-
 nal path responsive to a longitudinally-directed force;
 and

a linear power actuating unit attached to the reclining
 mechanism, the actuating unit configured to move the
 seating unit between (a) an upright position, in which the
 seat is generally horizontally disposed, the backrest is
 generally vertically disposed, and the ottoman are gen-
 erally vertically disposed and positioned below the seat,
 (b) an intermediate TV position, in which the ottoman is
 generally horizontally disposed in front of the seat and
 the backrest and the seat substantially maintain the same
 relationship as they have in the upright position, and (c)
 a fully reclined position, in which the angle between the
 backrest and the seat increases;

wherein the linear actuator includes opposed first and sec-
 ond ends, and wherein the first end of the linear actuator
 moves forwardly as the seating unit moves from the
 upright position to the TV position, and wherein the
 second end of the linear actuator moves rearwardly
 when the seating unit moves from the TV position to the
 fully reclined position.

17. The seating unit defined in claim 16, wherein the reclin-
 ing mechanism includes a lower swing link pivotally attached
 with the base unit and an upper swing link pivotally attached
 with the lower swing link and with the backrest, and wherein
 the second end of the linear actuator is attached with the upper
 swing link.

18. A gliding and reclining seating unit, comprising:

a base unit with a first bearing surface;
 a generally horizontally-disposed seat positioned above
 the base unit;
 a generally upright backrest positioned above the base unit
 and substantially rearward of the seat;
 an extendable ottoman;
 a reclining mechanism attached to the seat, the backrest,
 the ottoman and the base unit, the reclining mechanism
 comprising a plurality of pivotally interconnected links;
 a gliding mechanism attached to the base unit and the
 reclining mechanism, the gliding mechanism being con-
 figured to enable the seat, backrest and reclining mecha-
 nism to glide relative to the base unit along a longitudi-
 nal path responsive to a longitudinally-directed force;
 and

a linear actuator attached to the reclining mechanism, the
 linear actuator configured to move the seating unit
 between (a) an upright position, in which the seat is
 generally horizontally disposed, the backrest is gener-
 ally vertically disposed, and the ottoman is generally
 vertically disposed and positioned below the seat, (b) an
 intermediate TV position, in which the ottoman is gener-
 ally horizontally disposed in front of the seat and the
 backrest and the seat substantially maintain the same
 relationship as they have in the upright position, and (c)
 a fully reclined position, in which the angle between the
 backrest and the seat increases;

wherein the reclining mechanism includes a pantographic
 linkage on which the ottoman is mounted, and wherein
 in the TV and fully reclined positions, pivots between

12

links of the pantographic linkage form a near over-center
 arrangement that locks the ottoman in position; and
 wherein the reclining mechanism includes a backpost that
 is fixed relative to the backrest, a mounting bracket that
 is fixed relative to the gliding mechanism and pivotally
 attached to the backpost, and a seat adapter that is fixed
 relative to the seat and pivotally attached to the backpost.

19. The seating unit defined in claim 18, wherein the linear
 actuator includes opposed first and second ends, and wherein
 the first end of the linear actuator moves forwardly as the
 seating unit moves from the upright position to the TV posi-
 tion, and wherein the second end of the linear actuator moves
 rearwardly when the seating unit moves from the TV position
 to the fully reclined position.

20. The seating unit defined in claim 19, wherein the reclin-
 ing mechanism includes a lower swing link pivotally attached
 with the base unit and an upper swing link pivotally attached
 with the lower swing link and with the backrest, and wherein
 the second end of the linear actuator is attached with the upper
 swing link.

21. A gliding and reclining seating unit, comprising:

a base unit with a first bearing surface;
 a generally horizontally-disposed seat positioned above
 the base unit;
 a generally upright backrest positioned above the base unit
 and substantially rearward of the seat;
 an extendable ottoman;
 a reclining mechanism attached to the seat, the backrest,
 the ottoman and the base unit, the reclining mechanism
 comprising a plurality of pivotally interconnected links;
 a gliding mechanism attached to the base unit and the
 reclining mechanism, the gliding mechanism being con-
 figured to enable the seat, backrest and reclining mecha-
 nism to glide relative to the base unit along a longitudi-
 nal path responsive to a longitudinally-directed force;
 and

a power actuating unit attached to the reclining mecha-
 nism, the actuating unit configured to move the chair
 between (a) an upright position, in which the seat is
 generally horizontally disposed, the backrest is gener-
 ally vertically disposed, and the ottoman is generally
 vertically disposed and positioned below the seat, (b) an
 intermediate TV position, in which the ottoman is gener-
 ally horizontally disposed in front of the seat and the
 backrest and the seat substantially maintain the same
 relationship as they have in the upright position, and (c)
 a fully reclined position, in which the angle between the
 backrest and the seat increases;

wherein the reclining mechanism includes a backpost fixed
 relative to the backrest and a sequencer plate pivotally
 interconnected with the backrest and with others of the
 plurality of pivotally interconnected links of the reclin-
 ing mechanism, and wherein the sequencer plate rotates
 in a first rotative direction relative to the backrest when
 the seating unit moves from the upright position to the
 TV position, and wherein the backrest rotates relative to
 the sequencer plate in the first rotative direction when
 the seating unit moves from the TV position to the fully
 reclined position.

22. The seating unit defined in claim 21, wherein the back-
 rest includes one of a pin and a slot, and the sequencer plate
 includes the other of a pin and a slot, the pin being received in
 the slot.

23. The seating unit defined in claim 22, wherein the back-
 rest includes the pin, and the sequencer plate includes the slot.

(12) **United States Patent**
Hoffman et al.

(10) **Patent No.:** **US 8,016,348 B2**
(45) **Date of Patent:** **Sep. 13, 2011**

(54) **RECIPROCATING SEATING UNIT WITH
POWER ACTUATOR**

(75) Inventors: **D. Stephen Hoffman**, High Point, NC
(US); **Marcus L. Murphy**, Lexington,
NC (US)

(73) Assignee: **Ultra-Mek, Inc.**, Denton, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 207 days.

(21) Appl. No.: **12/508,901**

(22) Filed: **Jul. 24, 2009**

(65) **Prior Publication Data**

US 2010/0127556 A1 May 27, 2010

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/276,567,
filed on Nov. 24, 2008.

(51) **Int. Cl.**
A47C 1/031 (2006.01)

(52) **U.S. Cl.** **297/85 M**

(58) **Field of Classification Search** 297/85 M,
297/68, 342, 330, 344.21, 344.24, 344.26,
297/84

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

507,270 A	10/1893	Hirschfeld
2,526,623 A	10/1950	Maurer
2,714,922 A	8/1955	McKibban et al.
3,016,264 A *	1/1962	Hughes 297/69
3,147,038 A	9/1964	Barabas
3,163,464 A	12/1964	Martin

3,279,847 A	10/1966	Re
3,352,601 A	11/1967	Cycowicz
3,383,135 A	5/1968	Posh
3,493,264 A	2/1970	Re
3,622,198 A	11/1971	Re
3,622,202 A	11/1971	Brown
3,637,255 A	1/1972	Re

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2 106 777 A 4/1983

OTHER PUBLICATIONS

Lusch Brochure: "Functional Fitting and Tubular steel frames for
Relaxing Chairs (11 pages), Functional Fittings for Sofabeds and
Beds (10 pages), Bed Fitting (5 pages) and Upholstery joints and
accessories for furniture (9 pages)", (available before Apr. 7, 2006).

(Continued)


Primary Examiner — Milton Nelson, Jr.

(74) *Attorney, Agent, or Firm* — Myers Bigel Sibley &
Sajovec

(57) **ABSTRACT**

A reciprocating and reclining seating unit includes: a base
unit with a first bearing surface; a generally horizontally-
disposed seat positioned above the base; a generally upright
backrest positioned above the base and substantially rearward
of the seat; an extendable ottoman; a reclining mechanism
attached to the seat, the backrest, the ottoman and the base
unit, the reclining mechanism comprising a plurality of piv-
otally interconnected links; a reciprocating mechanism
attached to the base unit and the reclining mechanism, the
reciprocating mechanism being configured to enable the seat,
backrest and reclining mechanism to reciprocate relative to
the base unit along a longitudinal path responsive to a longi-
tudinally-directed force; and a power actuating unit attached
to the reclining mechanism.

15 Claims, 8 Drawing Sheets



PUBLIC VERSION

US 8,016,348 B2

Page 2


U.S. PATENT DOCUMENTS

3,863,980 A	2/1975	Ciner	6,000,754 A	12/1999	Lawson
4,307,912 A	12/1981	Watt et al.	6,135,559 A	10/2000	Kowaiski
4,386,803 A	6/1983	Gilderbloom	6,231,120 B1	5/2001	Wiecek
4,519,647 A	5/1985	Rogers	6,491,342 B1	12/2002	Smith
4,674,794 A	6/1987	Pine	6,540,291 B2	4/2003	Hoffman et al.
4,681,365 A	7/1987	Pine	6,612,650 B1	9/2003	Ambrosio et al.
4,682,815 A	7/1987	Steifensand	6,634,706 B2	10/2003	May
4,691,964 A	9/1987	Morgan	6,733,071 B2	5/2004	Guillot
4,696,512 A	9/1987	Burnett et al.	6,840,575 B2 *	1/2005	Hesse 297/85 M
4,707,025 A	11/1987	Rogers, Jr.	6,893,085 B2 *	5/2005	LaPointe et al. 297/85 M
4,722,566 A	2/1988	Castellini	6,945,599 B2	9/2005	May
4,813,743 A	3/1989	Mizelle	6,948,777 B2	9/2005	Marshall et al.
4,915,444 A	4/1990	Rogers, Jr.	7,021,711 B1	4/2006	Hoffman et al.
5,007,679 A	4/1991	Mizelle	7,040,692 B1	5/2006	Pine
5,086,769 A	2/1992	Vianello et al.	7,083,235 B2	8/2006	Grimm et al.
5,294,177 A	3/1994	Rasnack et al.	7,188,904 B2	3/2007	Bruck et al.
5,564,781 A	10/1996	Pine	7,293,834 B2	11/2007	Riach et al.
5,775,775 A	7/1998	Hoffman	7,311,359 B2	12/2007	Smith
5,876,094 A	3/1999	Hoffman	2006/0082195 A1	4/2006	Jiang
5,884,970 A	3/1999	Howard			
5,931,535 A	8/1999	Sweet			
5,954,392 A	9/1999	Liss et al.			

OTHER PUBLICATIONS

“Stawett Functional Bed Mechanisms Brochure”, pp. 3-93 (2001).

* cited by examiner








FIG. 2








FIG. 3A




FIG. 4




FIG. 4A




FIG. 5

US 8,016,348 B2

1

**RECIPROCATING SEATING UNIT WITH
POWER ACTUATOR****RELATED APPLICATIONS**

This application is a continuation-in-part of U.S. patent application Ser. No. 12/276,567, filed Nov. 24, 2008, the disclosure of which is hereby incorporated herein in its entirety.

FIELD OF THE INVENTION

This invention relates generally to seating units, and relates more particularly to reclining seating units with rocking capability.

BACKGROUND OF THE INVENTION

Recliner chairs and other reclining seating units have proven to be popular with consumers. These seating units typically move from an upright position, in which the backrest is generally upright, to one or more reclined positions, in which the backrest pivots to be less upright. The movement of the seating unit between the upright and reclined positions is typically controlled by a pair of matching reclining mechanisms that are attached to the seat, backrest and base of the chair.

In recent years, furniture designers have looked for alternatives to rocking chairs that can provide a similarly relaxing repetitive motion. One alternative has been the gliding chair, or “glider”, which includes structure that enables the seat portion of the chair to “glide” forwardly and rearwardly relative to its base to mimic generally the rocking motion of a rocking chair. Often the gliding structure comprises a set of swing links (usually two at the front of the chair, and two at the rear) that are pivotally attached at their upper ends to the base and extend downwardly therefrom to attach to a structure, such as a mounting bracket, that is attached to the seat. In this configuration, the seat is suspended from the base and is free to swing forwardly and rearwardly in a double pendulum-type motion in response to a forwardly or rearwardly-directed force applied by a seated occupant. The gliding path of the chair is controlled by the configuration and mounting of the swing links. These chairs can be constructed to resemble traditional rocking chairs and thus are quite popular.

Reclining capability has been combined with gliding capability in a single unit to provide a chair that both reclines and glides. This chair includes a reclining mechanism that enables it to move between upright and one or more reclined positions, and further includes the aforementioned swing links attached between the base and the seat, armrests, or mechanism itself to enable the chair to glide. Examples of such chairs are illustrated and described in U.S. Pat. Nos. 4,536, 029 and 4,544,201, both to Rogers, Jr., the disclosures of which are hereby incorporated herein by reference in their entireties.

Although they are already popular seating units, it may be desirable to provide additional functionality to glider-recliners.

SUMMARY OF THE INVENTION

As a first aspect, embodiments of the present invention are directed to a reciprocating and reclining seating unit. The seating unit comprises: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base

2

and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a power actuating unit attached to the reclining mechanism, the actuating unit configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The actuating unit is attached to an actuating mechanism, the actuating mechanism comprising a cross-member extending transversely across the seating unit and first and second projections fixed to the cross-member. The first projection is pivotally attached to the actuating unit. The second projection is pivotally attached to a lower swing link of the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism.

As a second aspect, embodiments of the present invention are directed to a reciprocating and reclining seating unit, comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a power linear actuating unit attached to the reclining mechanism, the actuating unit including a motor and an extendable rod and configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The actuating unit is attached to an actuating mechanism, the actuating mechanism comprising: a cross-member extending transversely across the seating unit; and first and second projections fixed to the cross-member. The first projection is pivotally attached to the actuating unit. The second projection is pivotally attached to a lower swing link of the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism. The actuating unit includes opposed first and second ends, wherein the first end of the actuating unit moves forwardly as the seating unit moves from the upright position to the TV position, and wherein the

3

second end of the actuating unit moves rearwardly when the seating unit moves from the TV position to the fully reclined position.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view of a glider-recliner chair according to embodiments of the present invention.

FIG. 2 is a side section view of the chair of FIG. 1 with the chair in its fully upright position.

FIG. 2A is an enlarged side section view of the actuating mechanism of the chair of FIG. 1 with the chair in its fully upright position.

FIG. 3 is a side section view of the chair of FIG. 1 with the chair in its TV position.

FIG. 3A is an enlarged side section view of the actuating mechanism of the chair of FIG. 1 with the chair in its TV position.

FIG. 4 is a side section view of the chair of FIG. 1 with the chair in its fully reclined position.

FIG. 4A is an enlarged side section view of the actuating mechanism of the chair of FIG. 1 with the chair in its fully reclined position.

FIG. 5 is a top cutaway view of the frame of the chair of FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The present invention now is described more fully herein-after with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

Like numbers refer to like elements throughout. In the figures, the thickness of certain lines, layers, components, elements or features may be exaggerated for clarity. Broken lines illustrate optional features or operations unless specified otherwise.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. As used herein, phrases such as “between X and Y” and “between about X and Y” should be interpreted to include X and Y. As used herein, phrases such as “between about X and Y” mean “between about X and about Y.” As used herein, phrases such as “from about X to Y” mean “from about X to about Y.”

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specifica-

4

tion and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

It will be understood that when an element is referred to as being “on”, “attached” to, “connected” to, “coupled” with, “contacting”, etc., another element, it can be directly on, attached to, connected to, coupled with or contacting the other element or intervening elements may also be present. In contrast, when an element is referred to as being, for example, “directly on”, “directly attached” to, “directly connected” to, “directly coupled” with or “directly contacting” another element, there are no intervening elements present. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature may have portions that overlap or underlie the adjacent feature.

This invention is directed to seating units that have a stationary base, a seat portion, and a backrest. As used herein, the terms “forward”, “forwardly”, and “front” and derivatives thereof refer to the direction defined by a vector extending from the backrest toward the seat parallel to the underlying surface. Conversely, the terms “rearward”, “rearwardly”, and derivatives thereof refer to the direction directly opposite the forward direction; the rearward direction is defined by a vector that extends from the seat toward the backrest parallel to the underlying surface. The terms “lateral,” “laterally”, and derivatives thereof refer to the direction parallel with the floor, perpendicular to the forward and rearward directions, and extending away from a plane bisecting the seating units between their armrests. The terms “medial,” “inward,” “inboard,” and derivatives thereof refer to the direction that is the converse of the lateral direction, i.e., the direction parallel with the floor, perpendicular to the forward direction, and extending from the periphery of the seating units toward the aforementioned bisecting plane.

The seating units illustrated and described herein comprise a plurality of pivotally interconnected links. Those skilled in this art will appreciate that the pivots between links can take a variety of configurations, such as pivot pins, rivets, bolt and nut combinations, and the like, any of which would be suitable for use with the present invention. Also, the shapes of the links may vary as desired, as may the locations of certain of the pivots. Moreover, in some instances combinations of pivot points may be replaced by equivalent structures, such as “slider-crank” configurations, like those described in B. Paul, *Kinematics and Dynamics of Planar Machinery* 4-21 (1979). In other embodiments, another mechanism that provides reciprocating motion along a longitudinal path, such as a rocking unit like that discussed in co-assigned and U.S. patent application Ser. No. 12/276,559, the disclosure of which is hereby incorporated herein in its entirety, may also be employed.

Referring now to the figures, a swiveling glider-recliner chair, designated broadly at 10, is illustrated in FIGS. 1-5. The chair 10 includes a base unit 11, a seat 13 that is generally horizontally disposed above the base unit 11, a backrest 15 that is generally vertically and disposed substantially above a rear portion of the seat 13, and two ottomans 17a, 17b, which, in the upright position of FIG. 1, are generally vertically disposed below a front portion of the seat 13. Arms 18 are positioned on either side of the seat 13 and move in concert with the seat 13.

A pair of mirror image reclining mechanisms 30 (only one of which is shown herein in FIGS. 2-4) are attached to the backrest 15, the seat 13, and the ottomans 17a, 17b. The reclining mechanisms 30, which comprise a plurality of inter-

5

connected links, move the chair 10 between (a) an upright position (FIGS. 1 and 2), in which the seat 13 is generally horizontally disposed, the backrest 15 is generally vertically disposed, and the ottomans 17a, 17b are generally vertically disposed and positioned below the seat 13, (b) an intermediate TV position (FIG. 3), in which the ottomans 17a, 17b are generally horizontally disposed in front of the seat 13 and the backrest 15 and the seat 13 substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position (FIG. 4), in which the angle between the backrest 15 and the seat 13 increases. These components are described in greater detail below.

The base unit 11 includes a circular lower base 12. A swivel unit 14 is mounted onto the top of the lower base 12. Cross-members 18 are mounted atop the swivel unit 14. Those skilled in this art will recognize that the base unit 11 may take other forms that provide mounting locations for the remaining components of the chair 10; for example, the swivel unit 14 may be omitted.

Glide foundation plates 24 are mounted to the top surfaces of the cross-members 18. A front glide link 20 is attached at a pivot 21 to the front end of the glide foundation plate 24, and a rear glide link 25 is attached at a pivot 26 to the rear end of the glide foundation plate 24. The front and rear glide links 20, 25 are suspended from the glide foundation plate 24 and together form a gliding mechanism 28 that provides a gliding motion to the chair 10 when it is in its upright position (FIG. 2). Those skilled in this art will appreciate that the gliding mechanism may take other forms; it may include glide links of different shapes, or it may include a "track"-based gliding mechanism.

Because the reclining mechanisms 30 are mirror images of each other, only one reclining mechanism will be described in detail herein, with the understanding that the discussion is equally applicable to the mirror image mechanism 30. Also, for clarity the mechanism will be described first with reference to FIG. 4 (with the mechanism 30 in its reclined position), then will be described in its upright and TV positions.

Turning now to FIG. 4, the reclining mechanism 30 includes a generally arcuate foundation link 31, which is attached at either end to the front and rear glide links 20, 25 at pivots 22, 27, respectively. A generally crescent-shaped mounting bracket 32 is fixed to the foundation link 31. A slot 32a is present at the front end of the mounting bracket 32. An L-shaped lower swing link 34 is attached to a lower region of the mounting bracket 32 at a pivot 36 and extends upwardly and rearwardly, then upwardly and forwardly therefrom. A straight upper swing link 38 is attached at its lower end to the upper end of the lower swing link 34 at a pivot 40 and extends upwardly therefrom.

A backpost 48 is fixed to the backrest 15 and extends generally forwardly from the lower front end of the backrest 15. The upper swing link 38 is attached to a forward portion of the backpost 48 at a pivot 50. A straight coupling link 52 having a slot 52a is attached to the backpost 48 via a pin 48a located forwardly of the pivot 50. The coupling link 52 extends forwardly and downwardly from the pin 48a to attach to the front end of the mounting bracket 32 via a pin 52b inserted into a slot 32a in the mounting bracket 32. A trapezoidal sequencer plate 54 is attached to the backpost 48 at a pivot 58, and also interacts with the backpost 48 via a slot 54a that receives a pin 48b. The sequencer plate 54 is also attached to the rear end of the mounting bracket 32 at a pivot 56.

Still referring to FIG. 4, a seat frame 62, to which the arms 18 are mounted, underlies the seat 13. A seat adapter 66 is fixed to the seat frame 62. The seat adapter 66 is attached to the backpost 48 at a pivot 68 that is located just rearward of the

6

pivot 50. An upper ottoman swing link 72 is attached to a front region of the seat adapter 66 at a pivot 74 and extends downwardly and forwardly therefrom. A tripartite lower ottoman swing link 76 is attached to a pivot 78 that is located rearwardly and downwardly from the pivot 74; the lower ottoman swing link 76 extends generally forwardly from the pivot 78. An upper ottoman extension link 80 is attached to the forward end of the lower ottoman swing link 76 at a pivot 82 and extends forwardly and upwardly therefrom. Also the upper ottoman extension link 80 is attached to the upper ottoman swing link at a pivot 84. A lower ottoman extension link 86 is attached to the forward end of the upper ottoman swing link at a pivot 88 that is positioned above and forward of the pivot 84 and extends upwardly and forwardly therefrom generally parallel with the upper ottoman extension link. An outer ottoman bracket 90 is generally horizontally disposed and is attached to the upper and lower ottoman extension links 80, 86 at pivots 92, 94 respectively. The ottoman 17a is mounted on the outer ottoman bracket 90.

A bi-angled inner ottoman bracket 96 is attached at its lower, forward end to the lower ottoman extension link 86 at a pivot 98. At its opposite end, the inner ottoman bracket 96 supports the ottoman 17b. The inner ottoman bracket 96 also includes a slot 96a that receives a pin 80a located on the upper ottoman extension link 80.

A connecting link 100 is attached to the sequencer plate 54 at a pivot 102. The connecting link 100 extends forwardly and slightly upwardly from the pivot 102 to a pivot 104 with the lower ottoman swing link 76.

A locking mechanism 130 is attached to the reclining mechanism 30 to prevent gliding of the chair 10 when it is in the TV or fully reclined positions. The locking mechanism 130 includes a drive link 132 that is pivotally interconnected at one end to the sequencer plate 54 at a pivot 134. The drive link 132 is a straight link that slopes downwardly and slightly forwardly from the pivot 134. The opposite end of the drive link 132 is pivotally interconnected with a downwardly-extending projection 138 of a hook-shaped locking link 136 at a pivot 140. The locking link 136 is attached to the mounting bracket 32 at the pivot 36.

Referring to FIG. 4A, The chair 10 includes a power unit 112 that drives the chair 10 between its upright, TV and fully reclined positions. The power unit 112 includes a motor unit 114, to which is attached a sleeve 116. The sleeve extends rearwardly from the motor unit 114 and receives a retractable rod 118. The motor unit 114 is electrically connected with an actuator (not shown), such as a toggle switch or the like, that energizes the motor unit 114 upon actuation.

The motor unit 114 is attached to an actuating mechanism 113 that includes a mounting bracket 110 at a pivot 120 via a mounting tab 114a (see FIG. 5). The mounting bracket 110 is then attached to a cross-member 108 that extends between the reclining mechanisms 30. A bracket 106 is fixed to each of the lower ottoman swing links 76 and to the cross-member 108.

The rod 118 of the power unit 112 is attached to a projecting bracket 46 of the actuating unit 113 (FIGS. 4, 4A and 5) at a pivot 122. The bracket 46 is then attached to a Z-shaped cross-member 44 that extends between the reclining mechanisms 30. The cross-member 44 is fixed to a second projecting bracket 42 that is pivotally attached to the lower swing link 34 of each reclining mechanism 30 at a pivot 140.

As can be seen in FIG. 2A, in the upright position, the rod 118 of the power unit 112 is retracted into the sleeve 116. In this position, the "internal leg" of the Z-shaped cross-member 44 is disposed at an angle α of approximately 45 degrees to horizontal, such that both of the pivots 40, 140 are positioned

below the axis A defined by the rod 118 of the power unit 112. The upper segment of the lower swing link 34 is generally parallel with the axis A.

Because the rod 118 is in its retracted position, a pantographic linkage formed by the upper and lower ottoman swing links 72, 76 and the upper and lower ottoman extension links 80, 86 is folded under the seat frame 62, which positions the ottoman 17b underneath a forward portion of the seat frame 62 and the ottoman 17a just forward of and below the seat frame 62 in a vertical orientation. Also, the lower and upper swing links 34, 38 are oriented such that the upper segment of the lower swing link 34 is generally horizontal, which positions the backpost 48 and, in turn, the backrest 15, in a generally upright position.

Additionally, the sequencer plate 54 is oriented such that the pivot 102 is located downwardly and rearwardly, such that the locking link 136 of the locking mechanism 130 is raised, with a pocket 137 formed at the vertex of the locking link 136 facing downwardly and positioned above a post 139 on the rear glide link 25. In this position, the front and rear glide links 20, 25 are free to swing on the pivots 21, 26, thereby enabling the reclining mechanisms 30, the seat 13, the backrest 15 and the ottomans 17a, 17b to move fore-and-aft relative to the base unit 11. During the gliding motion, the majority of the locking mechanism 130 is stationary relative to the reclining mechanisms 30. Because the locking link 136 does not move relative to the reclining mechanism 30 as the chair 10 glides, it does not interact with the post 139 to impede the gliding motion.

To move the chair 10 from the upright position to the TV position of FIG. 3, an occupant of the chair 10 actuates the actuator, which causes the rod 118 to begin to extend from the sleeve 116. Extension of the rod 118 attempts to force the lower swing link 34 to rotate slightly counterclockwise (from the vantage point of FIGS. 2 and 3) about the pivot 36. However, the weight of the seated occupant and the geometry of the lower swing link 34, the upper swing link 38, and the actuation mechanism 113 prevent any substantial rotation of the lower swing link 34 at this point. Because there is little to no fore-and-aft movement of the rear end of the rod 118, the motor unit 114 moves forwardly relative to the base unit 11, thereby driving the lower ottoman swing link 76 counterclockwise about the pivot 78. Rotation of the lower ottoman swing link 76 forces the upper ottoman extension link 80 forward, which in turn draws the upper ottoman swing link 72 counterclockwise around the pivot 74. Also, the lower ottoman extension link 86 moves forwardly more than the upper ottoman extension link 80, such that the outer ottoman bracket 90 and the inner ottoman bracket 96 rotate counterclockwise (rotation of the inner ottoman bracket 96 causes the pin 80a to move in the slot 96a toward the pivot 98). The rotation of the outer and inner ottoman brackets 90, 96 induces the ottomans 17a, 17b to rotate from a vertical orientation to a horizontal orientation. Motion of the ottomans 17a, 17b ceases when a pin 72a on the upper ottoman swing link 72 strikes the upper edge of the upper ottoman extension link 80.

In addition, the rotation of the lower ottoman swing link 76 draws the connecting link 100 forward. Movement of the connecting link 100 rotates the sequencer plate 54 counterclockwise about the pivot 58 with the backpost 48. The drive link 132 of the locking mechanism 130 is driven down and rotates the locking link 136 counterclockwise. The movement of the locking link 136 ceases when the pocket 137 of the locking link 136 descends sufficiently to receive the post 139 on the rear glide link 25. In this position, relative movement between the front and rear glide links 20, 25 and the

reclining mechanisms is restrained, thereby preventing the reclining mechanisms 30, and in turn the chair 10, from gliding relative to the base unit 11.

Rotation of the sequencer plate 54 and movement of the connecting link 100 also lower the backpost 48 relative to the base unit 11, which forces the seat link 64 to increase in pitch angle relative to its underlying surface. The upper swing link 38 rotates counterclockwise about the pivot 48 as a result.

To move the chair 10 from the TV position of FIG. 3 to the fully reclined position of FIG. 4, the occupant can continue to operate the actuator, which extends the rod 118 farther out of the sleeve 116. When the ottomans 17a, 17b are fully extended, the pivots 82, 84 and 88 are in a near "over-center" condition that helps to lock the ottomans 17a, 17b in an extended position. Thus, as the rod 118 continues to extend from the sleeve 116 when the chair is in the TV position, the motor unit 114 cannot move forward relative to the base unit 11 any farther, so the rear end of the rod 118 overcomes the resistance provided by the occupant's weight and the geometry of the actuating mechanism 113 and the lower and upper swing links 34, 38 and begins to move rearwardly relative to the base unit 11, resulting in counterclockwise rotation of the lower swing link 34 about the pivot 36. This rotation drives the upper swing link 38 clockwise about the pivot 36. Thus, this action causes the angle β defined by the pivots 36, 40, 50 to increase. The rotation of the upper swing link 38 drives the forward end of the backpost 48 upward. As a consequence, the backpost 48 rotates counterclockwise about the pivot 58 relative to the sequencer plate 54 (and to the seat adapter 66 and the seat frame 62). Rotation of the backpost 48 and, in turn, the backrest 15, continues until (a) the pin 48b on the backpost 48 reaches the upper end of the slot 54a in the sequencer plate 54 and (b) the pin 52b of the coupling link 52 reaches the rear end of the slot 32a of the mounting bracket 32. In this position, the backrest 15 has reclined relative to the seat 13 at a greater angle than in the upright and TV positions.

The rotation of the lower swing link 34 and of the coupling link 52 also causes the seat 15 to rise relative to the base unit 11.

As can also be seen in FIG. 4, the locking mechanism 130 continues to prevent the chair 10 from gliding as the chair 10 moves to the fully reclined position. It can also be seen that the seat 13 rises during movement from the TV position to the fully reclined position.

The chair 10 can be returned to its TV position from the fully reclined position by the occupant operating the actuator in the reverse direction. Because of the over-center condition of the pivots 82, 84, 88, the ottomans 17a, 17b remain extended, such that retraction of the rod 118 draws the backrest 15 to its upright position. Once the motion of the backrest 15 is complete, the over-center condition of the pivots 82, 84 and 88 can be overcome, and the ottomans 17a, 17b are able to retract to the upright position.

Those skilled in this art will recognize that other variations of the chair 10 are contemplated in connection with the present invention. For example, the power unit 112 may be reversed, such that the motor 114 is at the rear end of the power unit 112 and the rod 118 is at the front end. In such a case, the rod 118 would extend forwardly relative to the base unit 11 as the chair 10 moved from the upright position to the TV position, and the motor 114 would move rearwardly relative to the base unit 11 when the chair moved from the TV position to the fully reclined position. In either instance, the front end of the power unit 112 moves relative to the base unit 11 during the movement from the upright to the TV position,

and the rear end of the power unit moves relative to the base unit **11** during the movement from the TV to the fully reclined position.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as recited in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

That which is claimed is:

1. A seating unit, comprising:

a base unit with a first bearing surface;

a generally horizontally-disposed seat positioned above the base unit;

a generally upright backrest positioned above the base unit and substantially rearward of the seat;

an extendable ottoman;

a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links;

a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and

a power actuating unit attached to the reclining mechanism, the actuating unit configured to move the seating unit between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases;

wherein the actuating unit is attached to an actuating mechanism, the actuating mechanism comprising:

a cross-member extending transversely across the seating unit;

first and second projections fixed to the cross-member;

wherein the first projection is pivotally attached to the actuating unit; and

wherein the second projection is pivotally attached to a lower swing link of the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism.

2. The seating unit defined in claim **1**, wherein the reclining mechanism includes a pantographic linkage on which the ottoman is mounted, and wherein in the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position.

3. The seating unit defined in claim **1**, further comprising a locking mechanism that allows the seating unit to reciprocate while in the upright position but prevents reciprocating of the seating unit while in the TV and fully reclined positions.

4. The seating unit defined in claim **1**, wherein the seat rises in moving from the TV position to the fully reclined position.

5. The seating unit defined in claim **1**, wherein the reclining mechanism includes a backpost that is fixed relative to the backrest, a mounting bracket that is fixed relative to the reciprocating mechanism and pivotally attached to the backpost, and a seat adapter that is fixed relative to the seat and pivotally attached to the backpost.

6. The seating unit defined in claim **1**, wherein the reciprocating mechanism is a gliding mechanism.

7. The seating unit defined in claim **1**, wherein the power actuating unit includes opposed first and second ends, and wherein the first end of the power actuating unit moves forwardly as the seating unit moves from the upright position to the TV position, and wherein the second end of the power actuating unit moves rearwardly when the seating unit moves from the TV position to the fully reclined position.

8. The seating unit defined in claim **7**, wherein the upper swing link is pivotally attached with the backrest.

9. The seating unit defined in claim **7**, wherein the power actuating unit includes a motor and an extendable member at the first and second ends.

10. The seating unit defined in claim **9**, wherein the lower swing link is angled, and wherein a segment of the lower swing link attached to the upper swing link is generally parallel to an axis defined by the extendable member of the actuating unit when the seating unit is in the upright and TV positions.

11. The seating unit defined in claim **10**, wherein a first pivot defined by the second projection and the lower swing link and a second pivot defined by the lower swing link and the upper swing link are below the axis defined by the extendable member of the actuating unit when the seating unit is in the upright and TV positions.

12. The seating unit defined in claim **11**, wherein the lower swing link is attached to the mounting bracket at a third pivot, and wherein in the upright and TV positions, the first, second and third pivots define a first angle, and in the fully reclined position, the first, second and third pivots define a second angle that is larger than the first angle.

13. A reciprocating and reclining seating unit, comprising:

a base unit with a first bearing surface;

a generally horizontally-disposed seat positioned above the base unit;

a generally upright backrest positioned above the base unit and substantially rearward of the seat;

an extendable ottoman;

a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links;

a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and

a power linear actuating unit attached to the reclining mechanism, the actuating unit including a motor and an extendable rod and configured to move the seating unit between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases;

US 8,016,348 B2

11

wherein the actuating unit is attached to an actuating mechanism, the actuating mechanism comprising:
 a cross-member extending transversely across the seating unit;
 first and second projections fixed to the cross-member;
 wherein the first projection is pivotally attached to the actuating unit; and
 wherein the second projection is pivotally attached to a lower swing link of the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism; and
 wherein the actuating unit includes opposed first and second ends, and wherein the first end of the actuating unit moves forwardly as the seating unit moves from the upright position to the TV position, and wherein the

12

second end of the actuating unit moves rearwardly when the seating unit moves from the TV position to the fully reclined position.

14. The seating unit defined in claim **13**, wherein a first pivot defined by the second projection and the lower swing link and a second pivot defined by the lower swing link and the upper swing link are below an axis defined by the extendable rod of the actuating unit when the seating unit is in the upright and TV positions.

15. The seating unit defined in claim **14**, wherein in the upright and TV positions, the lower swing link is attached to the mounting bracket at a third pivot, and wherein in the upright and TV positions, the first, second and third pivots define a first angle, and in the fully reclined position, the first, second and third pivots define a second angle that is larger than the first angle.

* * * * *

PUBLIC VERSION

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 8,016,348 B2
APPLICATION NO. : 12/508901
DATED : September 13, 2011
INVENTOR(S) : Hoffman et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims:

Column 10, Claim 13, Line 60: Please correct "ottoman are is"
to read -- ottoman is --

Signed and Sealed this
Thirteenth Day of December, 2011

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, slightly stylized font.

David J. Kappos
Director of the United States Patent and Trademark Office

(12) **United States Patent**
Hoffman et al.

(10) **Patent No.:** **US 8,297,693 B2**
(45) **Date of Patent:** ***Oct. 30, 2012**

(54) **RECIPROCATING SEATING UNIT WITH
POWER ACTUATOR**

(75) Inventors: **D. Stephen Hoffman**, High Point, NC
(US); **Marcus L. Murphy**, Lexington,
NC (US)

(73) Assignee: **Ultra-Mek, Inc.**, Denton, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **13/228,746**

(22) Filed: **Sep. 9, 2011**

(65) **Prior Publication Data**

US 2012/0119547 A1 May 17, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/508,901, filed on
Jul. 24, 2009, now Pat. No. 8,016,348, which is a
continuation-in-part of application No. 12/276,567,
filed on Nov. 24, 2008, now Pat. No. 7,997,644.

(51) **Int. Cl.**
A47C 1/031 (2006.01)

(52) **U.S. Cl.** **297/85 M**

(58) **Field of Classification Search** 297/85 M,
297/69, DIG. 7

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

507,270 A 10/1893 Hirschfeld
2,526,623 A 10/1950 Maurer

2,714,922 A 8/1955 McKibban et al.
3,147,038 A 9/1964 Barabas
3,163,464 A 12/1964 Martin
3,279,847 A 10/1966 Re

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2 106 777 A 4/1983

OTHER PUBLICATIONS

Lusch Brochure: "Functional Fitting and Tubular steel frames for
Relaxing Chairs (11 pages), Functional Fittings for Sofabeds and
Beds (10 pages), Bed Fitting (5 pages) and Upholstery joints and
accessories for furniture (9 pages)", (available before Apr. 7, 2006).

(Continued)


Primary Examiner — Milton Nelson, Jr.

(74) *Attorney, Agent, or Firm* — Myers Bigel Sibley &
Sajovec

(57) **ABSTRACT**

A reciprocating and reclining seating unit includes: a base
unit with a first bearing surface; a generally horizontally-
disposed seat positioned above the base; a generally upright
backrest positioned above the base and substantially rearward
of the seat; an extendable ottoman; a reclining mechanism
attached to the seat, the backrest, the ottoman and the base
unit, the reclining mechanism comprising a plurality of piv-
otally interconnected links; a reciprocating mechanism
attached to the base unit and the reclining mechanism, the
reciprocating mechanism being configured to enable the seat,
backrest and reclining mechanism to reciprocate relative to
the base unit along a longitudinal path responsive to a longi-
tudinally-directed force; and a power actuating unit attached
to the reclining mechanism, the actuating unit configured to
move the chair between an upright position, an intermediate
TV position, and a fully reclined position.

14 Claims, 8 Drawing Sheets



PUBLIC VERSION

US 8,297,693 B2

Page 2


U.S. PATENT DOCUMENTS

3,352,601 A	11/1967	Cycowicz	5,876,094 A	3/1999	Hoffman
3,383,135 A	5/1968	Posh	5,884,970 A	3/1999	Howard
3,493,264 A	2/1970	Re	5,931,535 A	8/1999	Sweet
3,622,198 A	11/1971	Re	5,954,392 A	9/1999	Liss et al.
3,622,202 A	11/1971	Brown	6,000,754 A	12/1999	Lawson
3,637,255 A	1/1972	Re	6,135,559 A	10/2000	Kowalski
3,863,980 A	2/1975	Ciner	6,231,120 B1	5/2001	Wiecek
4,212,495 A *	7/1980	Gall 297/84	6,491,342 B1	12/2002	Smith
4,307,912 A	12/1981	Watt et al.	6,540,291 B2	4/2003	Hoffman et al.
4,365,836 A *	12/1982	Jackson et al. 297/85 M	6,612,650 B1	9/2003	Ambrosio et al.
4,386,803 A	6/1983	Gilderbloom	6,634,706 B2	10/2003	May
4,519,647 A	5/1985	Rogers	6,733,071 B2	5/2004	Guillot
4,674,794 A	6/1987	Pine	6,945,599 B2	9/2005	May
4,681,365 A	7/1987	Pine	6,948,777 B2	9/2005	Marshall et al.
4,682,815 A	7/1987	Steifensand	7,021,711 B1	4/2006	Hoffman et al.
4,691,964 A	9/1987	Morgan	7,040,692 B1	5/2006	Pine
4,696,512 A	9/1987	Burnett et al.	7,083,235 B2	8/2006	Grimm et al.
4,707,025 A	11/1987	Rogers, Jr.	7,188,904 B2	3/2007	Bruck et al.
4,722,566 A	2/1988	Castellini	7,293,834 B2	11/2007	Riach et al.
4,813,743 A	3/1989	Mizelle	7,311,359 B2	12/2007	Smith
4,915,444 A	4/1990	Rogers, Jr.	7,445,279 B2 *	11/2008	Crum 297/84
5,007,679 A	4/1991	Mizelle	2006/0082195 A1	4/2006	Jiang
5,086,769 A	2/1992	Vianello et al.			
5,294,177 A	3/1994	Rasnack et al.			
5,564,781 A	10/1996	Pine			
5,775,775 A	7/1998	Hoffman			

OTHER PUBLICATIONS

"Stawett Functional Bed Mechanisms Brochure", pp. 3-93 (2001).

* cited by examiner








FIG. 2









FIG. 3A






FIG. 4A




FIG. 5

US 8,297,693 B2

1

**RECIPROCATING SEATING UNIT WITH
POWER ACTUATOR**

RELATED APPLICATION

This application is a continuation application of U.S. patent application Ser. No. 12/508,901, filed Jul. 24, 2009, now U.S. Pat. No. 8,016,348, which is a continuation-in-part of U.S. patent application Ser. No. 12/276,567, filed Nov. 24, 2008 (now U.S. Pat. No. 7,997,644, issued Aug. 16, 2011, the disclosure of each of which is hereby incorporated herein in its entirety).

FIELD OF THE INVENTION

This invention relates generally to seating units, and relates more particularly to reclining seating units with rocking capability.

BACKGROUND OF THE INVENTION

Recliner chairs and other reclining seating units have proven to be popular with consumers. These seating units typically move from an upright position, in which the backrest is generally upright, to one or more reclined positions, in which the backrest pivots to be less upright. The movement of the seating unit between the upright and reclined positions is typically controlled by a pair of matching reclining mechanisms that are attached to the seat, backrest and base of the chair.

In recent years, furniture designers have looked for alternatives to rocking chairs that can provide a similarly relaxing repetitive motion. One alternative has been the gliding chair, or “glider”, which includes structure that enables the seat portion of the chair to “glide” forwardly and rearwardly relative to its base to mimic generally the rocking motion of a rocking chair. Often the gliding structure comprises a set of swing links (usually two at the front of the chair, and two at the rear) that are pivotally attached at their upper ends to the base and extend downwardly therefrom to attach to a structure, such as a mounting bracket, that is attached to the seat. In this configuration, the seat is suspended from the base and is free to swing forwardly and rearwardly in a double pendulum-type motion in response to a forwardly or rearwardly-directed force applied by a seated occupant. The gliding path of the chair is controlled by the configuration and mounting of the swing links. These chairs can be constructed to resemble traditional rocking chairs and thus are quite popular.

Reclining capability has been combined with gliding capability in a single unit to provide a chair that both reclines and glides. This chair includes a reclining mechanism that enables it to move between upright and one or more reclined positions, and further includes the aforementioned swing links attached between the base and the seat, armrests, or mechanism itself to enable the chair to glide. Examples of such chairs are illustrated and described in U.S. Pat. Nos. 4,536,029 and 4,544,201, both to Rogers, Jr., the disclosures of which are hereby incorporated herein by reference in their entireties.

Although they are already popular seating units, it may be desirable to provide additional functionality to glider-recliners.

SUMMARY OF THE INVENTION

As a first aspect, embodiments of the present invention are directed to a reciprocating and reclining seating unit. The

2

seating unit comprises: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a power actuating unit attached to the reclining mechanism, the actuating unit configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The actuating unit is attached to an actuating mechanism, the actuating mechanism comprising a cross-member extending transversely across the seating unit and first and second projections fixed to the cross-member. The first projection is pivotally attached to the actuating unit. The second projection is pivotally attached to a lower swing link of the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism.

As a second aspect, embodiments of the present invention are directed to a reciprocating and reclining seating unit, comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and a power linear actuating unit attached to the reclining mechanism, the actuating unit including a motor and an extendable rod and configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The actuating unit is attached to an actuating mechanism, the actuating mechanism comprising: a cross-member extending transversely across the seating unit; and first and second projections fixed to the cross-member. The first projection is pivotally attached to the actuating unit. The second projection is pivotally attached to a lower swing link of the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism. The actuating unit includes

3

opposed first and second ends, wherein the first end of the actuating unit moves forwardly as the seating unit moves from the upright position to the TV position, and wherein the second end of the actuating unit moves rearwardly when the seating unit moves from the TV position to the fully reclined position.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view of a glider-recliner chair according to embodiments of the present invention.

FIG. 2 is a side section view of the chair of FIG. 1 with the chair in its fully upright position.

FIG. 2A is an enlarged side section view of the actuating mechanism of the chair of FIG. 1 with the chair in its fully upright position.

FIG. 3 is a side section view of the chair of FIG. 1 with the chair in its TV position.

FIG. 3A is an enlarged side section view of the actuating mechanism of the chair of FIG. 1 with the chair in its TV position.

FIG. 4 is a side section view of the chair of FIG. 1 with the chair in its fully reclined position.

FIG. 4A is an enlarged side section view of the actuating mechanism of the chair of FIG. 1 with the chair in its fully reclined position.

FIG. 5 is a top cutaway view of the frame of the chair of FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The present invention now is described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

Like numbers refer to like elements throughout. In the figures, the thickness of certain lines, layers, components, elements or features may be exaggerated for clarity. Broken lines illustrate optional features or operations unless specified otherwise.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. As used herein, phrases such as “between X and Y” and “between about X and Y” should be interpreted to include X and Y. As used herein, phrases such as “between about X and Y” mean “between about X and about Y.” As used herein, phrases such as “from about X to Y” mean “from about X to about Y.”

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood

4

that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

It will be understood that when an element is referred to as being “on”, “attached” to, “connected” to, “coupled” with, “contacting”, etc., another element, it can be directly on, attached to, connected to, coupled with or contacting the other element or intervening elements may also be present. In contrast, when an element is referred to as being, for example, “directly on”, “directly attached” to, “directly connected” to, “directly coupled” with or “directly contacting” another element, there are no intervening elements present. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature may have portions that overlap or underlie the adjacent feature.

This invention is directed to seating units that have a stationary base, a seat portion, and a backrest. As used herein, the terms “forward”, “forwardly”, and “front” and derivatives thereof refer to the direction defined by a vector extending from the backrest toward the seat parallel to the underlying surface. Conversely, the terms “rearward”, “rearwardly”, and derivatives thereof refer to the direction directly opposite the forward direction; the rearward direction is defined by a vector that extends from the seat toward the backrest parallel to the underlying surface. The terms “lateral,” “laterally”, and derivatives thereof refer to the direction parallel with the floor, perpendicular to the forward and rearward directions, and extending away from a plane bisecting the seating units between their armrests. The terms “medial,” “inward,” “inboard,” and derivatives thereof refer to the direction that is the converse of the lateral direction, i.e., the direction parallel with the floor, perpendicular to the forward direction, and extending from the periphery of the seating units toward the aforementioned bisecting plane.

The seating units illustrated and described herein comprise a plurality of pivotally interconnected links. Those skilled in this art will appreciate that the pivots between links can take a variety of configurations, such as pivot pins, rivets, bolt and nut combinations, and the like, any of which would be suitable for use with the present invention. Also, the shapes of the links may vary as desired, as may the locations of certain of the pivots. Moreover, in some instances combinations of pivot points may be replaced by equivalent structures, such as “slider-crank” configurations, like those described in B. Paul, *Kinematics and Dynamics of Planar Machinery* 4-21 (1979). In other embodiments, another mechanism that provides reciprocating motion along a longitudinal path, such as a rocking unit like that discussed in co-assigned and co-pending U.S. patent application Ser. No. 12/276,559, the disclosure of which is hereby incorporated herein in its entirety, may also be employed.

Referring now to the figures, a swiveling glider-recliner chair, designated broadly at 10, is illustrated in FIGS. 1-5. The chair 10 includes a base unit 11, a seat 13 that is generally horizontally disposed above the base unit 11, a backrest 15 that is generally vertically and disposed substantially above a rear portion of the seat 13, and two ottomans 17a, 17b, which, in the upright position of FIG. 1, are generally vertically disposed below a front portion of the seat 13. Arms 18 are positioned on either side of the seat 13 and move in concert with the seat 13.

5

A pair of mirror image reclining mechanisms **30** (only one of which is shown herein in FIGS. 2-4) are attached to the backrest **15**, the seat **13**, and the ottomans **17a**, **17b**. The reclining mechanisms **30**, which comprise a plurality of interconnected links, move the chair **10** between (a) an upright position (FIGS. 1 and 2), in which the seat **13** is generally horizontally disposed, the backrest **15** is generally vertically disposed, and the ottomans **17a**, **17b** are generally vertically disposed and positioned below the seat **13**, (b) an intermediate TV position (FIG. 3), in which the ottomans **17a**, **17b** are generally horizontally disposed in front of the seat **13** and the backrest **15** and the seat **13** substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position (FIG. 4), in which the angle between the backrest **15** and the seat **13** increases. These components are described in greater detail below.

The base unit **11** includes a circular lower base **12**. A swivel unit **14** is mounted onto the top of the lower base **12**. Cross-members **18** are mounted atop the swivel unit **14**. Those skilled in this art will recognize that the base unit **11** may take other forms that provide mounting locations for the remaining components of the chair **10**; for example, the swivel unit **14** may be omitted.

Glide foundation plates **24** are mounted to the top surfaces of the cross-members **18**. A front glide link **20** is attached at a pivot **21** to the front end of the glide foundation plate **24**, and a rear glide link **25** is attached at a pivot **26** to the rear end of the glide foundation plate **24**. The front and rear glide links **20**, **25** are suspended from the glide foundation plate **24** and together form a gliding mechanism **28** that provides a gliding motion to the chair **10** when it is in its upright position (FIG. 2). Those skilled in this art will appreciate that the gliding mechanism may take other forms; it may include glide links of different shapes, or it may include a "track"—based gliding mechanism.

Because the reclining mechanisms **30** are mirror images of each other, only one reclining mechanism will be described in detail herein, with the understanding that the discussion is equally applicable to the mirror image mechanism **30**. Also, for clarity the mechanism will be described first with reference to FIG. 4 (with the mechanism **30** in its reclined position), then will be described in its upright and TV positions.

Turning now to FIG. 4, the reclining mechanism **30** includes a generally arcuate foundation link **31**, which is attached at either end to the front and rear glide links **20**, **25** at pivots **22**, **27**, respectively. A generally crescent-shaped mounting bracket **32** is fixed to the foundation link **31**. A slot **32a** is present at the front end of the mounting bracket **32**. An L-shaped lower swing link **34** is attached to a lower region of the mounting bracket **32** at a pivot **36** and extends upwardly and rearwardly, then upwardly and forwardly therefrom. A straight upper swing link **38** is attached at its lower end to the upper end of the lower swing link **34** at a pivot **40** and extends upwardly therefrom.

A backpost **48** is fixed to the backrest **15** and extends generally forwardly from the lower front end of the backrest **15**. The upper swing link **38** is attached to a forward portion of the backpost **48** at a pivot **50**. A straight coupling link **52** having a slot **52a** is attached to the backpost **48** via a pin **48a** located forwardly of the pivot **50**. The coupling link **52** extends forwardly and downwardly from the pin **48a** to attach to the front end of the mounting bracket **32** via a pin **52b** inserted into a slot **32a** in the mounting bracket **32**. A trapezoidal sequencer plate **54** is attached to the backpost **48** at a pivot **58**, and also interacts with the backpost **48** via a slot **54a** that receives a pin **48b**. The sequencer plate **54** is also attached to the rear end of the mounting bracket **32** at a pivot **56**.

6

Still referring to FIG. 4, a seat frame **62**, to which the arms **18** are mounted, underlies the seat **13**. A seat adapter **66** is fixed to the seat frame **62**. The seat adapter **66** is attached to the backpost **48** at a pivot **68** that is located just rearward of the pivot **50**. An upper ottoman swing link **72** is attached to a front region of the seat adapter **66** at a pivot **74** and extends downwardly and forwardly therefrom. A tripartite lower ottoman swing link **76** is attached to a pivot **78** that is located rearwardly and downwardly from the pivot **74**; the lower ottoman swing link **76** extends generally forwardly from the pivot **78**. An upper ottoman extension link **80** is attached to the forward end of the lower ottoman swing link **76** at a pivot **82** and extends forwardly and upwardly therefrom. Also the upper ottoman extension link **80** is attached to the upper ottoman swing link at a pivot **84**. A lower ottoman extension link **86** is attached to the forward end of the upper ottoman swing link at a pivot **88** that is positioned above and forward of the pivot **84** and extends upwardly and forwardly therefrom generally parallel with the upper ottoman extension link. An outer ottoman bracket **90** is generally horizontally disposed and is attached to the upper and lower ottoman extension links **80**, **86** at pivots **92**, **94** respectively. The ottoman **17a** is mounted on the outer ottoman bracket **90**.

A bi-angled inner ottoman bracket **96** is attached at its lower, forward end to the lower ottoman extension link **86** at a pivot **98**. At its opposite end, the inner ottoman bracket **96** supports the ottoman **17b**. The inner ottoman bracket **96** also includes a slot **96a** that receives a pin **80a** located on the upper ottoman extension link **80**.

A connecting link **100** is attached to the sequencer plate **54** at a pivot **102**. The connecting link **100** extends forwardly and slightly upwardly from the pivot **102** to a pivot **104** with the lower ottoman swing link **76**.

A locking mechanism **130** is attached to the reclining mechanism **30** to prevent gliding of the chair **10** when it is in the TV or fully reclined positions. The locking mechanism **130** includes a drive link **132** that is pivotally interconnected at one end to the sequencer plate **54** at a pivot **134**. The drive link **132** is a straight link that slopes downwardly and slightly forwardly from the pivot **134**. The opposite end of the drive link **132** is pivotally interconnected with a downwardly-extending projection **138** of a hook-shaped locking link **136** at a pivot **140**. The locking link **136** is attached to the mounting bracket **32** at the pivot **36**.

Referring to FIG. 4A, The chair **10** includes a power unit **112** that drives the chair **10** between its upright, TV and fully reclined positions. The power unit **112** includes a motor unit **114**, to which is attached a sleeve **116**. The sleeve extends rearwardly from the motor unit **114** and receives a retractable rod **118**. The motor unit **114** is electrically connected with an actuator (not shown), such as a toggle switch or the like, that energizes the motor unit **114** upon actuation.

The motor unit **114** is attached to an actuating mechanism **113** that includes a mounting bracket **110** at a pivot **120** via a mounting tab **114a** (see FIG. 5). The mounting bracket **110** is then attached to a cross-member **108** that extends between the reclining mechanisms **30**. A bracket **106** is fixed to each of the lower ottoman swing links **76** and to the cross-member **108**.

The rod **118** of the power unit **112** is attached to a projecting bracket **46** of the actuating unit **113** (FIGS. 4, 4A and 5) at a pivot **122**. The bracket **46** is then attached to a Z-shaped cross-member **44** that extends between the reclining mechanisms **30**. The cross-member **44** is fixed to a second projecting bracket **42** that is pivotally attached to the lower swing link **34** of each reclining mechanism **30** at a pivot **140**.

As can be seen in FIG. 2A, in the upright position, the rod **118** of the power unit **112** is retracted into the sleeve **116**. In

7

this position, the “internal leg” of the Z-shaped cross-member **44** is disposed at an angle α of approximately 45 degrees to horizontal, such that both of the pivots **40**, **140** are positioned below the axis A defined by the rod **118** of the power unit **112**. The upper segment of the lower swing link **34** is generally parallel with the axis A.

Because the rod **118** is in its retracted position, a pantographic linkage formed by the upper and lower ottoman swing links **72**, **76** and the upper and lower ottoman extension links **80**, **86** is folded under the seat frame **62**, which positions the ottoman **17b** underneath a forward portion of the seat frame **62** and the ottoman **17a** just forward of and below the seat frame **62** in a vertical orientation. Also, the lower and upper swing links **34**, **38** are oriented such that the upper segment of the lower swing link **34** is generally horizontal, which positions the backpost **48** and, in turn, the backrest **15**, in a generally upright position.

Additionally, the sequencer plate **54** is oriented such that the pivot **102** is located downwardly and rearwardly, such that the locking link **136** of the locking mechanism **130** is raised, with a pocket **137** formed at the vertex of the locking link **136** facing downwardly and positioned above a post **139** on the rear glide link **25**. In this position, the front and rear glide links **20**, **25** are free to swing on the pivots **21**, **26**, thereby enabling the reclining mechanisms **30**, the seat **13**, the backrest **15** and the ottomans **17a**, **17b** to move fore-and-aft relative to the base unit **11**. During the gliding motion, the majority of the locking mechanism **130** is stationary relative to the reclining mechanisms **30**. Because the locking link **136** does not move relative to the reclining mechanism **30** as the chair **10** glides, it does not interact with the post **139** to impede the gliding motion.

To move the chair **10** from the upright position to the TV position of FIG. 3, an occupant of the chair **10** actuates the actuator, which causes the rod **118** to begin to extend from the sleeve **116**. Extension of the rod **118** attempts to force the lower swing link **34** to rotate slightly counterclockwise (from the vantage point of FIGS. 2 and 3) about the pivot **36**. However, the weight of the seated occupant and the geometry of the lower swing link **34**, the upper swing link **38**, and the actuation mechanism **113** prevent any substantial rotation of the lower swing link **34** at this point. Because there is little to no fore-and-aft movement of the rear end of the rod **118**, the motor unit **114** moves forwardly relative to the base unit **11**, thereby driving the lower ottoman swing link **76** counterclockwise about the pivot **78**. Rotation of the lower ottoman swing link **76** forces the upper ottoman extension link **80** forward, which in turn draws the upper ottoman swing link **72** counterclockwise around the pivot **74**. Also, the lower ottoman extension link **86** moves forwardly more than the upper ottoman extension link **80**, such that the outer ottoman bracket **90** and the inner ottoman bracket **96** rotate counterclockwise (rotation of the inner ottoman bracket **96** causes the pin **80a** to move in the slot **96a** toward the pivot **98**). The rotation of the outer and inner ottoman brackets **90**, **96** induces the ottomans **17a**, **17b** to rotate from a vertical orientation to a horizontal orientation. Motion of the ottomans **17a**, **17b** ceases when a pin **72a** on the upper ottoman swing link **72** strikes the upper edge of the upper ottoman extension link **80**.

In addition, the rotation of the lower ottoman swing link **76** draws the connecting link **100** forward. Movement of the connecting link **100** rotates the sequencer plate **54** counterclockwise about the pivot **58** with the backpost **48**. The drive link **132** of the locking mechanism **130** is driven down and rotates the locking link **136** counterclockwise. The movement of the locking link **136** ceases when the pocket **137** of the

8

locking link **136** descends sufficiently to receive the post **139** on the rear glide link **25**. In this position, relative movement between the front and rear glide links **20**, **25** and the reclining mechanisms is restrained, thereby preventing the reclining mechanisms **30**, and in turn the chair **10**, from gliding relative to the base unit **11**.

Rotation of the sequencer plate **54** and movement of the connecting link **100** also lower the backpost **48** relative to the base unit **11**, which forces the seat link **64** to increase in pitch angle relative to its underlying surface. The upper swing link **38** rotates counterclockwise about the pivot **48** as a result.

To move the chair **10** from the TV position of FIG. 3 to the fully reclined position of FIG. 4, the occupant can continue to operate the actuator, which extends the rod **118** farther out of the sleeve **116**. When the ottomans **17a**, **17b** are fully extended, the pivots **82**, **84** and **88** are in a near “over-center” condition that helps to lock the ottomans **17a**, **17b** in an extended position. Thus, as the rod **118** continues to extend from the sleeve **116** when the chair is in the TV position, the motor unit **114** cannot move forward relative to the base unit **11** any farther, so the rear end of the rod **118** overcomes the resistance provided by the occupant’s weight and the geometry of the actuating mechanism **113** and the lower and upper swing links **34**, **38** and begins to move rearwardly relative to the base unit **11**, resulting in counterclockwise rotation of the lower swing link **34** about the pivot **36**. This rotation drives the upper swing link **38** clockwise about the pivot **36**. Thus, this action causes the angle β defined by the pivots **36**, **40**, **50** to increase. The rotation of the upper swing link **38** drives the forward end of the backpost **48** upward. As a consequence, the backpost **48** rotates counterclockwise about the pivot **58** relative to the sequencer plate **54** (and to the seat adapter **66** and the seat frame **62**). Rotation of the backpost **48** and, in turn, the backrest **15**, continues until (a) the pin **48b** on the backpost **48** reaches the upper end of the slot **54a** in the sequencer plate **54** and (b) the pin **52b** of the coupling link **52** reaches the rear end of the slot **32a** of the mounting bracket **32**. In this position, the backrest **15** has reclined relative to the seat **13** at a greater angle than in the upright and TV positions.

The rotation of the lower swing link **34** and of the coupling link **52** also causes the seat **15** to rise relative to the base unit **11**.

As can also be seen in FIG. 4, the locking mechanism **130** continues to prevent the chair **10** from gliding as the chair **10** moves to the fully reclined position. It can also be seen that the seat **13** rises during movement from the TV position to the fully reclined position.

The chair **10** can be returned to its TV position from the fully reclined position by the occupant operating the actuator in the reverse direction. Because of the over-center condition of the pivots **82**, **84**, **88**, the ottomans **17a**, **17b** remain extended, such that retraction of the rod **118** draws the backrest **15** to its upright position. Once the motion of the backrest **15** is complete, the over-center condition of the pivots **82**, **84** and **88** can be overcome, and the ottomans **17a**, **17b** are able to retract to the upright position.

Those skilled in this art will recognize that other variations of the chair **10** are contemplated in connection with the present invention. For example, the power unit **112** may be reversed, such that the motor **114** is at the rear end of the power unit **112** and the rod **118** is at the front end. In such a case, the rod **118** would extend forwardly relative to the base unit **11** as the chair **10** moved from the upright position to the TV position, and the motor **114** would move rearwardly relative to the base unit **11** when the chair moved from the TV position to the fully reclined position. In either instance, the front end of the power unit **112** moves relative to the base unit

11 during the movement from the upright to the TV position, and the rear end of the power unit moves relative to the base unit 11 during the movement from the TV to the fully reclined position.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as recited in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

That which is claimed is:

1. A seating unit, comprising:

a base unit with a first bearing surface;

a generally horizontally-disposed seat positioned above the base unit;

a generally upright backrest positioned above the base unit and substantially rearward of the seat;

an extendable ottoman;

a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links;

a reciprocating mechanism attached to the base unit and the reclining mechanism, the reciprocating mechanism being configured to enable the seat, backrest and reclining mechanism to reciprocate relative to the base unit along a longitudinal path responsive to a longitudinally-directed force; and

a linear actuating unit attached to the reclining mechanism, the linear actuating unit configured to move the seating unit between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases;

wherein the linear actuating unit includes opposed first and second ends, and wherein the first end of the linear actuating unit moves forwardly as the seating unit moves from the upright position to the TV position, and wherein the second end of the linear actuating unit moves rearwardly when the seating unit moves from the TV position to the fully reclined position.

2. The seating unit defined in claim 1, wherein the reclining mechanism includes a pantographic linkage on which the ottoman is mounted, and wherein in the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position.

3. The seating unit defined in claim 1, further comprising a locking mechanism that allows the seating unit to reciprocate while in the upright position but prevents reciprocating of the seating unit while in the TV and fully reclined positions.

4. The seating unit defined in claim 1, wherein the linear actuating unit is attached to an actuating mechanism, the actuating mechanism comprising a cross-member extending transversely across the seating unit, wherein the cross-member is pivotally attached to the actuating unit; and wherein the cross-member is pivotally attached to a lower swing link of

the reclining mechanism, the lower swing link being pivotally attached to an upper swing link of the reclining mechanism and to a mounting bracket that is attached to the reciprocating mechanism.

5. The seating unit defined in claim 4, wherein the upper swing link is pivotally attached with the backrest.

6. The seating unit defined in claim 1, wherein the seat rises in moving from the TV position to the fully reclined position.

7. The seating unit defined in claim 1, wherein the reclining mechanism includes a backpost that is fixed relative to the backrest, a mounting bracket that is fixed relative to the reciprocating mechanism and pivotally attached to the backpost, and a seat adapter that is fixed relative to the seat and pivotally attached to the backpost.

8. The seating unit defined in claim 7, wherein the lower swing link is angled, and wherein a segment of the lower swing link attached to the upper swing link is generally parallel to an axis defined by an extendable member of the linear actuating unit when the seating unit is in the upright and TV positions.

9. The seating unit defined in claim 8, wherein a first pivot defined by the cross-member and the lower swing link and a second pivot defined by the lower swing link and the upper swing link are below the axis defined by the extendable member of the actuating unit when the seating unit is in the upright and TV positions.

10. The seating unit defined in claim 9, wherein the lower swing link is attached to the mounting bracket at a third pivot, and wherein in the upright and TV positions, the first, second and third pivots define a first angle, and in the fully reclined position, the first, second and third pivots define a second angle that is larger than the first angle.

11. The seating unit defined in claim 1, wherein the reciprocating mechanism is a gliding mechanism.

12. A reciprocating seating unit, comprising:

a base;

a generally horizontally-disposed seat positioned above the base;

a generally upright backrest positioned above the base and substantially rearward of the seat;

an extendable ottoman;

a reclining mechanism attached to the seat, the backrest, the ottoman and the base, the reclining mechanism comprising a plurality of pivotally interconnected links;

a reciprocating mechanism attached with the base unit and the reclining mechanism, the reciprocating mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed reciprocating motion relative to the base unit; and

a linear actuator attached to the reclining mechanism, the linear actuator having first and second movable members, wherein the relative movement of the first and second movable members moves the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases;

wherein the reclining mechanism includes:

a backpost that is fixed relative to the backrest;

a mounting bracket that is attached to the second movable member of the linear actuator;

PUBLIC VERSION

US 8,297,693 B2

11

a lower swing link that is attached to the mounting bracket;
and

an upper swing link that is pivotally attached to the lower
swing link and to the backpost.

13. The seating unit defined in claim **12**, further comprising
a seat adapter that is fixed relative to the seat and directly
pivotally attached to the backpost.

12

14. The reciprocating seating unit defined in claim **13**,
wherein the reclining mechanism includes a pantographic
linkage that extends the footrest in the TV and fully reclined
positions, and wherein the pantographic linkage comprises
5 upper and lower ottoman swing links that are directly pivot-
ally attached to the seat adapter.

* * * * *

(12) **United States Patent**
Hoffman et al.

(10) **Patent No.:** **US 8,459,733 B2**
(45) **Date of Patent:** ***Jun. 11, 2013**

(54) **ROCKING-RECLINING SEATING UNIT
WITH POWER ACTUATOR**

(75) Inventors: **D. Stephen Hoffman**, High Point, NC
(US); **Marcus L. Murphy**, Lexington,
NC (US)

(73) Assignee: **Ultra-Mek, Inc.**, Denton, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 42 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **13/363,641**

(22) Filed: **Feb. 1, 2012**

(65) **Prior Publication Data**

US 2012/0153704 A1 Jun. 21, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/276,559, filed on
Nov. 24, 2008, now Pat. No. 8,113,574.

(51) **Int. Cl.**
A47C 1/35 (2006.01)
A47C 1/38 (2006.01)

(52) **U.S. Cl.**
USPC **297/85 M**; 297/362.11; 297/85 R;
297/362.14; 297/DIG. 7

(58) **Field of Classification Search**
USPC 297/85 R, 85 M, 362.11, 362.13,
297/362.14, DIG. 7

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,707,025	A *	11/1987	Rogers, Jr.	297/259.2
6,634,706	B2 *	10/2003	May	297/85 L
6,659,556	B2 *	12/2003	Pellerin	297/330
6,840,575	B2 *	1/2005	Hesse	297/85 M
6,945,599	B2 *	9/2005	May	297/270.1
7,021,711	B1 *	4/2006	Hoffman et al.	297/270.1
7,722,114	B2 *	5/2010	Smith	297/68
8,113,574	B2 *	2/2012	Hoffman et al.	297/85 M

* cited by examiner

Primary Examiner — David Dunn


Assistant Examiner — Tania Abraham


(74) *Attorney, Agent, or Firm* — Myers Bigel Sibley &
Sajovec, P.A.


(57) **ABSTRACT**


A rocking and reclining seating unit includes: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a rocker mechanism attached with the base unit and the reclining mechanism, the rocker mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed rocking motion relative to the base unit; and a power actuating unit attached to the reclining mechanism. The actuating unit is configured to move the chair between an upright position, an intermediate TV position, and a fully reclined position.

5 Claims, 5 Drawing Sheets












FIG. 4



US 8,459,733 B2

1

**ROCKING-RECLINING SEATING UNIT
WITH POWER ACTUATOR**

RELATED APPLICATIONS

This application is a continuation of prior U.S. patent application Ser. No. 12/276,559, filed Nov. 24, 2008 now U.S. Pat. No. 8,113,574 and entitled ROCKING-RECLINING SEATING UNIT WITH POWER ACTUATOR, the disclosure of which is hereby incorporated herein in its entirety.

FIELD OF THE INVENTION

This invention relates generally to seating units, and relates more particularly to reclining seating units with rocking capability.

BACKGROUND OF THE INVENTION

Recliner chairs and other reclining seating units have proven to be popular with consumers. These seating units typically move from an upright position, in which the backrest is generally upright, to one or more reclined positions, in which the backrest pivots to be less upright. The movement of the seating unit between the upright and reclined positions is typically controlled by a pair of matching reclining mechanisms that are attached to the seat, backrest and base of the chair.

One particularly popular reclining chair is the so-called "rocker-recliner," which can, when in the upright position, rock with a forward and rearward motion similar to that of a traditional rocking chair. A typical rocker recliner, one of which is illustrated in U.S. Pat. No. 4,519,647 to Rogers, includes an arcuate rocker cam that is attached with the lower portion of each mechanism, with the lower convex surface of the rocker cam contacting a level bearing surface of the base. Also, a spring assembly is mounted to the base of the chair and to each rocker cam. Each spring assembly includes two quite stiff, vertically-oriented helical springs attached to mounting brackets that are in turn fixed to the base and to the rocker cam. When the chair is in its upright position and is unoccupied, the seat, backrest and reclining mechanisms reside above the base, the rocker springs are deflected only along their longitudinal axes, and the rocker cams rest on a level portion of the base. When an occupant sits on the chair and applies a forwardly- or rearwardly-directed force to the seat or backrest, the seat and backrest move relative to the base. The path of movement is defined by the convex shape of the rocker cams as they rock on the level bearing surface of the base, with the result that the seat and backrest simulate the rocking motion of a rocking chair. During the rocking movement, the rocker springs deflect such that their top portions bend away from their longitudinal axes as the chair rocks forward and back. The deflection in the springs urges the springs (and, in turn, the seat and backrest) to return to their original positions as the chair returns to and through the upright position. In this manner, the chair is capable of providing a controlled rocking motion when in the upright position.

Although they are already popular seating units, it may be desirable to provide additional functionality to rocker-recliners.

SUMMARY OF THE INVENTION

As a first aspect, embodiments of the present invention are directed to a rocking and reclining seating unit. The rocker-

2

recliner comprises: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a rocker mechanism attached with the base unit and the reclining mechanism, the rocker mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed rocking motion relative to the base unit; and a power actuating unit attached to the reclining mechanism. The actuating unit is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

As a second aspect, embodiments of the present invention are directed to a rocking and reclining seating unit, comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a rocker mechanism attached with the base unit and the reclining mechanism, the rocker mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed rocking motion relative to the base unit; and a linear actuator attached to the reclining mechanism. The linear actuator is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases.

As a third aspect, embodiments of the present invention are directed to a rocking and reclining seating unit, comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a rocker mechanism attached with the base unit and the reclining mechanism, the rocker mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed rocking motion relative to the base unit; and a linear actuator attached to the reclining mechanism. The linear actuator is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relation-

3

ship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The reclining mechanism includes a pantographic linkage on which the ottoman is mounted. In the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position. The reclining mechanism also includes a backpost that is fixed relative to the backrest, a mounting bracket that is fixed relative to the rocker cams and pivotally attached to the backpost, and a seat adapter that is fixed relative to the seat and pivotally attached to the backpost.

As a fourth aspect, embodiments of the present invention are directed to a rocking and reclining seating unit comprising: a base unit with a first bearing surface; a generally horizontally-disposed seat positioned above the base; a generally upright backrest positioned above the base and substantially rearward of the seat; an extendable ottoman; a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links; a rocker mechanism attached with the base unit and the reclining mechanism, the rocker mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed rocking motion relative to the base unit; and a power actuating unit attached to the reclining mechanism. The actuating unit is configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman are generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases. The reclining mechanism includes a backpost fixed relative to the backrest and a sequencer plate pivotally interconnected with the backrest and with the remainder of the reclining mechanism, and wherein the sequencer plate rotates in a first rotative direction relative to the backrest when the seating unit moves from the upright position to the TV position, and wherein the backrest rotates relative to the sequencer plate in the first rotative direction when the seating unit moves from the TV position to the fully reclined position.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective view of a rocker-recliner chair according to embodiments of the present invention.

FIG. 2 is a side section view of the chair of FIG. 1 with the chair in its fully upright position.

FIG. 3 is a side section view of the chair of FIG. 1 with the chair in its TV position.

FIG. 4 is a side section view of the chair of FIG. 1 with the chair in its fully reclined position.

FIG. 5 is a top cutaway view of the frame of the chair of FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The present invention now is described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure

4

will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

Like numbers refer to like elements throughout. In the figures, the thickness of certain lines, layers, components, elements or features may be exaggerated for clarity. Broken lines illustrate optional features or operations unless specified otherwise.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. As used herein, phrases such as “between X and Y” and “between about X and Y” should be interpreted to include X and Y. As used herein, phrases such as “between about X and Y” mean “between about X and about Y.” As used herein, phrases such as “from about X to Y” mean “from about X to about Y.”

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

It will be understood that when an element is referred to as being “on”, “attached” to, “connected” to, “coupled” with, “contacting”, etc., another element, it can be directly on, attached to, connected to, coupled with or contacting the other element or intervening elements may also be present. In contrast, when an element is referred to as being, for example, “directly on”, “directly attached” to, “directly connected” to, “directly coupled” with or “directly contacting” another element, there are no intervening elements present. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature may have portions that overlap or underlie the adjacent feature.

This invention is directed to seating units that have a stationary base, a seat portion, and a backrest. As used herein, the terms “forward”, “forwardly”, and “front” and derivatives thereof refer to the direction defined by a vector extending from the backrest toward the seat parallel to the underlying surface. Conversely, the terms “rearward”, “rearwardly”, and derivatives thereof refer to the direction directly opposite the forward direction; the rearward direction is defined by a vector that extends from the seat toward the backrest parallel to the underlying surface. The terms “lateral,” “laterally”, and derivatives thereof refer to the direction parallel with the floor, perpendicular to the forward and rearward directions, and extending away from a plane bisecting the seating units between their armrests. The terms “medial,” “inward,” “inboard,” and derivatives thereof refer to the direction that is the converse of the lateral direction, i.e., the direction parallel with the floor, perpendicular to the forward direction, and

5

extending from the periphery of the seating units toward the aforementioned bisecting plane.

The seating units illustrated and described herein comprise a plurality of pivotally interconnected links. Those skilled in this art will appreciate that the pivots between links can take a variety of configurations, such as pivot pins, rivets, bolt and nut combinations, and the like, any of which would be suitable for use with the present invention. Also, the shapes of the links may vary as desired, as may the locations of certain of the pivots. Moreover, in some instances combinations of pivot points may be replaced by equivalent structures, such as “slider-crank” configurations, like those described in B. Paul, *Kinematics and Dynamics of Planar Machinery* 4-21 (1979).

Referring now to the figures, a swiveling rocker-recliner chair, designated broadly at 10, is illustrated in FIGS. 1-5. The chair 10 includes a base unit 11, a seat 13 that is generally horizontally disposed above the base unit 11, a backrest 15 that is generally vertically and disposed substantially above a rear portion of the seat 13, and two ottomans 17a, 17b, which, in the upright position of FIG. 1, are generally vertically disposed below a front portion of the seat 13. Arms 18 are positioned on either side of the seat 13 and move in concert with the seat 13.

A pair of mirror image reclining mechanisms 30 (only one of which is shown herein in FIGS. 2-4) are attached to the backrest 15, the seat 13, and the ottomans 17a, 17b. The reclining mechanisms 30, which comprise a plurality of interconnected links, move the chair 10 between (a) an upright position (FIGS. 1 and 2), in which the seat 13 is generally horizontally disposed, the backrest 15 is generally vertically disposed, and the ottomans 17a, 17b are generally vertically disposed and positioned below the seat 13, (b) an intermediate TV position (FIG. 3), in which the ottomans 17a, 17b are generally horizontally disposed in front of the seat 13 and the backrest 15 and the seat 13 substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position (FIG. 4), in which the angle between the backrest 15 and the seat 13 increases. These components are described in greater detail below.

The base unit 11 includes a circular lower base 12. A swivel unit 14 is mounted onto the top of the lower base 12. Rocker rails 16 are mounted atop the swivel unit 14 and are reinforced by cross-members 18. Rocker cams 20 rest on the upper bearing surfaces of the legs of the rails 16. A recliner foundation 24 is mounted to the top surfaces of the rocker cams 20; the foundation 24 includes longitudinal brackets 26 and cross-members 28a, 28b that span the longitudinal brackets 26. The arcuate lower surfaces of the cams 20 are configured for rolling contact with the bearing surfaces and enable the chair 10 to have a fore-to-aft rocking motion. This motion is controlled by rocker spring assemblies 22 that are attached to the cross-members 18 and to the cross-members 28a, 28b. The rocker cams 20, the rocker spring assemblies 22, and the components to which they are attached form a rocker mechanism 21. It is to be understood other rocker mechanisms may be employed; for example, the rocker spring assemblies 22 may also be attached directly to the reclining mechanisms 30 in other embodiments, such as in the manner illustrated in U.S. Pat. No. 5,876,094 to Hoffman, and the reclining mechanism can be mounted directly onto the rocker cams 20 as illustrated in the U.S. Pat. No. 6,000,754 to Lawson.

Because the reclining mechanisms 30 are mirror images of each other, only one reclining mechanism will be described in detail herein, with the understanding that the discussion is equally applicable to the mirror image mechanism 30. Also, for clarity the mechanism will be described first with refer-

6

ence to FIG. 4 (with the mechanism 30 in its reclined position), then will be described in its upright and TV positions.

Turning now to FIG. 4, the reclining mechanism 30 includes a generally crescent-shaped mounting bracket 32 that is fixed to the longitudinal rail 26. A slot 32a is present at the front end of the mounting bracket 30. An L-shaped lower swing link 34 is attached to a lower region of the mounting bracket 32 at a pivot 36 and extends upwardly and rearwardly, then upwardly and forwardly therefrom. An L-shaped upper swing link 38 is attached at its lower end to the upper end of the lower swing link 34 at a pivot 40 and extends upwardly and rearwardly, then upwardly therefrom.

A backpost 48 is fixed to the backrest 15 via a spacer 60 and extends generally forwardly from the lower front end of the backrest 15. The upper swing link 38 is attached to a forward portion of the backpost 48 at a pivot 50. A straight coupling link 52 having a slot 52a is attached to the backpost 48 via a pin 48a located forwardly of the pivot 50. The coupling link 52 extends forwardly and downwardly from the pin 48a to attach to the front end of the mounting bracket 32 via a pin 52b inserted into a slot 32a in the mounting bracket 32. A trap-ezoidal sequencer plate 54 is attached to the backpost 48 at a pivot 58, and also interacts with the backpost 48 via a slot 54a that receives a pin 48b. The sequencer plate 54 is also attached to the rear end of the mounting bracket 32 at a pivot 56.

Still referring to FIG. 4, a seat frame 62, to which the arms 18 are mounted, underlies the seat 13. A seat bracket 64 is fixed to the seat frame 62. In turn, a seat adapter 66 is fixed to the seat bracket 64. The seat adapter 66 is attached to the backpost 48 at a pivot 68 that is located just rearward of the pivot 50. An upper ottoman swing link 72 is attached to a front region of the seat adapter 66 at a pivot 74 and extends downwardly and forwardly therefrom. A tripartite lower ottoman swing link 76 is attached to a pivot 78 that is located rearwardly and downwardly from the pivot 74; the lower ottoman swing link 76 extends generally forwardly from the pivot 78. An upper ottoman extension link 80 is attached to the forward end of the lower ottoman swing link 76 at a pivot 82 and extends forwardly and upwardly therefrom. Also the upper ottoman extension link 80 is attached to the upper ottoman swing link at a pivot 84. A lower ottoman extension link 86 is attached to the forward end of the upper ottoman swing link at a pivot 88 that is positioned above and forward of the pivot 84 and extends upwardly and forwardly therefrom generally parallel with the upper ottoman extension link. An outer ottoman bracket 90 is generally horizontally disposed and is attached to the upper and lower ottoman extension links 80, 86 at pivots 92, 94 respectively. The ottoman 17a is mounted on the outer ottoman bracket 90.

An L-shaped inner ottoman bracket 96 is attached at its lower, forward end to the lower ottoman extension link 86 at a pivot 98. At its opposite end, the inner ottoman bracket 96 supports the ottoman 17b. The inner ottoman bracket 96 also includes a slot 96a that receives a pin 80a located on the upper ottoman extension link 80.

A connecting link 100 is attached to the sequencer plate 54 at a pivot 102. The connecting link 100 extends forwardly and slightly upwardly from the pivot 102 to a pivot 104 with the lower ottoman swing link 76.

A locking mechanism 130 is attached to the reclining mechanism 30 to prevent rocking of the chair 10 when it is in the TV or fully reclined positions. The locking mechanism 130 includes a drive link 132 that is pivotally interconnected at one end to the sequencer plate 54 at a pivot 134. The drive link 132 is a straight link that slopes downwardly and forwardly from the pivot 134. The opposite end of the drive link 132 is pivotally interconnected with the intermediate portion

7

of a straight bracing link **136** at a pivot **140**. The bracing link **136** includes a wheel **138** or other engagement structure at its rearward (or engagement) end, and further includes a pin **139** at its forward end. A straight control link **142** is pivotally interconnected with the longitudinal member **26** of the base unit **11** at a pivot **146**; the control link **142** extends upwardly and slightly forwardly therefrom. The control link **142** includes in its upper half a slot **144** within which the pin **139** of the bracing link **136** resides.

The chair **10** includes a power unit **112** that drives the chair **10** between its upright, TV and fully reclined positions. The power unit **112** includes a motor unit **114**, to which is attached a sleeve **116**. The sleeve extends rearwardly from the motor unit **114** and receives a retractable rod **118**. The motor unit **114** is electrically connected with an actuator (not shown), such as a toggle switch or the like, that energizes the motor unit **114** upon actuation.

The motor unit **114** is attached to a mounting bracket **110** at a pivot **120** via a mounting tab **114a** (see FIG. 5). The mounting bracket **110** is then attached to a cross-member **108** that extends between the reclining mechanisms **30**. A bracket **106** is fixed to each of the lower ottoman swing links **76** and to the cross-member **108**.

The rod **118** of the power unit **112** is attached to a bracket **46** (FIG. 5) at a pivot **122**. The bracket **46** is then attached to a cross-member **44** that extends between the reclining mechanisms **30**; the cross-member **44** is fixed to a bracket **42** that is in turn fixed to the upper swing link **38** of each reclining mechanism **30**.

As can be seen in FIG. 2, in the upright position, the rod **118** of the power unit **112** is retracted into the sleeve **116**. As a result, a pantographic linkage formed by the upper and lower ottoman swing links **72**, **76** and the upper and lower ottoman extension links **80**, **86** are folded under the seat frame **62**, which positions the ottoman **17b** underneath a forward portion of the seat frame **62** and the ottoman **17a** just forward of and below the seat frame **62** in a vertical orientation. Also, the lower and upper swing links **34**, **38** are oriented such that the segments thereof adjacent the pivot **36** partially overlap, which positions the backpost **48** and, in turn, the backrest **15**, in a generally upright position.

Additionally, the sequencer plate **54** is oriented such that the pivot **102** is located downwardly and rearwardly, such that the bracing link **136** of the locking mechanism **130** is raised, with the wheel **138** facing rearwardly. In this position, the chair **10** is free to rock as the rocker cams **20** engage in rolling motion relative to the rocker rails **16**. During the rocking motion, the majority of the locking mechanism **130** is stationary relative to the reclining mechanisms **30**. Because the bracing link **136** does not move relative to the reclining mechanism **30** as the chair **10** rocks, similarly the pin **139** that resides in the slot **144** in the control link **142** does not move relative to the reclining mechanism **30** as the chair **10** rocks. However, the presence of the slot **144** permits the pin **139** to slide and/or reciprocate therein when the chair **10** is rocking. In the illustrated embodiment, the control link **142** moves very little during the rocking motion; however, in other embodiments, the control link **142** may pivot about the pivot **146** during rocking.

To move the chair **10** from the upright position to the TV position of FIG. 3, an occupant of the chair **10** actuates the actuator, which causes the rod **118** to begin to extend from the sleeve **116**. Extension of the rod **118** forces the upper swing link **38** to rotate slightly counterclockwise (from the vantage point of FIGS. 2 and 3) about the pivot **40**. This movement draws the backpost **48** and rear end of the seat frame **62** downwardly, which causes the seat **13** to increase in pitch

8

angle relative to the underlying surface. However, the weight of the seated occupant prevents further rotation of the upper swing link **38** at this point. Because there is little to no fore-and-aft movement of the rear end of the rod **118**, the motor unit **114** moves forwardly relative to the base unit **11**, thereby driving the lower ottoman swing link **76** counterclockwise about the pivot **78**. Rotation of the lower ottoman swing link **76** forces the upper ottoman extension link **80** forward, which in turn draws the upper ottoman swing link **72** counterclockwise around the pivot **74**. Also, the lower ottoman extension link **86** moves forwardly more than the upper ottoman extension link **80**, such that the outer ottoman bracket **90** and the inner ottoman bracket **96** rotate counterclockwise (rotation of the inner ottoman bracket **96** causes the pin **80a** to move in the slot **96a** toward the pivot **98**). The rotation of the outer and inner ottoman brackets **90**, **96** induces the ottomans **17a**, **17b** to rotate from a vertical orientation to a horizontal orientation. Motion of the ottomans **17a**, **17b** ceases when a pin **72a** on the upper ottoman swing link **72** strikes the upper edge of the lower ottoman extension link **80**.

In addition, the rotation of the lower ottoman swing link **76** draws the connecting link **100** forward. Movement of the connecting link **100** rotates the sequencer plate **54** counterclockwise about the pivot **58** with the backpost **48**. The drive link **132** of the locking mechanism is driven forward and rotates the bracing link **136**. The forward motion of the drive link **132** causes the bracing link **136** to rotate such that its forward end rises and moves rearwardly and such that its rearward end, on which the wheel **138** is mounted, descends and moves forwardly (this rotation is counterclockwise from the vantage point of FIGS. 2 and 3). Also, the elevation of the forward end of the bracing link **136** causes the pin **139** to rise to the top of the slot **144** of the control link **142**. The control link **142** also rotates slightly about the pivot **146** to take a more vertical disposition. The movement of these links ceases when the wheel **138** engages a portion of the upper bearing surface of the rocker rail **16** rearward of the portion of the bearing surface beneath the rocker cams **20** (which substantially coincides with the pin **48b** reaching the lower end of the slot **54a**). In this position, the linkage between the bracing link **136**, the drive link **132** and the sequencer plate **54** restrains the mounting bracket **32**, thereby preventing the reclining mechanisms **30**, and in turn the chair **10**, from rocking relative to the base unit **11**.

To move the chair **10** from the TV position of FIG. 3 to the fully reclined position of FIG. 4, the occupant can continue to operate the actuator, which extends the rod **118** farther out of the sleeve **116**. When the ottomans **17a**, **17b** are fully extended, the pivots **84**, **88** and **94** are in a near "over-center" condition that helps to lock the ottomans **17a**, **17b** in an extended position. Thus, as the rod **118** continues to extend from the sleeve **116** when the chair is in the TV position, the motor unit **114** cannot move forward relative to the base unit **11** any farther, so the rear end of the rod **118** begins to move rearwardly relative to the base unit **11**, resulting in clockwise rotation of the upper swing link **38** about the pivot **40**. This rotation both drives the lower swing link **34** counterclockwise about the pivot **36** and drives the forward end of the backpost **48** upward. As a consequence, the backpost **48** rotates counterclockwise about the pivot **58** relative to the sequencer plate **54** (and to the seat adapter **66**, the seat frame **62** and the seat bracket **64**). Rotation of the backpost **48** and, in turn, the backrest **15**, continues until (a) the pin **48b** on the backpost **48** reaches the upper end of the slot **54a** in the sequencer plate **54** and the pin **52b** of the coupling link **52** reaches the rear end of the slot **32a** of the mounting bracket **32**. In this position, the

backrest **15** has reclined relative to the seat **13** at a greater angle than in the upright and TV positions.

It can also be seen in FIG. **4**, the locking mechanism **130** continues to prevent the chair **10** from rocking as the chair **10** moves to the fully reclined position. It can also be seen that the seat **13** rises during movement from the TV position to the fully reclined position.

The chair **10** can be returned to its TV position from the fully reclined position by the occupant operating the actuator in the reverse direction. Because of the over-center condition of the pivots **82**, **84**, **88**, the ottomans **17a**, **17b** remain extended, such that retraction of the rod **118** draws the backrest **15** to its upright position. Once the motion of the backrest **15** is complete, the over-center condition of the pivots **84**, **88** and **94** can be overcome, and the ottomans **17a**, **17b** are able to retract to the upright position.

Those skilled in this art will recognize that other variations of the chair **10** are contemplated in connection with the present invention. For example, the power unit **112** may be reversed, such that the motor **114** is at the rear end of the power unit **112** and the rod **118** is at the front end. In such a case, the rod **118** would extend forwardly relative to the base unit **11** as the chair **10** moved from the upright position to the TV position, and the motor **114** would move rearwardly relative to the base unit **11** when the chair moved from the TV position to the fully reclined position. In either instance, the front end of the power unit **112** moves relative to the base unit **11** during the movement from the upright to the TV position, and the rear end of the power unit moves relative to the base unit **11** during the movement from the TV to the fully reclined position.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as recited in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

That which is claimed is:

1. A reciprocating seating unit, comprising:

a base unit;

a generally horizontally-disposed seat positioned above the base unit;

a generally upright backrest positioned above the base unit and substantially rearward of the seat;

an extendable ottoman;

a reclining mechanism attached to the seat, the backrest, the ottoman and the base unit, the reclining mechanism comprising a plurality of pivotally interconnected links;

a reciprocating mechanism attached with the base unit and the reclining mechanism, the reciprocating mechanism configured to enable the seat, backrest and reclining mechanism to experience a longitudinally-directed reciprocating motion relative to the base unit; and

a linear actuator attached to the reclining mechanism, the linear actuator configured to move the chair between (a) an upright position, in which the seat is generally horizontally disposed, the backrest is generally vertically disposed, and the ottoman is generally vertically disposed and positioned below the seat, (b) an intermediate TV position, in which the ottoman is generally horizontally disposed in front of the seat and the backrest and the seat substantially maintain the same relationship as they have in the upright position, and (c) a fully reclined position, in which the angle between the backrest and the seat increases;

wherein the linear actuator includes first and second members that move relative to each other, and wherein the first member moves forwardly relative to the base when the seating unit moves to from the upright to the TV position, and wherein the second member moves rearwardly relative to the base when the seating unit moves from the TV position to the fully reclined position.

2. The seating unit defined in claim **1**, wherein the reclining mechanism includes a pantographic linkage on which the ottoman is mounted, and wherein in the TV and fully reclined positions, pivots between links of the pantographic linkage form a near over-center arrangement that locks the ottoman in position.

3. The seating unit defined in claim **2**, further comprising a seat adapter fixed relative to the seat, and wherein the pantographic linkage is mounted to the seat adapter.

4. The seating unit defined in claim **1**, further comprising a locking mechanism that allows the seating unit to rock while in the upright position but prevents rocking of the seating unit while in the TV and fully reclined positions.

5. The seating unit defined in claim **1**, wherein the seat rises in moving from the TV position to the fully reclined position.

* * * * *

PUBLIC VERSION

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,459,733 B2
APPLICATION NO. : 13/363641
DATED : June 11, 2013
INVENTOR(S) : Hoffman et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims:

Column 10, Claim 1, Line 28: Please correct “moves to from the upright”
to read -- moves from the upright --

Signed and Sealed this
Twentieth Day of May, 2014



Michelle K. Lee
Deputy Director of the United States Patent and Trademark Office

PUBLIC VERSION

IN THE UNITED STATES DISTRICT COURT
FOR THE MIDDLE DISTRICT OF NORTH CAROLINA

ULTRA-MEK, INC.,	)	
	)	
Plaintiff and	)	
Counter Defendant,	)	
	)	
v.	)	1:18-cv-281
	)	
UNITED FURNITURE INDUSTRIES,	)	
INC., OISEYS INTERNATIONAL,	)	
INC., MAN WAH HOLDINGS LTD.,	)	
JIANGSU YULONG SMART	)	
TECHNOLOGY CO., LTD.,	)	
REMACRO MACHINERY	)	
TECHNOLOGY CO., LTD.,	)	
TAIZHOU CHENGUANG VEHICLE CO.,	)	
LTD., and MAN WAH (USA), INC.,	)	
	)	
Defendants and	)	
Counter Claimants.	)	

CONSENT ORDER FOR PERMANENT INJUNCTION

This matter comes before the court on the Motion for Entry of Permanent Injunction on Consent, (Doc. 252), filed Plaintiff Ultra-Mek, Inc. ("Ultra-Mek"), and with the consent of Defendants United Furniture Industries, Inc., Oiseys International, Inc., Taizhou Chenguang Vehicle Co., Ltd., Man Wah (USA), Inc., Man Wah Holdings Ltd., Remacro Machinery

Technology Co., Ltd.¹, and Jiangsu Yulong Smart Technology Co., Ltd. (collectively "Defendants".) The parties have reached a confidential agreement in settlement of the dispute between them and have consented to the entry of this Permanent Injunction on Consent, based on the following stipulated findings of facts and conclusions of law. Upon agreement of the parties and for good cause shown,

IT IS HEREBY ORDERED that the parties' Motion for Entry of Permanent Injunction on Consent, (Doc. 252), is **GRANTED** and that:

FINDINGS OF FACT AND CONCLUSIONS OF LAW

1. Plaintiff Ultra-Mek, Inc. is a company organized under the laws of the State of North Carolina having its headquarters and principal place of business at 487 Bombay Road, Denton, North Carolina 27239.

2. Ultra-Mek is the owner of United States Patent No. 8,016,348 and United States Patent No. 8,297,693 (collectively "the Asserted Patents").

¹ Remacro Machinery Technology Co., Ltd. is now known as Remacro Technology Co., Ltd. and has also been formerly known or referred to as Remacro Machinery & Technology (Wujiang) Co., Ltd. and Remacro Machinery and Technology Co., Ltd. Any references herein to Remacro Machinery Technology Co., Ltd. or RMT refers to Remacro Technology Co., Ltd., its predecessors, successors, assigns, and other names, including Remacro Machinery & Technology (Wujiang) Co., Ltd. and Remacro Machinery and Technology Co., Ltd.

PUBLIC VERSION

3. United Furniture Industries, Inc. ("UFI") is a company organized under the laws of the State of Ohio with its principal place of business at 5380 Hwy 145 South, Tupelo, MS 38801. UFI is a furniture retailer that is engaged in the use, sales, offer for sale, and/or importation of various furniture items, including power-reclining rocking or reciprocating seating units.

4. Oiseys International, Inc. ("Oiseys") is a company organized under the laws of the State of North Carolina with its principal place of business at 3325 White Drive, Belden, MS 38826. Oiseys was at one time engaged in the use, sale, offer for sale, and/or importation of various furniture items, including mechanisms used in power-reclining rocking or reciprocating seating units.

5. Taizhou Chenguang Vehicle Co., Ltd. ("Taizhou") is a company organized under the laws of China with its principal place of business at No. 178, Longxiang Rd., Jiulong Industrial Park, Hailing District, Taizhou City, Jiangsu Province, China 225312. Taizhou was at one time engaged in the manufacture, use, sale, offer for sale, and/or importation of various furniture items, including mechanisms used in power-reclining rocking or reciprocating seating units.

PUBLIC VERSION

6. Man Wah (USA), Inc. ("Man Wah USA") is a company organized under the laws of the State of Nevada with its principal place of business at 308 Lindsay Street, High Point, NC 27262. Man Wah (USA) is a furniture retailer that uses, sells, offers for sale, and imports various furniture items, including power-reclining rocking or reciprocating seating units.

7. Man Wah Holdings Ltd. ("Man Wah Holdings") is a company organized under the laws of Bermuda, with a principal place of business at 1st Floor, Wah Lai Industrial Center, 10-14 Kwei Tei Street, Fotan, New Territories, Hong Kong 999077. Man Wah Holdings Ltd. is the parent company of Man Wah USA and has an ownership interest in Man Wah USA.

8. Remacro Technology Co., Ltd. f/k/a Remacro Machinery Technology, Co., Ltd., and/or Remacro Machinery & Technology (Wujiang) Co., Ltd. ("RMT") is a company organized under the laws of China with a principal place of business at No.5555, Tongjin Road, Wujiang Economic Development Zone, Suzhou, Jiangsu, China 215200. Man Wah Holdings has an ownership interest in RMT.

9. Jiangsu Yulong Smart Technology Co., Ltd. ("Yulong") is a company organized under the laws of China with a principal place of business at Building 7, No.208, Yaojia Road, Jiulong

Town, Hailing District, Taizhou City, Jiangsu Province, China 225312. RMT has an ownership interest in Yulong. Yulong makes, uses, sells, offers for sale, and/or imports various furniture items, including mechanisms used in power-reclining rocking or reciprocating seating units.

10. On April 10, 2018, Ultra-Mek commenced the above-captioned action (the "Civil Action") by filing a complaint (the "Complaint") against UFI and Oiseys. An Amended Complaint that added the remaining defendants was filed on September 24, 2018. The Amended Complaint alleged claims for patent infringement of each of the Asserted Patents as to all Defendants (Counts I and II), breach of a settlement agreement by Man Wah USA, Man Wah Holdings, and RMT (Count III), and violation of a permanent injunction order and contempt as to all Defendants (Count IV). In particular, Ultra-Mek alleges in its infringement contentions and expert reports that the manufacture, sale, offer for sale, and/or importation of two power reclining mechanisms, referenced herein as the 4152 Mechanism and the 5151 Mechanism, and chairs containing those mechanisms, infringe its patents, breach the settlement agreement, and violate the consent injunction in Ultra-Mek, Inc. v. Man Wah (USA), Inc., Case No. 1:16-cv-00041 (M.D.N.C.). Defendants filed an Answer denying liability as to

each Count, as well as counterclaims for non-infringement and invalidity of each of the Asserted Patents.

11. The parties have agreed to resolve their dispute by entry of this Permanent Injunction on Consent, as well as additional terms subject to a confidential agreement. For purposes of this Permanent Injunction and the associated motion, the Defendants agree to the findings of fact and conclusions of law and remedies set forth in this Order. Ultra-Mek has been represented by Kilpatrick Townsend & Stockton LLP, and the Defendants have been represented by Mayer Brown LLP, Arch & Lake LLP, and Ellis & Winters LLP, for purposes of the confidential agreement, this Order, and associated motion.

12. Pursuant to 28 U.S.C. §§ 1331 and 1338(a), this Court has subject matter jurisdiction over Ultra-Mek's claims against the Defendants.

13. This Court has personal jurisdiction over each of the Defendants because each of the Defendants has a principal place of business in this District, regularly does business in this District, and/or has otherwise submitted itself to the jurisdiction of this Court for purposes of this injunction.

14. Venue is proper in this District pursuant to 28 U.S.C. §§ 1391 and 1400.

PERMANENT INJUNCTION AND ORDER

Based on the parties' stipulation and agreement hereto, it is hereby **ORDERED, ADJUDGED, and DECREED** as follows:

1. The Defendants and their agents, representatives, employees, successors and assigns, and all others in active concert or participation with them, are hereby **PERMANENTLY ENJOINED, and RESTRAINED** from: (i) making, using, selling, or offering for sale in the United States, (ii) importing into the United States, and (iii) actively inducing others in the United States or contributing to others in the United States to make, use, sell, or offer for sale in the United States or to import into the United States, (a) the 4152 Mechanism or the 5151 Mechanism, or any power reclining mechanisms not colorably different therefrom, or (b) power-seating units that incorporate the 4152 Mechanism or the 5151 Mechanism, or that incorporate power reclining mechanisms not colorably different therefrom.

2. This Permanent Injunction and Order shall not apply to a power-seating unit with a reclining mechanism, or to a reclining mechanism, that is authorized by Ultra-Mek, including without limitation, authorized through the sale by Ultra-Mek's licensee, Leggett & Platt, Incorporated, of a reclining mechanism to be included or incorporated into such power-seating units.

PUBLIC VERSION

3. The Defendants acknowledge that they have knowingly and voluntarily entered into this Permanent Injunction after reviewing the same with their counsel. The Defendants understand the undertakings, obligations, and terms of this Permanent Injunction.

4. This Court shall retain jurisdiction over this matter to enforce a violation of this injunction's terms.

5. The provisions of this injunction shall apply only so long as at least one claim of the Asserted Patents remains valid and enforceable. In addition, the provisions of this injunction shall no longer be in force as of the date both of the Asserted Patents have expired.

This the 17th day of November, 2022.

William L. Osburn, Jr.
United States District Judge

IN THE UNITED STATES DISTRICT COURT
FOR THE MIDDLE DISTRICT OF NORTH CAROLINA

Ultra-Mek, Inc.,	)	
	)	
Plaintiff,	)	
	)	
v.	)	1:16CV41
	)	
Man Wah (USA), Inc.,	)	
	)	
Defendant.	)	
	)	

ENTRY OF PERMANENT INJUNCTION ON CONSENT

Plaintiff Ultra-Mek, Inc. (“Ultra-Mek”) and Defendant Man Wah (USA), Inc. (“Man Wah”), and its parent company Man Wah Holdings Ltd. and its affiliate Remacro Machinery & Technology, Co., Ltd., have reached a confidential agreement in settlement of the dispute between them and have consented to the entry of this Permanent Injunction on Consent, based on the following stipulated findings of facts and conclusions of law, which the Court hereby adopts for purposes of the entry of the Permanent Injunction.

FINDINGS OF FACT AND CONCLUSIONS OF LAW

1. Ultra-Mek is a company organized under the laws of the State of North Carolina having its headquarters and principal place of business at 487 Bombay Road, Denton, North Carolina 27239.
2. Ultra-Mek is the owner of United States Patent Number 7,997,644, United States Patent Number 8,016,348, and United States Patent Number 8,297,693 (collectively “the Asserted Patents”).

3. Man Wah is a company organized under the laws of the State of Nevada with its principal place of business at 688 North Main Street, High Point, NC 27260. Man Wah is a furniture retailer that uses, sells, offers for sale, and imports various furniture items, including power-reclining rocking, gliding, or reciprocating seating units.

4. Man Wah Holdings Ltd. is a Bermuda company, with a principal place of business at 1st Floor, Wah Lai Industrial Center, 10-14 Kwei Tei Street, Fotan, New Territories, Hong Kong. Man Wah Holdings Ltd. is the parent company of Man Wah and has an ownership interest in Man Wah.

5. Remacro Machinery & Technology, Co., Ltd., aka Remacro Machinery Technology (Wuijiang) Co., Ltd., (“RMT”), is a Peoples Republic of China company, with a principal place of business at No.5555, Tongjin Road, Wujiang Economic Development Zone, Suzhou, Jiangsu, China, 215200. RMT is an affiliate company of Man Wah, and Man Wah Holdings Ltd. has an ownership interest in RMT. RMT makes, uses, sells, offers for sale, and/or imports reclining mechanisms, including reclining mechanisms that are incorporated into Man Wah’s products.

6. On January 15, 2016, Ultra-Mek commenced the above-captioned action (the “Civil Action”) by filing a complaint (the “Complaint”) against Man Wah. The Complaint alleged claims for patent infringement of each of the Asserted Patents.

7. The parties, Man Wah Holdings Ltd., and RMT have agreed to resolve their dispute by entry of this Permanent Injunction on Consent, as well as additional terms subject to a confidential agreement. For purposes of this Permanent Injunction and the associated motion, Man Wah Holdings Ltd. and RMT agree to the findings of fact and

conclusions of law and remedies set forth in this Order. Man Wah Holdings Ltd. and RMT have been represented by Nexsen Pruet, PLLC for purposes of the confidential agreement, this Order, and associated motion.

8. Pursuant to 28 U.S.C. §§ 1331 and 1338(a), this Court has subject matter jurisdiction over Ultra-Mek's claims against Man Wah.

9. This Court has personal jurisdiction over Man Wah because Man Wah's principal place of business is in this District and has otherwise submitted itself to the jurisdiction of this Court.

10. Venue is proper in this District pursuant to 28 U.S.C. §§ 1391 and 1400.

PERMANENT INJUNCTION AND ORDER

Based on the parties' stipulation and agreement hereto, it is hereby **ORDERED, ADJUDGED, and DECREED** as follows:

1. Man Wah and its members, agents, representatives, employees, successors and assigns, and all others in active concert or participation with them, including Man Wah Holdings Ltd. and RMT, are hereby **PERMANENTLY ENJOINED, and RESTRAINED** from: (i) making, using, selling, or offering for sale in the United States, (ii) importing into the United States, and (iii) actively inducing others in the United States or contributing to others in the United States (a) to make, use, sell, or offer for sale in the United States or (b) to import into the United States the following:

- a. Power seating units (chairs, recliners, and other seating units) designated, as of or prior to the date of this Order, with product numbers, references, or names K859, K859M, K860, K861, K862, K862M, K863 (35686), K863,

K863M, K865 (2529), K865, K877M K883M, K885, K885M, K886, K887, K887M, K895M, RUK887M, XW9788, XW9788 (3512/3515), UK861M, UK863, UK863M, UK865, UK865M, UK876M, UK877M, UK881, UK881M, UK882, UK882M, UK883, UK883M, UK885, UK885M, UK887, UK887M, UK888, UK888M or UK895M, and power-seating units that have each element and perform substantially the same function in substantially the same way to yield the substantially same result as such power seating units;

- b. Power-seating units (chairs, recliners, and other seating units) that incorporate reclining mechanisms designated, as of or prior to the date of this Order, with product numbers, references, or names RMT No. 661X or RMT No. 761X, and power-seating units that incorporate reclining mechanisms that have each element and perform substantially the same function in substantially the same way to yield the substantially same result as such reclining mechanisms; and
- c. Reclining mechanisms designated, as of or prior to the date of this Order, with product numbers, references, or names RMT No. 661X or RMT No. 761X, and reclining mechanisms that have each element and perform substantially the same function in substantially the same way to yield the substantially same result as such reclining mechanisms.

2. This Permanent Injunction and Order shall not apply to a power-seating unit with a reclining mechanism, or to a reclining mechanism, that is authorized by Ultra-

Mek at Ultra-Mek's sole discretion, including without limitation, authorized through the sale by Ultra-Mek's licensee Leggett & Platt, Incorporated of a reclining mechanism to be included or incorporated into such power-seating units.

3. Ultra-Mek, Man Wah, Man Wah Holdings Ltd., and RMT acknowledge that they have knowingly and voluntarily entered into this Permanent Injunction after reviewing the same with their counsel. Ultra-Mek, Man Wah, Man Wah Holdings Ltd., and RMT understand the undertakings, obligations, and terms of this Permanent Injunction.

4. This Court shall retain jurisdiction over this matter to enforce a violation of this injunction's terms.

It is SO ORDERED, this the 17th day of March, 2017.

/s/ N. Carlton Tilley, Jr.
Senior United States District Judge

