

Exhibit 25

Claim Chart for the Practice of Independent Claims 1, 2, 40, 45, 49, 53, 67, and 68 of Complainant Vicor Corporation's United States Patent No. 10,903,734 by Vicor DCM3017S58A01C9T01 Power Module ("DCM3017") and Circuit Board Assemblies and Computing Systems Containing the Same¹


Claim 1

#	Limitation	Practice Evidence
1.pre	A method of powering a semiconductor device having power input terminals, the method comprising:	The DCM3017 practices "[a] method of powering a semiconductor device having power input terminals."

¹ The following analysis of DCM3017 is applicable to all other equivalent Vicor power modules as well as to circuit board assemblies and computing systems containing the same.

#	Limitation	Practice Evidence
		Ex. 26C at 1.

PUBLIC VERSION

#	Limitation	Practice Evidence
1.a	providing a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells,	The DCM3017 practices a method comprising “providing a power conversion module having conversion circuitry [red] arranged in a multi-cell structure having a plurality of conversion cells [blue].” 



#	Limitation	Practice Evidence
		Ex. 26C at 1. Ex. 26C at 29. Ex. 26C at 30.


#	Limitation	Practice Evidence
		Ex. 26C at 31. Ex. 26C at 28.

#	Limitation	Practice Evidence
		Ex. 26C at 26.

#	Limitation	Practice Evidence
		Ex. 26C at 27.

PUBLIC VERSION

#	Limitation	Practice Evidence
1.b	each conversion cell including one or more converter output terminals,	The DCM3017 practices a method comprising “each conversion cell including one or more converter output terminals [purple].”  Ex. 26C at 29. 

#	Limitation	Practice Evidence
		Ex. 26C at 27.  Ex. 26C at 30.  Ex. 26C at 27.


#	Limitation	Practice Evidence
		Ex. 26C at 31. Ex. 26C at 27.


#	Limitation	Practice Evidence		

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 27. <i>See also</i> 1.a.
1.c	the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage,	The DCM3017 practices a method comprising “the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage.”


#	Limitation	Practice Evidence
		Ex. 26C at 26.

#	Limitation	Practice Evidence
		 Ex. 26C at 28.
1.d	the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals	The DCM3017 practices a method comprising “the converter output terminals being arranged in a first pattern [blue] having a first spacing [yellow] between the converter output terminals.”

#	Limitation	Practice Evidence
		 Ex. 26C at 26.
1.e	providing an interconnection module having x-input terminals arranged on a first side of the interconnection module in a pattern configured to align with	The DCM3017 practices a method comprising “providing an interconnection module [purple] having x-input terminals [green] arranged on a first side [orange] of the interconnection module in a pattern configured to align with the first pattern of converter output terminals [blue].”

#	Limitation	Practice Evidence
	the first pattern of converter output terminals, and	Ex. 26C at 11.

--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 12.  Ex. 26C at 26.
1.f	x-output terminals arranged on a surface of a second opposite side	The DCM3017 practices a method comprising “x-output terminals arranged on a surface of a second opposite side [yellow] of the interconnection module in a second pattern [red] configured to align

PUBLIC VERSION

#	Limitation	Practice Evidence
	of the interconnection module in a second pattern configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals,	with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals [orange].”

#	Limitation	Practice Evidence
		Ex. 26C at 19.

#	Limitation	Practice Evidence
		Ex. 26C at 3.

#	Limitation	Practice Evidence
		Ex. 26C at 1.

#	Limitation	Practice Evidence
1.g	the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals;	The DCM3017 practices a method comprising “the second spacing [orange] being different than the first spacing [yellow], the x-input terminals [green] being electrically connected to the x-output terminals [red].”

--	--	--	--	--

PUBLIC VERSION


#	Limitation	Practice Evidence
		Ex. 26C at 19.

--	--	--	--

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 3.

--	--	--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 26.  Ex. 26C at 13.
1.h	assembling the power conversion module to the first side of the interconnection module with each converter output terminal mated with and electrically connected to a respective x-input terminal;	The DCM3017 practices a method comprising “assembling the power conversion module [red] to the first side [orange] of the interconnection module [purple] with each converter output terminal [blue] mated with and electrically connected to a respective x-input terminal [green].”

#	Limitation	Practice Evidence
		Ex. 26C at 11.

--	--	--	--

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 12.


--	--	--	--	--


#	Limitation	Practice Evidence
		Ex. 26C at 26.
1.i	wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern;	The DCM3017 practices a method comprising “wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern [blue] and the power input terminals of the semiconductor device arranged in the second pattern [red].”


#	Limitation	Practice Evidence

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 26.


#	Limitation	Practice Evidence
		

#	Limitation	Practice Evidence
		Ex. 26C at 3; <i>see also id.</i> at 14-19. 


#	Limitation	Practice Evidence
		Ex. 26C at 1.
1.j	wherein the power conversion module and the interconnection module are stacked to form a module sandwich including the power conversion module in a first layer, electrical connections between the converter output terminals and the x-input terminals in a second layer, and the interconnection module in a third layer.	The DCM3017 practices a method comprising “wherein the power conversion module [red] and the interconnection module [purple] are stacked to form a module sandwich including the power conversion module [red] in a first layer, electrical connections between the converter output terminals and the x-input terminals [green] in a second layer, and the interconnection module [purple] in a third layer.”  Ex. 26C at 11.

Claim 2

#	Limitation	Practice Evidence
2.pre	A method of powering a semiconductor device, including at least one semiconductor die having a plurality of die power	The DCM3017 practices a method comprising “[a] method of powering a semiconductor device, including at least one semiconductor die having a plurality of die power input terminals [red] arranged on a surface of the die and having edges of the semiconductor die defining a die footprint

#	Limitation	Practice Evidence
	input terminals arranged on a surface of the die and having edges of the semiconductor die defining a die footprint, the semiconductor device having power input terminals arranged within the footprint of the die, the method comprising:	[green], the semiconductor device having power input terminals arranged within the footprint of the die, the method comprising:” 

#	Limitation	Practice Evidence
		Ex. 26C at 1.


#	Limitation	Practice Evidence
		Ex. 26C at 3.  Ex. 26C at 46. <i>See also</i> 1.pre.
2.a	providing a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells,	The DCM3017 practices a method comprising “providing a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells.” <i>See</i> 1.a.

#	Limitation	Practice Evidence
2.b	each conversion cell including one or more converter output terminals,	The DCM3017 practices a method comprising “each conversion cell including one or more converter output terminals.” <i>See 1.b.</i>
2.c	the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage,	The DCM3017 practices a method comprising “the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage.” <i>See 1.c.</i>
2.d	the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals;	The DCM3017 practices a method comprising “the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals.” <i>See 1.d.</i>
2.e	providing an interconnection module having x-input terminals arranged on a first side of the interconnection module in a pattern configured to align with the first pattern of converter output terminals, and	The DCM3017 practices a method comprising “providing an interconnection module having x-input terminals arranged on a first side of the interconnection module in a pattern configured to align with the first pattern of converter output terminals.” <i>See 1.e.</i>
2.f	x-output terminals arranged on a surface of a second opposite side of the interconnection module in a second pattern arranged within the die footprint and configured to align with the power input	The DCM3017 practices a method comprising “x-output terminals [red] arranged on a surface of a second opposite side of the interconnection module in a second pattern arranged within the die footprint [green] and configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals.”

#	Limitation	Practice Evidence
	terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals,	<i>See 1.f.</i> The DCM3017 practices a method comprising “x-output terminals [red] . . . arranged within the die footprint [green].”

#	Limitation	Practice Evidence
		Ex. 26C at 19.

--	--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 3.  Ex. 26C at 45.
2.g	the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals;	The DCM3017 practices a method comprising “the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals.” <i>See</i> 1.g.

#	Limitation	Practice Evidence
2.h	assembling the power conversion module to the first side of the interconnection module with each converter output terminal mated with and electrically connected to a respective x-input terminal;	The DCM3017 practices a method comprising “assembling the power conversion module to the first side of the interconnection module with each converter output terminal mated with and electrically connected to a respective x-input terminal.” <i>See 1.h.</i>
2.i	wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern;	The DCM3017 practices a method comprising “wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern.” <i>See 1.i.</i>
2.j	wherein the power conversion module and the interconnection module are stacked to form a module sandwich including the power conversion module in a first layer, electrical connections between the converter output terminals and the x-input terminals in a second layer, and the interconnection module in a third layer.	The DCM3017 practices a method comprising “wherein the power conversion module and the interconnection module are stacked to form a module sandwich including the power conversion module in a first layer, electrical connections between the converter output terminals and the x-input terminals in a second layer, and the interconnection module in a third layer.” <i>See 1.j.</i>

Claim 40

PUBLIC VERSION

#	Limitation	Practice Evidence
40.pre	An apparatus comprising:	DCM3017 is “[a]n apparatus.” <i>See</i> 1.pre.
40.a	a semiconductor device having power input terminals;	DCM3017 is an apparatus comprising “a semiconductor device having power input terminals.” <i>See</i> 2.pre.
40.b	a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells,	DCM3017 is an apparatus comprising “a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells.” <i>See</i> 1.a.
40.c	each conversion cell including one or more converter output terminals,	DCM3017 is an apparatus comprising “each conversion cell including one or more converter output terminals.” <i>See</i> 1.b.
40.d	the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage,	DCM3017 is an apparatus comprising “the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage.” <i>See</i> 1.c.
40.e	the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals; and	DCM3017 is an apparatus comprising “the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals.” <i>See</i> 1.d.

#	Limitation	Practice Evidence
40.f	an interconnection module having x-input terminals arranged on a first surface of the interconnection module in a pattern configured to align with the first pattern of converter output terminals, and	DCM3017 is an apparatus comprising “an interconnection module having x-input terminals arranged on a first surface of the interconnection module in a pattern configured to align with the first pattern of converter output terminals.” <i>See 1.e.</i>
40.g	x-output terminals arranged on a second surface in a second pattern configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals,	DCM3017 is an apparatus comprising “x-output terminals arranged on a second surface in a second pattern configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals.” <i>See 1.f.</i>
40.h	the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals;	DCM3017 is an apparatus comprising “the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals.” <i>See 1.g.</i>
40.i	the converter output terminals of the power conversion module being mated with and electrically connected to respective x-input terminals of the interconnection module;	DCM3017 is an apparatus comprising “the converter output terminals of the power conversion module being mated with and electrically connected to respective x-input terminals of the interconnection module.” <i>See 1.h.</i>
40.j	wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input	DCM3017 is an apparatus “wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern.” <i>See 1.i.</i>


#	Limitation	Practice Evidence
	terminals of the semiconductor device arranged in the second pattern;	
40.k	wherein the power conversion module and the interconnection module are stacked with the power conversion module located at a first level, electrical connections between the converter output terminals and the x-input terminals at a second level, and the interconnection module at a third level.	DCM3017 is an apparatus “wherein the power conversion module and the interconnection module are stacked with the power conversion module located at a first level, electrical connections between the converter output terminals and the x-input terminals at a second level, and the interconnection module at a third level.” <i>See 1.j.</i>

Claim 45

#	Limitation	Practice Evidence
45.pre	A method of powering a semiconductor device having power input terminals, the method comprising:	DCM3017 practices “[a] method of powering a semiconductor device having power input terminals.” <i>See 2.pre.</i>
45.a	providing a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells,	DCM3017 practices a method comprising “providing a power conversion module having conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells.” <i>See 1.a.</i>
45.b	each conversion cell including one or more converter output terminals,	DCM3017 practices a method comprising “each conversion cell including one or more converter output terminals.”

PUBLIC VERSION

#	Limitation	Practice Evidence
		<i>See 1.b.</i>
45.c	the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage,	DCM3017 practices a method comprising “the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage.” <i>See 1.c.</i>
45.d	the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals;	DCM3017 practices a method comprising “the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals.” <i>See 1.d.</i>
45.e	providing an interconnection module having x-input terminals arranged on a first surface of the interconnection module in a pattern configured to align with the first pattern of converter output terminals, and	DCM3017 practices a method comprising “providing an interconnection module having x-input terminals arranged on a first surface of the interconnection module in a pattern configured to align with the first pattern of converter output terminals, and” <i>See 1.e.</i>
45.f	x-output terminals arranged on a second surface in a second pattern configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals,	DCM3017 practices a method comprising “x-output terminals arranged on a second surface in a second pattern configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals.” <i>See 1.f.</i>
45.g	the second spacing being different than the first spacing, the x-input terminals being	DCM3017 practices a method comprising “the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals.”

#	Limitation	Practice Evidence
	electrically connected to the x-output terminals;	<i>See</i> 1.g.
45.h	providing a plurality of conductive pillars for electrically connecting the converter output terminals with respective x-input terminals;	DCM3017 practices a method comprising “providing a plurality of conductive pillars [orange] for electrically connecting the converter output terminals [blue] with respective x-input terminals [green].”  Ex. 26C at 11.


#	Limitation	Practice Evidence
		Ex. 26C at 47.

#	Limitation	Practice Evidence

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 27.

--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 12.
45.i	assembling the power conversion module to the interconnection module with each converter output terminal aligned with and electrically connected to a respective x-input terminal by a respective one of the conductive pillars;	DCM3017 practices a method comprising “assembling the power conversion module to the interconnection module with each converter output terminal aligned with and electrically connected to a respective x-input terminal by a respective one of the conductive pillars [orange].” <i>See</i> 1.h.  Ex. 26C at 47.

#	Limitation	Practice Evidence
45.j	wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern;	DCM3017 practices a method “wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern.” <i>See 1.i.</i>
45.k	wherein the power conversion module and the interconnection module are stacked to form a module sandwich including the power conversion module in a first layer, the conductive pillars connecting the converter output terminals and the x-input terminals in a second layer, and the interconnection module in a third layer; and	DCM3017 practices a method “wherein the power conversion module and the interconnection module are stacked to form a module sandwich including the power conversion module in a first layer, the conductive pillars connecting the converter output terminals and the x-input terminals in a second layer, and the interconnection module in a third layer.” <i>See 1.j.</i>
45.l	wherein the x-output terminals are arranged with alternating polarities to reduce interconnection inductance.	DCM3017 practices a method “wherein the x-output terminals [red] are arranged with alternating polarities to reduce interconnection inductance.”

#	Limitation	Practice Evidence
		Ex. 26C at 3.

Claim 49

#	Limitation	Practice Evidence
49.pre	An apparatus comprising:	DCM3017 is “[a]n apparatus.” <i>See</i> 1.pre.
49.a	a semiconductor device, including at least one semiconductor die having a plurality of die power input terminals arranged on a surface of the die and having edges of the semiconductor die defining a die footprint, the semiconductor device having power input terminals arranged within the footprint of the die;	DCM3017 is an apparatus comprising “a semiconductor device, including at least one semiconductor die having a plurality of die power input terminals arranged on a surface of the die and having edges of the semiconductor die defining a die footprint, the semiconductor device having power input terminals arranged within the footprint of the die.” <i>See</i> 2.pre.
49.b	a power conversion module having switching power conversion circuitry arranged in a multi-cell structure having a plurality of conversion cells,	DCM3017 is an apparatus comprising “a power conversion module having switching power conversion circuitry [blue] arranged in a multi-cell structure having a plurality of conversion cells.” <i>See</i> 1.a.

#	Limitation	Practice Evidence
		Ex. 26C at 29.

#	Limitation	Practice Evidence
		Ex. 26C at 30.  Ex. 26C at 31.
49.c	each conversion cell including one or more converter output terminals,	DCM3017 is an apparatus comprising “each conversion cell including one or more converter output terminals.” <i>See</i> 1.b.
49.d	the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage,	DCM3017 is an apparatus comprising “the conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals of the plurality of conversion cells at a second lower voltage.” <i>See</i> 1.c.


#	Limitation	Practice Evidence
49.e	the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals; and	DCM3017 is an apparatus comprising “the converter output terminals being arranged in a first pattern having a first spacing between the converter output terminals.” <i>See 1.d.</i>
49.f	an interconnection module having x-input terminals arranged on a first surface of the interconnection module in a pattern configured to align with the first pattern of converter output terminals, and	DCM3017 is an apparatus comprising “an interconnection module having x-input terminals arranged on a first surface of the interconnection module in a pattern configured to align with the first pattern of converter output terminals.” <i>See 1.e.</i>
49.g	x-output terminals arranged on a second surface in a second pattern with alternating polarities configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals,	DCM3017 is an apparatus comprising “x-output terminals arranged on a second surface in a second pattern with alternating polarities configured to align with the power input terminals of the semiconductor device, the second pattern having a second spacing between x-output terminals.” <i>See 1.f; 45.l.</i>
49.h	the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals;	DCM3017 is an apparatus comprising “the second spacing being different than the first spacing, the x-input terminals being electrically connected to the x-output terminals.” <i>See 1.g.</i>
49.i	the converter output terminals of the power conversion module being mated with and electrically connected to respective x-input terminals of the interconnection module;	DCM3017 is an apparatus comprising “the converter output terminals of the power conversion module being mated with and electrically connected to respective x-input terminals of the interconnection module.” <i>See 1.h.</i>

#	Limitation	Practice Evidence
49.j	wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern;	DCM3017 is an apparatus “wherein the interconnection module is configured to provide electrical and mechanical translation between the converter output terminals arranged in the first pattern and the power input terminals of the semiconductor device arranged in the second pattern.” <i>See 1.i.</i>
49.k	wherein the power conversion module and the interconnection module are stacked with the power conversion module located at a first level, electrical connections between the converter output terminals and the x-input terminals at a second level, and the interconnection module at a third level.	DCM3017 is an apparatus “wherein the power conversion module and the interconnection module are stacked with the power conversion module located at a first level, electrical connections between the converter output terminals and the x-input terminals at a second level, and the interconnection module at a third level.” <i>See 1.j.</i>

Claim 53

#	Limitation	Practice Evidence
53.pre	An apparatus for delivering power vertically to a semiconductor die, the die having a plurality of semiconductor power input terminals arranged on a surface of the semiconductor die and having edges of the	DCM3017 is “[a]n apparatus for delivering power vertically to a semiconductor die, the die having a plurality of semiconductor power input terminals arranged on a surface of the semiconductor die and having edges of the semiconductor die defining a die footprint.” <i>See 2.pre.</i> DCM3017 is “[a]n apparatus for delivering power vertically to a semiconductor die.”

#	Limitation	Practice Evidence
	semiconductor die defining a die footprint, the apparatus comprising:	Ex. 26C at 11.

#	Limitation	Practice Evidence
		 Ex. 26C at 11.
53.a	switching power conversion circuitry arranged on a first substrate having a plurality of switching power conversion cells and a plurality of converter output terminals,	DCM3017 is an apparatus comprising “switching power conversion circuitry arranged on a first substrate having a plurality of switching power conversion cells and a plurality of converter output terminals.” <i>See</i> 49.b, 1.a, 1.b. DCM3017 is an apparatus comprising “switching power conversion circuitry arranged on a first substrate [blue].”


#	Limitation	Practice Evidence
		Ex. 26C at 26.

PUBLIC VERSION


#	Limitation	Practice Evidence
53.b	the switching power conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals at a second lower voltage;	DCM3017 is an apparatus comprising “the switching power conversion circuitry being configured to convert power received at a first voltage for delivery via the converter output terminals at a second lower voltage.” <i>See 1.c.</i>
53.c	translation interconnections including X-input terminals configured and arranged to align with and electrically connect to the converter output terminals,	DCM3017 is an apparatus comprising “translation interconnections including X-input terminals configured and arranged to align with and electrically connect to the converter output terminals.” <i>See 1.e.</i>
53.d	a plurality of X-output terminals configured and arranged with alternating polarities to align with respective power input terminals of the semiconductor die, and	DCM3017 is an apparatus comprising “a plurality of X-output terminals configured and arranged with alternating polarities to align with respective power input terminals of the semiconductor die.” <i>See 1.f, 45.l.</i>
53.e	a plurality of vertical conductors to make electrical connections to the X-output terminals;	DCM3017 is an apparatus comprising “a plurality of vertical conductors to make electrical connections to the X-output terminals.”

#	Limitation	Practice Evidence
		Ex. 26C at 3 (x-output terminals matching the pattern of the input terminals of the semiconductor device); <i>see also id.</i> at 13-18 (depicting the vertical connections through the layers).

#	Limitation	Practice Evidence
		Ex. 26C at 1.

#	Limitation	Practice Evidence
53.f	a capacitive array arranged between the power conversion circuitry and the semiconductor die and electrically connected to the translation interconnections to provide energy storage;	DCM3017 is an apparatus comprising “a capacitive array [blue] arranged between the power conversion circuitry [red] and the semiconductor die [green] and electrically connected to the translation interconnections [purple] to provide energy storage.”  Ex. 26C at 11.

#	Limitation	Practice Evidence
		Ex. 26C at 13.

#	Limitation	Practice Evidence
		 Ex. 26C at 46.
53.g	wherein the translation interconnections are configured to provide electrical and mechanical translation between the converter output terminals and the power input terminals of the semiconductor die;	DCM3017 is an apparatus “wherein the translation interconnections are configured to provide electrical and mechanical translation between the converter output terminals and the power input terminals of the semiconductor die.” <i>See</i> 1.i.
53.h	wherein the switching power conversion circuitry, the translation interconnections, and the capacitive array, are each	DCM3017 is an apparatus “wherein the switching power conversion circuitry [red], the translation interconnections [purple], and the capacitive array [blue], are each configured and arranged within a respective footprint configured to occupy substantially all of the die footprint [green], and are

PUBLIC VERSION


#	Limitation	Practice Evidence
	configured and arranged within a respective footprint configured to occupy substantially all of the die footprint, and are together configured and arranged to form a vertical stack configured to occupy substantially all of the die footprint.	together configured and arranged to form a vertical stack configured to occupy substantially all of the die footprint [green].”

--	--	--	--	--

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 26.

--	--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 27.  Ex. 26C at 19.

--	--	--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 12. Ex. 26C at 11.

#	Limitation	Practice Evidence
		Ex. 26C at 45. Ex. 26C at 1.


Claim 67

#	Limitation	Practice Evidence
67.pre	A vertical power delivery apparatus for a semiconductor die, the semiconductor die having a plurality of semiconductor power input terminals arranged on a surface of the semiconductor die and having edges of the semiconductor die defining a die footprint;	DCM3017 is “[a] vertical power delivery apparatus for a semiconductor die, the semiconductor die having a plurality of semiconductor power input terminals arranged on a surface of the semiconductor die and having edges of the semiconductor die defining a die footprint.” <i>See</i> 53.pre.
67.a	the vertical power delivery apparatus comprising in a vertical stack configured to occupy, in whole or in part, the die footprint, the vertical stack comprising:	DCM3017 is “the vertical power delivery apparatus comprising in a vertical stack configured to occupy, in whole or in part, the die footprint [green].”

--	--	--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 11. Ex. 26C at 11.

#	Limitation	Practice Evidence
		Ex. 26C at 45. Ex. 26C at 1.
67.b	(a) point-of-load (“POL”) switching power conversion	DCM3017 is an apparatus comprising “(a) point-of-load (“POL”) switching power conversion circuitry (i) arranged on a substrate within a conversion footprint [purple], (ii) including a plurality of

#	Limitation	Practice Evidence
	circuitry (i) arranged on a substrate within a conversion footprint, (ii) including a plurality of switching power conversion cells connected in parallel to convert power from an input at an input voltage for delivery to the semiconductor power input terminals at a die voltage,	switching power conversion cells [blue] connected in parallel to convert power from an input at an input voltage for delivery to the semiconductor power input terminals at a die voltage.”  Ex. 26C at 1.

#	Limitation	Practice Evidence
		Ex. 26C at 28.

#	Limitation	Practice Evidence		

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 26.

--	--	--	--	--

PUBLIC VERSION

#	Limitation	Practice Evidence
		Ex. 26C at 27. <i>See also</i> 1.c, 49.b.
67.c	(iii) the input voltage being at least five times higher than the die voltage, and (iv) the conversion footprint being configured to occupy, in whole or in part, the die footprint;	DCM3017 is an apparatus comprising “(iii) the input voltage being at least five times higher than the die voltage, and (iv) the conversion footprint [purple] being configured to occupy, in whole or in part, the die footprint [green].”

#	Limitation	Practice Evidence
		Ex. 26C at 1.

#	Limitation	Practice Evidence
		Ex. 26C at 28.

#	Limitation	Practice Evidence
		Ex. 26C at 26.



#	Limitation	Practice Evidence
		Ex. 26C at 27.


#	Limitation	Practice Evidence
		Ex. 26C at 45. Ex. 26C at 1.
67.d	(b) interdigitated output terminals (i) electrically connected to receive power from the switching power conversion cells, (ii) configured within a terminal	DCM3017 is an apparatus comprising “(b) interdigitated output terminals (i) electrically connected to receive power from the switching power conversion cells, (ii) configured within a terminal footprint to match the plurality of semiconductor power input terminals, (iii) the terminal footprint being configured to occupy, in whole or in part, the die footprint.”

PUBLIC VERSION

#	Limitation	Practice Evidence
	footprint to match the plurality of semiconductor power input terminals, (iii) the terminal footprint being configured to occupy, in whole or in part, the die footprint; and	<i>See</i> 1.i, 45.1. DCM3017 is an apparatus comprising “(b) interdigitated output terminals . . . configured within a terminal footprint [red] . . . (iii) the terminal footprint being configured to occupy, in whole or in part, the die footprint [green].”

--	--	--	--	--

#	Limitation	Practice Evidence
		Ex. 26C at 3.  Ex. 26C at 45.  Ex. 26C at 1.
67.e	(c) a capacitive array (i) arranged between the power conversion circuitry and the semiconductor	DCM3017 is an apparatus comprising “(c) a capacitive array [blue] (i) arranged between the power conversion circuitry [red] and the semiconductor die, (ii) within a filter footprint [dark red]

#	Limitation	Practice Evidence
	die, (ii) within a filter footprint configured to occupy, in whole or in part, the die footprint and (iii) electrically connected to the interdigitated output terminals.	configured to occupy, in whole or in part, the die footprint [green] and (iii) electrically connected to the interdigitated output terminals.”  Ex. 26C at 11.

#	Limitation	Practice Evidence

#	Limitation	Practice Evidence
		Ex. 26C at 12. Ex. 26C at 45. Ex. 26C at 1.

#	Limitation	Practice Evidence
		<i>See 45.l, 53.f, 53.g.</i>

Claim 68

#	Limitation	Practice Evidence
68.pre	A vertical power delivery apparatus for a semiconductor die, the semiconductor die having a plurality of semiconductor power input terminals arranged on a surface of the semiconductor die and having edges of the semiconductor die defining a die footprint;	DCM3017 comprises “[a] vertical power delivery apparatus for a semiconductor die, the semiconductor die having a plurality of semiconductor power input terminals arranged on a surface of the semiconductor die and having edges of the semiconductor die defining a die footprint.” <i>See 67.pre.</i>
68.a	the vertical power delivery apparatus comprising in a vertical stack configured to occupy, in whole or in part, the die footprint, the vertical stack comprising:	DCM3017 comprises “the vertical power delivery apparatus comprising in a vertical stack configured to occupy, in whole or in part, the die footprint.” <i>See 67.a.</i>
68.b	(a) point-of-load (“POL”) switching power conversion circuitry (i) arranged on a substrate within a conversion footprint, (ii) including a plurality of switching power conversion cells connected in parallel to convert power from an input at an input voltage to the	DCM3017 is an apparatus comprising “(a) point-of-load (“POL”) switching power conversion circuitry (i) arranged on a substrate within a conversion footprint, (ii) including a plurality of switching power conversion cells connected in parallel to convert power from an input at an input voltage to the semiconductor power input terminals at a die voltage.” <i>See 67.b.</i>

PUBLIC VERSION

#	Limitation	Practice Evidence
	semiconductor power input terminals at a die voltage,	
68.c	(iii) the input voltage being at least five times higher than the die voltage, (iv) the conversion footprint being configured to occupy, in whole or in part, the die footprint;	DCM3017 is an apparatus comprising “(iii) the input voltage being at least five times higher than the die voltage, (iv) the conversion footprint being configured to occupy, in whole or in part, the die footprint.” <i>See 67.c.</i>
68.d	(b) interdigitated output terminals (i) electrically connected to receive power from the switching power conversion cells, (ii) configured within a terminal footprint to match the plurality of semiconductor power input terminals, (iii) the terminal footprint being configured to occupy, in whole or in part, the die footprint;	DCM3017 is an apparatus comprising “(b) interdigitated output terminals (i) electrically connected to receive power from the switching power conversion cells, (ii) configured within a terminal footprint to match the plurality of semiconductor power input terminals, (iii) the terminal footprint being configured to occupy, in whole or in part, the die footprint.” <i>See 67.d.</i>
68.e	(c) a capacitive array (i) arranged between the power conversion circuitry and the semiconductor die, (ii) within a filter footprint configured to occupy, in whole or in part, the die footprint, and (iii) electrically connected to the interdigitated output terminals; and	DCM3017 is an apparatus comprising “(c) a capacitive array (i) arranged between the power conversion circuitry and the semiconductor die, (ii) within a filter footprint configured to occupy, in whole or in part, the die footprint, and (iii) electrically connected to the interdigitated output terminals.” <i>See 68.e.</i>
68.f	(d) a plurality of vertical conductors arranged within the die footprint to connect the	DCM3017 is an apparatus comprising “(d) a plurality of vertical conductors arranged within the die footprint to connect the interdigitated output terminals to the switching power conversion cells.”

PUBLIC VERSION

#	Limitation	Practice Evidence
	interdigitated output terminals to the switching power conversion cells.	<i>See</i> 45.l, 53.c, 53.e, 53.h.