


Oct.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




NOTE 1 LEAD CO-PLANARITY SHALL BE 0.1 MAX
2 PIN ASSIGNMENT
3 PACKING QUANTITY : 1600 PCS/REEL

△數 COUNT	訂正事項 DISCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE	△數 COUNT	訂正事項 DISCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE
1	- Revised	LSH	LHJ	18. 04. 09	1				
2	- Revised	LSH	LHJ	18. 06. 12	2				
△					△				

7	COVER TAPE	PET	-	-
6	EMBOSS TAPE	PS	-	-
5	MAIN SHELL	STAINLESS STEEL	Ni1.25μm MIN	-
4	CONTACT 2nd	COPPER ALLOY	△Contact Area : Au0.05μm MIN OVER Pd-Ni0.75μm MIN OVER Ni2.0μm MIN Lead Area : Au0.05μm MIN OVER Ni2.0μm MIN	-
3	CONTACT 1st			-
2	MID PLATE	STAINLESS STEEL	Ni1.0μm MIN	-
1	INSULATOR	THERMOPLASTIC	UL94V-0, BLACK COLOR	-
NO.	DESCRIPTION	MATERIAL	FINISH	REMARKS
CODE NO. (OLD)		DRAWN S.Y.PARK 17.11.14	DESIGNED S.Y.PARK 17.11.14	CHECKED H.J.LEE 17.11.14
		APPROVED T.S.KANG 17.11.14		RELEASED ENG 18.06.15 DEPT
DRAWING NO. EDC3-632317		PART NO. CX90M-16P		
SCALE 5:1 UNITS mm		CODE NO CL 6240-0008-8		1/2

Oct.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[CX90M-16P](#)