

# Week-6: Code-along

Phua Zong Yao

2023-09-12

## II. Code to edit and execute using the Code-along-6.Rmd file

### A. for loop

#### 1. Simple for loop (Slide #6)

```
# Enter code here

for(x in c(3,6,9)) {

  print(x)

}
```

```
## [1] 3
## [1] 6
## [1] 9
```

#### 2. for loops structure (Slide #7)

```
# Left-hand side code: for Loop for passing values

for (x in 1:8) {

  print(x)

}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
## [1] 5
## [1] 6
## [1] 7
## [1] 8
```

```
# Right-hand side code: for loop for passing indices
```

```
for (x in 1:8)
  {y <- seq(from=100,to=200,by=5)
  print(y[x])}
```

```
## [1] 100
## [1] 105
## [1] 110
## [1] 115
## [1] 120
## [1] 125
## [1] 130
## [1] 135
```

### 3. Example: find sample means (Slide #9)

```
# Enter code here
```

```
# 1. determine what to loop over
sample_sizes <- c(5,10,15,20,25000)

# 2. pre-allocate space to store output
sample_means <- double(length(sample_sizes))

for(i in seq_along(sample_sizes)) {
  sample_means[i] <- mean(rnorm(sample_sizes)[i])
}

sample_means
```

```
## [1] 1.2477222 3.2439299 -1.8252047 0.7494137 0.3708245
```

### 4. Alternate ways to pre-allocate space (Slide #12)

```
# Example 3 for data_type=double
```

```
sample_means <- rep(0,length(sample_sizes))
```

```
# Initialisation of data_list
```

```
data_list <- vector("list",length = 5)
```

## 5. Review: Vectorized operations (Slide #18)

```
# Example: bad idea!
# Vector with numbers from 7 to 11
a <- 7:11
# Vector with numbers from 8 to 12
b <- 8:12
# Vector of all zeros of length 5
out <- rep(0L,5)
# Loop along the length of vector a
for(i in seq_along(a)){
  # Each entry of out is the sum of the corresponding
  out[i] <- a[i] + b[i]
}

out
```

```
## [1] 15 17 19 21 23
```

```
# Taking advantage of vectorization

a <- 7:11
b <- 8:12
out <- a+b
out
```

```
## [1] 15 17 19 21 23
```

## B. Functionals

### 6. for loops vs Functionals (Slides #23 and #24)

*# Slide 23*

```
# Initialise a vector with the size of 5 different samples
sample_sizes <- c(5,10,15,25000)
# Create a functional- function inside a function
sample_summary <- function(sample_sizes,fun){
  # Initialise a vector of the same size as sample_sizes
  out <- vector("double", length(sample_sizes))
  # Run the for loop for as long as the length of sample_sizes
  for (i in seq_along(sample_sizes)) {
    # Perform operations indicated fun
    out[i] <- fun(rnorm(sample_sizes[i]))
  }
  return(out)
}
```

*# Slide 24*

```
#Compute mean
sample_summary(sample_sizes,mean)
```

```
## [1] -0.551836001  0.694319482 -0.284991889  0.006140631
```

```
# Compute median
sample_summary(sample_sizes,median)
```

```
## [1] -0.2118435255  0.0570140641  0.1725811418  0.0001547835
```

```
# Compute sd
sample_summary(sample_sizes, sd)
```

```
## [1] 0.6175202 0.7102996 1.2797624 1.0010314
```

## C. while loop

### 7. while loop (Slides #27)

```
# Left-hand side code: for Loop
for(i in 1:5){
  print(i)
}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
## [1] 5
```

```
# Right-hand side code: while loop
```

```
i <- 1
while(i <= 5){
  # body
  print(i)
  i <- i + 1
}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
## [1] 5
```