

291K

Deep Learning for Machine Translation
Recurrent Neural Network
Sequence to sequence learning

Lei Li

UCSB

10/4/2021

Outline

- Language Modeling
- Recurrent Neural Network
- Long-short term memory network (LSTM)
- Gated Recurrent Unit (GRU)
- Attention
- Encoder-decoder framework
- LSTM Seq2seq

Language Modeling

- Given a sentence y , estimate the probability

$$P(y) = \prod_t P(y_{t+1} | y_1 \dots y_t)$$

						$p(y_6 y_1, \dots, y_5)$	
$- P(y_{t+1} y_1 \dots y_t) = f_\theta(y_1, \dots, y_t)$						mat	0.15
						rug	0.13
The cat sits on a ____						chair	0.08
y_1	y_2	y_3	y_4	y_5	y_6	hat	0.05
						dog	0.01

Predict Next Token Probability

There are many methods to predict the next token:

- N-gram: assuming $p(x_t \mid x_1, \dots, x_{t-1}) = p(x_t \mid x_{t-k}, \dots, x_{t-1})$, and estimate it directly
- Context MLP: use DNN to estimate $p(x_t \mid x_{t-k}, \dots, x_{t-1})$
- CNN-LM (previous lecture)
- RNN-LM, LSTM, GRU
- GPT

CNN Language Model (recap)


$$P(y_{t+1} | y_1, \dots, y_t) \approx \text{CNN}_{\theta}(y_{t-k}, \dots, y_t)$$

predict the next token

But,
limited context

No pooling between convolutions: do not want to lose positional information

Padding to shift tokens: we need to prevent information flow from future tokens



condition on the previous tokens

Limitation of CNN-LM

- CNN-LM only has a fixed-length receptive field
 - probability of next token only dependent on a fixed-size context
- But sentences are of variable length
- How to handle sentences with variable length?
- Idea:
 - adding memory to network
 - adaptive updating memory

Recurrent Memory

- Introduce memory representation
- RNN-LM: use RNN to estimate

$$p(x_t \mid x_1, \dots, x_{t-1}) = \text{softmax}(W \cdot h_t)$$


$$h_t = \text{RNN}(h_{t-1}, \text{Emb}(x_{t-1}))$$

- RNN cell can be
 - Simple feedforward neural network
 - Long-short term memory
 - Gated recurrent units

Recurrent Neural Network

$$p(x_t | x_1, \dots, x_{t-1}) = \text{softmax}(U \cdot h_t)$$

$$h_t = \sigma \left(W \cdot \begin{bmatrix} h_{t-1} \\ x_t \end{bmatrix} + b \right)$$



Training RNN-LM

- Risk:
 - Loss: cross-entropy for every next-token given prefix context
 - $\text{CE}(x_{t+1}, f(x_1, \dots, x_t))$
- SGD
 - Calculate gradient: Back-propagation through time (BPTT)
 - ∇E_t


Exercise: Gradient for RNN

Back-propagation for RNN (python)

```
1 def bptt(self, x, y):
2     T = len(y)
3     # Perform forward propagation
4     o, s = self.forward_propagation(x)
5     # We accumulate the gradients in these variables
6     dLdU = np.zeros(self.U.shape)
7     dLdV = np.zeros(self.V.shape)
8     dLdW = np.zeros(self.W.shape)
9     delta_o = 0
10    delta_o[np.arange(len(y)), y] -= 1.
11    # For each output backwards...
12    for t in np.arange(T)[::-1]:
13        dLdV += np.outer(delta_o[t], s[t].T)
14        # Initial delta calculation: dL/dz
15        delta_t = self.V.T.dot(delta_o[t]) * (1 - (s[t] ** 2))
16        # Backpropagation through time (for at most self.bptt_truncate steps)
17        for bptt_step in np.arange(max(0, t-self.bptt_truncate), t+1)[::-1]:
18            # Add to gradients at each previous step
19            dLdW += np.outer(delta_t, s[bptt_step-1])
20            dLdU[:,x[bptt_step]] += delta_t
21            # Update delta for next step dL/dz at t-1
22            delta_t = self.W.T.dot(delta_t) * (1 - s[bptt_step-1] ** 2)
23    return [dLdU, dLdV, dLdW]
```


Computational Issue: Gradient Vanishing

- \tanh has derivative close to zero at both ends




Gradient Exploding

- Use gradient clipping
- Two options: clip by absolute value or rescale norm
- if $|g| > \eta$, $\hat{g} \leftarrow \eta$
- if $|g| > \eta$, $\hat{g} \leftarrow \frac{\eta}{|g|} g$



Long-Short Term Memory (LSTM)

- Replace cell with more advanced one
- Adaptively memorize short and long term information



$$i_{t+1} = \sigma(M_{ix}x_{t+1} + M_{ih}h_t + b_i)$$

$$f_{t+1} = \sigma(M_{fx}x_{t+1} + M_{fh}h_t + b_f)$$

$$o_{t+1} = \sigma(M_{ox}x_{t+1} + M_{oh}h_t + b_o)$$


$$a_{t+1} = \tanh(M_{cx}x_{t+1} + M_{ch}h_t + b_a)$$

$$c_{t+1} = f_{t+1} \otimes c_t + i_{t+1} \otimes a_{t+1}$$

$$h_{t+1} = o_{t+1} \otimes \tanh(c_{t+1})$$

Gated Recurrent Unit (GRU)

- Adaptively memorize short and long term information
- like LSTM, but fewer parameters



Input: x_t

Memory: h_t

$$r_{t+1} = \sigma(M_{rx}x_{t+1} + M_{rh}h_t + b_r)$$

$$z_{t+1} = \sigma(M_{zx}x_{t+1} + M_{zh}h_t + b_z)$$

$$\tilde{h}_{t+1} = \tanh(M_{hx}x_{t+1} + M_{hh}(r_{t+1} \otimes h_t) + b_h)$$


$$h_{t+1} = z_{t+1} \otimes \tilde{h}_{t+1} + (1 - z_{t+1}) \otimes h_t$$

Expressive power of RNN-LM

$$\text{Perplexity: } PPL = P(x_1, \dots, x_N)^{-\frac{1}{N}} = \exp\left(-\frac{1}{N} \sum_{n=1}^N \log P(x_n | x_1 \dots x_{n-1})\right)$$


MODEL	TEST PERPLEXITY	NUMBER OF PARAMS [BILLIONS]
SIGMOID-RNN-2048 (JI ET AL., 2015A)	68.3	4.1
INTERPOLATED KN 5-GRAM, 1.1B N-GRAMS (CHELBA ET AL., 2013)	67.6	1.76
SPARSE NON-NEGATIVE MATRIX LM (SHAZEER ET AL., 2015)	52.9	33
RNN-1024 + MAXENT 9-GRAM FEATURES (CHELBA ET AL., 2013)	51.3	20
LSTM-512-512	54.1	0.82
LSTM-1024-512	48.2	0.82
LSTM-2048-512	43.7	0.83
LSTM-8192-2048 (NO DROPOUT)	37.9	3.3
LSTM-8192-2048 (50% DROPOUT)	32.2	3.3
2-LAYER LSTM-8192-1024 (BIG LSTM)	30.6	1.8
BIG LSTM+CNN INPUTS	30.0	1.04
BIG LSTM+CNN INPUTS + CNN SOFTMAX	39.8	0.29
BIG LSTM+CNN INPUTS + CNN SOFTMAX + 128-DIM CORRECTION	35.8	0.39
BIG LSTM+CNN INPUTS + CHAR LSTM PREDICTIONS	47.9	0.23

Attention



Generation by Attention

A **context vector c** will be predicted before, which represents the related source context for current predicted word.




$$\alpha_{nj} = \text{Softmax}(D(s_n, h_{1..n-1})) = \frac{\exp(D(s_n, h_j))}{\sum_k \exp(D(s_n, h_k))}$$

$$c_n = \sum_j \alpha_{nj} h_j$$

The probability of word y_i is computed as:

$$p(y_i) \propto \exp(Wh_i) \Rightarrow p(y_i) \propto \exp(Wh_i + Vc_i)$$

Encoder-decoder framework




A generic formulation

- ImageCaption
- Text-to-Image Generation
- ASR (speech-to-text)
- MT (text-to-text)

Sequence To Sequence (Seq2seq)

- Machine translation as directly learning a function mapping from source sequence to target sequence



$$P(Y|X) = \prod P(y_t | y_{<t}, x)$$


Training loss: Cross-Entropy

$$l = - \sum_n \sum_t \log f_{\theta}(x_n, y_{n,1}, \dots, y_{n,t-1})$$

Teacher-forcing during training.

(pretend to know groundtruth for prefix)

Performance (2014)




Sutskever et al. Sequence to Sequence Learning with Neural Networks. 2014


Durrani et al. Edinburgh's Phrase-based Machine Translation Systems for WMT-14. 2014

Stacked LSTM for seq-2-seq


- More layers of LSTM




LSTM Seq2seq with Attention



LSTM Seq2Seq w/ Attention



Performance with Model Ensemble



Reading

- Gers et al. Learning to Forget: Continual Prediction with LSTM. 2000
- Sutskever et al. Sequence to Sequence Learning with Neural Networks. 2014
- Bahdanau et al., Neural Machine Translation by Jointly Learning to Align and Translate. 2015
- Luong et al. Effective Approaches to Attention-based Neural Machine Translation. 2015