Weather Planner

CSU44000 Internet Applications – Assignment 1 Liliana Berenguer Jin

1. Requirements

Weather Planner is a small reactive Internet Application that takes a destination city and tells the traveller what to pack. The client runs in the browser using Vue 3. It talks to a Node.js / Express server, which does the actual work: it calls OpenWeather, reduces what comes back into a short summary, and returns that as one JSON object for the page to display. The calls to OpenWeather have to live on the server because of the browser's same-origin policy, and it keeps the API key out of the client anyway.

Before writing any code, I listed the core requirements from the assignment and matched each one to the OpenWeather API that could provide the data. This gave me a starting point for how to structure the server and, more importantly, what the client would never need to know about. Table 1 is what I ended up with.

Table 1 – Requirements and the OpenWeather API used for each

Requirement	OpenWeather API	What it provides
Turn the city name into a location	Geocoding (`/geo/1.0/direct`)	Latitude and longitude
Three-day table of temperature, wind speed and rainfall	5-day / 3-hour Forecast (`/data/2.5/forecast`)	Around 40 readings at three-hour intervals
Umbrella if rain is forecast; Cold / Mild / Hot packing advice (below 8 °C, 8–24 °C, above 24 °C)	Forecast (same response)	Rain and temperature per reading
Warning for each pollutant above the "Good" level, with its level and health risk	Air Pollution (`/data/2.5/air_pollution`)	AQI (1–5) and the concentration of each pollutant
Compare two cities side by side (extra feature)	All of the above, twice	Two summaries plus a verdict

One thing the table made obvious is the order of the requests: Geocoding has to go first, since the other two APIs want coordinates rather than a name.

2. System architecture




Figure 1 – System architecture. The browser loads the page from Express and then sends it a city through one of the two routes. Express calls `getWeatherForCity`, which asks OpenWeather for the location, the forecast and the air quality, builds the summary, and returns it to the browser as JSON. For a comparison the same function runs twice.

Some main observations:

- The route handlers only deal with HTTP. They read and validate the query string and turn errors into status codes. Everything else happens in `getWeatherForCity`, which fetches and processes the data for one city. Both routes call it, so when I added the comparison feature I did not have to duplicate the lookup. The helpers below it (`makeDailySummaries`, `makePackingAdvice`, `makeAirQualitySummary`) contain the rules and have no idea they are inside a web server.
- The server is stateless. Both routes are plain `GET` requests, there are no sessions and nothing is stored between calls, so the same request always gives the same answer. This was the simplest option and it also made the server easy to test on its own, by opening the route in the browser with a city in the URL.
- The client follows the MVC paradigm: the JSON from the server is the model, the HTML template is the view, and the Vue instance holding the data and methods is the controller. There is no manual DOM manipulation: the template describes what each state should look like and Vue updates the DOM when the data changes.
- I kept dependencies to a minimum. Node 22 already has `fetch` and can load `.env` itself, and Vue comes from a CDN, so the project only installs Express and nothing needs to be built before running it.

3. Design process

I found myself building the server in three iterations, each one answering a different question: first, can I get anything out of OpenWeather at all; then, what do I do with what comes back; and finally, what goes wrong once I try it with real cities. The client went through two.

3.1 Server

Iteration 1: the first version just called OpenWeather and passed the response straight through. It took the city from the query string, called Geocoding to get the coordinates, called Forecast with them, and returned the raw readings exactly as OpenWeather sent them, with nothing processed and no error handling. Two things came out of this:

- Getting `async/await` right with two requests where the second depends on the first. `fetch` returns a promise, and while the server waits for OpenWeather to reply, `await` lets the event loop carry on handling other requests instead of blocking on the one thread Node has.

- Understanding the Forecast response. OpenWeather does not return "days"; it returns a `list` of about forty entries, one every three hours, each with its own `main.temp`, `wind.speed` and `rain` values. So to show three days I would have to group those entries myself. Looking through them also showed that the timestamps are in UTC, that `rain["3h"]` is missing when it did not rain, and that the response includes a `city.timezone` offset. These were the motivations for what to do with the response in iteration 2.

Iteration 2: this is where the core features got mostly done:

- The three-hourly entries in `list` are grouped by date, and for each day the server computes the min, max and average of `main.temp`, the average `wind.speed`, the total `rain["3h"]` and whether rain is expected.
- The Cold / Mild / Hot thresholds from the brief are applied to each day's average. If the three days fall into different categories the advice becomes "pack layers". The umbrella flag, on the other hand, is set if any day expects rain.
- The Air Pollution call was added. Each pollutant is compared with the upper limit of OpenWeather's "Good" band, and anything above it is reported with its band and a short health risk.
- The route now validates the city it receives from the client and replies with a proper HTTP status code when something goes wrong (Table 2), so the client can show a sensible message instead of a generic failure. A small `getOpenWeatherJson` helper wraps `fetch` and throws an error carrying a status when the network fails or OpenWeather replies with an error, which keeps the route handler readable.

Table 2 – Responses from `GET /api/weather`

Status	Condition
200	Success: `city`, `today`, `days[3]`, `packing`, `airQuality`
400	City missing or over 100 characters
404	Geocoding returns no match
500	API key missing from `.env`
502	OpenWeather unreachable, returned an error, or returned too little data

Iteration 3: testing with more cities and at different times of day exposed three problems, each of which changed the code:

- *The first day was wrong.* Searching in the evening produced a "day" with one or two readings, and for Tokyo the grouping landed on the wrong date because I was grouping by UTC. Each reading is now shifted by `city.timezone` before its date is taken, the current partial day is shown separately as "today", and the table shows the next three full local days.
- *One failing API took down the page.* When Air Pollution returned an error, the forecast was lost as well. That call now sits in its own `try/catch` and returns `{ available: false }` on failure, so the forecast still renders with a note.
- *The route handler had grown too large.* Everything lived inside one `app.get`. I moved the lookup into `getWeatherForCity(city)`, which throws errors tagged with a status and a message that the route simply passes on. This refactor is what made the comparison feature cheap to add.




Figure 2 – Sequence of one search against the final server

3.2 Client

Iteration 1: one input, one button and the raw response in a `<pre>` element: `v-model` on the input, a method calling `fetch`, and `{{ result }}` in the template. Its only purpose was to prove the round trip.

Iteration 2: the final client keeps that skeleton, but the whole page is derived from a handful of reactive variables: `city`, `loading`, `result` and `error`. The template declares what each state looks like and Vue updates the DOM when the variables change; I never manipulate the DOM directly. Compared with the `XMLHttpRequest` approach of locating an element and setting its `innerHTML`, it removes an entire category of bugs where the page and the data disagree.

Table 3 – Vue features used in the client

Feature	Used for
`v-model.trim`	Two-way binding on both city inputs
`@submit.prevent`	Running the search without a page reload
`:disabled`	Blocking buttons while a request is in flight
`v-if` / `v-else-if` / `v-else`	Loading, error, empty and result panels
`v-for` with `:key`	Forecast rows, pollutant warnings, comparison cards
`:class`	Colour badges for Cold / Mild / Hot, umbrella, AQI, "better forecast"
`{{ }}`	All text output
`computed`	`cityLabel` from city, state and country

Feature	Used for
`methods`	Fetch calls and formatting helpers

`searchWeather` calls `fetch` inside `try / catch / finally`, so `loading` is always reset. A shared `readJsonResponse` helper parses the reply and throws the server's error message when the status is not OK, so the search and the comparison handle failures identically, each showing the message with a Retry button.

For the layout, today's summary sits on the left and the forecast table, packing advice and air quality on the right. Weather icons come from an SVG sprite mapped from OpenWeather's icon codes, and on narrow screens the table collapses into stacked cards.

Figure 3 – Result view for Dublin *(screenshot)*

3.3 Iteration 3 – comparing two destinations

Once a city is loaded, the user can enter a second one and see both forecasts side by side with a short verdict: which has the better weather, which needs an umbrella, and which has worse air. I chose this feature because deciding between places is the real reason someone would open the app, and it required non-trivial work on both sides.

- **Server.** A second route, `GET /api/compare?cities=A&cities=B`. It accepts repeated parameters so that names with country codes ("Dublin, IE") are not split on the comma. It runs `getWeatherForCity` for both cities with `Promise.all`, so the two lookups proceed concurrently rather than one after the other. `makeCityComparison` then ranks them: fewer rainy days wins, more Mild days breaks a tie, and the worse AQI is flagged. The verdict text is composed on the server so the wording stays consistent.
- **Client.** A second form bound to `comparisonCity`, with its own `comparing` and `comparisonError` state so it never interferes with the main search, and a `v-for` over the two results rendering a card each, with the winner highlighted through `:class`.

Figure 4 – Dublin compared with Lisbon *(screenshot)*

4. Testing, limitations and future work

I tested manually against a checklist: a known city (Dublin, IE), an ambiguous one (Paris vs Paris, US), a made-up city, a missing API key, the Air Pollution URL deliberately broken, Tokyo for the local-date grouping, and a comparison with one invalid city to confirm the 404 is reported cleanly. Because the API is stateless, I could also exercise the server on its own from the address bar.

Known limitations: only the first Geocoding match is used, air quality is the current reading rather than a forecast, and the comparison ranking is a simple heuristic. The natural next steps are deploying the server on AWS so the app no longer has to run locally, and caching OpenWeather responses for a few minutes, since a comparison currently costs six upstream calls.

What I mainly took from this assignment is that most of the work in an application like this happens on the server, reshaping someone else's data into exactly what the page needs, and that the client becomes much simpler once the UI is a function of its state.