\bigcirc

Good morning © Notebooks and slides are in:

https://github.com/AlineQuadros/teaching_data_science

Packages we'll need:

```
scipy==1.4.1
statsmodels==0.11.1
prophet == 0.7.1
pmdarima == 1.7.1
Plotly >= 4
```

Installation instructions for Prophet (please check): https://facebook.github.io/prophet/docs/installation.html#python





DR. ALINE QUADROS DSR JANUARY 2021

Contents


- What are time series?
- What kind of time series properties are there? (buzz words)
 - Trend, seasonality
 - Stationarity
 - Autocorrelation
 - Baselines
 - average, naïve, smoothing moving average
- 'Traditional' time series analysis:
 - Exponential smoothing (a.k.a ETS models)
 - Autoregressive models (a.k.a. AR models): ARIMA family (ARMA, ARIMA, SARIMA, SARIMAX)
- ML-based time series:
 - Random forests and boosting trees
 - Prophet
 - RNNs and LSTMs (not here; in the Sequences class)



Resources

- Free excellent book
 - Hyndman, R.J., & Athanasopoulos, G. (2018) *Forecasting: principles and practice*, 2nd edition, OTexts: Melbourne, Australia. www.OTexts.com/fpp2
 - Most of the plots used in this presentation come from this book
- Bastian Kubsch's repository: <u>https://github.com/bkubsch/time_series</u>
- Online class = https://online.stat.psu.edu/stat510/lesson/1
- Exercises:
 https://github.com/AlineQuadros/Timeseries_predictive_modelling


TIME SERIES PROPERTIES




Trend Seasonality Stationarity



Time series decomposition



Additive = the components add to each other Multiplicative= the effects are multiplied




Time series decomposition

Example of additive decomposition:

Look at the value at time 2001:

The observed value (130) is decomposed as

130 = 111 (trend) + 11 (seasonal) + 8 (residue)



100 50

Stationarity


- Stationary data is data without trends or seasonality
- In stationary data, the mean and variance of the time series don't change over time
- Meaning, even though the data has a time axis, its values do not depend on the time component itself
- How to detect non-stationarity?
 - Plots, ACF plots
 - Hypothesis tests (AD Fuller test)



100

Differencing

How to deal with non-stationary data?
 Use the differences between observations



Autocorrelation

Autocorrelation = correlation with itself in the past The presence of a strong, significant autocorrelation with a fixed interval is a very strong indicator of seasonality

Example:


Rossman's stores are closed on sundays, ans sales pick up on mondays


Correlation with itself is always 1, or 100%


Recurrent very strong correlation (65%) at 7 days intervals

The shaded area indicates the 95% confidence intervals.

The null hypothesis is that autocorrelation=0







BASELINES

\bigcirc

Simplest possible forecast (baselines)

Simplest representation of trend, seasonality and autocorrelation

In practice, they will be used as a reference to compare our candidate models




Figure 3.1: Forecasts of Australian quarterly beer production.



EXPONENTIAL SMOOTHING




Exponential Smoothing

Exponential smoothing methods are weighted averages of past observations

The weights decrease exponentially as the observations get older

The degree is given by parameter alpha.






\bigcirc

Exponential Smoothing

The way the weights are distributed along time is determined by the smoothing parameter alpha (α)





Alpha

How the weights are distributed along time is determined by the smoothing parameter alpha (α)

	lpha=0.2	lpha=0.4	$\alpha = 0.6$	$\alpha = 0.8$
y_T	0.2000	0.4000	0.6000	0.8000
y_{T-1}	0.1600	0.2400	0.2400	0.1600
y_{T-2}	0.1280	0.1440	0.0960	0.0320
y_{T-3}	0.1024	0.0864	0.0384	0.0064
y_{T-4}	0.0819	0.0518	0.0154	0.0013
y_{T-5}	0.0655	0.0311	0.0061	0.0003




Methods

- Simple Exponential Smoothing
 - For time series without a clear trend or seasonality, i. e. for stationary data
- Holt-Winter's family of methods
 - Can be applied in time series with trend and/or seasonality
 - Trend and seasonality can be additive or multiplicative:
 - Additive: magnitude does not change over time
 - Multiplicative: magnitude of trend or length of cycle (seasonality) changes over time
 - How to check? Plotting the data



Time series scenarios (and appropriate models)

		SEASONALITY		
		<u>None</u>	<u>Constant</u> (Additive)	Increasing (Multiplicative)
TREND	<u>None</u>	(N,N) Simple exponential smoothing (uses just alpha)	(N, A)	(N, M)
	<u>Linear</u> (Additive)	(A, N) Holt's linear method	(A, A) Additive Holt- Winter's	(A, M) Multiplicative Holt- Winter's
	Exponential (Additive damped)	(Ad, N) Additive damped trend method	(Ad, A)	(Ad, M) Holt-Winter's damped





AUTO REGRESSIVE MODELS

Autoregressive models

- Classic and robust methods. Can be applied in many different situations
- Univariate
- ARIMA = Autoregressive Integrated Moving Average
- ARIMA models describe the autocorrelation in the data
- Can deal with non-stationarity, trend and seasonality (SARIMA)





ARIMA

AUTOREGRESSIVE component a.k.a. **p**

Linear combination of past values; Regression against itself DIFFERENCING component a.k.a. **d**

Helps to stabilise the mean, reducing trend and seasonality

MOVING AVERAGE component

a.k.a. **q**

Weighted moving average of past errors

VARIATIONS:

NON-SEASONAL ARIMA ARIMA(p, d, q) SEASONAL ARIMA ARIMA (p, d, q) (P, D, Q)m SARIMAX + features



Understanding (p, d, q) and m

- p = is the AR term. Is the number of lags of Y to use as predictors
- q = is the MA term. Is the number of lags to use to get the forecast errors
- d determines how many periods to lag before calculating the differences
 - For an Array[10, 4, 2, 9, 34] => d =1 results in [-6, -2, 7, 25]
 - If the data is already stationary, d = 0
- The m indicates the number of observations per seasonal cycle, will be used in SARIMA and SARIMAX.





ARMA

Family of models

ARMA Only handles stationary data

ARIMA Can handle trends by applying differentiation

SARIMA Can handle trends and seasonality

SARIMAx Can handle trends + seasonality + regressors





WHAT'S NEXT?

M L M O D E L S





OVERVIEW OF TIMESERIES METHODS

Components	Only univariate (i. e., one time series at time)	Univariate + regressors (other related timeseries)	Multivariate (i. e., multiple time series for multiple features)
Stationary	ARMA Exponential smoothing (ES) (classical)	SARIMAX Prophet LSTM	Tree algorithms RNN
Trend	ARIMA ES Holz-winter	SARIMAX Prophet LSTM	RNN
Seasonality	SARIMA ES Holz-winter	SARIMAX Prophet LSTM	Tree algorithms RNN
Trend+seasonality	SARIMA ES Holz-winter	SARIMAX Prophet LSTM	RNN
Complex seasonality	TBATS	LSTM Prophet	Tree algorithms RNN



JANUAR 21 SEPTEMBER 2020

\bigcirc

ML-based time series forecasting

- Tree models (Random forests, boosted trees)
- Prophet (can handle combinations of seasonality (e.g. weekday + yearly))
- LSTMs and RNN (next classes)

- AWS SAGEMAKER DEEPAR
 - Based on RNN
 - https://docs.aws.amazon.com/sagemaker/latest/dg/deepar.html



\bigcirc

ML and TIME SERIES basics

- Never shuffle the data: order matters!
- Always create a baseline model (naïve, average, moving average) to have a clearer understanding of how well your candidate models are performing
 - They should at least be better than the average
- Use as validation and test sets a period as long as the one you are being asked to predict:
 - Example: If you need to predict sales of next 3 months, use the last 3 months of data as test set, and the 3 months before that for cross-validation (for gridsearch, for example)



Forecast with Prophet

Prophet is a procedure for forecasting time series data based on an additive model where non-linear trends are fit with yearly, weekly, and daily seasonality, plus holiday effects. It works best with time series that have strong seasonal effects and several seasons of historical data. Prophet is robust to missing data and shifts in the trend, and typically handles outliers well.

Note: Prophet is optimized for business data, i. e., timeseries on calendar dates. Can account for holidays *out-of-the-box*

https://facebook.github.io/prophet/

Based on this publication: https://peerj.com/preprints/3190/ (super recommended reading)



RCPHET

JANUAR 21 SEPTEMBER 2020