

Automated Java Method Naming Task Report

Li Zhen

Experiments & Results: I constructed the dataset using the SEART GitHub search engine. I queried for Java repositories with at least 100 commits, at least 10 contributors, a minimum of 10 stars, and excluded forks, with the search results sorted by number of commits in descending order. I downloaded the list and used a script to clone the top 500 repositories to my local machine. Using javalang, I parsed all Java files and extracted method declarations, stopping mining once I had about 2000k methods. I removed exact duplicates based on the method body, filtered out any method whose name contained the string `test` (these were mostly auto-generated names like `test_0967`, `test_0564`, etc.), and discarded methods longer than 256 tokens. In addition, to avoid noisy or potentially sensitive identifiers, I filtered out any method whose name or body contained substrings such as `accesssecret`, `access_secret`, `accesskey`, `access_key`, `secretkey`, `secret_key`, `_id`, `user_id`, or `client_id`. After these cleaning and filtering steps, I capped the dataset at 50k unique methods and then split it into 40k training methods and 10k test methods (80/20 split).

I first trained for one epoch on CPU with max sequence length 512, per-device batch size 1 and gradient accumulation 4 (effective batch size 4), using AdamW with learning rate $1e-4$; this run had about 9.8k training steps, a total runtime of roughly 12 hours, and a final training loss of about 2.32, yielding an exact-match accuracy of 44.6% on the 10k-method held-out test set using greedy FIM inference with up to 8 generated tokens. After this initial run, I adjusted the training hyperparameters to learning rate 5×10^{-5} , weight decay 0.01, and warmup ratio 0.05, and retrained for one epoch with the same data and batch settings; this second run reported a final training loss of about 1.82 and achieved a higher exact-match accuracy of 60.29% on the same 10k-method test set.

Based on this second, improved test result, I analyzed the 10k test predictions in more detail: overall accuracy was 60.29% (6029 correct, 3971 wrong). Short names (≤ 10 characters) were the easiest (72.39% accuracy), followed by medium names (11–20 characters, 52.98%), while long names (> 20 characters) were much harder (37.28%). A similar trend appeared by subtoken count: single-token names reached 73.18% accuracy, 2–3 token names 60.62%, and names with more than 3 subtokens only 40.64%. For wrong predictions, the average normalized string similarity between true and predicted names was 0.41; many “near-miss” cases differed only by small edits (for example, singular/plural changes or off-by-one suffixes), while a smaller subset of errors were completely off (e.g., load vs getApi). Finally, in more than 99% of all examples (both correct and wrong), all subtokens of the true method name appeared somewhere in the method body, confirming that the model is operating in a setting where the key lexical signals are present in the code but it still sometimes fails to assemble the exact target name.

Screenshots:

Dataset:

```
Total collected methods (before dedup): 200035
Reached max_unique = 50000, stopping dedup.
Total unique methods collected (capped): 50000
Train examples: 40000, Test examples: 10000
```

First training result:

```
{
  "loss": 1.4922, "grad_norm": 29.79486465451815, "learning_rate": 7.382272727272727e-05, "epoch": 1.0
}
{"train_runtime": 43428.8421, "train_samples_per_second": 0.908, "train_steps_per_second": 0.227, "train_loss": 2.3181177932148113, "epoch": 1.0}
done
Training done.
Saved fine-tuned model + tokenizer to qwen_methodname_finetuned
```

Second training result:

```
{ 'loss': 1.12658, 'grad_norm': 26.3983358482888, 'learning_rate': 3.35843823325848E-06, 'epoch': 1.0}
{'train_runtime': 45130.3599, 'train_samples_per_second': 0.874, 'train_steps_per_second': 0.218, 'train_loss': 1.8209629728218788, 'epoch': 1.0}
100%|
Training done.
Saved fine-tuned model + tokenizer to E:\qwen_methodname_finetune
```

First testing result:

```
W1117 01:18:25.378000 13004 .venv\Lib\site-packages\torch\di
Loaded 10000 test examples.
The attention mask is not set and cannot be inferred from in
Exact-match accuracy on test set: 44.62% (4462/10000)
(.venv) PS D:\method_name_prediction>
```

Second testing result:

```
Loaded 10000 test examples.
The attention mask is not set and cannot be inferred from
Exact-match accuracy on test set: 60.29% (6029/10000)
Saved all predictions to predictions.jsonl
```

Analyzing result:

```
(.venv) PS D:\method_name_prediction> python analyze_prediction.py --predictions-file predictions1.jsonl
Total evaluated examples: 10000
Correct: 6029, Wrong: 3971
Accuracy: 60.29%

Accuracy by true method name length:
  short (<=10 chars): 72.39% (4545 examples)
  medium (11-20 chars): 52.98% (4492 examples)
  long (>20 chars): 37.28% (963 examples)

Accuracy by number of subtokens in true name:
  1 token: 73.18% (2110 examples)
  2-3 tokens: 60.62% (6399 examples)
  >3 tokens: 40.64% (1491 examples)

Average similarity for wrong predictions (0-1): 0.410

Top 5 near-miss wrong predictions (high similarity):
-----
True: buildNegativeViewUsersQueryConstraint | Pred: buildNegativeViewUserQueryConstraint | sim = 0.973
True: modifyRenderItemAndEffectIntoGUI1 | Pred: modifyRenderItemAndEffectIntoGUI2 | sim = 0.970
True: mcpatcherforge$redirectColor17 | Pred: mcpatcherforge$redirectColor1 | sim = 0.967
True: mcpatcherforge$redirectColor14 | Pred: mcpatcherforge$redirectColor1 | sim = 0.967
True: setComputeWorkGroupsRelative | Pred: setComputeWorkGroupRelative | sim = 0.964
-----
```

Top 5 most off wrong predictions (low similarity):

```
-----  
True: load | Pred: getApi | sim = 0.000  
True: ping | Pred: close | sim = 0.000  
True: loadInCache | Pred: putDictionary | sim = 0.000  
True: fromType | Pred: makeClassInfo | sim = 0.000  
True: reg | Pred: of | sim = 0.000  
-----
```

Subtoken coverage of TRUE name in method body (all examples):

```
all subtokens appear: 9917 (99.17%)  
some subtokens appear: 0 (0.00%)  
no subtokens appear: 83 (0.83%)
```

For CORRECT predictions:

```
total: 6029  
all subtokens appear: 5962 (98.89%)  
some subtokens appear: 0 (0.00%)  
no subtokens appear: 67 (1.11%)
```

For WRONG predictions:

```
total: 3971  
all subtokens appear: 3955 (99.60%)  
some subtokens appear: 0 (0.00%)  
no subtokens appear: 16 (0.40%)
```