

root

[Go Up](#)

Name	LogisticRegression
Version	3.0.0
Description	Logistic Regression implementation
License	http://www.apache.org/licenses/LICENSE-2.0
Copyright	Copyright (C) 2017 HPCC Systems
Authors	HPCCSystems
DependsOn	ML_Core 3.2.1, PBblas
Platform	6.2.0

Table of Contents

BinomialConfusion.ecl
Calculate the binomial confusion matrix
BinomialLogisticRegression.ecl
Binomial logistic regression using iteratively re-weighted least squares
Confusion.ecl
Generate the confusion matrix, to compare actual versus predicted response variable values
Constants.ecl
Constants used by Logistic Regression
DataStats.ecl
Produce summary information about the datasets
Deviance_Analysis.ecl
Analysis of Deviance Report
Deviance_Detail.ecl
Deviance detail report
dimm.ecl
Matrix multiply when either A or B is a diagonal and is passed as a vector
enum_workitems.ecl

Create an enumeration of string contents to be used as work items
ExtractBeta.ecl Extract the beta values form the model dataset
ExtractBeta_CI.ecl Extract the beta values and confidence intervals from the model dataset
ExtractBeta_full.ecl Extract the coefficient information including confidence intervals, z and p values
ExtractBeta_pval.ecl Extract the beta values including z and p value from the model
ExtractReport.ecl Create a model report from a model
LogitPredict.ecl Predict the category values with the logit function and the the supplied beta coefficients
LogitScore.ecl Calculate the score using the logit function and the the supplied beta coefficients
LUCI_Model.ecl Create a LUCI model file description of the model(s) from the external version of the model
Model_Deviance.ecl Model Deviance Report
Named_Model.ecl Apply external labels for work items and field names to a model
Null_Deviance.ecl Return Deviance information for the null model, that is, a model with only an intercept
Types.ecl Type definitions for LogisticRegression bundle

<div>

LogisticRegression

June 23, 2022

Bundle for binomial, multinomial, and ordinal logistic regression.

BinomialConfusion

[Go Up](#)

IMPORTS

Types | __versions.ML_Core.V3_2_2.ML_Core.Types |

DESCRIPTIONS

BINOMIALCONFUSION BinomialConfusion

<code>/ EXPORT DATASET(Types.Binomial_Confusion_Summary)</code>	BinomialConfusion
<code>(DATASET(Core_- Types.Confusion_Detail) d)</code>	

Calculate the binomial confusion matrix. Work items with multinomial responses are ignored by this function. The higher value lexically is considered to be the positive indication.

PARAMETER `d` ||| TABLE (Confusion_Detail) — confusion detail for the work item and classifier.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 classifier , UNSIGNED8 true_positive , UNSIGNED8 true_negative , UNSIGNED8 false_positive , UNSIGNED8 false_negative , UNSIGNED8 cond_pos , UNSIGNED8 pred_pos , UNSIGNED8 cond_neg , UNSIGNED8 pred_neg , REAL8 prevalence , REAL8 accuracy , REAL8 true_pos_rate , REAL8 false_neg_rate , REAL8 false_pos_rate , REAL8 true_neg_rate , REAL8 pos_pred_val , REAL8 false_disc_rate , REAL8 false_omit_rate , REAL8 neg_pred_val }) — confusion matrix for a binomial classifier in Binomial_Confusion_Summary format.

SEE Types.Binomial_Confusion_Summary

BinomialLogisticRegression

[Go Up](#)

IMPORTS

Constants | `_versions.ML_Core.V3_2_2.ML_Core.Interfaces` |
`_versions.ML_Core.V3_2_2.ML_Core.Types` |

DESCRIPTIONS

BINOMIALLOGISTICREGRESSION BinomialLogisticRegression

/ EXPORT	BinomialLogisticRegression
<code>(UNSIGNED max_iter=200, REAL8 epsilon=Constants.default_epsilon, REAL8 ridge=Constants.default_ridge)</code>	

Binomial logistic regression using iteratively re-weighted least squares.

PARAMETER max_iter ||| UNSIGNED8 — (Optional) The maximum number of iterations to try.
Default = 200.

PARAMETER epsilon ||| REAL8 — (Optional) The minimum change in the Beta value estimate to continue

PARAMETER ridge ||| REAL8 — (Optional) A value to populate a diagonal matrix that is added to a matrix help assure that the matrix is invertible.

PARENT `_versions.ML_Core.V3_2_2.ML_Core.Interfaces.IClassify`
</home/amar/.HPCCSystems/bundles/_versions/ML_Core/V3_2_2/ML_Core/Interfaces/IClassify.ecl>

Children

1. [GetModel](#) : Calculate the model to fit the observation data to the observed classes
2. [Classify](#) : Classify the observations using a model as previously returned from GetModel
3. [Report](#) : Report the confusion matrix for the classifier and training data

GETMODEL GetModel

[BinomialLogisticRegression](#) \

DATASET (Types.Layout_Model)	GetModel
(DATASET(Types.NumericField) observations, DATASET(Types.DiscreteField) classifications)	

Calculate the model to fit the observation data to the observed classes.

PARAMETER observations ||| TABLE (NumericField) — the observed explanatory values in NumericField format.

PARAMETER classifications ||| TABLE (DiscreteField) — the observed classification used to build the model in DiscreteField format.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , REAL8 value }) — the encoded model in Layout_Model format.

SEE ML_Core.Types.NumericField

SEE ML_Core.Types.DiscreteField

SEE ML_Core.Types.Layout_Model

OVERRIDE

CLASSIFY Classify

[BinomialLogisticRegression](#) \

<code>DATASET(Types.Classify_Result)</code>	Classify
<code>(DATASET(Types.Layout_Model) model, DATASET(Types.NumericField) new_observations)</code>	

Classify the observations using a model as previously returned from GetModel.

PARAMETER model ||| TABLE (Layout_Model) — The model in Layout_Model format.

PARAMETER new_observations ||| TABLE (NumericField) — observations to be classified in NumericField format.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number ,
INTEGER4 value , REAL8 conf }) — Classification with a confidence value in Classify_Result format.

SEE ML_Core.Types.Layout_Model

SEE ML_Core.Types.NumericField

SEE ML_Core.Types.Classify_Result

OVERRIDE

REPORT Report

[BinomialLogisticRegression](#) \

<code>DATASET(Types.Confusion_Detail)</code>	Report
<code>(DATASET(Types.Layout_Model) model, DATASET(Types.NumericField) observations, DATASET(Types.DiscreteField) classifications)</code>	

Report the confusion matrix for the classifier and training data.

PARAMETER model ||| TABLE (Layout_Model) — the encoded model as returned from GetModel.

PARAMETER observations ||| TABLE (NumericField) — the explanatory values in NumericField format.

PARAMETER classifications ||| TABLE (DiscreteField) — the actual classifications associated with the observations (i.e. ground truth) in DiscreteField format.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 classifier , INTEGER4 actual_class , INTEGER4 predict_class , UNSIGNED4 occurs , BOOLEAN correct , REAL8 pctActual , REAL8 pctPred }) — the confusion matrix showing correct and incorrect results in Confusion_Detail format.

SEE ML_Core.Types.NumericField

SEE ML_Core.Types.DiscreteField

SEE ML_Core.Types.ConfusionDetail

OVERRIDE

Confusion

[Go Up](#)

IMPORTS

```
__versions.ML_Core.V3_2_2.ML_Core |  
__versions.ML_Core.V3_2_2.ML_Core.Types | Types |
```

DESCRIPTIONS

CONFUSION Confusion

<code>/ EXPORT DATASET(Confusion_Detail)</code>	Confusion
<code>(DATASET(DiscreteField) dependents, DATASET(DiscreteField) predicts)</code>	

Generate the confusion matrix, to compare actual versus predicted response variable values.

PARAMETER dependents ||| TABLE (DiscreteField) — the original response values.

PARAMETER predicts ||| TABLE (DiscreteField) — the predicted responses.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 classifier , INTEGER4 actual_class , INTEGER4 predict_class , UNSIGNED4 occurs , BOOLEAN correct , REAL8 pctActual , REAL8 pctPred }) — confusion matrix in Confusion_Detail format.

SEE ML_Core.Types.Confusion_Detail

Constants

[Go Up](#)

DESCRIPTIONS

CONSTANTS Constants

	Constants
--	-----------

Constants used by Logistic Regression. Most of these are the nominal values used by the Model data set. A few are used to control behavior.

Children

1. [limit_card](#) : No Documentation Found
2. [default_epsilon](#) : No Documentation Found
3. [default_ridge](#) : No Documentation Found
4. [local_cap](#) : No Documentation Found
5. [id_base](#) : No Documentation Found
6. [id_iters](#) : No Documentation Found
7. [id_delta](#) : No Documentation Found
8. [id_correct](#) : No Documentation Found
9. [id_incorrect](#) : No Documentation Found
10. [id_stat_set](#) : No Documentation Found
11. [id_betas](#) : No Documentation Found
12. [id_betas_coef](#) : No Documentation Found
13. [id_betas_SE](#) : No Documentation Found
14. [base_builder](#) : No Documentation Found

- 15. [base_max_iter](#) : No Documentation Found
- 16. [base_epsilon](#) : No Documentation Found
- 17. [base_ind_vars](#) : No Documentation Found
- 18. [base_dep_vars](#) : No Documentation Found
- 19. [base_obs](#) : No Documentation Found
- 20. [builder_irls_local](#) : No Documentation Found
- 21. [builder_irls_global](#) : No Documentation Found
- 22. [builder_softmax](#) : No Documentation Found

LIMIT_CARD limit_card

[Constants](#) \

UNSIGNED2	limit_card
-----------	------------

No Documentation Found

RETURN UNSIGNED2 —

DEFAULT_EPSILON default_epsilon

[Constants](#) \

REAL8	default_epsilon
-------	-----------------

No Documentation Found

RETURN REAL8 —

DEFAULT_RIDGE default_ridge

[Constants](#) \

REAL8	default_ridge
-------	---------------

No Documentation Found

RETURN REAL8 —

LOCAL_CAP local_cap

[Constants](#) \

UNSIGNED4	local_cap
-----------	-----------

No Documentation Found

RETURN UNSIGNED4 —

ID_BASE id_base

[Constants](#) \

id_base

No Documentation Found

RETURN INTEGER8 —

ID_ITERS id_iters

[Constants](#) \

	id_iters
--	----------

No Documentation Found

RETURN INTEGER8 —

ID_DELTA id_delta

[Constants](#) \

	id_delta
--	----------

No Documentation Found

RETURN INTEGER8 —

ID_CORRECT id_correct

[Constants](#) \

	id_correct
--	------------

No Documentation Found

RETURN INTEGER8 —

ID_INCORRECT id_incorrect

[Constants](#) \

	id_incorrect
--	--------------

No Documentation Found

RETURN INTEGER8 —

ID_STAT_SET id_stat_set

[Constants](#) \

	id_stat_set
--	-------------

No Documentation Found

RETURN SET (INTEGER8) —

ID_BETAS id_betas

[Constants](#) \

	id_betas
--	----------

No Documentation Found

RETURN INTEGER8 —

ID_BETAS_COEF id_betas_coef

[Constants](#) \

	id_betas_coef
--	---------------

No Documentation Found

RETURN INTEGER8 —

ID_BETAS_SE id_betas_SE

[Constants](#) \

	id_betas_SE
--	-------------

No Documentation Found

RETURN INTEGER8 —

BASE_BUILDER base_builder

[Constants](#) \

	base_builder
--	--------------

No Documentation Found

RETURN INTEGER8 —

BASE_MAX_ITER base_max_iter

[Constants](#) \

	base_max_iter
--	---------------

No Documentation Found

RETURN INTEGER8 —

BASE_EPSILON base_epsilon

[Constants](#) \

	base_epsilon
--	--------------

No Documentation Found

RETURN INTEGER8 —

BASE_IND_VARS base_ind_vars

[Constants](#) \

	base_ind_vars
--	---------------

No Documentation Found

RETURN INTEGER8 —

BASE_DEP_VARS base_dep_vars

[Constants](#) \

	base_dep_vars
--	---------------

No Documentation Found

RETURN INTEGER8 —

BASE_OBS base_obs

[Constants](#) \

	base_obs
--	----------

No Documentation Found

RETURN INTEGER8 —

BUILDER_IRLS_LOCAL builder_irls_local

[Constants](#) \

	builder_irls_local
--	--------------------

No Documentation Found

RETURN INTEGER8 —

BUILDER_IRLS_GLOBAL builder_irls_global

[Constants](#) \

	builder_irls_global
--	---------------------

No Documentation Found

RETURN INTEGER8 —

BUILDER_SOFTMAX builder_softmax

[Constants](#) \

	builder_softmax
--	-----------------

No Documentation Found

RETURN INTEGER8 —

DataStats

[Go Up](#)

IMPORTS

```
__versions.LogisticRegression.V3__0__0.LogisticRegression.Types |  
__versions.LogisticRegression.V3__0__0.LogisticRegression.Constants |  
__versions.ML_Core.V3__2__2.ML_Core.Types |
```

DESCRIPTIONS

DATASTATS DataStats

<code>/ EXPORT DATASET(Types.Data_Info)</code>	DataStats
<code>(DATASET(Core_Types.NumericField) indep, DATASET(Core_Types.DiscreteField) dep, BOOLEAN field_details=FALSE)</code>	

Produce summary information about the datasets.

When `field_details = FALSE`, indicates the range for the x and y (independent and dependent) columns.

When `field_details = TRUE`, the cardinality, minimum, and maximum values are returned. A zero cardinality is returned when the field cardinality exceeds the `Constants.limit_card` value.

Note that a column of all zero values cannot be distinguished from a missing column.

PARAMETER indep ||| TABLE (NumericField) — data set of independent variables.

PARAMETER dep ||| TABLE (DiscreteField) — data set of dependent variables.

PARAMETER field_details ||| BOOLEAN — Boolean directive to provide field level info.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 dependent_fields , UNSIGNED4 dependent_records , UNSIGNED4 independent_fields , UNSIGNED4 independent_records , UNSIGNED4 dependent_count , UNSIGNED4 independent_count , TABLE (Field_Desc) dependent_stats , TABLE (Field_Desc) independent_stats }) — a data set of information on each work item in Data_Info format.

SEE Types.Data_Info

SEE Constants.limit_card

Deviance__Analysis

[Go Up](#)

IMPORTS

Types | __versions.ML_Core.V3_2_2.ML_Core.Math |

DESCRIPTIONS

DEVIANCE_ANALYSIS Deviance__Analysis

/ EXPORT DATASET(Types.AOD_Record)	Deviance__Analysis
(DATASET(Types.Deviance_Record) proposed, DATASET(Types.Deviance_Record) base)	

Analysis of Deviance Report.

Compare deviance information between two models, a base and and proposed model.

Analysis of Deviance is analogous to the Analysis of Variance (ANOVA) used in least-squares modeling, but adapted to the general linear model (GLM). In this case it is adapted specifically to the logistic model.

The inputs are the deviance records for each model as obtained from a call to Model__Deviance.

PARAMETER **proposed** ||| TABLE (Deviance_Record) — deviance records of the proposed model.

PARAMETER **base** ||| TABLE (Deviance_Record) — deviance records of the base model for comparison.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 classifier , UNSIGNED8 residual_df , UNSIGNED8 df , REAL8 residual_dev , REAL8 deviance , REAL8 p_value }) — the comparison of the deviance between the models in AOD_Record format.

SEE Model_Deviance

SEE Types.Deviance_Record

SEE Types.AOD_Record

Deviance_Detail

[Go Up](#)

IMPORTS

```
__versions.ML_Core.V3_2_2.ML_Core |  
__versions.ML_Core.V3_2_2.ML_Core.Types | Types |
```

DESCRIPTIONS

DEVIANCE_DETAIL Deviance_Detail

<code>/ EXPORT DATASET(Types.Observation_Deviance)</code>	Deviance_Detail
<code>(DATASET(Core_Types.DiscreteField) dependents, DATASET(Types.Raw_Prediction) predicts)</code>	

Deviance detail report.

Provides deviance information for each observation.

Analysis of Deviance is analogous to the Analysis of Variance (ANOVA) used in least-squares modeling, but adapted to the general linear model (GLM). In this case it is adapted specifically to the logistic model.

PARAMETER [dependents](#) ||| TABLE ([DiscreteField](#)) — original dependent records for the model

PARAMETER [predicts](#) ||| TABLE ([Raw_Prediction](#)) — the predicted values of the response variable

RETURN TABLE ({ UNSIGNED2 [wi](#) , UNSIGNED8 [id](#) , UNSIGNED4 [classifier](#) ,
INTEGER4 [actual](#) , INTEGER4 [predicted](#) , REAL8 [mod_ll](#) , REAL8

mod_dev_component , REAL8 mod_dev_residual , REAL8 nil_ll , REAL8 nil_dev_component , REAL8 nil_dev_residual }) — the deviance information by observation and the log likelihood of the predicted result in Observation_Deviance format.

SEE Types.Observation_Deviance

dimmm

[Go Up](#)

IMPORTS

std.blas | std.BLAS.Types |

DESCRIPTIONS

DIMM dimmm

<code>Types.matrix_t</code>	<code>dimmm</code>
<pre>(BOOLEAN transposeA, BOOLEAN transposeB, BOOLEAN diagonalA, BOOLEAN diagonalB, Types.dimension_t m, Types.dimension_t n, Types.dimension_t k, Types.value_t alpha, Types.matrix_t A, Types.matrix_t B, Types.value_t beta=0.0, Types.matrix_t C=[])</pre>	

Matrix multiply when either A or B is a diagonal and is passed as a vector.

Computes: $\alpha * \text{op}(A) \text{ op}(B) + \beta * C$ where $\text{op}()$ is transpose.

PARAMETER transposeA ||| BOOLEAN — true when transpose of A is used.

PARAMETER transposeB ||| BOOLEAN — true when transpose of B is used.

PARAMETER diagonalA ||| BOOLEAN — true when A is the diagonal matrix.

PARAMETER diagonalB ||| BOOLEAN — true when B is the diagonal matrix.

PARAMETER m ||| UNSIGNED4 — number of rows in product.

PARAMETER n ||| UNSIGNED4 — number of columns in product.

PARAMETER k ||| UNSIGNED4 — number of columns/rows for the multiplier/multiplicand.

PARAMETER alpha ||| REAL8 — scalar used on A.

PARAMETER A ||| SET (REAL8) — matrix A.

PARAMETER B ||| SET (REAL8) — matrix B.

PARAMETER beta ||| REAL8 — scalar for matrix C.

PARAMETER C ||| SET (REAL8) — matrix C or empty.

RETURN SET (REAL8) — result matrix in matrix_t format.

SEE Std.BLAS.Types.matrix_t

enum_workitems

[Go Up](#)

DESCRIPTIONS

ENUM_WORKITEMS enum_workitems

enum_workitems
(dsIn, dsOut, src_field, wi_name)

Create an enumeration of string contents to be used as work items.

This macro produces 2 external symbols, dsOut and dsOut_Map.

The dsOut extends the input dataset with a numeric work-item number.

The dsOut_Map dataset captures the relationship between the strings that name the work items and the nominal assigned in Workitem_Mapping format.

PARAMETER dsIn ||| INTEGER8 — the input recordset.

PARAMETER dsOut ||| INTEGER8 — the symbol to use for the appended data.

PARAMETER src_field ||| INTEGER8 — a field name to use to discriminate work-items.

PARAMETER wi_name ||| INTEGER8 — the field name for the work item value assigned.

RETURN — Nothing. The macro creates the symbols 'dsOut' and 'dsOut_Map' inline.

SEE Types.Workitem_Mapping

ExtractBeta

[Go Up](#)

IMPORTS

Types | `__versions.ML_Core.V3_2_2.ML_Core.Types` |

DESCRIPTIONS

EXTRACTBETA ExtractBeta

<code>/ EXPORT</code>	ExtractBeta
<code>(DATASET(Core_Types.Layout_Model) mod_ds)</code>	

Extract the beta values form the model dataset.

PARAMETER `mod_ds` ||| TABLE (Layout_Model) — the model as returned from GetModel.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 ind_col , UNSIGNED4 dep_nom , REAL8 w , REAL8 SE }) — the beta values as Model_Coef records, with zero as the constant term.

SEE Types.Model_Coef

ExtractBeta_CI

[Go Up](#)

IMPORTS

Types | __versions.ML_Core.V3_2_2.ML_Core.Types |

DESCRIPTIONS

EXTRACTBETA_CI ExtractBeta_CI

/ EXPORT DATASET(Types.Confidence_Model_Coef)	ExtractBeta_CI
(DATASET(Core_Types.Layout_Model) mod_ds, REAL8 level)	

Extract the beta values and confidence intervals from the model dataset.

PARAMETER mod_ds ||| TABLE (Layout_Model) — the model as returned from GetModel.

PARAMETER level ||| REAL8 — the significance value for the intervals.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 ind_col , UNSIGNED4 dep_nom ,
REAL8 w , REAL8 SE , REAL8 upper , REAL8 lower }) — the beta values with
confidence intervals in Confidence_Model_Coef format, with zero as the constant term.

SEE Types.Confidence_Model_Coef

ExtractBeta_full

[Go Up](#)

IMPORTS

```
Types | __versions.ML_Core.V3_2_2.ML_Core.Math |  
__versions.ML_Core.V3_2_2.ML_Core.Types |
```

DESCRIPTIONS

EXTRACTBETA_FULL ExtractBeta_full

<code>/ EXPORT DATASET(Types.Full_Model_Coef)</code>	<code>ExtractBeta_full</code>
<code>(DATASET(Core_Types.Layout_Model) mod_ds, REAL8 level=0.05)</code>	

Extract the coefficient information including confidence intervals, z and p values.

PARAMETER `mod_ds` ||| TABLE (Layout_Model) — the model as returned from GetModel.

PARAMETER `level` ||| REAL8 — the significance value for the intervals.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 ind_col , UNSIGNED4 dep_nom ,
REAL8 w , REAL8 SE , REAL8 z , REAL8 p_value , REAL8 upper , REAL8 lower }
) — the coefficient information for the model in Full_Model_Coef format, with zero as the
constant term.

SEE Types.Full_Model_Coef

ExtractBeta_pval

[Go Up](#)

IMPORTS

Types | __versions.ML_Core.V3_2_2.ML_Core.Types |

DESCRIPTIONS

EXTRACTBETA_PVAL ExtractBeta_pval

/ EXPORT DATASET(Types.pval_Model_Coef)	ExtractBeta_pval
(DATASET(Core_Types.Layout_Model) mod_ds)	

Extract the beta values including z and p value from the model.

PARAMETER mod_ds ||| TABLE (Layout_Model) — the model as returned from GetModel.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 ind_col , UNSIGNED4 dep_nom , REAL8 w , REAL8 SE , REAL8 z , REAL8 p_value }) — the beta values with p-values in pval_Model_Coef format, with zero as the constant term.

SEE Types.pval_Model_Coef

ExtractReport

[Go Up](#)

IMPORTS

Types | Constants | `__versions.ML_Core.V3_2_2.ML_Core.Types` |

DESCRIPTIONS

EXTRACTREPORT ExtractReport

<code>/ EXPORT DATASET(<code>Types.Model_Report</code>)</code>	ExtractReport
<code>(DATASET(<code>Core_Types.Layout_Model</code>) <code>mod_ds</code>)</code>	

Create a model report from a model.

PARAMETER `mod_ds` ||| TABLE (`Layout_Model`) — the model as returned from `GetModel`.

RETURN TABLE ({ UNSIGNED2 `wi` , UNSIGNED4 `max_iterations` , REAL8 `epsilon` , UNSIGNED4 `dep_vars` , UNSIGNED4 `ind_vars` , UNSIGNED8 `obs` , UNSIGNED2 `builder` , TABLE (`Classifier_Stats`) `stats` }) — the model report in `Model_Report` format.

SEE `Types.Model_Report`

LogitPredict

[Go Up](#)

IMPORTS

Types | `__versions.ML_Core.V3_2_2.ML_Core.Types` |

DESCRIPTIONS

LOGITPREDICT LogitPredict

<code>/ EXPORT DATASET(Classify_Result)</code>	LogitPredict
<code>(DATASET(Model_Coef) coef, DATASET(NumericField) independents)</code>	

Predict the category values with the logit function and the the supplied beta coefficients.

PARAMETER `coef` ||| TABLE (Model_Coef) — the model beta coefficients as returned from ExtractBeta.

PARAMETER `independents` ||| TABLE (NumericField) — the observations.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , INTEGER4 value , REAL8 conf }) — the predicted category values and a confidence score in Classify_Result format.

SEE ExtractBeta

SEE ML_Core.Types.Classify_Result

LogitScore

[Go Up](#)

IMPORTS

Types | `_versions.ML_Core.V3_2_2.ML_Core.Types` |

DESCRIPTIONS

LOGITSCORE `LogitScore`

<code>/ EXPORT DATASET(Raw_Prediction)</code>	LogitScore
<code>(DATASET(Model_Coef) coef, DATASET(NumericField) independents)</code>	

Calculate the score using the logit function and the the supplied beta coefficients.

PARAMETER `coef` ||| `TABLE (Model_Coef)` — the model beta coefficients as returned from `ExtractBetas`.

PARAMETER `independents` ||| `TABLE (NumericField)` — the observations.

RETURN `TABLE ({ UNSIGNED2 wi , UNSIGNED8 id , UNSIGNED4 number , REAL8 raw })` — the raw prediction value in `Raw_Prediction` format.

SEE `ExtractBetas`

SEE `Types.Raw_Prediction`

LUCI_Model

[Go Up](#)

IMPORTS

Types | std.Str | std.system.ThorLib |

DESCRIPTIONS

LUCI_MODEL LUCI_Model

/ EXPORT DATASET(Types.LUCI_Rec)	LUCI_Model
(DATASET(Types.LUCI_Model_Rqst) rqst, DATASET(Types.External_Model) mod, STRING wi_field='work_item')	

Create a LUCI model file description of the model(s) from the external version of the model.

LUCI is a proprietary format used within LexisNexis.

The multi-score card per model case assumes that the score card selection is based solely upon the work item field. If this is not the case, the L1SE records will need to be patched.

The model id and name may have a "\$" character that is updated to match the work item when there are multiple models applied. If the strings do not have a "\$" character, the work item string is appended.

The score card name may have a "\$" character which is updated to match the work item. If the name is blank, the score card is named for the work item.

LUCI data fields may not contain comma characters. This function requires that the work item identification strings do not contain characters that need special handling for CSV data.

PARAMETER rqst ||| TABLE (LUCI_Model_Rqst) — the information to map work items to

models in LUCI_Model_Rqst format.

PARAMETER mod ||| TABLE (External_Model) — the model with the external field names applied in External_Model format as returned from Named_Model.

PARAMETER wi_field ||| STRING — the field name holding the work item identification string.

RETURN TABLE ({ STRING line }) — The lines of the LUCI file in LUCI_Rec format.

SEE Types.External_Model

SEE Named_Model

SEE Types.LUCI_Model_Rqst

SEE Types.LUCI_Rec

Model_Deviance

[Go Up](#)

IMPORTS

Types |

DESCRIPTIONS

MODEL_DEVIANC Model_Deviance

<code>/ EXPORT DATASET(Types.Deviance_Record)</code>	Model_Deviance
<code>(DATASET(Types.Observation_Deviance) od, DATASET(Types.Model_Coef) mod)</code>	

Model Deviance Report.

Create a report of deviance information for a model.

Analysis of Deviance is analogous to the Analysis of Variance (ANOVA) used in least-squares modeling, but adapted to the general linear model (GLM). In this case it is adapted specifically to the logistic model.

PARAMETER od ||| TABLE (Observation_Deviance) — observation-deviance records, as obtained from a call to Deviance_Detail.

PARAMETER mod ||| TABLE (Model_Coef) — model co-efficients records, as obtained from a call to ExtractBeta.

RETURN TABLE ({ UNSIGNED2 wi , UNSIGNED4 classifier , UNSIGNED8 df ,
REAL8 deviance , REAL8 AIC }) — model deviance in Deviance_Record format.

SEE Deviance_Detail

SEE ExtractBeta

SEE Types.Deviance_Record

Named__Model

[Go Up](#)

IMPORTS

Types |

DESCRIPTIONS

NAMED_MODEL Named__Model

<code>/ EXPORT DATASET(Types.External_Model)</code>	Named__Model
<code>(DATASET(Types.Layout_Model) mod_ds, DATASET(Types.FieldName_Mapping) expl_map, DATASET(Types.FieldName_Mapping) resp_map, DATASET(Types.WorkItem_mapping) wi_map=empty, REAL8 level=0.05)</code>	

Apply external labels for work items and field names to a model.

Returns an expanded model that includes:

- coefficients
- z and p-values
- independent variable field names
- dependent variable field names
- work-item names

PARAMETER mod_ds ||| TABLE (Layout_Model) — the model as returned from GetModel.

PARAMETER expl_map ||| TABLE (`FieldName_Mapping`) — the relation of the explanatory or independent variables to the field names for those variables in `FieldName_Mapping` format.

PARAMETER resp_map ||| TABLE (`FieldName_Mapping`) — the relation of the response variable column numbers to the field names in `FieldName_Mapping` format.

PARAMETER wi_map ||| TABLE (`WorkItem_Mapping`) — (optional) mapping of workitem strings to workitem nominals in `FieldName_Mapping` format.

PARAMETER level ||| REAL8 — (optional) value for confidence intervals. Default = 0.05.

RETURN TABLE ({ `STRING` `work_item` , `STRING` `response_field` , `UNSIGNED2` `wi` , `UNSIGNED4` `dep_nom` , TABLE (`External_Coef`) `coef` }) — an expanded model in `External_Model` format.

SEE `Types.FieldName_Mapping`

SEE `Types.External_Model`

Null_Deviance

[Go Up](#)

IMPORTS

Types |

DESCRIPTIONS

NULL_DEVIANCE Null_Deviance

<code>/ EXPORT DATASET(Types.Deviance_Record)</code>	Null_Deviance
<code>(DATASET(Types.Observation_Deviance) od)</code>	

Return Deviance information for the null model, that is, a model with only an intercept.

Analysis of Deviance is analogous to the Analysis of Variance (ANOVA) used in least-squares modeling, but adapted to the general linear model (GLM). In this case it is adapted specifically to the logistic model.

PARAMETER `od` ||| TABLE (Observation_Deviance) — Observation Deviance record set as returned from Deviance_Detail.

RETURN TABLE ({ UNSIGNED2 `wi` , UNSIGNED4 `classifier` , UNSIGNED8 `df` , REAL8 `deviance` , REAL8 `AIC` }) — a data set of the null model deviances for each work item and classifier in Deviance_Record format.

SEE Types.Observation_Deviance

SEE Types.Deviance_Record

SEE Deviance_Detail

Types

[Go Up](#)

IMPORTS

`_versions.ML_Core.V3_2_2.ML_Core.Types` |

DESCRIPTIONS

TYPES Types

Types

Type definitions for LogisticRegression bundle

Children

1. [AnyField](#) : No Documentation Found
2. [NumericField](#) : The NumericField layout defines a matrix of Real valued data-points
3. [DiscreteField](#) : The Discrete Field layout defines a matrix of Integer valued data-points
4. [Layout_Model](#) : No Documentation Found
5. [t_work_item](#) : No Documentation Found
6. [t_RecordID](#) : No Documentation Found
7. [t_FieldNumber](#) : No Documentation Found
8. [t_FieldReal](#) : No Documentation Found
9. [t_Discrete](#) : No Documentation Found
10. [t_Universe](#) : No Documentation Found

11. [Field_Desc](#) : Describe information about each field in a training set
 12. [Data_Info](#) : Describes information about a training dataset composed of independent and dependent columns
 13. [NumericField_U](#) : Record structure to add a 'Universe Number' to a NumericField allowing multiple independent NumericField matrixes within a work-item
 14. [DiscreteField_U](#) : Record structure to add a 'Universe Number' to a DiscreteField allowing multiple independent DiscreteField matrixes within a work-item
 15. [Layout_Column_Map](#) : Layout for a column map record that is used to remap column numbers
 16. [Classifier_Stats](#) : Statistics about the effectiveness of each classifier in a model
 17. [Model_Report](#) : Statistical information about a model
 18. [Binomial_Confusion_Summary](#) : Accuracy stats for binomial classifications
 19. [Model_Coef](#) : Model Coefficients
 20. [Confidence_Model_Coef](#) : Model Coefficients with confidence intervals
 21. [pval_Model_Coef](#) : Model coefficients with z and p-value
 22. [Full_Model_Coef](#) : Model coefficients with confidence intervals and p-value
 23. [External_Coef](#) : Model coefficients, confidence intervals, and p-value, plus independent field names, for each coefficient
 24. [External_Model](#) : Expanded version of a model with statistics and field names
 25. [Raw_Prediction](#) : Record for raw prediction without confidence information
 26. [Observation_Deviance](#) : Record to contain deviance information about each observation
 27. [Deviance_Record](#) : Record to hold deviance summary information about a model
 28. [AOD_Record](#) : Record to hold Analysis of Deviance (AOD) information for a model
 29. [FieldName_Mapping](#) : Layout used to hold the mapping between a field's number and its name
 30. [WorkItem_Mapping](#) : Layout used to hold the mapping between a work-item number and a textual name for that work-item
 31. [LUCI_Rec](#) : Layout to store the lines of a generated LUCI model file
 32. [LUCI_Model_Rqst](#) : Format for information to guide the generation of a LUCI file
-

ANYFIELD AnyField

Types \

	AnyField
--	----------

No Documentation Found

NUMERICFIELD NumericField

Types \

	NumericField
--	--------------

The NumericField layout defines a matrix of Real valued data-points. It acts as the primary Dataset layout for interacting with most ML Functions. Each record represents a single cell in a matrix. It is most often used to represent a set of data-samples or observations, with the 'id' field representing the data-sample or observation, and the 'number' field representing the various fields within the observation.

FIELD wi ||| — The work-item id, supporting the Myriad style interface. This allows multiple independent matrixes to be contained within a single dataset, supporting independent ML activities to be processed in parallel.

FIELD id ||| — This field represents the row-number of this cell of the matrix. It is also considered the record-id for observations / data-samples.

FIELD number ||| — This field represents the matrix column number for this cell. It is also considered the field number of the observation

FIELD value ||| — The value of this cell in the matrix.

DISCRETEFIELD DiscreteField

Types \

	DiscreteField
--	---------------

The Discrete Field layout defines a matrix of Integer valued data-points. It is similar to the NumericField layout above, except for only containing discrete (integer) values. It is typically used to convey the class-labels for classification algorithms.

FIELD wi ||| — The work-item id, supporting the Myriad style interface. This allows multiple independent matrixes to be contained within a single dataset, supporting independent ML activities to be processed in parallel.

FIELD id ||| — This field represents the row-number of this cell of the matrix. It is also considered the record-id for observations / data-samples.

FIELD number ||| — This field represents the matrix column number for this cell. It is also considered the field number of the observation

FIELD value ||| — The value of this cell in the matrix.

LAYOUT_MODEL Layout_Model

Types \

	Layout_Model
--	--------------

No Documentation Found

T_WORK_ITEM t_work_item

Types \

	t_work_item
--	-------------

No Documentation Found

RETURN UNSIGNED2 —

T_RECORDID t_RecordID

[Types \](#)

	t_RecordID
--	------------

No Documentation Found

RETURN UNSIGNED8 —

T_FIELDNUMBER t_FieldNumber

[Types \](#)

	t_FieldNumber
--	---------------

No Documentation Found

RETURN UNSIGNED4 —

T_FIELDREAL t_FieldReal

[Types \](#)

	t_FieldReal
--	-------------

No Documentation Found

RETURN REAL8 —

T_DISCRETE t_Discrete

Types \

t_Discrete

No Documentation Found

RETURN INTEGER4 —

T_UNIVERSE t_Universe

Types \

t_Universe

No Documentation Found

RETURN UNSIGNED1 —

FIELD_DESC Field_Desc

Types \

Field_Desc

Describe information about each field in a training set.

FIELD number ||| UNSIGNED4 — the column (feature) number.

FIELD cardinality ||| UNSIGNED4 — the number of unique values in the field.

FIELD min_value ||| REAL8 — the minimum value for the field.

FIELD max_value ||| REAL8 — the maximum value for the field.

DATA_INFO Data_Info

Types \

	Data_Info
--	-----------

Describes information about a training dataset composed of independent and dependent columns.

FIELD wi ||| UNSIGNED2 — the work-item number.

FIELD dependent_fields ||| UNSIGNED4 — the number of fields in the dependent data.

FIELD dependent_records ||| UNSIGNED4 — the number of records in the dependent data.

FIELD independent_fields ||| UNSIGNED4 — the number of fields in the independent data.

FIELD independent_records ||| UNSIGNED4 — the number of records in the independent data.

FIELD dependent_stats ||| TABLE (Field_Desc) — dataset of Field_Desc records describing each of the fields of the dependent data.

FIELD independent_stats ||| TABLE (Field_Desc) — dataset of Field_Desc records describing each of the fields of the independent data.

FIELD dependent_count ||| UNSIGNED4 — No Doc

FIELD independent_count ||| UNSIGNED4 — No Doc

SEE Field_Desc

NUMERICFIELD_U NumericField_U

Types \

	NumericField_U
--	----------------

Record structure to add a 'Universe Number' to a NumericField allowing multiple independent NumericField matrixes within a work-item.

FIELD u ||| UNSIGNED1 — the 'universe' number identifying a distinct matrix within a NumericField dataset and work-item.

FIELD wi ||| UNSIGNED2 — No Doc

FIELD id ||| UNSIGNED8 — No Doc

FIELD number ||| UNSIGNED4 — No Doc

FIELD value ||| REAL8 — No Doc

DISCRETEFIELD_U DiscreteField_U

Types \

	DiscreteField_U
--	-----------------

Record structure to add a 'Universe Number' to a DiscreteField allowing multiple independent DiscreteField matrixes within a work-item.

FIELD u ||| UNSIGNED1 — the 'universe' number identifying a distinct matrix within a DiscreteField dataset and work-item.

FIELD wi ||| UNSIGNED2 — No Doc

FIELD id ||| UNSIGNED8 — No Doc

FIELD number ||| UNSIGNED4 — No Doc

FIELD value ||| INTEGER4 — No Doc

LAYOUT_COLUMN_MAP Layout_Column_Map

Types \

	Layout_Column_Map
--	-------------------

Layout for a column map record that is used to remap column numbers.

FIELD wi ||| UNSIGNED2 — the work-item number.

FIELD orig_number ||| UNSIGNED4 — the original field number.

FIELD remap_number ||| UNSIGNED4 — the mapped-to field number.

CLASSIFIER_STATS Classifier_Stats

Types \

	Classifier_Stats
--	------------------

Statistics about the effectiveness of each classifier in a model.

FIELD column ||| UNSIGNED4 — the classifier field number.

FIELD max_delta ||| REAL8 — the max_delta value for the classifier.

FIELD iterations ||| UNSIGNED4 — the number of iterations used to train the classifier.

FIELD correct ||| UNSIGNED4 — the number of classes predicted correctly in the training data.

FIELD incorrect ||| UNSIGNED4 — the number of classes predicted incorrectly in the training data.

MODEL_REPORT Model_Report

Types \

	Model_Report
--	--------------

Statistical information about a model.

One record is generated per work-item.

FIELD wi ||| UNSIGNED2 — the work-item

FIELD max_iterations ||| UNSIGNED4 — the maximum iterations use to train the model.

- FIELD** epsilon ||| REAL8 — the 'epsilon' value used within the model.
- FIELD** dep_vars ||| UNSIGNED4 — the number of dependent variables (i.e. classifiers).
- FIELD** ind_vars ||| UNSIGNED4 — the number of independent variables (i.e. features).
- FIELD** obs ||| UNSIGNED8 — the number of observations (i.e. records) in the training data.
- FIELD** builder ||| UNSIGNED2 — the identifier for the builder used to train the model.
- FIELD** stats ||| TABLE (Classifier_Stats) — child dataset of Classifier_Stats, one for each classifier in the work-item.
- SEE** Classifier_Stats

BINOMIAL_CONFUSION_SUMMARY Binomial_Confusion_Summary

Types \

Binomial_Confusion_Summary

Accuracy stats for binomial classifications.

One record per work-item and classifier.

- FIELD** wi ||| UNSIGNED2 — the work-item number.
- FIELD** classifier ||| UNSIGNED4 — the classifier field number (i.e. dependent field number).
- FIELD** true_positive ||| UNSIGNED8 — the count of true positive results (i.e. predicted = TRUE, actual = TRUE).
- FIELD** true_negative ||| UNSIGNED8 — the count of true negative results (i.e. predicted = FALSE, actual = FALSE).
- FIELD** false_positive ||| UNSIGNED8 — the count of false_positive results (i.e. predicted = TRUE, actual = FALSE).
- FIELD** false_negative ||| UNSIGNED8 — the count of false_negative results (i.e. predicted = FALSE, actual = TRUE).
- FIELD** cond_pos ||| UNSIGNED8 — the count of results where actual = TRUE.
- FIELD** pred_pos ||| UNSIGNED8 — the count of results where predicted = TRUE.
- FIELD** cond_neg ||| UNSIGNED8 — the count of results where actual = FALSE.

FIELD pred_neg ||| UNSIGNED8 — the count of results where predicted = FALSE.

FIELD prevalence ||| REAL8 — cond_pos / total.

FIELD accuracy ||| REAL8 — (true_positive + true_negative) / total.

FIELD true_pos_rate ||| REAL8 — true_positive / cond_pos.

FIELD false_pos_rate ||| REAL8 — false_positive / cond_neg.

FIELD true_neg_rate ||| REAL8 — true_negative / cond_neg.

FIELD pos_pred_val ||| REAL8 — true_positive / pred_pos.

FIELD false_disc_rate ||| REAL8 — false_positive / pred_pos.

FIELD false_omit_rate ||| REAL8 — false_negative / pred_neg.

FIELD neg_pred_val ||| REAL8 — true_negative / pred_neg.

FIELD false_neg_rate ||| REAL8 — No Doc

MODEL_COEF Model_Coef

Types \

Model_Coef

Model Coefficients.

FIELD wi ||| UNSIGNED2 — the work-item number.

FIELD ind_col ||| UNSIGNED4 — the independent column number (i.e feature number).

FIELD dep_nom ||| UNSIGNED4 — the dependent column number (i.e. classifier number).

FIELD w ||| REAL8 — the learned weight (i.e. coefficient).

FIELD SE ||| REAL8 — the Standard Error of the coefficient.

CONFIDENCE_MODEL_COEF Confidence_Model_Coef

Types \

	Confidence_Model_Coef
--	-----------------------

Model Coefficients with confidence intervals.

FIELD upper ||| REAL8 — the upper range of the confidence interval

FIELD lower ||| REAL8 — the lower range of the confidence interval

FIELD wi ||| UNSIGNED2 — No Doc

FIELD ind_col ||| UNSIGNED4 — No Doc

FIELD dep_nom ||| UNSIGNED4 — No Doc

FIELD w ||| REAL8 — No Doc

FIELD se ||| REAL8 — No Doc

PVAL_MODEL_COEF pval_Model_Coef

Types \

	pval_Model_Coef
--	-----------------

Model coefficients with z and p-value.

FIELD z ||| REAL8 — the z value.

FIELD p_value ||| REAL8 — the p_value of the coefficient.

FIELD wi ||| UNSIGNED2 — No Doc

FIELD ind_col ||| UNSIGNED4 — No Doc

FIELD dep_nom ||| UNSIGNED4 — No Doc

FIELD w ||| REAL8 — No Doc

FIELD se ||| REAL8 — No Doc

FULL_MODEL_COEF Full_Model_Coef

Types \

Full_Model_Coef

Model coefficients with confidence intervals and p-value

FIELD z ||| REAL8 — the z value.

FIELD p_value ||| REAL8 — the p_value of the coefficient.

FIELD upper ||| REAL8 — the upper range of the confidence interval

FIELD lower ||| REAL8 — the lower range of the confidence interval

FIELD wi ||| UNSIGNED2 — No Doc

FIELD ind_col ||| UNSIGNED4 — No Doc

FIELD dep_nom ||| UNSIGNED4 — No Doc

FIELD w ||| REAL8 — No Doc

FIELD se ||| REAL8 — No Doc

EXTERNAL_COEF External_Coef

Types \

External_Coef

Model coefficients, confidence intervals, and p-value, plus independent field names, for each coefficient.

FIELD isIntercept ||| BOOLEAN — Boolean field is TRUE if this is the intercept coefficient, otherwise FALSE.

FIELD field_name ||| STRING — the name of the independent field for this coefficient.

FIELD w ||| REAL8 — the coefficient value (weight)

FIELD SE ||| REAL8 — the Standard Error of the coefficient

FIELD z ||| REAL8 — the z value.

FIELD p_value ||| REAL8 — the p-value.

FIELD upper ||| REAL8 — the upper bound of the confidence interval.

FIELD lower ||| REAL8 — the lower bound of the confidence interval.

FIELD ind_col ||| UNSIGNED4 — the field number of the independent field for this coefficient.

EXTERNAL_MODEL External_Model

Types \

	External_Model
--	----------------

Expanded version of a model with statistics and field names.

Field names include independent data field names, dependent data field names and work-item names.

FIELD work_item ||| STRING — the work-item's name.

FIELD response_field ||| STRING — the name of the classifier field (i.e. dependent field name).

FIELD wi ||| UNSIGNED2 — the work-item number.

FIELD dep_nom ||| UNSIGNED4 — the field number of the classifier (i.e. dependent field number).

FIELD coef ||| TABLE (External_Coef) — child dataset of External_Coef format. One record per model coefficient.

SEE External_Coef

RAW_PREDICTION Raw_Prediction

Types \

	Raw_Prediction
--	----------------

Record for raw prediction without confidence information.

FIELD raw ||| REAL8 — the raw prediction value.

FIELD wi ||| UNSIGNED2 — No Doc

FIELD id ||| UNSIGNED8 — No Doc

FIELD number ||| UNSIGNED4 — No Doc

OBSERVATION_DEVIANCE Observation_Deviance

Types \

Observation_Deviance

Record to contain deviance information about each observation.

FIELD wi ||| UNSIGNED2 — the work-item number.

FIELD id ||| UNSIGNED8 — the record id (i.e. observation number).

FIELD classifier ||| UNSIGNED4 — the dependent field number.

FIELD actual ||| INTEGER4 — the actual (i.e. ground truth value).

FIELD predicted ||| INTEGER4 — the value predicted by the model.

FIELD mod_ll ||| REAL8 — log likelihood of the model

FIELD mod_dev_component ||| REAL8 — the deviance explained by the model

FIELD mod_dev_residual ||| REAL8 — the deviance not explained by the model (i.e. the residual)

FIELD nil ||| — ll log likelihood of the nil model (i.e. model with only a constant term).

FIELD nil_dev_component ||| REAL8 — the deviance explained by the null model

FIELD nil_dev_residual ||| REAL8 — the deviance not explained by the null model (i.e. the residual)

FIELD nil_ll ||| REAL8 — No Doc

DEVIANCE_RECORD Deviance_Record

Types \

	Deviance_Record
--	-----------------

Record to hold deviance summary information about a model.

FIELD wi ||| UNSIGNED2 — the work-item number

FIELD classifier ||| UNSIGNED4 — the classifier number (i.e. field number of the dependent variable).

FIELD df ||| UNSIGNED8 — degrees-of-freedom of the chi squared distribution.

FIELD deviance ||| REAL8 — the total deviance for this classifier.

FIELD AIC ||| REAL8 — the Akaike Information Criteria value.

AOD_RECORD AOD_Record

Types \

	AOD_Record
--	------------

Record to hold Analysis of Deviance (AOD) information for a model.

FIELD wi ||| UNSIGNED2 — the work-item number

FIELD classifier ||| UNSIGNED4 — the classifier number (i.e. field number of the dependent variable).

FIELD df ||| UNSIGNED8 — degrees of freedom of the chi squared distribution.

FIELD residual_dev ||| REAL8 — the deviance not explained by the model.

FIELD deviance ||| REAL8 — the total deviance.

FIELD p ||| — value the probability that the null hypothesis is correct.

FIELD residual_df ||| UNSIGNED8 — No Doc

FIELD p_value ||| REAL8 — No Doc

FIELDNAME_MAPPING `FieldName_Mapping`

Types \

	<code>FieldName_Mapping</code>
--	--------------------------------

Layout used to hold the mapping between a field's number and its name.

FIELD `orig_name` ||| STRING — typically the field number as a text string (e.g. '2').

FIELD `assigned_name` ||| STRING — the textual name of the field (e.g. 'age').

WORKITEM_MAPPING `WorkItem_Mapping`

Types \

	<code>WorkItem_Mapping</code>
--	-------------------------------

Layout used to hold the mapping between a work-item number and a textual name for that work-item.

FIELD `wi` ||| UNSIGNED2 — the work-item number.

FIELD `orig_wi` ||| STRING — the work-item name.

LUCI_REC `LUCI_Rec`

Types \

	<code>LUCI_Rec</code>
--	-----------------------

Layout to store the lines of a generated LUCI model file.

FIELD `line` ||| STRING — the text for a single line for the LUCI file.

LUCI_MODEL_RQST LUCI_Model_Rqst

Types \

	LUCI_Model_Rqst
--	-----------------

Format for information to guide the generation of a LUCI file.

FIELD model_id ||| STRING — a short textual name for the model as used in the LUCI L1MD format.

FIELD model_name ||| STRING — an expanded name for the model as used in the LUCI L1MD format.

FIELD response_field ||| STRING — name of the dependent field (aka classifier name).

FIELD wi_list ||| SET (STRING) — can be set to ['ALL'], or can be a list of work-item names.

FIELD score_card_name ||| STRING — the score card name pattern (see LUCI_Model.ecl for details).
