

International Cybersecurity and Digital Forensics Academy (ICDFA)

CTF 1: Practical Lab Submission

CIP-A105 — Offensive Security Operations II

Student Name	Lilian Wanjiku
Registration Number	EHIT/2026/16969
Cohort / Programme	Cohort 11
Submission Date	17th September 2026
Instructor / Assessor	Abubakar Salisu

Virtual Machine Information

- **Attacker VM**
Linux Distribution: Kali GNU/Linux Rolling
Kernel: Linux 6.12.13-amd64
Hostname: kali
Username: kali
IP Address: 192.168.56.101
- **Target VM**
Name: OPFOR-01 (Operation Iron Raven)
Distribution: Debian GNU/Linux 8 (Raven)
IP Address: 192.168.56.102
Network Segment: 192.168.56.0/24 — Host-Only isolated lab network

Tools and Environment Used

- **Oracle VM VirtualBox** — Used to host both the attacker VM and OPFOR-01 on an isolated Host-Only network segment.
- **Kali Linux** — Operating system used to perform all offensive activity including scanning, enumeration, exploitation, and post-exploitation.
- **OPFOR-01** — Instructor-issued intentionally vulnerable target VM running Debian 8, Apache 2.4.10, WordPress 4.8.7, OpenSSH 6.7p1, and an exposed PHPMailer 5.2.16 vendor library.
- **nmap** — Used for host discovery, full TCP/UDP port sweeping, service version detection, and vulnerability script scanning.

- **arp-scan** — Used for ARP-based host discovery to confirm OPFOR-01's IP address.
- **gobuster** — Used for web content and directory discovery against the Apache web server.
- **curl** — Used for HTTP header inspection, manual banner grabbing, WordPress author enumeration, vendor directory inspection, and PHPMailer version retrieval.
- **whatweb** — Used for web technology fingerprinting.
- **searchsploit** — Used to search the local Exploit-DB database for known exploits matching identified service versions.
- **hydra** — Used for dictionary-based credential attack against the WordPress wp-login.php endpoint using rockyou.txt.
- **Python 3** — Used to write and execute a custom exploit script targeting CVE-2016-10033 via the contact form.
- **Firefox Browser** — Used to manually browse the Raven Security website and WordPress installation.
- **Windows Snipping Tool** — Used to capture screenshots as evidence of completed lab tasks.

Safety Controls Used

- Both virtual machines were confirmed on the isolated Host-Only Adapter network (192.168.56.0/24) before any offensive activity commenced. No bridged adapter was active during the assessment.
- A clean baseline snapshot named CIP-A105-CTF1-CLEAN-BASELINE was taken before any reconnaissance traffic was sent to OPFOR-01.
- All offensive activity was conducted exclusively against OPFOR-01 at 192.168.56.102. No external or production system was contacted at any point.
- The attacker VM had no route to the internet or any production network during the assessment, confirmed via ip a and ip route.
- Only harmless proof-of-concept techniques were used to demonstrate impact. No destructive actions, unnecessary data exfiltration, or persistence mechanisms beyond what was required for evidence collection were deployed.
- No credentials, flags, exploitation paths, or screenshots were shared with other learners.
- The clean baseline snapshot was restored at the conclusion of the assessment.

Executive Summary

A black-box offensive security assessment was conducted against OPFOR-01, an instructor-issued target virtual machine hosted on an isolated laboratory network. The assessment was conducted independently with no prior knowledge of the target's configuration, credentials, or vulnerabilities.

Scope and Rules of Engagement

- **Target:** OPFOR-01 — single instructor-issued virtual machine
- **Target IP:** 192.168.56.102
- **Attacker System:** ICDFA-KALI-LINUX at 192.168.56.101
- **Network:** Isolated Host-Only Adapter (192.168.56.0/24) — no internet, no bridged or production exposure
- **Assessment Type:** Black-box, unauthenticated, individual

Authorized techniques:

Host discovery and network reconnaissance, full TCP and UDP port scanning, service version detection and manual banner grabbing, web content enumeration and technology fingerprinting, vulnerability research and exploit validation, credential testing against identified authentication endpoints, exploitation of validated vulnerabilities against OPFOR-01 only, post-exploitation enumeration and privilege escalation analysis, artifact and flag recovery.

Prohibited Actions

- Any activity against external, production, or internet-connected systems. Sharing of credentials, flags, screenshots, or exploitation paths with other learners. Destructive actions against the target. Use of another learner's attack path or walkthrough.
- ROE compliance was maintained throughout. Both VMs were confirmed on the isolated network before any offensive activity commenced.

Reconnaissance

Host discovery was performed using two independent methods to avoid relying on a single tool's output.

Enumeration

```

ICDFA-KALI-LINUX (ICDFA-CIP-A104-BASELINE) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

--(kali@kali)~--
$ nmap -sC -sV -p 22,80,111,56816 -oN ~/targeted.txt 192.168.56.100 192.168.56.102
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-16 02:06 -0400
Nmap scan report for 192.168.56.100
Host is up (0.00001s latency).
PORT      STATE SERVICE VERSION
22/tcp    closed ssh
80/tcp    closed http
111/tcp   closed rpcbind
56816/tcp closed unknown
MAC Address: 08:00:27:CD:30:48 (Oracle VirtualBox virtual NIC)

Nmap scan report for 192.168.56.102
Host is up (0.0021s latency).
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 6.7p1 Debian 5+deb8u4 (protocol 2.0)
|_ ssh-hostkey:
|_ 102A 26:81:c1:f3:5e:01:ef:93:49:3d:91:3e:ae:8b:3c:fc (DSA)
|_ 2046 31:58:01:19:4d:a2:08:a6:b9:06:48:98:1c:97:aa:53 (RSA)
|_ 256 1f:77:31:19:d6:30:e1:6d:ca:77:87:76:84:d3:a9:a0 (ECDSA)
|_ 256 0e:85:71:a8:a2:c3:00:69:9c:91:c0:3f:84:18:df:ae (ED25519)
80/tcp    open  http     Apache httpd 2.4.10 ((Debian))
|_ http-server-header: Apache/2.4.10 (Debian)
|_ http-title: Raven Security
111/tcp   open  rpcbind  2-4 (RPC #100000)
|_ rpcinfo:
|_  program version  port/proto  service
|_ 100000  2,3,4      111/tcp    rpcbind
|_ 100000  2,3,4      111/udp    rpcbind
|_ 100000  3,4        111/tcp6   rpcbind
|_ 100000  3,4        111/udp6   rpcbind
|_ 100024  1          41891/udp6 status
|_ 100024  1          51985/tcp6 status
|_ 100024  1          5447/udp   status
|_ 100024  1          56816/tcp  status
56816/tcp open  status  1 (RPC #100024)
MAC Address: 08:00:27:47:E1:84 (Oracle VirtualBox virtual NIC)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 2 IP addresses (2 hosts up) scanned in 13.15 seconds

--(kali@kali)~--
$ nmap -p- -T4 -oN ~/full_tcp.txt 192.168.56.100 192.168.56.102
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-16 01:55 -0400
Nmap scan report for 192.168.56.100
Host is up (0.00037s latency).
All 65535 scanned ports on 192.168.56.100 are in ignored states.
Not shown: 65535 closed tcp ports (reset)
MAC Address: 08:00:27:CD:30:48 (Oracle VirtualBox virtual NIC)

Nmap scan report for 192.168.56.102
Host is up (0.00000s latency).
Not shown: 65531 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
111/tcp   open  rpcbind
56816/tcp open  unknown
MAC Address: 08:00:27:47:E1:84 (Oracle VirtualBox virtual NIC)

Nmap done: 2 IP addresses (2 hosts up) scanned in 75.94 seconds

--(kali@kali)~--
$ sudo nmap -sU -p- --top-ports 100 -oN ~/udp_top100.txt 192.168.56.100 192.168.56.102
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-16 01:56 -0400
Nmap scan report for 192.168.56.100
Host is up (0.00089s latency).
Not shown: 99 closed udp ports (port-unreach)
PORT      STATE SERVICE
67/udp    open|filtered dhcp
MAC Address: 08:00:27:CD:30:48 (Oracle VirtualBox virtual NIC)

Nmap scan report for 192.168.56.102
Host is up (0.0035s latency).
Not shown: 50 open|filtered udp ports (no-response), 49 closed udp ports (port-unreach)
PORT      STATE SERVICE
111/udp   open  rpcbind
MAC Address: 08:00:27:47:E1:84 (Oracle VirtualBox virtual NIC)


Nmap done: 2 IP addresses (2 hosts up) scanned in 47.95 seconds

```

Port	Protocol	Service	Version
22	TCP	SSH	OpenSSH 6.7p1 Debian 5+deb8u4
80	TCP	HTTP	Apache httpd 2.4.10 (Debian)
111	TCP/UDP	rpcbind	v2-4

56816	TCP	RPC status	—
-------	-----	------------	---

Web Enumeration



```

(kali@kali)~$ curl -sI http://192.168.56.102
HTTP/1.1 200 OK
Date: Wed, 16 Sep 2026 06:10:23 GMT
Server: Apache/2.4.10 (Debian)
Last-Modified: Sun, 12 Aug 2018 22:29:32 GMT
ETag: "41b3-5734482bdc00"
Accept-Ranges: bytes
Content-Length: 16019
Vary: Accept-Encoding
Content-Type: text/html

(kali@kali)~$ whatweb http://192.168.56.102
*Chhhhh/usr/lib/ruby/vendor_ruby/whatweb/scan.rb:78:in "alive?": Interrupt
From /usr/lib/ruby/vendor_ruby/whatweb/scan.rb:78:in "block (2 levels) in scan"
From /usr/lib/ruby/vendor_ruby/whatweb/scan.rb:78:in "map"
From /usr/lib/ruby/vendor_ruby/whatweb/scan.rb:78:in "block in scan"
From <internal:kernel>:187:in "loop"
From /usr/lib/ruby/vendor_ruby/whatweb/scan.rb:74:in "scan"
From /usr/bin/whatweb:709:in "<main>"

(kali@kali)~$ whatweb http://192.168.56.102
http://192.168.56.102 [200 OK] Apache[2.4.10], Bootstrap, Country[RESERVED][ZZ], HTML5, HTTPServer[Debian Linux][Apache/2.4.10 (Debian)], IP[192.168.56.102], JQuery[2.2.4], Meta-Author[codepixer], Script[text/javascript], Title[Raven Security]

(kali@kali)~$ gobuster dir -u http://192.168.56.102 -w /usr/share/wordlists/dirb/common.txt -o ~/gobuster.txt
gobuster v3.8.2
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url: http://192.168.56.102
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirb/common.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.8.2
[+] Timeout: 10s

Starting gobuster in directory enumeration mode

.htaccess (Status: 403) [Size: 298]
.htpasswd (Status: 403) [Size: 298]
.hta (Status: 403) [Size: 293]
.css (Status: 301) [Size: 314] [→ http://192.168.56.102/css/]
.fonts (Status: 301) [Size: 316] [→ http://192.168.56.102/fonts/]
.img (Status: 301) [Size: 314] [→ http://192.168.56.102/img/]
.index.html (Status: 200) [Size: 16019]
.js (Status: 301) [Size: 213] [→ http://192.168.56.102/js/]
.manual (Status: 301) [Size: 317] [→ http://192.168.56.102/manual/]
.server-status (Status: 403) [Size: 302]
.vendor (Status: 301) [Size: 317] [→ http://192.168.56.102/vendor/]
.wordpress (Status: 301) [Size: 320] [→ http://192.168.56.102/wordpress/]
Progress: 4613 / 4613 (100.00%)
Finished

```

Vulnerability Analysis

OpenSSH 6.7p1 — searchsploit returned username enumeration vulnerabilities for versions below 7.7. No direct RCE applicable. Classified as medium priority, secondary use only.

Apache 2.4.10 — searchsploit returned multiple entries. None directly applicable to this configuration without CGI or mod_ssl context. Classified as low exploitability in current configuration.

rpcbind — searchsploit returned Denial of Service entries only. Low priority — not a viable access vector.

```

ICDFA-KALI-LINUX (ICDFA-CIP-A104-BASELINE) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

kali@kali:~$ searchsploit openssh 6.7

Exploit Title | Path
-----|-----
OpenSSH 2.3 < 7.7 - Username Enumeration | linux/remote/45233.py
OpenSSH 2.3 < 7.7 - Username Enumeration (Poc) | linux/remote/45218.py
OpenSSH < 7.4 - 'UsePrivilegeSeparation Disabled' Forwarded Unix Domain Sockets Privilege Escalation | linux/local/40962.txt
OpenSSH < 7.4 - agent Protocol Arbitrary Library Loading | linux/remote/40963.txt
OpenSSH < 7.7 - User Enumeration (2) | linux/remote/45939.py

Shellcodes: No Results

kali@kali:~$ searchsploit apache 2.4.10

Exploit Title | Path
-----|-----
Apache + PHP < 5.3.12 / < 5.4.2 - cgi-bin Remote Code Execution | php/remote/29290.c
Apache + PHP < 5.3.12 / < 5.4.2 - Remote Code Execution + Scanner | php/remote/29316.py
Apache < 2.2.34 / < 2.4.27 - OPTIONS Memory Leak | linux/webapps/42745.py
Apache CXF < 2.5.10/2.6.7/2.7.4 - Denial of Service | multiple/dos/26710.txt
Apache mod_ssl < 2.8.7 OpenSSL - 'OpenFuck.c' Remote Buffer Overflow | unix/remote/21671.c
Apache mod_ssl < 2.8.7 OpenSSL - 'OpenFuckV2.c' Remote Buffer Overflow (1) | unix/remote/764.c
Apache mod_ssl < 2.8.7 OpenSSL - 'OpenFuckV2.c' Remote Buffer Overflow (2) | unix/remote/47080.c
Apache OpenMeetings 1.9.x < 3.1.0 - 'ZIP' File Directory Traversal | linux/webapps/39642.txt
Apache Tomcat < 5.5.17 - Remote Directory Listing | multiple/remote/2963.txt
Apache Tomcat < 6.0.18 - 'utf8' Directory Traversal | unix/remote/14489.c
Apache Tomcat < 6.0.18 - 'utf8' Directory Traversal (Poc) | multiple/remote/6229.txt
Apache Tomcat < 9.0.1 (Beta) / < 8.5.23 / < 8.0.47 / < 7.0.8 - JSP Upload Bypass / Remote Code Execution (1) | windows/webapps/42953.txt
Apache Tomcat < 9.0.1 (Beta) / < 8.5.23 / < 8.0.47 / < 7.0.8 - JSP Upload Bypass / Remote Code Execution (2) | jsp/webapps/42966.py
Apache Xerces-C XML Parser < 3.1.2 - Denial of Service (Poc) | linux/dos/36906.txt
Webroot Shoutbox < 2.32 (Apache) - Local File Inclusion / Remote Code Execution | linux/remote/34.pl

Shellcodes: No Results

kali@kali:~$ searchsploit rpcbind

Exploit Title | Path
-----|-----
rpcbind - CALLIT procedure UDP Crash (Poc) | linux/dos/26887.rb
RPCbind / libtirpc - Denial of Service | linux/dos/41974.rb
victis Venema RPCbind Replacement 2.1 - Denial of Service | unix/dos/28376.txt

Shellcodes: No Results

kali@kali:~$

```

PHPMailer 5.2.16 — searchsploit confirmed multiple Remote Code Execution entries for all versions below 5.2.18, 5.2.19, and 5.2.20. CVE-2016-10033 confirmed applicable. The flaw allows injection of arbitrary shell arguments via the email field passed to PHP's mail() function.

```

ICDFA-KALI-LINUX (ICDFA-CIP-A104-BASELINE) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

kali@kali:~$ searchsploit -x php/webapps/40970.php

Exploit: PHPMailer < 5.2.18 - Remote Code Execution
URL: https://www.exploit-db.com/exploits/40970
Path: /usr/share/exploitdb/exploits/php/webapps/40970.php
Codes: CVE-2016-10033
Verified: False
File Type: PHP script, ASCII text
The requested URL /contact.html was not found on this server.

kali@kali:~$ searchsploit -x php/webapps/40970.php

Exploit: PHPMailer < 5.2.18 - Remote Code Execution
URL: https://www.exploit-db.com/exploits/40970
Path: /usr/share/exploitdb/exploits/php/webapps/40970.php
Codes: CVE-2016-10033
Verified: False
File Type: PHP script, ASCII text
Copied to: /home/kali/40970.php

kali@kali:~$

```

WordPress wp-login.php — No lockout mechanism observed during manual testing. Two confirmed valid usernames. Dictionary attack initiated via hydra against user michael using rockyou.txt.

nmap vuln scan — Confirmed WordPress login page, CSRF candidates on multiple form endpoints, directory listing on /vendor/ flagged as interesting.

```

ICDFA-KALI-LINUX (ICDFA-CIP-A104-BASELINE) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

kali@kali: ~
$ nmap -script vuln -p 22,80,111,56816 -oN -/vuln_scan.txt 192.168.56.102
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-16 02:41 -0400
Nmap scan report for 192.168.56.102
Host is up (0.0033s latency).

PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
|_http-dombased-xss: Couldn't find any DOM based XSS.
|_http-csrf:
|_Spidering limited to: maxdepth=3; maxpagecount=20; withinhost=192.168.56.102
|_Found the following possible CSRF vulnerabilities:
|_
|_   Path: http://192.168.56.102:80/
|_   Form id:
|_   Form action: https://spondonit.us12.list-manage.com/subscribe/post?u=1462626880adelac87bd9c93abid=92a4423d01
|_
|_   Path: http://192.168.56.102:80/wordpress/
|_   Form id: search-form-6aaa3a0b3a27c
|_   Form action: http://raven.local/wordpress/
|_
|_   Path: http://192.168.56.102:80/team.html
|_   Form id:
|_   Form action: https://spondonit.us12.list-manage.com/subscribe/post?u=1462626880adelac87bd9c93abid=92a4423d01
|_
|_   Path: http://192.168.56.102:80/service.html
|_   Form id:
|_   Form action: https://spondonit.us12.list-manage.com/subscribe/post?u=1462626880adelac87bd9c93abid=92a4423d01
|_
|_   Path: http://192.168.56.102:80/index.html
|_   Form id:
|_   Form action: https://spondonit.us12.list-manage.com/subscribe/post?u=1462626880adelac87bd9c93abid=92a4423d01
|_http-stored-xss: Couldn't find any stored XSS vulnerabilities.
|_http-enum:
|_   /wordpress/: Blog
|_   /wordpress/wp-login.php: Wordpress login page.
|_   /css/: Potentially interesting directory w/ listing on 'apache/2.4.10 (debian)'
|_   /img/: Potentially interesting directory w/ listing on 'apache/2.4.10 (debian)'
|_   /js/: Potentially interesting directory w/ listing on 'apache/2.4.10 (debian)'
|_   /manual/: Potentially interesting folder
|_   /vendor/: Potentially interesting directory w/ listing on 'apache/2.4.10 (debian)'
111/tcp    open  rpcbind
56816/tcp  open  unknown
MAC Address: 08:00:27:47:E1:04 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 34.56 seconds

kali@kali: ~

```

Primary hypothesis: PHPMailer 5.2.16 at contact.php exploitable via CVE-2016-10033 — injecting shell parameters into the email field causes sendmail to write a PHP webshell to the server filesystem. Confidence: High based on exact version match against all listed CVE ranges.

Secondary hypothesis: WordPress wp-login.php susceptible to dictionary credential attack — hydra running in background against confirmed username michael. Confidence: Medium pending wordlist completion.

Findings


Finding 001 — WordPress Username Enumeration via Author Parameter

CWE-284 | Severity: Medium | Confidence: High

WordPress discloses registered usernames via unauthenticated HTTP GET requests using the author ID parameter. No authentication required. Confirmed usernames: michael (ID 1) and steven (ID 2). author ID 3 returned Page not found confirming enumeration was exhaustive.

Impact: Valid usernames directly enabled targeted credential attacks against wp-login.php and reduced attack complexity.

Remediation: Disable author archive pages; block author parameter requests via .htaccess or security plugin; disable REST API user endpoint.




Right Ctrl

CWE-548 | Severity: High | Confidence: High

Impact: PHPMailer version 5.2.16 retrieved directly from the VERSION file, enabling immediate and precise CVE targeting. Without this disclosure, version identification would have required additional effort.

Remediation: Set Options -Indexes in Apache configuration globally; move vendor/dependency libraries outside the web root; ensure PHP library files are never directly accessible via HTTP.



```
ICDFA-KALI-LINUX (ICDFA-CIP-A104-BASELINE) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

kali@kali:~$ curl -s http://192.168.56.102/vendor/
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN>
<html>
<head>
<title>Index of /vendor/</title>
</head>
<body>
<h1>Index of /vendor/</h1>
<table>
<tr><th>valign="top"</th><th><a href="/">Name</a></th><th><a href="/C-Mj0-A">Last modified</a></th><th><a href="/C-Sj0-A">Size</a></th><th><a href="/C-Dj0-A">Description</a></th></tr>
<tr><th colspan="5"><hr></th></tr>
<tr><td>valign="top"</td><td><a href="/">Parent Directory</a></td><td align="right"> - </td><td align="right"></td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/LICENSE">LICENSE</a></td><td align="right">2018-08-13 07:56 </td><td align="right">20K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/PATH">PATH</a></td><td align="right">2018-11-09 08:17 </td><td align="right">62 </td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/PHPMailerAutoload.php">PHPMailerAutoload.php</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>1.6K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/README.md">README.md</a></td><td align="right">2018-08-13 07:56 </td><td align="right">13K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/SECURITY.md">SECURITY.md</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>2.3K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/VERSION">VERSION</a></td><td align="right">2018-08-13 07:56 </td><td align="right">6 </td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/changelog.md">changelog.md</a></td><td align="right">2018-08-13 07:56 </td><td align="right">38K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/class.phpmailer.php">class.phpmailer.php</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>141K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/class.phpmailerauth.php">class.phpmailerauth.php</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>7.0K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/class.phpmailerauthgoogle.php">class.phpmailerauthgoogle.php</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>44K</td><td align="right"></td></tr>
</table>
<tr><td>valign="top"</td><td><a href="/class.phpmailer.lock">class.phpmailer.lock</a></td><td align="right">2018-08-13 07:56 </td><td align="right"></td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/composer.json">composer.json</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>1.1K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/examples">examples</a></td><td align="right">2018-08-13 07:56 </td><td align="right"></td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/extras">extras</a></td><td align="right">2018-08-13 07:56 </td><td align="right"></td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/get_outh_token.php">get_outh_token.php</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>34.9K</td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/language">language</a></td><td align="right">2018-08-13 07:56 </td><td align="right"></td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/test">test</a></td><td align="right">2018-08-13 07:56 </td><td align="right"></td><td align="right"></td></tr>
<tr><td>valign="top"</td><td><a href="/travis.phpunit.xml.dist">travis.phpunit.xml.dist</a></td><td align="right">2018-08-13 07:56 </td><td align="right">>1.0K</td><td align="right"></td></tr>
</table>
<tr><th colspan="5"><hr></th></tr>
</table>
<address>Apache/2.4.10 (Debian) Server at 192.168.56.102 Port 80</address>
</body></html>

kali@kali:~$
```

Remediation

Conclusion