

Acme Corp API Documentation v3.2

API Overview

Base URL: `https://api.acmecorp.com/v3`

Authentication: All API requests require a Bearer token in the Authorization header.

Rate Limits: Free tier: 100 requests/hour. Pro tier: 10,000 requests/hour.

Response Format: All responses are in JSON format.

Authentication Endpoint:

POST `/auth/token`

Body: `{"email": "user@example.com", "password": "yourpassword"}`

Response: `{"token": "eyJhbGciOi...", "expires_in": 3600}`

The token is valid for 1 hour. Use the refresh endpoint to get a new token without re-authenticating:

POST `/auth/refresh`

Header: Authorization: Bearer `<current_token>`

Response: `{"token": "newtoken...", "expires_in": 3600}`

User Management Endpoints

GET /users - List all users (admin only)

Query Parameters:

- page (int): Page number, default 1
- limit (int): Results per page, default 20, max 100
- role (string): Filter by role (admin, user, viewer)

Response: {"users": [...], "total": 150, "page": 1, "pages": 8}

GET /users/{id} - Get a specific user

Response: {"id": 42, "name": "Alice", "email": "alice@example.com", "role": "admin"}

POST /users - Create a new user (admin only)

Body: {"name": "Bob", "email": "bob@example.com", "role": "user"}

Response: 201 Created with user object

PUT /users/{id} - Update a user

Body: {"name": "Updated Name"} (partial updates allowed)

Response: Updated user object

DELETE /users/{id} - Delete a user (admin only)

Response: 204 No Content

Error Codes:

- 400 - Bad Request (invalid parameters)
- 401 - Unauthorized (missing or invalid token)
- 403 - Forbidden (insufficient permissions)
- 404 - Not Found
- 429 - Rate Limit Exceeded

Data Endpoints

GET /data/reports - List available reports

Query Parameters:

- start_date (string): Format YYYY-MM-DD
- end_date (string): Format YYYY-MM-DD
- type (string): daily, weekly, monthly

POST /data/export - Export data as CSV

Body: {"report_id": 123, "format": "csv", "filters": {"department": "engineering"}}

Response: {"download_url": "https://...", "expires_in": 300}

WebSocket Endpoint:

ws://api.acmecorp.com/v3/stream

Use for real-time data updates. Supports channels:

- "trades" - real-time trade data
- "alerts" - system alerts
- "metrics" - live performance metrics

Message format: {"channel": "trades", "action": "subscribe"}

Server pushes: {"channel": "trades", "data": {...}, "timestamp": "..."}

Webhook Configuration:

POST /webhooks - Register a webhook

Body: {"url": "https://yoursite.com/hook", "events": ["user.created", "report.ready"]}

The webhook payload includes: event type, timestamp, and relevant data object.