

Lab 8

Meihe Liu

11:59PM April 29, 2021

I want to make some use of my CART package. Everyone please try to run the following:

```
if (!pacman::p_isinstalled(YARF)){
  pacman::p_install_gh("kapelner/YARF/YARFJARs", ref = "dev")
  pacman::p_install_gh("kapelner/YARF/YARF", ref = "dev", force = TRUE)
}
options(java.parameters = "-Xmx4000m")
pacman::p_load(YARF)
```

For many of you it will not work. That's okay.

Throughout this part of this assignment you can use either the `tidyverse` package suite or `data.table` to answer but not base R. You can mix `data.table` with `magrittr` piping if you wish but don't go back and forth between `tbl_df`'s and `data.table` objects.

```
pacman::p_load(tidyverse, magrittr, data.table)
```

We will be using the `storms` dataset from the `dplyr` package. Filter this dataset on all storms that have no missing measurements for the two diameter variables, "ts_diameter" and "hu_diameter".

```
data(storms)

storms2 = storms %>%
  filter(!is.na(ts_diameter) & !is.na(hu_diameter) & hu_diameter>0)

storms2

## # A tibble: 1,022 x 13
##   name   year month   day  hour   lat   long status   category  wind pressure
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <chr>      <ord>    <int>    <int>
## 1 Alex   2004     8     3     6   33   -77.4 hurricane 1       70     983
## 2 Alex   2004     8     3    12   34.2 -76.4 hurricane 2       85     974
## 3 Alex   2004     8     3    18   35.3 -75.2 hurricane 2       85     972
## 4 Alex   2004     8     4     0   36   -73.7 hurricane 1       80     974
## 5 Alex   2004     8     4     6   36.8 -72.1 hurricane 1       80     973
## 6 Alex   2004     8     4    12   37.3 -70.2 hurricane 2       85     973
## 7 Alex   2004     8     4    18   37.8 -68.3 hurricane 2       95     965
## 8 Alex   2004     8     5     0   38.5 -66   hurricane 3      105     957
## 9 Alex   2004     8     5     6   39.5 -63.1 hurricane 3      105     957
## 10 Alex  2004     8     5    12   40.8 -59.6 hurricane 3      100     962
## # ... with 1,012 more rows, and 2 more variables: ts_diameter <dbl>,
## #   hu_diameter <dbl>
```

From this subset, create a data frame that only has storm, observation period number for each storm (i.e., 1, 2, ..., T) and the "ts_diameter" and "hu_diameter" metrics.

```

storms2 = storms2 %>%
  select(name,ts_diameter,hu_diameter)%>%
  group_by(name)%>%
  mutate(period = row_number())
storms2

```

```

## # A tibble: 1,022 x 4
## # Groups:   name [63]
##   name  ts_diameter hu_diameter period
##   <chr>      <dbl>      <dbl>   <int>
## 1 Alex         150.         46.0     1
## 2 Alex         150.         46.0     2
## 3 Alex         190.         57.5     3
## 4 Alex         178.         63.3     4
## 5 Alex         224.         74.8     5
## 6 Alex         224.         74.8     6
## 7 Alex         259.         74.8     7
## 8 Alex         259.         80.6     8
## 9 Alex         345.         80.6     9
## 10 Alex        437.         80.6    10
## # ... with 1,012 more rows

```

Create a data frame in long format with columns “diameter” for the measurement and “diameter_type” which will be categorical taking on the values “hu” or “ts”.

```

storms_long = pivot_longer(storms2, cols = matches("diameter"), names_to = "diameter")

storms_long

```

```

## # A tibble: 2,044 x 4
## # Groups:   name [63]
##   name  period diameter  value
##   <chr>  <int> <chr>      <dbl>
## 1 Alex      1 ts_diameter 150.
## 2 Alex      1 hu_diameter 46.0
## 3 Alex      2 ts_diameter 150.
## 4 Alex      2 hu_diameter 46.0
## 5 Alex      3 ts_diameter 190.
## 6 Alex      3 hu_diameter 57.5
## 7 Alex      4 ts_diameter 178.
## 8 Alex      4 hu_diameter 63.3
## 9 Alex      5 ts_diameter 224.
## 10 Alex     5 hu_diameter 74.8
## # ... with 2,034 more rows


```

Using this long-formatted data frame, use a line plot to illustrate both “ts_diameter” and “hu_diameter” metrics by observation period for four random storms using a 2x2 faceting. The two diameters should appear in two different colors and there should be an appropriate legend.

```

storms_sample = sample(unique(storms2$name), 4)
ggplot(storms_long)%>%
  filter(name %in% storms_sample)) +
  geom_line(aes(x = period, y = value, col = diameter)) +
  facet_wrap(name~.,nrow=2)

```



In this next first part of this lab, we will be joining three datasets in an effort to make a design matrix that predicts if a bill will be paid on time. Clean up and load up the three files. Then I'll rename a few features and then we can examine the data frames:

```
rm(list = ls())
pacman::p_load(tidyverse, magrittr, data.table, R.utils)
bills = fread("https://github.com/kapelner/QC_MATH_342W_Spring_2021/raw/master/labs/bills_dataset/bills")
payments = fread("https://github.com/kapelner/QC_MATH_342W_Spring_2021/raw/master/labs/bills_dataset/payments")
discounts = fread("https://github.com/kapelner/QC_MATH_342W_Spring_2021/raw/master/labs/bills_dataset/discounts")
setnames(bills, "amount", "tot_amount")
setnames(payments, "amount", "paid_amount")
head(bills)
```

```
##           id  due_date invoice_date tot_amount customer_id discount_id
## 1: 15163811 2017-02-12 2017-01-13  99490.77   14290629    5693147
## 2: 17244832 2016-03-22 2016-02-21  99475.73   14663516    5693147
## 3: 16072776 2016-08-31 2016-07-17  99477.03   14569622    7302585
## 4: 15446684 2017-05-29 2017-05-29  99478.60   14488427    5693147
## 5: 16257142 2017-06-09 2017-05-10  99678.17   14497172    5693147
## 6: 17244880 2017-01-24 2017-01-24  99475.04   14663516    5693147
```

```
head(payments)
```

```
##           id paid_amount transaction_date bill_id
## 1: 15272980   99165.60      2017-01-16 16571185
## 2: 15246935   99148.12      2017-01-03 16660000
## 3: 16596393   99158.06      2017-06-19 16985407
## 4: 16596651   99175.03      2017-06-19 17062491
## 5: 16687702   99148.20      2017-02-15 17184583
```

```
## 6: 16593510    99153.94      2017-06-11 16686215
```

```
head(discounts)
```

```
##           id num_days pct_off days_until_discount
## 1: 5000000    20      NA           NA
## 2: 5693147     NA       2           NA
## 3: 6098612    20      NA           NA
## 4: 6386294   120      NA           NA
## 5: 6609438     NA       1            7
## 6: 6791759    31       1           NA
```

```
bills = as_tibble(bills)
payments = as_tibble(payments)
discounts = as_tibble(discounts)
```

The unit we care about is the bill. The y metric we care about will be “paid in full” which is 1 if the company paid their total amount (we will generate this y metric later).

Since this is the response, we would like to construct the very best design matrix in order to predict y.

I will create the basic steps for you guys. First, join the three datasets in an intelligent way. You will need to examine the datasets beforehand.

```
bills_with_payments = left_join(bills, payments, by = c("id"= "bill_id"))
bills_with_payments
```

```
## # A tibble: 279,118 x 9
##           id due_date   invoice_date tot_amount customer_id discount_id   id.y
##       <dbl> <date>     <date>         <dbl>         <int>      <dbl>   <dbl>
## 1 15163811 2017-02-12 2017-01-13     99491.    14290629    5693147 14670862
## 2 17244832 2016-03-22 2016-02-21     99476.    14663516    5693147 16691206
## 3 16072776 2016-08-31 2016-07-17     99477.    14569622    7302585      NA
## 4 15446684 2017-05-29 2017-05-29     99479.    14488427    5693147 16591210
## 5 16257142 2017-06-09 2017-05-10     99678.    14497172    5693147 16538398
## 6 17244880 2017-01-24 2017-01-24     99475.    14663516    5693147 16691231
## 7 16214048 2017-03-08 2017-02-06     99475.    14679281    5693147 16845763
## 8 15579946 2016-06-13 2016-04-14     99476.    14450223    5693147 16593380
## 9 15264234 2014-06-06 2014-05-07     99480.    14532786    7708050 16957842
## 10 17031731 2017-01-12 2016-12-13     99476.    14658929    5693147      NA
## # ... with 279,108 more rows, and 2 more variables: paid_amount <dbl>,
## #   transaction_date <date>
```

```
bills_with_payments_with_discounts = left_join(bills_with_payments, discounts, by = c("discount_id" = "id"))
bills_with_payments_with_discounts
```

```
## # A tibble: 279,118 x 12
##           id due_date   invoice_date tot_amount customer_id discount_id   id.y
##       <dbl> <date>     <date>         <dbl>         <int>      <dbl>   <dbl>
## 1 15163811 2017-02-12 2017-01-13     99491.    14290629    5693147 14670862
## 2 17244832 2016-03-22 2016-02-21     99476.    14663516    5693147 16691206
## 3 16072776 2016-08-31 2016-07-17     99477.    14569622    7302585      NA
## 4 15446684 2017-05-29 2017-05-29     99479.    14488427    5693147 16591210
## 5 16257142 2017-06-09 2017-05-10     99678.    14497172    5693147 16538398
## 6 17244880 2017-01-24 2017-01-24     99475.    14663516    5693147 16691231
## 7 16214048 2017-03-08 2017-02-06     99475.    14679281    5693147 16845763
## 8 15579946 2016-06-13 2016-04-14     99476.    14450223    5693147 16593380
## 9 15264234 2014-06-06 2014-05-07     99480.    14532786    7708050 16957842
```

```
## 10 17031731 2017-01-12 2016-12-13      99476.    14658929    5693147      NA
## # ... with 279,108 more rows, and 5 more variables: paid_amount <dbl>,
## #   transaction_date <date>, num_days <int>, pct_off <dbl>,
## #   days_until_discount <int>
```

Now create the binary response metric `paid_in_full` as the last column and create the beginnings of a design matrix `bills_data`. Ensure the unit / observation is bill i.e. each row should be one bill!

```
bills_data = bills_with_payments_with_discounts%>%
  mutate(tot_amount = if_else(is.na(pct_off), tot_amount, tot_amount*(1-pct_off/100 )))%>%
  group_by(id)%>%
  mutate(sum_of_payment_amount = sum(paid_amount))%>%
  mutate(paid_in_full = if_else(sum_of_payment_amount >= tot_amount, 1, 0, missing = 0))%>%
  slice(1)%>%
  ungroup()
table(bills_data$paid_in_full, useNA = "always")
```

```
##
##      0      1  <NA>
## 112664 113770      0
```

How should you add features from transformations (called “featurization”)? What data type(s) should they be? Make some features below if you think of any useful ones. Name the columns appropriately so another data scientist can easily understand what information is in your variables.

```
pacman::p_load("lubridate")
bills_data = bills_data %>%
  select(-id, -id.y, -num_days, -transaction_date, -pct_off, -days_until_discount, -sum_of_payment_amount)
  mutate(num_days_to_pay = as.integer(ymd(due_date) - ymd(invoice_date))) %>%
  select(-due_date, -invoice_date) %>%
  mutate(discount_id = as.factor(discount_id)) %>%
  group_by(customer_id) %>%
  mutate(bill_num = row_number()) %>%
  ungroup() %>%
  select(-customer_id) %>%
  relocate(paid_in_full, .after = last_col())
```

Now let’s do this exercise. Let’s retain 25% of our data for test.

```
K = 4
test_indices = sample(1 : nrow(bills_data), round(nrow(bills_data) / K))
train_indices = setdiff(1 : nrow(bills_data), test_indices)
bills_data_test = bills_data[test_indices, ]
bills_data_train = bills_data[train_indices, ]
```

Now try to build a classification tree model for `paid_in_full` with the features (use the `Xy` parameter in `YARF`). If you cannot get `YARF` to install, use the package `rpart` (the standard R tree package) instead. You will need to install it and read through some documentation to find the correct syntax.

Warning: this data is highly anonymized and there is likely zero signal! So don’t expect to get predictive accuracy. The value of the exercise is in the practice. I think this exercise (with the joining exercise above) may be one of the most useful exercises in the entire semester.

```
install.packages('rpart')
```

```
## Installing package into '/home/rstudio-user/R/x86_64-pc-linux-gnu-library/4.0'
## (as 'lib' is unspecified)
```

```
pacman::p_load(rpart)
mod1 = rpart(paid_in_full ~., data = bills_data_train, method = "class")
mod1

## n= 169826
##
## node), split, n, loss, yval, (yprob)
##      * denotes terminal node
##
## 1) root 169826 84498 1 (0.49755632 0.50244368)
##    2) discount_id=5e+06,6098612,6609438,7079442,7197225,7302585,7397895,7484907,7564949,7708050,8091
##    3) discount_id=5693147,6945910,7890372,7944439,7995732,8258097,8367296,8806662,9043051,9060443 13
##    6) tot_amount< 99476.98 117817 47789 1 (0.40562058 0.59437942)
##    12) bill_num>=1240.5 31238 13864 0 (0.55618157 0.44381843)
##    24) tot_amount>=97487.14 16246 5944 0 (0.63412532 0.36587468) *
##    25) tot_amount< 97487.14 14992 7072 1 (0.47171825 0.52828175)
##    50) bill_num< 3060.5 9658 4354 0 (0.54918203 0.45081797) *
##    51) bill_num>=3060.5 5334 1768 1 (0.33145857 0.66854143) *
##    13) bill_num< 1240.5 86579 30415 1 (0.35129766 0.64870234) *
##    7) tot_amount>=99476.98 18675 4006 1 (0.21451138 0.78548862) *
```


For those of you who installed YARF, what are the number of nodes and depth of the tree?

```
nrow(mod1$frame)
```

```
## [1] 11
```

For those of you who installed YARF, print out an image of the tree.

```
plot(mod1, uniform=TRUE)
text(mod1, use.n=TRUE, all=TRUE, cex=.5)
```



Predict on the test set and compute a confusion matrix.

```
yhat = predict(mod1, bills_data_test, type = c("class"), na.action = na.pass)
oos_confus_matrix = table(bills_data_test$paid_in_full,yhat )
oos_confus_matrix
```

```
##      yhat
##      0      1
## 0 15991 12175
```

```
## 1 3573 24869
```

Report the following error metrics: misclassification error, precision, recall, F1, FDR, FOR.

```
n = sum(oos_confus_matrix)
fp = oos_confus_matrix[1, 2]
fn = oos_confus_matrix[2, 1]
tp = oos_confus_matrix[2, 2]
tn = oos_confus_matrix[1, 1]
num_predicted_pos = sum(oos_confus_matrix[, 2])
num_predicted_neg = sum(oos_confus_matrix[, 1])
num_pos = sum(oos_confus_matrix[2, ])
num_neg = sum(oos_confus_matrix[1, ])
precision = tp / num_predicted_pos
cat("precision", round(precision * 100, 2), "%\n")
```

```
## precision 67.13 %
```

```
recall = tp / num_pos
cat("recall", round(recall * 100, 2), "%\n")
```

```
## recall 87.44 %
```

```
FDR = 1 - precision
cat("FDR", round(FDR * 100, 2), "%\n")
```

```
## FDR 32.87 %
```

```
FOR = fn / num_predicted_neg
cat("FOR", round(FOR * 100, 2), "%\n")
```

```
## FOR 18.26 %
```

```
ME = (fn + fp) / n
cat("ME", round(ME * 100, 2), "%\n")
```

```
## ME 27.82 %
```

Is this a good model? (yes/no and explain).

#TO-DO

There are probability asymmetric costs to the two types of errors. Assign the costs below and calculate oos total cost.

```
cost_fp = 100
cost_fn = 1
oos_total_cost = (cost_fn * fn) + (cost_fp * fp)
oos_total_cost
```

```
## [1] 1221073
```

We now wish to do asymmetric cost classification. Fit a logistic regression model to this data.

```
logistic_regression_mod = glm(paid_in_full ~., bills_data_train, family = binomial(link = "logit"))
```

Use the function from class to calculate all the error metrics for the values of the probability threshold being 0.001, 0.002, ..., 0.999 in a data frame.

```
compute_metrics_prob_classifier = function(p_hats, y_true, res = 0.001){
  #we first make the grid of all prob thresholds
  p_thresholds = seq(0 + res, 1 - res, by = res) #values of 0 or 1 are trivial
```

```

#now we create a matrix which will house all of our results
performance_metrics = matrix(NA, nrow = length(p_thresholds), ncol = 12)
colnames(performance_metrics) = c(
  "p_th",
  "TN",
  "FP",
  "FN",
  "TP",
  "miscl_err",
  "precision",
  "recall",
  "FDR",
  "FPR",
  "FOR",
  "miss_rate"
)

#now we iterate through each p_th and calculate all metrics about the classifier and save
n = length(y_true)
for (i in 1 : length(p_thresholds)){
  p_th = p_thresholds[i]
  y_hats = factor(ifelse(p_hats >= p_th, 1, 0))
  confusion_table = table(
    factor(y_true, levels = c(0, 1)),
    factor(y_hats, levels = c(0, 1))
  )

  fp = confusion_table[1, 2]
  fn = confusion_table[2, 1]
  tp = confusion_table[2, 2]
  tn = confusion_table[1, 1]
  npp = sum(confusion_table[, 2])
  npn = sum(confusion_table[, 1])
  np = sum(confusion_table[2, ])
  nn = sum(confusion_table[1, ])

  performance_metrics[i, ] = c(
    p_th,
    tn,
    fp,
    fn,
    tp,
    (fp + fn) / n,
    tp / npp, #precision
    tp / np, #recall
    fp / npp, #false discovery rate (FDR)
    fp / nn, #false positive rate (FPR)
    fn / npn, #false omission rate (FOR)
    fn / np #miss rate
  )
}
performance_metrics
}

```



```
p_hats_train = predict(logistic_regression_mod, bills_data_train, type = "response")

ytrue = bills_data_train$paid_in_full
performance_metrics = compute_metrics_prob_classifier(p_hats_train, ytrue)
prob_classifier_metric_tbl = as_tibble(performance_metrics)
```

Calculate the column `total_cost` and append it to this data frame.

```
cost_fp = 100
cost_fn = 1

prob_classifier_metric_tbl = prob_classifier_metric_tbl %>%
  mutate(total_cost = (cost_fn * FN) + (cost_fp * FP))
prob_classifier_metric_tbl
```

```
## # A tibble: 999 x 13
##   p_th    TN    FP    FN    TP misc_err precision recall   FDR   FPR    FOR
##   <dbl> <dbl> <dbl> <dbl> <dbl>   <dbl>   <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 0.001 10595 72944     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 2 0.002 10595 72944     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 3 0.003 10595 72944     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 4 0.004 10595 72944     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 5 0.005 10595 72944     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 6 0.006 10595 72944     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 7 0.007 10596 72943     1 85306    0.430    0.539 1.00 0.461 0.873 9.44e-5
## 8 0.008 10725 72814     2 85305    0.429    0.539 1.00 0.461 0.872 1.86e-4
## 9 0.009 17440 66099    24 85283    0.389    0.563 1.00 0.437 0.791 1.37e-3
## 10 0.01 20910 62629    92 85215    0.369    0.576 0.999 0.424 0.750 4.38e-3
## # ... with 989 more rows, and 2 more variables: miss_rate <dbl>,
## #   total_cost <dbl>
```

Which is the winning probability threshold value and the total cost at that threshold?

```
winning_prob_threshold_value = which.min(prob_classifier_metric_tbl$total_cost)
winning_prob_threshold_value
```

```
## [1] 967
```

```
winning_prob_threshold_metrics = prob_classifier_metric_tbl[winning_prob_threshold_value, ]
winning_prob_threshold_metrics
```


```
## # A tibble: 1 x 13
##   p_th    TN    FP    FN    TP misc_err precision recall   FDR   FPR    FOR
##   <dbl> <dbl> <dbl> <dbl> <dbl>   <dbl>   <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 0.967 83535     4 85253    54    0.502    0.931 6.33e-4 0.0690 4.79e-5 0.505
## # ... with 2 more variables: miss_rate <dbl>, total_cost <dbl>
```

```
cat("Winning Probability Threshold total cost", min(winning_prob_threshold_metrics$total_cost))
```

```
## Winning Probability Threshold total cost 85653
```

Plot an ROC curve and interpret.

```
pacman::p_load(ggplot2)
ggplot(prob_classifier_metric_tbl) +
  geom_line(aes(x = FPR, y = recall)) +
  geom_abline(intercept = 0, slope = 1, col = "Red") +
  coord_fixed() + xlim(0, 1) + ylim(0, 1)
```



#TO-DO interpretation

Calculate AUC and interpret.

#TO-DO interpretation

Plot a DET curve and interpret.

#TO-DO interpretation