WeightLoop: Weight-Space Programming with Experimental Feedback

Anonymous Author(s)

Abstract

Scientific predictors guide costly experiments, yet returned measurements often reveal errors that matter for subsequent experimental choices. WeightLoop turns this feedback into persistent model updates through a reusable Weight-Space Programming (WSP) editor. We use GPT-6 Astra and DeepSeek to construct update programs from the scientific objective, model computation and editable parameters. These programs use accumulated measurements to estimate parameter corrections, validate them on feedback and save accepted changes into the original model. With identical feedback and writable parameters, four pretrained scientific predictors obtain 5.10–18.56% lower primary error. For weather prediction, changing four output-bias parameters reduces root mean squared error by 13.28%. Functional ranking and sequential discovery further connect reusable editing programs to improved experimental choices. Code: https://anonymous.4open.science/r/WeightLoop-C75A/.

CCS Concepts

• **Information systems** → **Recommender systems**; • **Computing methodologies** → *Machine learning approaches.*

Keywords

Scientific recommendation, model editing, experimental feedback, weight-space programming

1 Introduction

Scientific predictors determine which costly experiments are performed and which evidence becomes available next [12, 24, 25]. A deployed predictor initially has few relevant assays. Its selected experiments return observations, including discrepancies from predictions, that should improve the model used for the next choice. The challenge is to turn a small, growing set of measurements into useful changes the model's parameters can express.

Useful updates must respect the scientific objective and the deployed computation. Model editing changes network behavior [5, 19, 27] and factual associations [16, 17]. Weight-Space Programming (WSP) shows that language models can inspect and modify weights [29]; WeightCode installs computations from task knowledge through reusable programs [14]. Scientific feedback makes updating recurrent: predictions select measurements, and those measurements inform the next predictions and choices.

WeightLoop uses GPT-6 Astra [21] to construct a program that translates measured discrepancies into native parameter corrections. GPT-6 Astra inspects the objective, forward computation, editable parameters and validation interface; returned measurements determine the numerical correction. We also construct programs independently with DeepSeek [6]. Both workflows supply update code to the same feedback-validation and deployment interface.

WSDM '27, Hong Kong
2027.

Figure 1 shows feedback returning to the predictor. Each round estimates a total correction from the original model and accumulated measurements. The updated predictor chooses the next batch, whose results extend the feedback used by the program.

To test whether feedback improves scientific predictions, we compare updates under identical feedback and writable parameters in cell biology [23], earthquake monitoring [31], weather prediction [20] and fluid dynamics [15]. Functional ranking and sequential discovery then evaluate which experiments the updated models select. RNA calibration tests the same approach on larger decoders. Together, these studies examine how experimental measurements improve predictions and subsequent decisions.

2 WeightLoop

2.1 From a scientific objective to an update program

New measurements help when the deployed predictor can express what they reveal. We provide GPT-6 Astra with the task, model code and permitted parameters in an interactive coding session to build an update program. Separately, we send these inputs to DeepSeek through its official API to generate another program. We check each program's input and output formats on synthetic data. Subsequent rounds run the program on returned measurements to fit, validate and save parameter updates.

Let f_θ be the native predictor with parameter vector θ, and let θ_0 denote its original parameters. At feedback round $t = 1, 2, \ldots$, the accumulated measurements are $S_t = \{(x_i, y_i)\}_{i=1}^{n_t}$, where x_i is an experimental input, y_i its measured outcome, and n_t the number of returned observations. A reusable program P proposes

$$\Delta = P(\theta_0, S_t; \eta), \qquad \Delta_j = 0 \quad (j \notin \mathcal{I}), \tag{1}$$

where Δ is the correction vector, j indexes a parameter coordinate, $\mathcal{I}$ is the permitted coordinate set, and $\eta \in \mathcal{H}$ selects a numerical configuration from a fixed menu $\mathcal{H}$.

The program describes how permitted parameter changes affect predictions. Each round supplies new measurements to this computation, which estimates a correction and evaluates it through the model.

2.2 Selecting and committing a correction

A correction must help beyond the observations used to fit it. WeightLoop divides returned measurements into V feedback folds, with fitting subset $S_{t,k}^{\mathrm{fit}}$ and validation subset $S_{t,k}^{\mathrm{val}}$ for fold $k \in \{1, \ldots, V\}$. The task loss $\mathcal{L}(f, S)$ evaluates predictor f on measurements S. Let $\mathcal{H}_t \subseteq \mathcal{H}$ contain settings passing the fixed acceptance checks. When this set is nonempty, WeightLoop selects

$$\eta_t^* = \arg\min_{\eta \in \mathcal{H}_t} \sum_{k=1}^{V} \mathcal{L}\left(f_{\theta_0 + P(\theta_0, S_{t,k}^{\mathrm{fit}}; \eta)}, S_{t,k}^{\mathrm{val}}\right), \tag{2}$$




Figure 1: Feedback updates the predictor used to choose the next experiments. The HepG2 grid zooms into 128 output weights: 116 blue cells are edited and 12 white cells unchanged. Including 128 hidden biases, the 244 edited parameters account for 0.0068% of the model. w_0 and b_0 denote the first output weight and hidden bias.

where η_t^* is the selected configuration. This evaluates proposals through the native forward computation.

Using the selected configuration, the program refits a correction on all accumulated feedback and writes it into the model:

$$\theta_t = \theta_0 + P(\theta_0, S_t; \eta_t^*), \qquad A_{t+1} = \mathcal{D}(f_{\theta_t}). \tag{3}$$

Here θ_t is the deployed parameter vector, $\mathcal{D}$ is the experimental-selection rule applied to the remaining candidates, and A_{t+1} is the next experimental batch. Its returned outcomes extend S_t. If no setting passes acceptance, WeightLoop retains the previous deployment θ_{t-1}. Every total correction is reconstructed against θ_0, so accumulating evidence revises one common reference. Native save and reload reproduce the accepted predictor before it guides another batch.

3 Experiments

3.1 Tasks and common evaluation settings

Four prediction tasks. We evaluate four prediction tasks (Table 1). *Cell responses:* GEARS [23] predicts gene-expression changes after gene silencing in Adamson CRISPRi [1]. We measure mean squared error (MSE) on nine target genes and 1,024 RNA outputs selected from untreated controls. *Earthquake timing:* PhaseNet [31] predicts when a seismic P wave arrives in 64 whole INSTANCE [18] events. Mean absolute error (MAE, seconds) uses the 100 Hz grid and includes events without a thresholded pick. *Weather prediction:* ClimaX [20] predicts the 500 hPa geopotential field, which describes upper-air circulation. We measure area-weighted root mean squared error (RMSE, $m^2\ s^{-2}$) on 59 ERA5 Z500 states in six whole months [22]. *Shallow-water flow:* a two-dimensional Fourier neural operator (FNO2d) [15] predicts water-height fields after a radial dam break in PDEBench [28]. Relative L_2 error compares predicted and observed fields over 32 initial-state groups, using ten observed fields; L_2 is the Euclidean field norm. The published split includes training-equivalent initial states.

The four tasks use execution seed17 and a regularized numerical editor within DeepSeek-selected parameter pools. WeightLoop and Adam [13] start from the same model and receive the same ordered feedback, writable coordinates, validation folds and acceptance rules. We add feedback in three batches: cumulative totals are 8/12/16 genes, 24/40/56 earthquakes, 20/41/61 weather states and 10/18/26 simulation groups. The respective editable pools contain 1,024/27/192/129 parameters. Each update is fitted before the next batch is revealed. Final evaluation objects remain outside feedback fitting.

Choosing new experiments. We also test which genes a model recommends for new experiments. Four biological tasks seek reduced growth in HepG2 and Jurkat cells using negative Chronos effects from DepMap [3, 7], or reduced HL60 proliferation and migration [2]. Three sequential tasks seek higher LC3/NBR1 autophagic flux, a measure of cellular recycling [26], or lower HuH7 uptake of LDL cholesterol [8]. Each predictor is a multilayer perceptron (MLP) using GO [30], scGPT [4] and MAP-KG [9] gene features. Editing changes its final hidden biases and output weights. The initial MLP has 25 training labels. Single-update editing receives 75 additional assays; sequential policies select five batches of 20 genes and use their own returned results. Single-update evaluation genes stay outside feedback fitting. We average five gene folds within each of three model-training seeds, then report the mean and sample standard deviation across those three seed means.

Table 1: Prediction with identical feedback and writable parameters. Each error metric is lower-is-better (↓). E_{Adam} and E_{WL} are the reported task errors; relative improvement is $100(E_{\text{Adam}} - E_{\text{WL}})/E_{\text{Adam}}$.

Task	Predictor	Metric	Adam	WeightLoop	Improvement (%)
Cell responses	GEARS	RNA MSE ↓	4.496×10^{-2}	$\mathbf{4.258\times10^{-2}}$	5.31
Earthquake timing	PhaseNet	P MAE (s) ↓	6.446	**5.250**	18.56
Weather prediction	ClimaX	RMSE ($m^2\ s^{-2}$) ↓	1187.58	**1029.83**	13.28
Shallow-water flow	FNO2d	Relative L_2 ↓	8.467×10^{-3}	$\mathbf{8.035\times10^{-3}}$	5.10

RNA calibration. An H1 CRISPRi study uses scGPT [4] and scFoundation with GEARS (scF+GEARS) [10, 23]. Three fixed partitions per training seed contain 40 adaptation, 16 feedback and 20 query targets. Adam and the GPT-6 Astra editor share the adapted checkpoint, the 16 feedback targets, writable tensors and two feedback-validation folds. We report overall MSE across three training seeds after averaging their three partitions.

Choosing and fitting an update. For the four prediction tasks, we test each update on feedback withheld from fitting. We accept it when validation loss improves by at least 0.1% over the initial model and loss on observed history worsens by no more than 5% relative to the current model. Otherwise, we keep the current model. Accepted updates are saved in the model's float32 format before predicting the next batch.

We test 12 preset fitting settings. They combine squared error or smooth MAE with two penalties: one keeps predictions on reference inputs close to the original model; the other limits the parameter change. Squared-error settings use regularized least squares [11]. Each feedback gene, event, weather state or simulation group receives equal weight, averaged over its outputs. Output and parameter scales make the fit comparable across quantities with different units.

For linear parameter-to-output relationships, the editor computes the effect of a change exactly. For nonlinear PhaseNet, it approximates this effect to propose an update, then validates the updated model's actual predictions. Smooth MAE is fitted with L-BFGS using $\sqrt{e^2 + 0.01^2} - 0.01$, where e is the normalized prediction error. Adam fits the same 12 objectives from zero correction, with learning rate 0.03, moment coefficients 0.9/0.999 and denominator stabilizer $\epsilon = 10^{-8}$. Its best-objective iterate supplies the proposal. Both approaches use the same validation procedure. Bold blue cells mark the best value in each comparison row.

3.2 Same-feedback updates improve prediction

Table 1 shows lower primary error in every matched-feedback task: relative improvements range from 5.10% for FNO2d to 18.56% for PhaseNet. Figure 2(d) expresses these task-specific improvements on a common percentage scale.

Repeated updates change native parameters (Figure 2(e)): final counts are 1,024 for GEARS, 26 for PhaseNet, four for ClimaX and 129 for FNO2d. PhaseNet retains its deployment on the second prefix and accepts a correction on the third. Native checkpoint reload reproduces the accepted predictions.

Table 2: Functional recommendation, BU ↑. All predictors are MLPs. WL-A denotes the editor constructed with GPT-6 Astra. Mean ± sample SD across three training seeds after averaging five gene folds per seed.

Task	B	Initial MLP	WL-A
HepG2	20	.5157±.0162	**.5785±.0195**
HepG2	50	.5069±.0243	**.5688±.0177**
Jurkat	20	.5141±.0217	**.5872±.0211**
Jurkat	50	.5014±.0293	**.5834±.0105**
HL60 prolif.	20	.2132±.0209	**.2446±.0026**
HL60 prolif.	50	.2490±.0113	**.2951±.0052**
HL60 migr.	20	−.0121±.0116	**.0361±.0351**
HL60 migr.	50	.0070±.0059	**.0225±.0287**

3.3 Feedback improves experimental ranking

For recommendation budget B, let $r \in \{1, \dots, B\}$ be a rank, π_r the candidate at that rank, and y_{π_r} its measured outcome, oriented so that larger is preferred. Discount weights satisfy $d_r \propto 1/\log_2(r+1)$ and $\sum_{r=1}^{B} d_r = 1$. We report

$$U_B = \sum_{r=1}^{B} d_r y_{\pi_r}, \qquad \text{BU}_B = \frac{U_B - \bar{y}_C}{U_B^{\text{oracle}} - \bar{y}_C}, \tag{4}$$

where U_B is discounted utility, C is the evaluation candidate pool, $\bar{y}_C$ its mean outcome, and U_B^{oracle} the utility of the best ordering under the measured outcomes. Higher BU_B is better; zero is same-pool random selection. Score ties use expected utility over tied orders.

Table 2 shows higher mean utility at both recommendation budgets for every task. The GPT-6 Astra editor uses returned assays to improve the MLP responsible for subsequent recommendations.

3.4 Repeated updates improve sequential discovery

Let K be the number of acquired targets, $A_K \subseteq C$ the acquired set, and g a target index with measured outcome y_g. Cumulative discovery utility is

$$D_K = \frac{\sum_{g \in A_K} y_g - K\bar{y}_C}{\sum_{g \in \text{Top}_K(C)} y_g - K\bar{y}_C}, \tag{5}$$

where $\text{Top}_K(C)$ contains the K highest-outcome targets in pool C. Higher D_K is better; zero is same-pool random acquisition. Each batch is selected before its outcomes return, and each policy follows its own feedback trajectory.

Both GPT-6 Astra and DeepSeek programs improve final mean D_{100} on all three tasks (Table 3). Relative to the initial MLP, GPT-6




Figure 2: Experimental choices and parameter updates. (a–c) Relative discovery improvements from GPT-6 Astra editing. At each budget, paired seed differences are expressed as a percentage of the initial MLP policy's three-seed mean utility. Dashed lines show the three training seeds; solid lines and bands show their mean ± sample SD, after averaging five gene folds per seed. (d) Relative prediction improvement over Adam with identical feedback and writable parameters, using DeepSeek-selected pools. (e) Parameters changed from the initial model (log scale); crosses mark retained models. Colors match (d).

Table 3: Sequential discovery, D_{100} ↑. All MLP policies acquire 100 genes. Mean ± sample SD across three training seeds.

Task	Initial MLP	GPT-6 Astra	DeepSeek
LC3	.1910±.0245	.2068±.0213	**.2180±.0228**
NBR1	.1621±.0043	**.1864±.0268**	.1783±.0127
HuH7	.0097±.0180	.0391±.0025	**.0675±.0013**

Table 4: RNA output calibration, MSE ↓ in units of 10^{-3}. Base denotes the adapted checkpoint; WL-A denotes the GPT-6 Astra editor. Mean ± sample SD across three training-seed means.

Predictor	Base	Adam	WL-A
scGPT	11.204±.182	**10.992±.015**	10.997±.013
scF+GEARS	12.075±.035	12.075±.035	**11.171±.026**

Astra editing improves mean utility by 8.30%, 14.97% and 303.43% for LC3, NBR1 and HuH7. Relative improvement is $100(\bar{D}_K^{\mathrm{WL}} - \bar{D}_K^{\mathrm{init}})/\bar{D}_K^{\mathrm{init}}$, where the bars denote three-seed means and superscripts identify the edited and initial policies. Figure 2(a–c) tracks this improvement as five batches of experimental results arrive.

3.5 Feedback calibrates native RNA outputs

The program estimates a response-amplitude correction and writes it through the native decoder. The correction adjusts the size of the predicted gene-expression response using the feedback targets. Once stored in the decoder, it is applied automatically when the model predicts responses for new target genes. Table 4 shows mean MSE reductions of 1.85% for scGPT and 7.49% for scF+GEARS relative to their adapted checkpoints. Both update strategies reach close MSE values on scGPT; WeightLoop gives the lowest MSE on scF+GEARS. This supports feedback-driven output calibration on the two RNA architectures.

4 Conclusion

WeightLoop uses experimental measurements to improve the model that selects subsequent experiments. Programs constructed with GPT-6 Astra and DeepSeek estimate and validate parameter updates from returned feedback. Functional ranking and sequential discovery improve, and four scientific predictors obtain 5.10–18.56% lower primary error than Adam with identical feedback. RNA calibration also lowers overall MSE relative to adapted checkpoints. Accepted updates are saved in the original model and reused for subsequent experimental choices.

Ethical Considerations

This study reuses public assay, seismic, weather and simulation data. It involves no new studies with human participants or collection of personal information. Recommendations guide research assays. Original checkpoints are retained so updates remain reversible.

References

[1] Britt Adamson, Thomas M. Norman, Marco Jost, et al. 2016. A Multiplexed Single-Cell CRISPR Screening Platform Enables Systematic Dissection of the Unfolded Protein Response. *Cell* 167, 7 (2016), 1867–1882.e21. doi:10.1016/j.cell.2016.11.048

[2] Nathan M. Belliveau, Matthew J. Footer, Emel Akdoğan, Aaron P. van Loon, Sean R. Collins, and Julie A. Theriot. 2023. Whole-Genome Screens Reveal Regulators of Differentiation State and Context-Dependent Migration in Human Neutrophils. *Nature Communications* 14, 1 (2023), 5770. doi:10.1038/s41467-023-41452-x

[3] Broad DepMap. 2024. DepMap 24Q4 Public. Figshare+, dataset, version 1. doi:10.25452/figshare.plus.27993248.v1

[4] Haotian Cui, Chloe Wang, Hassaan Maan, Kuan Pang, Fengning Luo, Nan Duan, and Bo Wang. 2024. scGPT: Toward Building a Foundation Model for Single-Cell Multi-omics Using Generative AI. *Nature Methods* 21 (2024), 1470–1480. doi:10.1038/s41592-024-02201-0

[5] Nicola De Cao, Wilker Aziz, and Ivan Titov. 2021. Editing Factual Knowledge in Language Models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 6491–6506. doi:10.18653/v1/2021.emnlp-main.522

[6] DeepSeek. 2026. DeepSeek API: Models and Pricing. https://api-docs.deepseek.com/quick_start/pricing/. Official model documentation; accessed November 10, 2026. Model deepseek-flash serves DeepSeek-V4.1-Flash-1017.

[7] Joshua M. Dempster, Isabella Boyle, Francisca Vazquez, David E. Root, Jesse S. Boehm, William C. Hahn, Aviad Tsherniak, and James M. McFarland. 2021. Chronos: A Cell Population Dynamics Model of CRISPR Experiments That Improves Inference of Gene Fitness Effects. *Genome Biology* 22, 1 (2021), 343. doi:10.1186/s13059-021-02540-7

[8] Brian T. Emmer, Emily J. Sherman, Paul J. Lascuna, Sarah E. Graham, Cristen J. Willer, and David Ginsburg. 2021. Genome-Scale CRISPR Screening for Modifiers of Cellular LDL Uptake. *PLOS Genetics* 17, 1 (2021), e1009285. doi:10.1371/journal.pgen.1009285

[9] Jinghao Feng, Ziheng Zhao, Xiaoman Zhang, Mingfei Liu, Jingyi Chen, Xingran Quan, Boyang Fu, Jian Zhang, Yanfeng Wang, Ya Zhang, and Weidi Xie. 2026. A knowledge-driven framework for predicting single-cell responses for unprofiled drugs. *Nature Machine Intelligence* 8 (2026), 1478–1491. doi:10.1038/s42256-026-01286-w

[10] Minsheng Hao, Jing Gong, Xin Zeng, Chiming Liu, Yucheng Guo, Xingyi Cheng, Taifeng Wang, Jianzhu Ma, Xuegong Zhang, and Le Song. 2024. Large-scale foundation model on single-cell transcriptomics. *Nature Methods* 21, 8 (2024), 1481–1491. doi:10.1038/s41592-024-02305-7

[11] Arthur E. Hoerl and Robert W. Kennard. 1970. Ridge Regression: Biased Estimation for Nonorthogonal Problems. *Technometrics* 12, 1 (1970), 55–67. doi:10.1080/00401706.1970.10488634

[12] Ross D. King, Jem Rowland, Stephen G. Oliver, Michael Young, Wayne Aubrey, Emma Byrne, Maria Liakata, Magdalena Markham, Pinar Pir, Larisa N. Soldatova, Andrew Sparkes, Kenneth E. Whelan, and Amanda Clare. 2009. The Automation of Science. *Science* 324, 5923 (2009), 85–89. doi:10.1126/science.1165620

[13] Diederik P. Kingma and Jimmy Ba. 2015. Adam: A Method for Stochastic Optimization. In *International Conference on Learning Representations*. https://arxiv.org/abs/1412.6980

[14] Bo Li, Taoyong Cui, Bob Zhang, Mengran Li, Chengyang Zhang, Yang Zhang, Pheng Ann Heng, Wanli Ouyang, Zhenfei Yin, Yingcheng Wu, and Ling Yang. 2026. WeightCode: Installing New Capabilities into Neural Networks via Weight Programming. https://github.com/Gen-Verse/WeightCode. Technical manuscript and project repository.

[15] Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. 2021. Fourier Neural Operator for Parametric Partial Differential Equations. In *International Conference on Learning Representations*. https://arxiv.org/abs/2010.08895

[16] Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. Locating and Editing Factual Associations in GPT. In *Advances in Neural Information Processing Systems*, Vol. 35. https://proceedings.neurips.cc/paper_files/paper/2022/hash/6f1d43d5a82a37e89b0665b33bf3a182-Abstract-Conference.html

[17] Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. 2023. Mass-Editing Memory in a Transformer. In *International Conference on Learning Representations*. https://openreview.net/forum?id=MkbcAHIYgyS

[18] Alberto Michelini, Spina Cianetti, Sonja Gaviano, Carlo Giunchi, Dario Jozinović, and Valentino Lauciani. 2021. INSTANCE—The Italian Seismic Dataset for Machine Learning. *Earth System Science Data* 13 (2021), 5509–5544. doi:10.5194/essd-13-5509-2021

[19] Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. 2022. Fast Model Editing at Scale. In *International Conference on Learning Representations*. https://arxiv.org/abs/2110.11309

[20] Tung Nguyen, Johannes Brandstetter, Ashish Kapoor, Jayesh K. Gupta, and Aditya Grover. 2023. ClimaX: A Foundation Model for Weather and Climate. In *Proceedings of the 40th International Conference on Machine Learning*, Vol. 202. PMLR, 25904–25938. https://proceedings.mlr.press/v202/nguyen23a.html

[21] OpenAI. 2026. GPT-6 Astra. OpenAI API model documentation. https://developers.openai.com/api/docs/models/gpt-6-astra Accessed: 2026-11-13.

[22] Stephan Rasp, Stephan Hoyer, Alexander Merose, et al. 2024. WeatherBench 2: A Benchmark for the Next Generation of Data-Driven Global Weather Models. *Journal of Advances in Modeling Earth Systems* 16 (2024). doi:10.1029/2023MS004019

[23] Yusuf Roohani, Kexin Huang, and Jure Leskovec. 2023. Predicting Transcriptional Outcomes of Novel Multigene Perturbations with GEARS. *Nature Biotechnology* (2023). doi:10.1038/s41587-023-01905-6 Published online 17 August 2023.

[24] Yusuf Roohani, Andrew Lee, Qian Huang, Jian Vora, Zachary Steinhart, Kexin Huang, Alexander Marson, Percy Liang, and Jure Leskovec. 2025. BioDiscoveryAgent: An AI Agent for Designing Genetic Perturbation Experiments. In *International Conference on Learning Representations*. https://proceedings.iclr.cc/paper_files/paper/2025/hash/4252dc94531833029000f85dc5fac792-Abstract-Conference.html

[25] Burr Settles. 2009. *Active Learning Literature Survey*. Computer Sciences Technical Report 1648. University of Wisconsin–Madison. https://research.cs.wisc.edu/techreports/2009/TR1648.pdf

[26] Christopher J. Shoemaker, Tina Q. Huang, Nicholas R. Weir, Nicole J. Polyakov, Sebastian W. Schultz, and Vladimir Denic. 2019. CRISPR Screening Using an Expanded Toolkit of Autophagy Reporters Identifies TMEM41B as a Novel Autophagy Factor. *PLOS Biology* 17, 4 (2019), e2007044. doi:10.1371/journal.pbio.2007044

[27] Anton Sinitsin, Vsevolod Plokhotnyuk, Dmitriy Pyrkin, Sergei Popov, and Artem Babenko. 2020. Editable Neural Networks. arXiv:2004.00345 [cs.LG] doi:10.48550/arXiv.2004.00345

[28] Makoto Takamoto, Timothy Praditia, Raphael Leiteritz, Daniel MacKinlay, Francesco Alesiani, Dirk Pflüger, and Mathias Niepert. 2022. PDEBench: An Extensive Benchmark for Scientific Machine Learning. In *Advances in Neural Information Processing Systems*, Vol. 35. 1596–1611. https://proceedings.neurips.cc/paper_files/paper/2022/hash/0a9747136d411fb83f0cf81820d44afb-Abstract-Datasets_and_Benchmarks.html

[29] Rikiya Takehi, Jayden Teoh, Alex Zhang, and Omar Khattab. 2026. Sparks of Weight-Space Programming: LLMs can natively read & write neural network weights. https://rikiyat.github.io/blog/weight-space-programming/. Blog post.

[30] The Gene Ontology Consortium. 2023. The Gene Ontology Knowledgebase in 2023. *Genetics* 224, 1 (2023), iyad031. doi:10.1093/genetics/iyad031

[31] Weiqiang Zhu and Gregory C. Beroza. 2019. PhaseNet: A Deep-Neural-Network-Based Seismic Arrival-Time Picking Method. *Geophysical Journal International* 216, 1 (2019), 261–273. doi:10.1093/gji/ggy423