







基于Center OS7安装Redis

● 下载安装包

wget http://download.redis.io/releases/redis-?.?.tar.gz

● 解压

tar -xvf 文件名.tar.gz

编译

make

● 安装

make install [destdir=/目录]



Redis基础环境设置

● 创建软链接

In -s 原始目录名 快速访问目录名

● 创建配置文件管理目录

mkdir config

● 创建数据文件管理目录

mkdir data



Redis服务启动

● 默认配置启动

```
redis-server --port 6379
redis-server --port 6380 .....
```

● 指定配置文件启动

```
redis-server redis.conf
redis-server redis-6379.conf
redis-server redis-6380.conf ......
redis-server conf/redis-6379.conf
redis-server config/redis-6380.conf ......
```



Redis客户端连接

● 默认连接

redis-cli

● 连接指定服务器

```
redis-cli -h 127.0.0.1
redis-cli -port 6379
redis-cli -h 127.0.0.1 -port 6379
```



Redis服务端配置

● 基本配置

daemonize yes

以守护进程方式启动,使用本启动方式,redis将以服务的形式存在,日志将不再打印到命令窗口中 port 6***

设定当前服务启动端口号

dir "/自定义目录/redis/data "

设定当前服务文件保存位置,包含日志文件、持久化文件(后面详细讲解)等

logfile "6***.log "

设定日志文件名,便于查阅

总结





Redis安装

◆ 基于Center OS7安装Redis



传智播客旗下高端IT教育品牌