


Stacks



1

The Stack ADT (Abstract Data Type)

- A Stack is an ordered collection of homogeneous elements, in which all insertions and deletions are made at one end of the list called the "**top**" of the stack
- A stack has a **LIFO** "last in, first out" structure
- Think of a spring-loaded plate dispenser



Stack ADT (cont.)

- Main stack operations:
 - **push**(item): inserts an element
 - item **pop**(): removes and returns the last inserted element
- Auxiliary stack operations:
 - item **top**(): returns the last inserted element without removing it
 - integer **size**(): returns the number of elements stored
 - boolean **isEmpty**(): indicates whether no elements are stored

3

Example

Method	Return Value	Stack Contents
push(5)	—	(5)
push(3)	—	(5, 3)
size()	2	(5, 3)
pop()	3	(5)
isEmpty()	false	(5)
pop()	5	()
isEmpty()	true	()
pop()	null	()
push(7)	—	(7)
push(9)	—	(7, 9)
top()	9	(7, 9)
push(4)	—	(7, 9, 4)
size()	3	(7, 9, 4)
pop()	4	(7, 9)
push(6)	—	(7, 9, 6)
push(8)	—	(7, 9, 6, 8)
pop()	8	(7, 9, 6)

4

Applications of Stacks

- ❑ Direct applications
 - Page-visited history in a Web browser
 - Undo sequence in a text editor
 - Chain of method calls in the Java Virtual Machine
- ❑ Indirect applications
 - Auxiliary data structure for algorithms
 - Component of other data structures

5


Method Stack in the JVM

- ❑ The Java Virtual Machine (JVM) keeps track of the chain of active methods with a stack
- ❑ When a method is called, the JVM pushes on the stack a **stack frame** (or activation record) for the called method
- ❑ When a method ends, its frame is popped from the stack and control is passed to the method on top of the stack
- ❑ Allows for **recursion**

```
main() {
    int i = 5;
    foo(i);
}
```

```
foo(int j) {
    int k;
    k = j+1;
    bar(k);
}
```

```
bar(int m) {
    ...
}
```



6

Stack Interface in Java

- ❑ Java interface corresponding to our Stack ADT
- ❑ Requires the definition of class `EmptyStackException`
- ❑ Different from the built-in Java class `java.util.Stack`

```
public interface Stack<E> {  
    public int size();  
    public boolean isEmpty();  
    public E top()  
        throws EmptyStackException;  
    public void push(E element);  
    public E pop()  
        throws EmptyStackException;  
}
```

7

Exceptions

- ❑ Attempting the execution of an operation of ADT may sometimes cause an error condition, called an exception
- ❑ Exceptions are said to be “thrown” by an operation that cannot be executed
- ❑ In the Stack ADT, operations pop and top cannot be performed if the stack is empty
- ❑ Attempting the execution of pop or top on an empty stack throws an `EmptyStackException`

8

EmptyStackException

```
public class EmptyStackException extends RuntimeException {
    private static final long serialVersionUID = 1L;

    public EmptyStackException() {
        super();
    }

    public EmptyStackException(String e) {
        super(e);
    }
}
```

9

Array-based Stack

- A simple way of implementing the Stack ADT uses an array
- We add elements from left to right
- A variable keeps track of the index of the top element

Algorithm *size()*

return $t + 1$

Algorithm *pop()*

if *isEmpty()* then

throw *EmptyStackException*

else

$t \leftarrow t - 1$

return $S[t + 1]$



10

Array-based Stack (cont.)

- The array storing the stack elements may become full
- A push operation will then throw a **FullStackException**
 - Limitation of the array-based implementation
 - Not intrinsic to the Stack ADT

```
Algorithm push(o)  
  if  $t = S.length - 1$  then  
    throw FullStackException  
  else  
     $t \leftarrow t + 1$   
     $S[t] \leftarrow o$ 
```



11

Performance and Limitations

- Performance
 - Let n be the number of elements in the stack
 - The space used is $O(n)$
 - Each operation runs in time $O(1)$
- Limitations
 - The maximum size of the stack must be defined a priori and cannot be changed
 - Trying to push a new element into a full stack causes an implementation-specific exception

12

Array-based Stack in Java

```
public class ArrayStack<E>
    implements Stack<E> {
    // holds the stack elements
    private E S[ ];
    // index to top element
    private int top = -1;
    // constructor
    public ArrayStack(int capacity) {
        S = (E[]) new Object[capacity];
    }
}
```

```
public E pop()
    throws EmptyStackException {
    if isEmpty()
        throw new EmptyStackException
            ("Empty stack: cannot pop");
    E temp = S[top];
    // facilitate garbage collection:
    S[top] = null;
    top = top - 1;
    return temp;
}
... (other methods of Stack interface)
```

13

Example use in Java

```
public class Tester {
    // ... other methods
    public intReverse(Integer a[]) {
        Stack<Integer> s;
        s = new ArrayStack<Integer>();
        ... (code to reverse array a) ...
    }
}
```

```
public floatReverse(Float f[]) {
    Stack<Float> s;
    s = new ArrayStack<Float>();
    ... (code to reverse array f) ...
}
```

14

Linked-Based Implementation

- In this section we study a link-based implementation of the Stack ADT.
- To support this we first define a **LLObjectNode** class
- After discussing the link-based approach we compare our stack implementation approaches.

15

The Node class

- Our stacks hold elements of type E.

```
class Node<E> {  
    private Node<E> link;  
    private E info;  
  
    Node(E info) {...}  
  
    void setInfo(E info) {...}  
    E    getInfo() {...}  
  
    void    setLink(Node<E> link){...}  
    Node<E> getLink() {...}  
}
```

16

The LinkedStack Class


```
public class LinkedStack<E> implements Stack<E>
{
    // reference to the top of this stack
    protected LLNode<E> top;

    public LinkedStack()
    {
        top = null;
    }
    . . .
}
```

17

The push(C) operation (step 1)


- ❑ **Allocate space for the next stack node and set the node info to element**
- ❑ Set the node link to the previous top of stack
- ❑ Set the top of stack to the new stack node



18

The push(C) operation (step 2)


- ❑ Allocate space for the next stack node and set the node info to element
- ❑ **Set the node link to the previous top of stack**
- ❑ Set the top of stack to the new stack node



19

The push(C) operation (step 3)

- ❑ Allocate space for the next stack node and set the node info to element
- ❑ Set the node link to the previous top of stack
- ❑ **Set the top of stack to the new stack node**



20

Code for the push method

```
public void push(E element)
// Places element at the top of this stack.
{
    LLNode<E> newNode = new LLNode<T>(element);
    newNode.setLink(top);
    top = newNode;
}
```

21

Code for the pop method

```
public E pop()
// Throws EmptyStackException if this stack is empty,
// otherwise removes top element from this stack.
{
    E temp;
    if (!isEmpty())
    {
        temp = top.getInfo();
        top = top.getLink();
    }
    else
        throw new EmptyStackException(
            "Pop attempted on an empty stack.");
    return temp;
}
```

22

(Better) Code for the pop method



```
public E pop()
// Throws EmptyStackException if this stack is empty,
// otherwise removes top element from this stack.
{
    if (isEmpty())
        throw new EmptyStackException(
            "Pop attempted on an empty stack.");

    E temp = top.getInfo();
    top = top.getLink();

    return temp;
}
```

23

Pop from
a stack
with three
elements



24

The remaining operations

```
public E top()
// Throws EmptyStackException if this stack is empty,
// otherwise returns top element from this stack.
{
    if (!isEmpty())
        return top.getInfo();
    else
        throw new StackUnderflowException(
            "Top attempted on an empty stack.");
}

public boolean isEmpty()
// Returns true if this stack is empty, otherwise returns false.
{
    if (top == null)
        return true;
    else
        return false;
}
```

25

Comparing Stack Implementations

- ❑ Storage Size
 - Array-based: takes the same amount of memory, no matter how many array slots are actually used, proportional to maximum size
 - Link-based: takes space proportional to actual size of the stack (but each element requires more space than with array approach)
- ❑ Operation efficiency
 - All operations, for each approach, are $O(1)$
 - Except for the Constructors:
 - ◆ Array-based: $O(N)$
 - ◆ Link-based: $O(1)$

26

Parentheses Matching

- Each "(", "{", or "[" must be paired with a matching ")", "}", or "]"
 - correct: ()(()){([])}
 - correct: ((())(()){([])})
 - incorrect:)(()){([])}
 - incorrect: ({[]})
 - incorrect: (

27

Parentheses Matching Algorithm

Algorithm ParenMatch(X, n):

Input: An array X of n tokens, each of which is either a grouping symbol, a variable, an arithmetic operator, or a number

Output: **true** if and only if all the grouping symbols in X match

Let S be an empty stack

for $i=0$ to $n-1$ **do**

if $X[i]$ is an opening grouping symbol **then**

$S.push(X[i])$

else if $X[i]$ is a closing grouping symbol **then**

if $S.isEmpty()$ **then**

return false {nothing to match with}

if $S.pop()$ does not match the type of $X[i]$ **then**

return false {wrong type}

if $S.isEmpty()$ **then**

return true {every symbol matched}

else return false {some symbols were never matched}

28

Parenthesis Matching (Java)

```
public static boolean isMatched(String expression) {
    final String opening = "{["; // opening delimiters
    final String closing = "}]"; // respective closing delimiters
    Stack<Character> buffer = new LinkedStack<>( );
    for (char c : expression.toCharArray( )) {
        if (opening.indexOf(c) != -1) // this is a left delimiter
            buffer.push(c);
        else if (closing.indexOf(c) != -1) { // this is a right delimiter
            if (buffer.isEmpty( )) // nothing to match with
                return false;
            if (closing.indexOf(c) != opening.indexOf(buffer.pop( )))
                return false; // mismatched delimiter
        }
    }
    return buffer.isEmpty( ); // were all opening delimiters matched?
}
```

29

HTML Tag Matching

❑ For fully-correct HTML, each `<name>` should pair with a matching `</name>`

```
<body>
<center>
<h1> The Little Boat </h1>
</center>
<p> The storm tossed the little
boat like a cheap sneaker in an
old washing machine. The three
drunken fishermen were used to
such treatment, of course, but
not the tree salesman, who even as
a stowaway now felt that he
had overpaid for the voyage. </p>
<ol>
<li> Will the salesman die? </li>
<li> What color is the boat? </li>
<li> And what about Naomi? </li>
</ol>
</body>
```

The Little Boat

The storm tossed the little boat like a cheap sneaker in an old washing machine. The three drunken fishermen were used to such treatment, of course, but not the tree salesman, who even as a stowaway now felt that he had overpaid for the voyage.

1. Will the salesman die?
2. What color is the boat?
3. And what about Naomi?

30

HTML Tag Matching (Java)

```
public static boolean isHTMLMatched(String html) {
    Stack<String> buffer = new LinkedStack<>( );
    int j = html.indexOf('<'); // find first '<' character (if any)
    while (j != -1) {
        int k = html.indexOf('>', j+1); // find next '>' character
        if (k == -1)
            return false; // invalid tag
        String tag = html.substring(j+1, k); // strip away < >
        if (!tag.startsWith("/")) // this is an opening tag
            buffer.push(tag);
        else { // this is a closing tag
            if (buffer.isEmpty( ))
                return false; // no tag to match
            if (!tag.substring(1).equals(buffer.pop( )))
                return false; // mismatched tag
        }
        j = html.indexOf('<', k+1); // find next '<' character (if any)
    }
    return buffer.isEmpty( ); // were all opening tags matched?
}
```

31

Evaluating Arithmetic Expressions

$$14 - 3 * 2 + 7 = (14 - (3 * 2)) + 7$$

Operator precedence

* has precedence over +/–

Associativity

operators of the same precedence group
evaluated from left to right

Example: $(x - y) + z$ rather than $x - (y + z)$

Idea: push each operator on the stack, but first pop and perform higher and *equal* precedence operations.

32

Algorithm for Evaluating Expressions

Two stacks:

- opStk holds operators
- valStk holds values
- Use \$ as special "end of input" token with lowest precedence

Algorithm **doOp()**

```
x ← valStk.pop();
y ← valStk.pop();
op ← opStk.pop();
valStk.push( y op x )
```

Algorithm **repeatOps(refOp)**:

```
while ( valStk.size() > 1 ∧
       prec(refOp) ≤
       prec(opStk.top())
       doOp()
```

Algorithm **EvalExp()**

Input: a stream of tokens representing an arithmetic expression (with numbers)

Output: the value of the expression

while there's another token z

if isNumber(z) **then**

valStk.push(z)

else

repeatOps(z);


opStk.push(z)

repeatOps(\$);

return valStk.top()

33

Algorithm on an Example Expression



34