WUMIKA Engage

Production server

Deployment and operations details for the production VPS: what runs where, how to reach it, how to deploy, back up, restore and release to every customer. No passwords, keys or tokens appear in this document.

Deployed	19 October 2026, release 8644f6b (branch dev)
Server	46.202.164.251 (Hostinger VPS, srv849896)
Addresses	https://engage.wumika.com (integrations) · https://admin.wumika.com (console)
Audience	Restricted to one customer: marylindajohnson22@gmail.com

1. At a glance

Item	Value
Provider / plan	Hostinger VPS, 1 vCPU, 3.8 GB RAM, 2 GB swap, 49 GB disk (42 GB free)
Operating system	Ubuntu 22.04.5 LTS, freshly reinstalled 19 Oct 2026, kernel 5.15
IP address	46.202.164.251
engage.wumika.com	ingest-api: Shopify, Razorpay, Meta, MSG91, Shiprocket webhooks; storefront App Proxy; web pixel; push poster and icon images
admin.wumika.com	Admin console (Angular) and its API (admin-api); sign-in with password + authenticator code
TLS	Let's Encrypt certificates for both names, valid to 17 Jan 2027, renewed automatically (certbot.timer)
Runtime	Docker 29.9, Docker Compose 5.6; nginx 1.18 on the host terminates TLS
Database	PostgreSQL 16 in a container, volume wumika_pgdata, schema v41, not reachable from outside
Store	Live Shopify store e4bac4-ef.myshopify.com (www.wumika.com), app wumikaEngage version wumikaengage-6
Messaging audience	CUSTOMER_ALLOWLIST_EMAILS = marylindajohnson22@gmail.com (nobody else is stored or messaged)

2. Containers

All defined in `/opt/wumika/docker-compose.yml`, restarted automatically (`unless-stopped`), each with a memory cap so one service cannot take the server down.

Container	Image	Role	Listens	Memory cap
wumika-db-1	postgres:16-alpine	Database	internal network only	512 MB
wumika-migrate-1	wumika/ingest-api:prod	Applies database migrations, then exits (run on every deploy)	—	320 MB
wumika-ingest-1	wumika/ingest-api:prod	Webhooks, storefront calls, pixel, media	127.0.0.1:8081 (nginx → engage.wumika.com)	512 MB
wumika-worker-1	wumika/worker:prod	Journeys, campaigns, sending (push, WhatsApp, SMS), nightly jobs	none	512 MB
wumika-admin-1	wumika/admin-api:prod	Console API, sign-in, roles, audit	internal (console proxies /api)	448 MB
wumika-console-1	wumika/console:prod	Admin console web app (nginx), proxies /api to admin	127.0.0.1:8090 (nginx → admin.wumika.com)	64 MB

Images are tagged `:prod` and with the release (e.g. `:8644f6b`). They are built on the server from the compiled apps by the deploy script, so the server never runs a full source build.

3. Files and folders

Path	What	Access
/opt/wumika/.env	All production settings and secrets (33 keys, see section 6)	root only (600)
/opt/wumika/docker-compose.yml	The services	root
/opt/wumika/secrets/firebase-service-account.json	Firebase key for push	uid 10001 read-only (400)
/opt/wumika/keys/admin-jwt.pem	Console sign-in signing key (created by admin-api)	uid 10001 (700)
/opt/wumika/backups/	Nightly database dumps, 14 days kept	root
/opt/wumika/REVISION	The release currently running	root
/usr/local/bin/wumika-backup	The backup script	root
/etc/cron.d/wumika-backup	Backup schedule: 21:45 UTC (03:15 IST) daily; log /var/log/wumika-backup.log	root
/etc/nginx/sites-available/engage.wumika.com, admin.wumika.com	Reverse proxy and TLS	root
/etc/ssh/sshd_config.d/10-hardening.conf	SSH keys only, no passwords	root

4. Access and security

Control	State
SSH	Port 22, public keys only (password sign-in disabled), root allowed with a key only
Keys on root	linda@LAPTOP-AIA09OQO (yours, passphrase-protected); claude-automation-2026-10 (used for this deployment, file l:\projects\wumika-ssh\wumika-root-2026-10); Hostinger browser terminal key (temporary, expires on its own)
Firewall (ufw)	Inbound 22 (SSH), 80 and 443 (web) only
fail2ban	SSH: 5 failures → banned for 1 hour
Updates	Automatic security updates (unattended-upgrades)
Database	No published port; reachable only by the containers
Console	Rate-limited (10 requests/s per IP, bursts of 40), framing denied, strict content security policy, sign-in with password + authenticator code for Owner and admins
Webhooks	Every provider signature verified before anything is stored
Logs	Docker logs rotated at 20 MB × 5 files per container

Remove the automation key when you no longer want Claude to manage the server:

```
sed -i '/claude-automation-2026-10/d' /root/.ssh/authorized_keys
```

5. Addresses to configure at each provider

Secrets named here live in `/opt/wumika/.env`. Read one on the server with `grep ^NAME= /opt/wumika/.env` and paste it into the provider; never send it by chat or email.

Provider	Where	Address	Secret
Shopify (live app)	Done by the deploy (wumikaengage-6)	https://engage.wumika.com/webhooks/shopify; App Proxy /apps/push → https://engage.wumika.com/shopify/proxy	SHOPIFY_API_SECRET (app client secret)
Meta WhatsApp	Meta app → WhatsApp → Configuration → Webhook	https://engage.wumika.com/meta/webhook (subscribe to "messages")	Verify token: WA_WEBHOOK_VERIFY_TOKEN
Razorpay (live)	Dashboard → Settings → Webhooks	https://engage.wumika.com/webhooks/razorpay (payment.failed, payment.captured, payment.authorized)	RAZORPAY_WEBHOOK_SECRET (the secret set on that webhook)
Shiprocket	Settings → API → Webhooks	https://engage.wumika.com/webhooks/courier	Security token: COURIER_WEBHOOK_TOKEN
MSG91 delivery reports	MSG91 → delivery report URL	https://engage.wumika.com/webhooks/sms?token=<MSG91_DLR_TOKEN>	MSG91_DLR_TOKEN
Web pixel	Created through the Admin API (pending, see section 9)	https://engage.wumika.com/pixel/events	PIXEL_WRITE_KEY
Firebase (push)	Theme editor → App embeds → Engage push	Same Firebase project as the dev store (wumika-75a48): web push key, API key, sender id, app id	—

6. Settings in /opt/wumika/.env

Key	Purpose	Value
CUSTOMER_ALLOWLIST_EMAILS	Who may be stored and messaged	marylindajohnson22@gmail.com (release: `*`)
SHOPIFY_SHOP_DOMAIN, STOREFRONT_BASE_URL	Live store and link domain	e4bac4-ef.myshopify.com, https://www.wumika.com
SHOPIFY_CLIENT_ID, SHOPIFY_API_SECRET	Live app wumikaEngage	from the app (secret)
SHOPIFY_ADMIN_TOKEN	Admin API token for the live store	empty: to be obtained (section 9)
RAZORPAY_WEBHOOK_SECRET, RAZORPAY_MODE	Razorpay	secret; live
WA_ACCESS_TOKEN, WA_APP_SECRET, WA_PHONE_NUMBER_ID, WA_BUSINESS_ACCOUNT_ID, WA_GRAPH_VERSION	WhatsApp Cloud API	permanent system-user token (secret); Meta test number +1 555-796-3126 "Wumika Jewels"; v25.0
WA_WEBHOOK_VERIFY_TOKEN	Meta webhook verification	generated 19 Oct (secret)
MSG91_AUTH_KEY, MSG91_DLR_TOKEN	SMS	secret; generated

Key	Purpose	Value
COURIER_WEBHOOK_TOKEN, PIXEL_WRITE_KEY, METRICS_TOKEN	Shiprocket, pixel, /prometheus	generated 19 Oct (secret)
DB_NAME, DB_USER, DB_PASSWORD	Database	engage, engage, generated (secret)
ADMIN_MFA_KEY, ADMIN_BOOTSTRAP_EMAIL	Console MFA encryption; first Owner	generated (secret); nithinkr24@gmail.com
PUBLIC_BASE_URL	Public address for images and links	https://engage.wumika.com
CHECKOUT_NOTICE_SINCE	Date the checkout WhatsApp notice went live	empty (off)
EMAIL_FROM	Email through SES	empty (off: email stays with Shopify)

After editing `.env`, apply it with `cd /opt/wumika && docker compose up -d --force-recreate ingest admin worker`.

7. Everyday operations

Status and logs

```
cd /opt/wumika
docker compose ps                          # what is running
docker compose logs -f --tail 100 worker   # follow one service (ingest, admin, worker, console, db)
cat REVISION                               # the release running
curl -s https://engage.wumika.com/health
```

Restart

```
cd /opt/wumika && docker compose restart worker      # or ingest, admin, console
```

Deploy a new release (from the developer PC)

```
cd L:\projects\Wumika_Admin\engage-platform
./gradlew build                     # all tests first
bash deploy/prod/deploy.sh          # compiles, ships, builds images, migrates, recreates the services
```

The deploy runs migrations as their own step and stops before restarting anything if one fails.

First console sign-in (Owner)

```
docker compose -f /opt/wumika/docker-compose.yml logs admin | grep set-password
# open https://admin.wumika.com/set-password?token=... within 24 hours,
# set a password, then scan the QR code with an authenticator app
```

WhatsApp templates

```
cd /opt/wumika
docker compose run --rm -T worker wa-check          # number, quality, every template's status (read-only)
docker compose run --rm -T worker wa-submit         # what would be submitted (dry run)
docker compose run --rm -T worker wa-submit --yes   # submit new templates to Meta
```

8. Backups and restore

A compressed dump runs every night at 03:15 IST into `/opt/wumika/backups` (14 days kept). **Copy them off the server** regularly (a backup on the same disk does not survive losing the server), and use Hostinger's VPS snapshots before risky changes.

Back up now

```
/usr/local/bin/wumika-backup && ls -lh /opt/wumika/backups
```

Copy to the PC

```
scp -i l:\projects\wumika-ssh\wumika-ssh root@46.202.164.251:/opt/wumika/backups/engage-YYYYMMDD-HHMM.sql.gz .
```

Restore (stops the apps; replaces the database)

```
cd /opt/wumika && set -a && . ./.env && set +a
docker compose stop ingest admin worker console
docker compose exec -T db psql -U $DB_USER -d postgres -c "DROP DATABASE $DB_NAME" -c "CREATE DATABASE $DB_NAME
OWNER $DB_USER"
gunzip -c backups/engage-YYYYMMDD-HHMM.sql.gz | docker compose exec -T db psql -U $DB_USER -d $DB_NAME
docker compose up -d
```

9. Channel status for the allowed customer

Channel	State	What makes it work
Push notifications	Ready on the server	Approve the new app permissions in the store admin; turn on the "Engage push" app embed in the live theme with the Firebase values; the customer signs in on www.wumika.com and allows notifications.
WhatsApp	19 templates submitted to Meta 19 Oct, pending review	Meta approval (hours to a day; the worker syncs every 30 minutes). Set the Meta webhook (section 5). While on the test number, add the customer's phone as a test recipient in Meta (API Setup → To). The customer needs a WhatsApp opt-in (cart, thank-you page or checkout notice).
SMS	MSG91 key installed; cannot send yet	DLT registration: entity, sender ID and the 4 templates; then put the DLT and MSG91 ids in templates/sms/ and deploy. Set the MSG91 delivery-report URL.
Shopify Admin API	Not available yet (shop_not_permitted)	The live store is not in the app's developer organisation, so production needs a permanent token from a one-time app install sign-in. Needed for the web pixel (browse journey), back-in-stock and single-use discount codes. Webhooks work without it.
Razorpay, Shiprocket	Endpoints ready	Point their webhooks at production (section 5).

10. Releasing to every customer

Only when you say so. Today only marylindajohnson22@gmail.com is stored or messaged; every other customer's webhooks are acknowledged and dropped.

```
# on the server, as root
cd /opt/wumika
sed -i 's/^CUSTOMER_ALLOWLIST_EMAILS=.*/CUSTOMER_ALLOWLIST_EMAILS=*/' .env
docker compose up -d --force-recreate ingest admin worker
```

To add a few more test customers first, list them comma-separated instead of `*`. Before releasing: WhatsApp templates approved, the Indian number registered, the business settings reviewed in the console (budgets, caps, quiet hours, discounts), and the alert forwarding set up.

History

- 27 Sep 2026: server cleaned of a crypto-miner (dev use).
- 18 Oct 2026: miner configuration found still present (2.3 GB of huge pages reserved); dev deployment removed, dev database backed up to the PC.
- 19 Oct 2026: OS reinstalled, hardened, production deployed, live app connected, WhatsApp templates submitted.