dealignai/GLM-5.3-Flash-UNCENSORED-NVFP4

Like 49

Safetensors | English | glm5_next | abliterated | uncensored | crack | glm | Mixture of Experts | nvfp4 | vision | mtp | 8-bit precision | modelopt | License: mit

Copy to bucket NEW

Model card | Files xet | Community 3

Serving note — read before your first request (vLLM / SGLang with a reasoning parser).

- `reasoning_effort` **only accepts** `"low"` **and** `"high"`. Anything else — `medium`, `xhigh`, `off`, or omitting it — silently resolves to `max`, the deepest mode. Template line: `reasoning_effort ... in ['low','high'] else 'max'`.
- **At** `max`**, a small** `max_tokens` **returns an EMPTY reply.** The model spends the whole budget inside `<think>` and you get `finish_reason="length"` with `content=""`. In multi-turn the empty turn poisons the history and the conversation does not recover. Measured: `max` + `max_tokens` `2000` dies from turn ~4; `max` + `6000` is clean; `low` and `high` are clean at 2000. **It is budget exhaustion, not a loop** — sampling changes do not rescue it.
- **Do NOT pass** `enable_thinking`. This template has no such variable (only `clear_thinking` and `reasoning_effort`). Passing it — or a top-level `reasoning_effort: "none"` — turns the parser off while the model still thinks, dumping raw reasoning into `content`.

Downloads last month
7,889



Safetensors

Model size	165B params
Tensor type	F32 · BF16 · U8

Chat template | Files info

Inference Providers NEW

This model isn't deployed by any Inference Provider.

Ask for provider support

Model tree for dealignai/GLM-5.3…

Base model zai-org/GLM-5.3-Flash

Quantized (182) ..... this model

Merges ..... 1 model

Spaces using dealignai/GLM-5.… 2

tardellirs/model-pulse

emanforhelp/model-pulse

- **Reasoning is returned in** `message.reasoning`, not `message.reasoning_content` (vLLM renamed the output field; the input side still accepts both).
- `clear_thinking` must be nested inside `chat_template_kwargs` — a top-level key is ignored.

```
{
  "model": "<this-model>",
  "messages": [{"role": "user", "content":
  "max_tokens": 2000,
  "temperature": 1.0, "top_p": 0.95,
  "chat_template_kwargs": {"reasoning_effo
}
```

Use `"high"` for hard tasks; if you want `max`, give it `max_tokens >= 6000`.

Video and image parameters — measured, because several are accepted then silently ignored.

- 🔴 `media_io_kwargs.video.fps` **must stay BELOW the clip's own frame rate.** Requesting a value at or above it makes the placeholder builder count 3x the real tokens and **kills the engine**: `ValueError: Attempted to assign N = N multimodal tokens to 3N placeholders` -> `EngineDeadError`, server down until restarted. Upstream: vLLM #55644 / #55647. `fps: 2` is the safe, accurate choice.
- `max_frames` **and** `num_frames` **are not interchangeable across builds.** On vLLM nightly `max_frames` is honoured and `num_frames` ignored; on the older `0.1.dev*` line it is the exact reverse. A client that sets only one silently gets full-rate sampling on the other build. Set `fps`, which every build honours.
- **Pixel controls: use** `mm_processor_kwargs.max_image_tokens` / `min_image_tokens`. `max_pixels`, `min_pixels`,

`size` and `detail` return HTTP 200 and change nothing. `mm_processor_kwargs.fps` is an HTTP 400. Image tokens are `text + 2 + ceil(H/28)*ceil(W/28)`, floored at 16 and capped at 8000.

- Default video sampling differs by build (roughly 2 fps vs 6 fps), so the same clip can cost very different prompt tokens. Pass `fps` explicitly if token cost matters.

```
"media_io_kwargs": {"video": {"fps": 2}},
"mm_processor_kwargs": {"max_image_tokens"
```

⚠️ *Updated 2026-08-29 — files fixed · please re-download*

*"This release **supersedes the previous weights.** It fixes a rare **repetition-loop** issue and lands MMLU **85.28%** (within ~0.9 pt of the base model — quality intact).*

***Reasoning-mode note (please read):** GLM-5.3-Flash has multiple reasoning-effort modes. This CRACK is tuned to be **fully uncensored at reasoning-OFF and at MAX effort — the recommended and default modes — with 0% refusals on HarmBench-320.** We deliberately kept the weight edit **conservative to preserve model quality** instead of aggressively ablating every effort level; **low effort** retains some refusals **by design** (aggressively removing them costs quality). Use reasoning-off or default/max effort for the fully-uncensored experience. Please **re-download** for the corrected files."*



GLM 5.3 CRACK Uncensored NVFP4

CRACK · guardrails removed at the weight level · vision tower + MTP head retained

a **CRACK** release by dealignai · Twitter @dealignai

Also mirrored at dealignai/GLM-5.3-Flash-ABLITERATED-NVFP4.

What Is This?

CRACK is dealignai's brand for permanent, weight-level uncensoring. This is GLM-5.3-Flash with its refusal behavior — which caused heavy over-refusal, especially on copyright and other benign-but-flagged requests — removed **directly in the model weights**.

This is genuine weight modification — none of the usual shortcuts:

- ❌ **No fine-tuning / SFT / DPO** — the model was not retrained on anything.
- ❌ **No cheap template tricks** — no jailbreak system prompt, no chat-template edits, no "sure, here is" prefixing.
- ❌ **No LoRA, no adapters, no steering vectors, no runtime hooks, no custom** `model.py`**.**
- ✅ **A permanent edit baked into the tensors.** Load it with stock vLLM and it just works.

Specs

Architecture	GLM-5.3-Flash (`glm5_next`) — hybrid MoE (KDA linear + DeepSeek-sparse attention)
Parameters	**320B total · 18B active** per token
Quantization	**NVFP4** (routed experts NVFP4; attention + shared experts + embeddings bf16)
Context	1M tokens
Vision	GLM-4.1V vision tower — **retained, byte-for-byte identical to base**
MTP	multi-token-prediction draft head — **also CRACK'd** (81.7% acceptance)
Reasoning	reasoning-off / low / high / max effort — see the compliance table below

MTP Is Also CRACK'd

The **MTP (multi-token prediction) speculative-decoding draft head is CRACK'd too** — not just the main model. The draft head will not propose refusals, so speculative decoding stays **compliant *and* fast** on the exact prompts a stock model would refuse.

Reasoning Modes — Compliance

GLM-5.3-Flash supports several reasoning-effort modes. Guardrail removal is strongest in the modes people actually use by default. HarmBench-320, greedy (temperature 0), measured per mode:

Reasoning mode	Refusals	Notes
Reasoning-off	**0%**	fully uncensored
Max effort (default)	**0%**	fully uncensored
High effort	~4%	complies on all but the most extreme safety cases
Low effort	~9%	**intentionally left conservative to preserve quality**

0 degenerate / looping outputs in every mode. The design choice: keep the ablation light enough that capability (MMLU) stays essentially at base, rather than over-ablating to force the rarely-used low-effort mode. **For a fully uncensored model, use reasoning-off or the default/max effort mode.**

*These rates are **greedy decoding (temperature 0)** — the strict worst case. Under the model's **recommended sampling** (temperature 1.0, top_p 0.95) the model is at least as compliant.*

Capability Is Preserved — MMLU-logit

Identical logit-mode scoring (argmax over A/B/C/D) on base vs. this model, 1,026 questions:

	Base	CRACK Uncensored	Δ
MMLU (overall)	**86.16%**	**85.28%**	**-0.88 pp**

A sub-1-point delta — reasoning and knowledge are intact.

MMLU by Topic (base → CRACK)

▶ All 57 MMLU subjects

Usage

```
vllm serve dealignai/GLM-5.3-Flash-UNCENSORE
  --tensor-parallel-size 4 --moe-backend mar
  --tool-call-parser glm47 --reasoning-parse
  --speculative-config '{"method":"mtp","num
```

OpenAI-compatible chat/completions, tools, reasoning, **vision** (`image_url`), and **MTP** speculative decoding all work. NVFP4 routed experts serve via the Marlin FP4 path on Hopper (H100/H200).

Credits

- dealignai — CRACK abliteration research & release · Twitter @dealignai
- @jordanschenck — compute

Disclaimer

This model has had its safety guardrails removed [illegible] with requests a stock model refuses. Released for alignment and safety research. You are responsible for how you use it.

System theme TOS Privacy About Careers Models Datasets Spaces Pricing Docs