

```

print("Hello! I am your smart-search helper. 🤖")
print("Give me a puzzle and I will find the shortest answer with A*! ⭐")
def astar(start, goal, get_neighbours, guess):
    # The to-do list. Each note is [f, g, place, path_so_far].
    frontier = [[guess(start), 0, start, [start]]]
    visited = [] # places we already explored
    explored_count = 0 # how many places we explored (for comparing)

    while len(frontier) > 0:
        # 1) Find the note with the SMALLEST f by looking through the list.
        best = 0
        for i in range(len(frontier)):
            if frontier[i][0] < frontier[best][0]:
                best = i
        note = frontier.pop(best) # take that note out of the list

        f, g, place, path = note # unpack the note

        # 2) If we already explored this place, skip it.
        if place in visited:
            continue
        visited.append(place)
        explored_count = explored_count + 1

        # 3) Did we reach the goal? Then we are done.
        if place == goal:
            return path, explored_count

        # 4) Add each neighbour to the to-do list as a new note.
        for nxt in get_neighbours(place):
            if nxt not in visited:
                new_g = g + 1 # one more step
                new_f = new_g + guess(nxt) # f = g + h
                frontier.append([new_f, new_g, nxt, path + [nxt]])

    return None, explored_count # no path found

print("A* is ready. ✅")
grid = [
    ".....",
    "....###...",
    "S.....G",
    "....###...",
    ".....",
]

def find(letter):
    for r in range(len(grid)):
        for c in range(len(grid[r])):
            if grid[r][c] == letter:
                return (r, c)

start = find("S")
goal = find("G")
rows, cols = len(grid), len(grid[0])

print("Start S is at", start)
print("Goal G is at", goal)
print()
for line in grid:
    print(" " + " ".join(line))
def grid_neighbours(box):
    r, c = box
    out = []
    for dr, dc in [(-1, 0), (1, 0), (0, -1), (0, 1)]: # up, down, left, right
        nr, nc = r + dr, c + dc
        if 0 <= nr < rows and 0 <= nc < cols: # stay on the grid
            if grid[nr][nc] != "#": # not a wall

```

```

        out.append((nr, nc))
    return out

print("From the start", start, "the robot can step to:", grid_neighbours(start))
# Guess 1: no hint at all
def grid_zero(box):
    return 0

# Guess 2: the Manhattan distance (rows apart + columns apart)
def grid_manhattan(box):
    r, c = box
    return abs(r - goal[0]) + abs(c - goal[1])

print("Manhattan guess from the start:", grid_manhattan(start))
path_zero, explored_zero = astar(start, goal, grid_neighbours, grid_zero)
path_manh, explored_manh = astar(start, goal, grid_neighbours, grid_manhattan)

print("Guess          Path length    Boxes explored")
print("-" * 46)
print("Zero (no hint) ", len(path_zero) - 1, "steps      ", explored_zero)
print("Manhattan      ", len(path_manh) - 1, "steps      ", explored_manh)
print()
print("Same shortest path. But Manhattan explores FEWER boxes. ★")
def show_grid_path(path):
    path_set = set(path)
    for r in range(rows):
        line = ""
        for c in range(cols):
            if (r, c) == start:
                line += " S "
            elif (r, c) == goal:
                line += " G "
            elif (r, c) in path_set:
                line += " * "
            else:
                line += " " + grid[r][c] + " "
        print(line)

print("The robot's path:")
print()
show_grid_path(path_manh)
goal_state = "123456780"      # the tidy goal (0 is the empty space)
start_state = "123450678"     # a scrambled start

def show_puzzle(state):
    for r in range(3):
        row = state[r*3 : r*3 + 3]
        row = row.replace("0", "_")      # show the empty space as _
        print(" " + " ".join(row))

print("Start:")
show_puzzle(start_state)
print()
print("Goal:")
show_puzzle(goal_state)
def puzzle_neighbours(state):
    out = []
    zero = state.index("0")      # where the empty space is
    r, c = zero // 3, zero % 3
    for dr, dc in [(-1, 0), (1, 0), (0, -1), (0, 1)]:
        nr, nc = r + dr, c + dc
        if 0 <= nr < 3 and 0 <= nc < 3:      # stay inside the box
            new_zero = nr * 3 + nc
            tiles = list(state)
            # swap the empty space with the tile next to it
            tiles[zero], tiles[new_zero] = tiles[new_zero], tiles[zero]
            out.append("".join(tiles))
    return out

print("From the start, we can reach these arrangements:")

```

```

for s in puzzle_neighbours(start_state):
    print(" ", s)
# Guess 1: no hint
def puzzle_zero(state):
    return 0

# Guess 2: count tiles that are NOT in the right place (ignore the empty space)
def puzzle_wrong_tiles(state):
    count = 0
    for i in range(9):
        if state[i] != "0" and state[i] != goal_state[i]:
            count = count + 1
    return count

print("Wrong tiles in the start:", puzzle_wrong_tiles(start_state))
ans_zero, count_zero = astar(start_state, goal_state, puzzle_neighbours, puzzle_zero)
ans_smart, count_smart = astar(start_state, goal_state, puzzle_neighbours, puzzle_wrong_tiles)

print("Guess          Moves to solve   Arrangements explored")
print("-" * 56)
print("Zero (no hint)   ", len(ans_zero) - 1, "moves          ", count_zero)
print("Wrong-tiles      ", len(ans_smart) - 1, "moves          ", count_smart)
print()
print("Same number of moves. But the smart guess explores FAR fewer arrangements! ★")
print("Solving the puzzle, one slide at a time:")
print()
for step, state in enumerate(ans_smart):
    print("Move", step, ":")
    show_puzzle(state)
    print()

```

```

. . . . # # # . . . .
S . . . . . . . . . G
. . . . # # # . . . .
. . . . . . . . . .
. . . . . . . . . .
From the start (2, 0) the robot can step to: [(1, 0), (3, 0), (2, 1)]
Manhattan guess from the start: 10
Guess          Path length   Boxes explored
-----
Zero (no hint) 10 steps      43
Manhattan     10 steps      11

```

Same shortest path. But Manhattan explores FEWER boxes. ★
The robot's path:

```

. . . . # # # . . . .
. . . . # # # . . . .
S * * * * * * * * * G
. . . . # # # . . . .
. . . . . . . . . .
Start:
 1 2 3
 4 5 _
 6 7 8

```

Goal:

```

 1 2 3
 4 5 6
 7 8 _

```

From the start, we can reach these arrangements:

```

120453678
123458670
123405678

```

```

Wrong tiles in the start: 3
Guess          Moves to solve   Arrangements explored
-----
Zero (no hint) 13 moves          2710
Wrong-tiles    13 moves          190

```

Same number of moves. But the smart guess explores FAR fewer arrangements! ★
Solving the puzzle, one slide at a time:

```
4 5 8  
6 7 _
```

Move 2 :

```
1 2 3  
4 5 8  
6 _ 7
```

Move 3 :

```
1 2 3
```