

Implementation and Evaluation of a Compact Table Propagator in Gecode

Linnea Ingmar

10th February 2017

Contents

1	Introduction	2
1.1	Goal	2
1.2	Contributions	2
2	Background	2
2.1	Constraint Programming	2
2.2	Gecode	2
2.3	The TABLEConstraint	2
3	Algorithms	3
3.1	Sparse Bit-Set	3
3.2	Compact-Table (CT) Algorithm	3
3.2.1	Propagator Status Messages	3
4	Implementation	3
5	Evaluation	4
5.1	Evaluation Setup	4
5.2	Results	4
5.3	Discussion	4
6	Conclusions and Future Work	4
A	Source Code	4

1 Introduction

In Constraint Programming (CP), every constraint is associated with a propagator algorithm. The propagator algorithm filters out impossible values for the variables related to the constraint. For the TABLEconstraint, several propagator algorithms are known. In 2016, a new propagator algorithm for the TABLEconstraint was published [1], called Compact Table (CT). Preliminary results indicate that CT outperforms the previously known algorithms. There has been no attempt to implement CT in the constraint solver Gecode [2], and consequently its performance in Gecode is unknown.

1.1 Goal

The goal of this thesis is to implement a CT propagator algorithm for the TABLEconstraint in Gecode, and to evaluate its performance with respect to the existing propagators.

1.2 Contributions

Todo: State the contributions, perhaps as a bulleted list, referring to the different parts of the paper, as opposed to giving a traditional outline. (As suggested by Olle Gallmo.)

This thesis contributes with the following:

- The relevant preliminaries have been covered in Section 2.
- The algorithms presented in [1] have been modified to suit the target constraint solver Gecode, and are presented and explained in Section 3.
- The CT algorithm has been implemented in Gecode, see Section 4.
- The performance of the CT algorithm has been evaluated, see Section 5.
- ...

2 Background

This chapter provides a background that is relevant for the following chapters. It is divided into three parts: Section 2.1 introduces Constraint Programming. Section 2.2 gives an overview of Gecode, a constraint solver. Finally, Section 2.3 introduces the TABLEconstraint.

2.1 Constraint Programming

This section introduces the concept of Constraint Programming (CP).

2.2 Gecode

Gecode [2] is a popular constraint programming solver written in C++.

2.3 The TableConstraint

The TABLEconstraint, called `EXTENSIONAL` in Gecode, explicitly expresses the possible combinations of values for the variables as a sequence of n -tuples.

3 Algorithms

This chapter presents the algorithms that are used in the implementation of the CT propagator in Section 4.

3.1 Sparse Bit-Set

This section describes the class `SparseBitSet` which is the main datastructure in the CT algorithm for maintaining the supports.

3.2 Compact-Table (CT) Algorithm

This section describes the CT algorithm.

3.2.1 Propagator Status Messages

A propagator signals a status message after propagation. For CT there are three possible status messages; *Fail*, *Subsumed* and *Fixpoint*.

Fail. A propagator must correctly signal failure if the constraint is unsatisfiable for the input store S . At the latest a propagator must be able to decide whether or not a S is a solution store when all variables have been assigned. CT has two ways of detecting a failure: either when all bits in `currTable` are set to zero – meaning that none of the tuples are valid, or when the size of the domain of a variable is zero.

Subsumption. A propagator is not allowed to signal subsumption if it could propagate further at a later point. At the latest, a propagator must signal subsumption if all the variables are assigned in S and a S is a solution store. CT signals subsumption when all variables are assigned, since this is the earliest point the propagator can be subsumed.

Fixpoint. A propagator is not allowed to claim that it has computed a fixpoint if it could still propagate. CT always computes a fixpoint if it is not subsumed or wipes out the domain of a variable. To understand this, consider two consecutive calls to `propagate()`. Let T be the set of valid tuples and x be the set of variables. The first time `propagate()` is executed, a (possibly empty) subset T_r of T is invalidated (that is, the corresponding bits in `currTable` are set to 0) in `updateTable()`. Assuming `currTable` is not empty after the return of `updateTable()`, which would cause a backtrack in the search, `filterDomains()` is called. This method removes a (possibly empty) set of values V_i from the domain of each variable x_i . Each value $v_i \in V_i$ has the property that a subset T_{v_i} of the tuples in T_r are the last supports for (x_i, v_i) . In other words, $T \setminus T_{v_i}$ does not contain a support for (x_i, v_i) . So in the second call to `updateTable()`, no tuples are invalidated, because none of the tuples in $T \setminus T_r$ is a support for any variable-value pair $(x_i, v_i) \in \{x_i\} \times V_i, i \in \{1 \dots |x|\}$. Hence, the second call to `propagate()` does not give any further propagation.

4 Implementation

This chapter describes an implementation of the CT propagator using the algorithms presented in Section 3. The implementation was made in the C++ programming language in the Gecode library.

The bit-set matrix `supports` is static and can be shared between all solution spaces.

The bit-set `currTable` changes dynamically during propagation and must therefore be copied for every new space. Can save memory by only copying the non-zero words.

No need to save the `tuples` as a field in the propagator class as all the necessary information is encoded in `currTable` and `supports`.

5 Evaluation

This chapter presents the evaluation of the implementation of the CT propagator presented in Section 4. In Section 5.1, the evaluation setup is described. In Section 5.2 presents the results of the evaluation. The results are discussed in Section 5.3.

5.1 Evaluation Setup

5.2 Results

5.3 Discussion

6 Conclusions and Future Work

References

- [1] J. Demeulenaere, R. Hartert, C. Lecoutre, G. Perez, L. Perron, J. Régin, and P. Schaus. Compact-Table: Efficiently filtering table constraints with reversible sparse bit-sets. In M. Rueher, editor, *CP*, volume 9892 of *Lecture Notes in Computer Science*, pages 207–223. Springer, 2016.
- [2] Gecode Team. Gecode: A generic constraint development environment, 2016.

A Source Code

This appendix presents the source code for the implementation described in Section 4.

```

1: Class SparseBitSet

2: words: array of long                                // words.length = p
3: index: array of int                                // index.length = p
4: limit: int
5: mask: array of long                                // mask.length = p

6: method isEmpty() : Boolean
7:   return limit = -1

8: method clearMask()
9:   foreach  $i$  from 0 to limit do
10:    offset  $\leftarrow$  index[ $i$ ]
11:    mask[offset]  $\leftarrow$   $0^{64}$ 

12: method reverseMask()                                // Not currently used in CT algorithm
13:   foreach  $i$  from 0 to limit do
14:    offset  $\leftarrow$  index[ $i$ ]
15:    mask[offset]  $\leftarrow$   $\sim$ mask[offset]                // bitwise NOT

16: method addToMask(m: array of long)
17:   foreach  $i$  from 0 to limit do
18:    offset  $\leftarrow$  index[ $i$ ]
19:    mask[offset]  $\leftarrow$  mask[offset] | mask[offset]    // bitwise OR

20: method intersectWithMask()
21:   foreach  $i$  from limit downto 0 do
22:    offset  $\leftarrow$  index[ $i$ ]
23:     $w \leftarrow$  words[offset] & mask[offset]            // bitwise AND
24:    if  $w \neq$  words[offset] then
25:      words[offset]  $\leftarrow$   $w$ 
26:      if  $w = 0^{64}$  then
27:        index[ $i$ ]  $\leftarrow$  index[limit]
28:        index[limit]  $\leftarrow$  offset
29:        limit  $\leftarrow$  limit - 1

30: method intersectIndex(m: array of long) : int
31:   foreach  $i$  from 0 to limit do
32:    offset  $\leftarrow$  index[ $i$ ]
33:    if words[offset] & m[offset]  $\neq$   $0^{64}$  then
34:      return offset
35:   return -1

```

Algorithm 1: Pseudo code for the class SparseBitSet.

```

1: Class CT-Propagator

2: scp: array of variables
3: currTable: SparseBitSet                                // Current supported tuples
4: supports                                         // supports[x, a] is the bit-set of supports for (x, a)
5: lastSize: array of int                            // lastSize[x] is the last size of the domain of x.c
6: residues                                         // residues[x, a] is the last found support for (x, a). No residues yet!

7: method initialise(variables, tuples)                // Initialise the propagator
8:   scp ← variables
9:   foreach x ∈ scp do                                // Initial bounds propagation
10:    dom(x) ← dom(x) \ {a ∈ dom(x) : a > tuples.max()}
11:    dom(x) ← dom(x) \ {a ∈ dom(x) : a < tuples.min()}
12:   size ← sum{|dom(x)| : x ∈ scp}
13:   ntuples ← tuples.size()                            // Number of tuples
14:   supports ← BitSets(size, ntuples)                // bit-set matrix with size rows and ntuples columns
15:   no_supports ← 0
16:   foreach t ∈ tuples do
17:     supported ← true
18:     foreach x ∈ scp do
19:       if t[x] ∉ dom(x) then
20:         supported ← false
21:       continue                                       // Exit loop
22:     if supported then
23:       no_supports ← no_supports + 1
24:       supports.setElemsInColumn(no_supports, t)      // Mark tuple as supported
25:       supports.trimToWidth(no_supports)             // Keep only the first no_supports bits for each row
26:       currTable ← SparseBitSet(no_supports)         // SparseBitSet with no_supports bits

27: method updateTable()
28:   foreach x ∈ scp such that |dom(x)| ≠ lastSize[x] do
29:     lastSize[x] ← |dom(x)|
30:     currTable.clearMask()
31:     foreach a ∈ dom(x) do                            // No incremental update yet!
32:       currTable.addToMask(supports[x, a])
33:     currTable.intersectWithMask()
34:     if currTable.isEmpty() then
35:       break

36: method filterDomains()
37:   msg ← Subsumed
38:   foreach x ∈ scp do
39:     foreach a ∈ dom(x) do
40:       index ← currTable.intersectIndex(supports[x, a])
41:       if index ≠ -1 then
42:         continue                                       // No residues yet!
43:     else
44:       dom(x) ← dom(x) \ {a}
45:       if |dom(x)| = 0 then
46:         return Failed
47:       else if |dom(x)| > 1 then
48:         msg ← Fixpoint
49:   return msg

50: method propagate()
51:   updateTable()
52:   if currTable.isEmpty() then
53:     return Failed
54:   return filterDomains()

```

Algorithm 2: Pseudo code for CT propagator class.