

FETCH

Browsers called services with XHR (XMLHttpRequest)

- It was horrible
- Libraries were made to help (jquery, axios, etc)

Now we have `fetch()`!

- No need for those other libraries
- Polyfills available (remember polyfills?)

Node does **not** have fetch built in

- `node-fetch` package is available

FETCH RETURNS A PROMISE

```
const promise = fetch('/people');  
promise.then( () => console.log('fetch complete') );
```

The promise resolves with a Response object

(google: [MDN Response](#))

```
fetch('/people/')  
  .then( response => console.log(response.status) );
```

RESPONSE OBJECT LACKS PARSED BODY

If you are getting data, you want the body

The body has not been parsed for the response object

Call a method to parse the body (`.text()` or `.json()`)

These parsing methods **are async**

```
fetch('/people/')  
  .then( response => response.json() )  
  .then( body => console.log(body) );
```

USING THE BODY

```
<ul class="example"></ul>
```

```
const list = document.querySelector('.example');
fetch('/people/')
  .then( response => response.json() )
  .then( people => {
    const names = people.map(
      name => `<li>${name}</li>`
    ).join('')
    list.innerHTML = names;
  });
```

HANDLING ERRORS

`fetch` promise **NOT** rejected if service returns error

Service errors are successful communication

- `fetch().catch()`: only network errors

Instead, you can check the status code

- If the service is using status codes meaningfully
- `response.ok` is shorthand for status code ranges
- Then react as you want

Does service give error/non-error messages in same format (e.g. JSON)?

ERROR EXAMPLE

```
<ul class="example"></ul>
<div class="status"></div>
```

```
const status = document.querySelector('.status');
fetch('/people/')
  .then( response => {
    if(response.ok) { return response.json(); }

    return response.json().then(err => Promise.reject(err) );
  })
  .then( people => {
    const names = people.map(
      name => `<li>${name}</li>`
    ).join('')
    document.querySelector('.example').innerHTML = names;
  })
  .catch( err => status.innerText = err.error );
```

ERROR TIPS

- Don't leave the user confused
- `console.log()` is **NOT** error handling
- You almost never SHOW the error message directly from the service

Students lose multiple points on their assignments and projects every semester

- Tell the user what they need to do just like you see on actual websites

DIFFERENT METHODS

`fetch()` defaults to GET method.

It accepts an optional object

- The `method` key allows you to set the method

```
fetch('/people/', {  
  method: 'POST'  
})
```


SENDING DATA

Query params are sent as part of the URL

- the first argument to `fetch()`

Body params can be sent as the `body` option

- Remember: Not with GET
- Body params can be in multiple formats

```
fetch('/people/', {  
  method: 'POST',  
  body: JSON.stringify({ name: 'bob', age: 32 })  
})
```

SENDING HEADERS

There is a `Headers()` object and a `headers` property

```
fetch('/people/', {  
  method: 'POST',  
  headers: new Headers({  
    'content-type': 'application/json'  
  }),  
  body: JSON.stringify({ name: 'bob', age: 32 })  
})
```

NodeJS node-fetch has no `Headers()` - just pass an object

CONSUME THE LIST OF NAMES REST SERVICE

- Page has empty ``, a text field, and a button
- On page load, populate `` with the names
- Each name has an "X" to delete it
- Button will add the name to the list
- Show an error if an error

Consider:

- What makes the service easy/hard to use?
- How is it easy to translate the error code to a friendly message?