

Lab 1: Packet analysis at application layer using Wireshark

SCSR1213 Network Communications

Universiti Teknologi Malaysia

Objective:

1. Understanding of network protocols by observing the sequence of messages exchanged between two protocol entities, delving down into the details of protocol operation, and causing protocols to perform certain actions and then observing these actions and their consequences.
2. To introduce student with Wireshark software tool for packet analyzer.
3. To analyze protocol used in application layer such as http and dns.

Reference material: Computer Networking: A Top-Down Approach, 7th ed., J.F. Kurose and K.W. Ross.

Name :LING YU QIAN

Metric No :A23CS0301

Section :1



Mark

PART A: Wireshark Getting Started

1.0 Introduction

The basic tool for observing the messages exchanged between executing protocol entities is called a **packet sniffer**. As the name suggests, a packet sniffer captures (“sniffs”) messages being sent/received from/by your computer; it will also typically store and/or display the contents of the various protocol fields in these captured messages. A packet sniffer itself is passive. It observes messages being sent and received by applications and protocols running on your computer, but never sends packets itself. Similarly, received packets are never explicitly addressed to the packet sniffer. Instead, a packet sniffer receives a *copy* of packets that are sent/received from/by application and protocols executing on your machine.

Figure A.1 shows the structure of a packet sniffer. At the right of Figure 1 are the protocols (in this case, Internet protocols) and applications (such as a web browser or ftp client) that normally run on your computer. The packet sniffer, shown within the dashed rectangle in Figure A.1 is an addition to the usual software in your computer, and consists of two parts. The **packet capture library** receives a copy of every link-layer frame that is sent from or received by your computer. In Figure A.1, the assumed physical media is an Ethernet, and so all upper-layer protocols are eventually encapsulated within an Ethernet frame. Capturing all link-layer frames thus gives you all messages sent/received from/by all protocols and applications executing in your computer.




Figure A.1: Packet sniffer structure

The second component of a packet sniffer is the **packet analyzer**, which displays the contents of all fields within a protocol message. In order to do so, the packet analyzer must “understand” the structure of all messages exchanged by protocols. The packet analyzer understands the format of Ethernet frames, and so can identify the IP datagram within an Ethernet frame. It also understands the IP datagram format, so that it can extract the TCP segment within the IP datagram. Finally, it understands the TCP segment structure, so it can extract the HTTP message contained in the TCP segment. Finally, it understands the HTTP protocol and so, for example, knows that the first bytes of an HTTP message will contain the string “GET,” “POST,” or “HEAD”.

2.0 Getting Wireshark Ready

- Download and install the Wireshark software
- Run Wireshark. Wireshark startup screen shown in Figure A.2.




Figure A.2: Initial Wireshark startup screen

- The Wireshark interface has five major components as shown in Figure A.3.




Figure A.3: Wireshark Graphical User Interface, during packet capture and

- The **command menus** are standard pulldown menus located at the top of the window.
- The **packet display filter field**, into which a protocol name or other information can be entered in order to filter the information displayed in the packet-listing window.
- The **packet-listing window** displays a one-line summary for each packet captured, including the packet number, the time at which the packet was captured, the packet's source and destination addresses, the protocol type, and protocol-specific information contained in the packet.
- The **packet-header details window** provides details about the packet selected (highlighted) in the packet-listing window. These details include information about the Ethernet frame and IP datagram that contains this packet. The amount of Ethernet and IP-layer detail displayed can be expanded or minimized by clicking on the plus minus boxes to the left of the Ethernet frame or IP datagram line in the packet details window. If the packet has been carried over TCP or UDP, TCP or UDP details will also be displayed, which can similarly be expanded or minimized. Finally, details about the highest-level protocol that sent or received this packet are also provided.
- The **packet-contents window** displays the entire contents of the captured frame, in both ASCII and hexadecimal format.

3.0 Test Run Wireshark

- Start up the Wireshark software.
- To begin packet capture, select the Capture pull down menu and pick Options menu. Select appropriate interfaces on your compute and click Start button to begin packet capture. Refer to Figure A4




Figure A.4: Capture and Options Menu

- Once you begin packet capture, result will be shown as in Figure A.5.




Figure A.5: Wireshark packet capture result

- By selecting Capture pulldown menu and selecting Stop, you can stop packet capture.

- Type “arp” in packet display filter field and press Enter key. This will cause only ARP message to be displayed in the packet-listing window as shown in Figure A.6.




Figure A.6: ARP packet capture

- To save the trace result, use File pulldown menu and select Save function as shown in Figure A.7.





Figure A.7: Save Wireshark trace result

PART B: HTTP Trace

In this part, we'll explore several aspects of the HTTP protocol: the basic GET/response interaction, HTTP message formats and retrieving HTML files with embedded objects. Before beginning these labs, you might want to review Section 2.2 of the textbook.

B.1 The Basic HTTP GET/response interaction

- Open packet trace file **lab1-http-B01.pcapng**.
- Enter “**http**” (just the letters, not the quotation marks) in the **packet display filter field**, so that only captured HTTP messages will be displayed later in the packet-listing window. Refer to figure below:



packet display filter

- By looking at the information in the HTTP GET and response messages, answer the following questions:

http							
No.	Time	Source	Destination	Protocol	Length	Info	
10	4.694850	192.168.1.102	gaia.cs.umass.edu	HTTP	555	GET /ethereal-labs/lab2-1.html	HTTP/1.1
12	4.718993	gaia.cs.umass.edu	192.168.1.102	HTTP	439	HTTP/1.1 200 OK	(text/html)
13	4.724332	192.168.1.102	gaia.cs.umass.edu	HTTP	541	GET /favicon.ico	HTTP/1.1
14	4.750366	gaia.cs.umass.edu	192.168.1.102	HTTP	1395	HTTP/1.1 404 Not Found	(text/html)

1. What version of HTTP is the server running?
HTTP/1.1
2. What is the IP address of the client computer?
192.168.1.102
3. What is the IP address of the gaia.cs.umass.edu server?
128.119.245.12
4. How many bytes of content are being returned to client browser?

For the successful request (Status 200 OK), 73 bytes

For 404 not found, 1071 bytes

```
✓ HTTP/1.1 200 OK\r\n
  Response Version: HTTP/1.1
  Status Code: 200
  [Status Code Description: OK]
  Response Phrase: OK
  Date: Tue, 23 Sep 2003 05:29:50 GMT\r\n
  Server: Apache/2.0.40 (Red Hat Linux)\r\n
  Last-Modified: Tue, 23 Sep 2003 05:29:00 GMT\r\n
  ETag: "1bfed-49-79d5bf00"\r\n
  Accept-Ranges: bytes\r\n
> Content-Length: 73\r\n

✓ Hypertext Transfer Protocol
  ✓ HTTP/1.1 404 Not Found\r\n
    Response Version: HTTP/1.1
    Status Code: 404
    [Status Code Description: Not Found]
    Response Phrase: Not Found
    Date: Tue, 23 Sep 2003 05:29:50 GMT\r\n
    Server: Apache/2.0.40 (Red Hat Linux)\r\n
    Vary: accept-language\r\n
    Accept-Ranges: bytes\r\n
> Content-Length: 1071\r\n
```

5. What is the status code returned from the server to client browser?

200(OK) and 404(Not Found)

B.2 The HTTP CONDITIONAL GET/response interaction

- Open packet trace file **lab1-http-B02.pcapng**.
- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. Inspect the contents of the first HTTP GET request from your browser to the server. Do you see an “IF-MODIFIED-SINCE” line in the HTTP GET?

There is no “IF-MODIFIED-SINCE” line in the HTTP GET.

No.	Time	Source	Destination	Protocol	Length	Info
8	2.331268	192.168.1.102	gaia.cs.umass.edu	HTTP	555	GET /etherreal-labs/lab2-2.html HTTP/1.1
10	2.357902	gaia.cs.umass.edu	192.168.1.102	HTTP	739	HTTP/1.1 200 OK (text/html)
14	5.517390	192.168.1.102	gaia.cs.umass.edu	HTTP	668	GET /etherreal-labs/lab2-2.html HTTP/1.1
15	5.540216	gaia.cs.umass.edu	192.168.1.102	HTTP	243	HTTP/1.1 304 Not Modified

> Frame 8: 555 bytes on wire (4440 bits), 555 bytes captured (4440 bits) on interface unknown, id 0	0030	fa f0 39 a2
> Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: LinksysGroup_da:af:73 (00:06:25:da:af:73)	0040	65 61 6c 2d
> Internet Protocol Version 4, Src: 192.168.1.102 (192.168.1.102), Dst: gaia.cs.umass.edu (128.119.245.12)	0050	68 74 6d 6c
> Transmission Control Protocol, Src Port: 4247 (4247), Dst Port: http (80), Seq: 1, Ack: 1, Len: 501	0060	6f 73 74 3a
> Hypertext Transfer Protocol	0070	73 73 2e 65
GET /etherreal-labs/lab2-2.html HTTP/1.1\r\n	0080	6e 74 3a 20
Request Method: GET	0090	28 57 69 6e
Request URI: /etherreal-labs/lab2-2.html	00a0	64 6f 77 73
Request Version: HTTP/1.1	00b0	55 53 3b 20
	00c0	63 6b 6f 2f
	00d0	73 63 61 70

2. Inspect the contents of the server response after the first GET request from client. Did the server explicitly return the contents of the file? How can you tell?

No.	Time	Source	Destination	Protocol	Length	Info
8	2.331268	192.168.1.102	gaia.cs.umass.edu	HTTP	555	GET /etherreal-labs/lab2-2.html HTTP/1.1
10	2.357902	gaia.cs.umass.edu	192.168.1.102	HTTP	739	HTTP/1.1 200 OK (text/html)
14	5.517390	192.168.1.102	gaia.cs.umass.edu	HTTP	668	GET /etherreal-labs/lab2-2.html HTTP/1.1
15	5.540216	gaia.cs.umass.edu	192.168.1.102	HTTP	243	HTTP/1.1 304 Not Modified


The server explicitly return the contents of the file shown by the status code 200.

Content:

Line-based text data: text/html (10 lines)

```
\n
<html>\n
\n
Congratulations again! Now you've downloaded the file lab2-2.html. <br>\n
This file's last modification date will not change. <p>\n
Thus if you download this multiple times on your browser, a complete copy <br>\n
will only be sent once by the server due to the inclusion of the IN-MODIFIED-SINCE<br>\n
field in your browser's HTTP GET request to the server.\n
\n
</html>\n
```

The server explicitly return the contents of the file as the content return to my browser is same as the content in server.



Congratulations again! Now you've downloaded the file lab2-2.html.
This file's last modification date will not change.

Thus if you download this multiple times on your browser, a complete copy will only be sent once by the server due to the inclusion of the IN-MODIFIED-SINCE field in your browser's HTTP GET request to the server.

3. Now inspect the contents of the second HTTP GET request from your browser to the server. Do you see an "IF-MODIFIED-SINCE:" line in the HTTP GET? If so, what information follows the "IF-MODIFIED-SINCE:" header?

```
▼ Hypertext Transfer Protocol
> GET /ethereal-labs/lab2-2.html HTTP/1.1\r\n
Host: gaia.cs.umass.edu\r\n
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.0.2) Gecko/20021120 Netscape/7.01\r\n
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,video/x-mng\r\n
Accept-Language: en-us,en;q=0.50\r\n
Accept-Encoding: gzip, deflate, compress;q=0.9\r\n
Accept-Charset: ISO-8859-1, utf-8;q=0.66, *;q=0.66\r\n
Keep-Alive: 300\r\n
Connection: keep-alive\r\n
If-Modified-Since: Tue, 23 Sep 2003 05:35:00 GMT\r\n
If-None-Match: "1bfef-173-8f4ae900"\r\n
Cache-Control: max-age=0\r\n
\r\n
[Response in frame: 15]
[Full request URI: http://gaia.cs.umass.edu/ethereal-labs/lab2-2.html]
```

Yes there is IF-MODIFIED-SINCE ,Followed by "Tue, 23 SEP 2003 05:35:00"

4. What is the HTTP status code and phrase returned from the server in response to this second HTTP GET? Did the server explicitly return the contents of the file? Explain.

The HTTP status code returned from the server in response to the second HTTP GET request is **304**, with the status phrase "**Not Modified**".

When a server responds with a 304 status code, it indicates that the requested resource has not been modified since the last time the client requested it. This means the server did not explicitly return the contents of the file, as the client already has a cached version that is still valid. The server only provided headers to confirm that the cached version can be reused, saving bandwidth by not retransmitting the file content.

In this case, the response includes headers such as "ETag" and "Date," which help manage caching, but no file content is sent in the response body.

No.	Time	Source	Destination	Protocol	Length	Info
8	2.331268	192.168.1.102	gaia.cs.umass.edu	HTTP	555	GET /ethereal-labs/lab2-2.html HTTP/1.1
10	2.357902	gaia.cs.umass.edu	192.168.1.102	HTTP	739	HTTP/1.1 200 OK (text/html)
14	5.517390	192.168.1.102	gaia.cs.umass.edu	HTTP	668	GET /ethereal-labs/lab2-2.html HTTP/1.1
15	5.540216	gaia.cs.umass.edu	192.168.1.102	HTTP	243	HTTP/1.1 304 Not Modified

Acknowledgment Number: 1116 (relative ack number)	0000 00 00 74 4f 3c 78 00 06 25 da af 73 08 00 45 00	..TOG..X..s..E..
Acknowledgment number (raw): 4203218316	0010 00 e5 dc 88 40 00 37 06 2e f8 80 77 f5 0c c0 a8	...@-7-...W....
0101 = Header Length: 20 bytes (5)	0020 01 66 00 50 10 97 81 6a b6 2e fa 88 05 8c 50 18	..f.P...j...P...
> Flags: 0x018 (PSH, ACK)	0030 1f 2e 89 37 00 00 48 54 54 50 2f 31 2e 31 20 33	..-7-..HT P/1.1 3
Window: 7982	0040 30 34 20 4e 6f 74 20 4d 6f 64 69 66 69 65 64 0d	04 Not Modified
[Calculated window size: 7982]	0050 0a 44 61 74 65 3a 20 54 75 65 2c 20 32 33 20 53	..Date: T ue, 23 S
[Window size scaling factor: -2 (no window scaling used)]	0060 65 70 20 32 30 30 33 20 30 35 3a 33 35 3a 35 33	ep 2003 05:35:53
Checksum: 0x8937 [unverified]	0070 20 47 4d 54 0d 0a 53 65 72 76 65 72 3a 20 41 70	GMT-Se rver: Ap
[Checksum Status: Unverified]	0080 61 63 68 65 2f 32 2e 30 2e 34 30 20 28 52 65 64	ache/2.0 .40 (Red
Urgent Pointer: 0	0090 20 48 61 74 20 4c 69 6e 75 78 29 0d 0a 43 6f 6e	Hat Lin ux)..Con
> [Timestamps]	00a0 6e 65 63 74 69 6f 6e 3a 20 4b 65 65 70 2d 41 6c	nection: Keep-Al
> [SEQ/ACK analysis]	00b0 69 76 65 0d 0a 4b 65 65 70 2d 41 6c 69 76 65 3a	ive-Keep p-Alive:
TCP payload (189 bytes)	00c0 20 74 69 6d 65 6f 75 74 3d 31 30 2c 20 6d 61 78	timeout=10, max
> Hypertext Transfer Protocol	00d0 3d 39 39 0d 0a 45 54 61 67 3a 20 22 31 62 66 65	=99- ETag: "1bfe
> HTTP/1.1 304 Not Modified\r\n	00e0 66 2d 31 37 33 2d 38 66 34 61 65 39 30 30 22 0d	f-173-8f 4ae900"
Date: Tue, 23 Sep 2003 05:35:53 GMT\r\n	00f0 0a 0d 0a	...
Server: Apache/2.0.40 (Red Hat Linux)\r\n		
Connection: Keep-Alive\r\n		
Keep-Alive: timeout=10, max=99\r\n		
ETag: "1bfe-173-8f4ae900"\r\n		
\r\n		
[Request in frame: 14]		
[Time since request: 0.022826000 seconds]		
[Request URI: /ethereal-labs/lab2-2.html]		
[Full request URI: http://gaia.cs.umass.edu/ethereal-labs/lab2-2.html]		

B.3 HTML Documents with Embedded Objects

- Open packet trace file **lab1-http-B03.pcapng**.
- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. How many HTTP GET request messages did client browser send?

Source	Destination	Protocol	Length	Info
192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-4.html HTTP/1.1
128.119.245.12	192.168.1.102	HTTP	1057	HTTP/1.1 200 OK (text/html)
192.168.1.102	165.193.123.218	HTTP	625	GET /catalog/images/pearson-logo-footer.gif HTTP/1.1
192.168.1.102	134.241.6.82	HTTP	609	GET /~kurose/cover.jpg HTTP/1.1
165.193.123.218	192.168.1.102	HTTP	912	HTTP/1.1 200 OK (GIF89a)
134.241.6.82	192.168.1.102	HTTP	1096	HTTP/1.0 200 Document follows (JPEG JFIF image)

3 HTTP GET request messages sent

2. To which Internet addresses were these GET requests sent?
128.119.245.12, 165.193.123.218 and 134.241.6.82

3. any bytes of content are being returned to client browser for the **pearson-logo-footer.gif** image file?

3357 bytes

4. How many bytes of content are being returned to client browser for the **cover.jpg** image file?


15642 bytes

PART C: DNS Trace

1.0 nslookup

nslookup tool allows the host running the tool to query any specified DNS server for a DNS record. The queried DNS server can be a root DNS server, a top-level-domain DNS server, an authoritative DNS server, or an intermediate DNS server. To accomplish this task, nslookup sends a DNS query to the specified DNS server, receives a DNS reply from that same DNS server, and displays the result.

- To run it in Windows, open the Command Prompt (cmd) and run nslookup on the command line as shown in Figure C.1 and Figure C.2



```
C:\WINDOWS\system32\cmd.exe
C:\Users\pc-vastro220>nslookup yahoo.com
Server: ns1.utm.my
Address: 161.139.250.2


Non-authoritative answer:
Name: yahoo.com
Addresses: 2001:4998:58:1836::11
           2001:4998:c:1023::4
           2001:4998:44:41d::4
           2001:4998:44:41d::3
           2001:4998:58:1836::10
           2001:4998:c:1023::5
           72.30.35.10
           98.137.246.7
           98.137.246.8
           98.138.219.231
           98.138.219.232
           72.30.35.9

C:\Users\pc-vastro220>nslookup -type=any yahoo.com
Server: jlb.utm.my
Address: 161.139.250.2

Non-authoritative answer:
yahoo.com      MX preference = 1, mail exchanger = mta5.am0.yahoodns.net
yahoo.com      MX preference = 1, mail exchanger = mta6.am0.yahoodns.net
yahoo.com      MX preference = 1, mail exchanger = mta7.am0.yahoodns.net
yahoo.com      AAAA IPv6 address = 2001:4998:c:1023::4
yahoo.com      AAAA IPv6 address = 2001:4998:44:41d::4
yahoo.com      AAAA IPv6 address = 2001:4998:44:41d::3
yahoo.com      AAAA IPv6 address = 2001:4998:58:1836::10
yahoo.com      AAAA IPv6 address = 2001:4998:c:1023::5
yahoo.com      AAAA IPv6 address = 2001:4998:58:1836::11
yahoo.com      nameserver = ns5.yahoo.com
yahoo.com      nameserver = ns2.yahoo.com
yahoo.com      nameserver = ns4.yahoo.com
yahoo.com      nameserver = ns1.yahoo.com
yahoo.com      nameserver = ns3.yahoo.com
yahoo.com      internet address = 98.137.246.7
yahoo.com      internet address = 98.137.246.8
yahoo.com      internet address = 98.138.219.231
yahoo.com      internet address = 98.138.219.232
yahoo.com      internet address = 72.30.35.9
yahoo.com      internet address = 72.30.35.10

C:\Users\pc-vastro220>
```

Figure C.1: nslookup result



```
C:\WINDOWS\system32\cmd.exe
C:\Users\pc-vastro220>nslookup google.com ns1.time.net.my
Server: ns1.test.time.net.my
Address: 203.121.16.85

Non-authoritative answer:
Name: google.com
Addresses: 2404:6800:4001:804::200e
           172.217.24.174

C:\Users\pc-vastro220>
```

Figure C.2: nslookup result

1. Run nslookup to obtain the IP address of a www.microsoft.com server. What is the IP address of that server? Add screenshot to your answer.

```
Microsoft Windows [Version 10.0.22631.4317]
(c) Microsoft Corporation. All rights reserved.

C:\Users\User>nslookup www.microsoft.com
Server:  ns1.utm.my
Address:  161.139.250.2

Non-authoritative answer:
Name:     e13678.dscb.akamaiedge.net
Addresses: 2001:f40:a:c84::356e
           2001:f40:a:c81::356e
           23.202.182.15
Aliases:  www.microsoft.com
           www.microsoft.com-c-3.edgekey.net
           www.microsoft.com-c-3.edgekey.net.globalredir.akadns.net
```

161.139.250.2

2. Run nslookup to determine the non-authoritative DNS servers for domain microsoft.com. Add screenshot to your answer.

```
C:\Users\User>nslookup microsoft.com
Server:  ns1.utm.my
Address:  161.139.250.2


Non-authoritative answer:
Name:     microsoft.com
Addresses: 2603:1010:3:3::5b
           2603:1020:201:10::10f
           2603:1030:c02:8::14
           2603:1030:20e:3::23c
           2603:1030:b:3::152
           20.112.250.133
           20.70.246.20
           20.236.44.162
           20.76.201.171
           20.231.239.246
```

the non-authoritative DNS server is ns1.utm.my with IP address **161.139.250.2**. This server provided the non-authoritative answer with the IP addresses of microsoft.com.

2.0 ipconfig

ipconfig can be used to show your current TCP/IP information, including your address, DNS server addresses, adapter type and so on.

- Information about host, use the following command: ipconfig /all



```
C:\WINDOWS\system32\cmd.exe
Description . . . . . : TAP-ProtonVPN Windows Adapter V9
Physical Address. . . . . : 00-FF-AA-18-73-0D
DHCP Enabled. . . . . : Yes
Autoconfiguration Enabled . . . . : Yes

Ethernet adapter Ethernet:


    Connection-specific DNS Suffix  . : utm.my
    Description . . . . . : Realtek PCIe GbE Family Controller
    Physical Address. . . . . : 00-24-E8-23-E3-3A
    DHCP Enabled. . . . . : Yes
    Autoconfiguration Enabled . . . . : Yes
    Link-local IPv6 Address . . . . . : fe80::b8c5:7857:8b37:ddfe%4(Preferred)
    IPv4 Address. . . . . : 10.60.82.216(Preferred)
    Subnet Mask . . . . . : 255.255.252.0
    Lease Obtained. . . . . : Tuesday, September 18, 2018 6:08:09 AM
    Lease Expires . . . . . : Thursday, September 20, 2018 6:08:10 AM
    Default Gateway . . . . . : 10.60.80.1
    DHCP Server . . . . . : 10.60.80.1
    DHCPv6 IAID . . . . . : 33563880
    DHCPv6 Client DUID. . . . . : 00-01-00-01-1F-D8-2F-7E-00-24-E8-23-E3-3A
    DNS Servers . . . . . : 161.139.250.2
                           161.139.168.168
    NetBIOS over Tcpip. . . . . : Enabled

Ethernet adapter Ethernet 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
    Description . . . . . : TAP-Windows Adapter V9
```

Figure C.3: ipconfig /all result

- ipconfig is also very useful for managing the DNS information stored in your host. Each entry shows the remaining Time to Live (TTL) in seconds.
Command: ipconfig /displaydns



```
C:\WINDOWS\system32\cmd.exe
Record Name . . . . . : wpad.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 5917
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.163.188

aimswb.utm.my
-----
Record Name . . . . . : aimswb.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 16483
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.18.215

my.utm.my
-----
Record Name . . . . . : my.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 16484
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.20.240

C:\Users\pc-vastro220>
```

Figure C.4: ipconfig /displaydns result

- Flushing the DNS cache clears all entries and reloads the entries from the hosts file.

Command: ipconfig /flushdns

```
C:\WINDOWS\system32\cmd.exe
C:\Users\pc-vastro220>ipconfig /flushdns

Windows IP Configuration

Successfully flushed the DNS Resolver Cache.


C:\Users\pc-vastro220>
```

Figure C.5: ipconfig /flushdns result

3.0 Tracing DNS with Wireshark


- Open packet trace file dns-trace-1. Answer the following questions.
- 1. Locate the DNS query and response messages. Are then sent over UDP or TCP? Add screenshots in your answer.

UDP(Query)




UDP(Response)

No.	Time	Source	Destination	Protocol	Length	Info
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A www.ietf.org
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0x006e A www.ietf.org A 132.151.6.75 A 65.246.255.51




2. What is the destination port for the DNS query message? What is the source port of DNS response message? Add screenshots in your answer.

Destination port (query): 53



[Stream Index: 1]
> User Datagram Protocol, Src Port: 3163, Dst Port: 53

Source port (response): 53



> User Datagram Protocol, Src Port: 53, Dst Port: 3163

3. To what IP address is the DNS query message sent? Add screenshots in your answer.

128.238.29.2

No.	Time	Source	Destination	Protocol	Length	Info
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A www.ietf.org
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0x006e A www.ietf.org A 132.151.6.75 A 65.246.255.51

4. Examine the DNS query message. What “Type” of DNS query is it? Does the query message contain any “answers”? Add screenshots in your answer.

Type A, 0 answer(No answer)

✓ **Domain Name System (query)**

Transaction ID: 0x006e

➤ **Flags: 0x0100 Standard query**

Questions: 1

Answer RRs: 0

Authority RRs: 0

Additional RRs: 0

▼ **Queries**

➤ **www.ietf.org: type A, class IN**

5. Examine the DNS response message. How many “answers” are provided? What do each of these answers contain? Add screenshots in your answer.

2 answers

Answer contain in the picture

```
Domain Name System (response)
  Transaction ID: 0x006e
  > Flags: 0x8180 Standard query response, No error
  Questions: 1
  Answer RRs: 2
  Authority RRs: 0
  Additional RRs: 0
  > Queries
  v Answers
    v www.ietf.org: type A, class IN, addr 132.151.6.75
      Name: www.ietf.org
      Type: A (1) (Host Address)
      Class: IN (0x0001)
      Time to live: 1678 (27 minutes, 58 seconds)
      Data length: 4
      Address: 132.151.6.75
    v www.ietf.org: type A, class IN, addr 65.246.255.51
      Name: www.ietf.org
      Type: A (1) (Host Address)
      Class: IN (0x0001)
      Time to live: 1678 (27 minutes, 58 seconds)
      Data length: 4
      Address: 65.246.255.51
  [Request In: 8]
  [Time: 0.000844000 seconds]
```

6. Consider the subsequent TCP SYN packet sent by your host. Does the destination IP address of the SYN packet correspond to any of the IP addresses provided in the DNS response message? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
10	3.078479	128.238.38.160	132.151.6.75	TCP	62	3369 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
11	3.096413	132.151.6.75	128.238.38.160	TCP	62	80 → 3369 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM

Correspond address: 132.151.6.75

7. This web page contains images. Before retrieving each image, does your host issue new DNS queries?

10	3.078479	128.238.38.160	132.151.6.75	TCP	62	3369 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
11	3.096413	132.151.6.75	128.238.38.160	TCP	62	80 → 3369 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM
12	3.096463	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=1 Ack=1 Win=64860 Len=0
13	3.096708	128.238.38.160	132.151.6.75	HTTP	429	GET / HTTP/1.1
14	3.111678	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK] Seq=1 Ack=376 Win=6432 Len=0
15	3.120640	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=1 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
16	3.128093	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=1381 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
17	3.128148	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=2761 Win=64860 Len=0
18	3.148016	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=2761 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
19	3.148069	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=4141 Win=64860 Len=0
20	3.153211	132.151.6.75	128.238.38.160	HTTP	1055	HTTP/1.1 200 OK (text/html)
21	3.153293	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=5143 Win=63859 Len=0
22	3.161867	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [FIN, ACK] Seq=376 Ack=5143 Win=63859 Len=0
23	3.174716	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK] Seq=5143 Ack=377 Win=6432 Len=0
24	3.178159	128.238.38.160	132.151.6.75	TCP	62	3370 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
25	3.179283	128.238.38.160	132.151.6.75	TCP	62	3371 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
26	3.191649	132.151.6.75	128.238.38.160	TCP	62	80 → 3370 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM
27	3.191726	128.238.38.160	132.151.6.75	TCP	54	3370 → 80 [ACK] Seq=1 Ack=1 Win=64860 Len=0
28	3.191998	128.238.38.160	132.151.6.75	HTTP	320	GET /images/ietflogo2e.gif HTTP/1.1

No, it is because DNS query will only appear once in the entire tracing. There is no new DNS queries issue by host between line number 10 and number 27 before retrieving image in line number 28 as shown

- Open packet trace file dns-trace-2 for nslookup.
- We see from Wireshark that nslookup actually sent three DNS queries and received three DNS responses. For the purpose of this lab, ignore the first two sets of queries/responses, as they are specific to nslookup and are not normally generated by standard Internet applications. You should instead focus on the last query and response messages.
- Answer the following questions.

8. What is the destination port for the DNS query message? What is the source port of DNS response message? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
15	4.951232	128.238.38.160	128.238.29.22	DNS	86	Standard query 0x0001 PTR 22.29.238.128.in-addr.arpa
16	4.951638	128.238.29.22	128.238.38.160	DNS	118	Standard query response 0x0001 PTR 22.29.238.128.in-addr.arpa PTR dns-prime.poly.edu
17	4.952571	128.238.38.160	128.238.29.22	DNS	80	Standard query 0x0002 A www.mit.edu.poly.edu
18	4.952953	128.238.29.22	128.238.38.160	DNS	139	Standard query response 0x0002 No such name A www.mit.edu.poly.edu SOA dns-prime.poly.edu
19	4.953172	128.238.38.160	128.238.29.22	DNS	71	Standard query 0x0003 A www.mit.edu
20	4.960929	128.238.29.22	128.238.38.160	DNS	196	Standard query response 0x0003 A www.mit.edu A 18.7.22.83 NS BITSV.mit.edu NS STRAW.mit.edu NS W20NS.mit.edu A 18.72.0.3 A 18.71.0.1...

Destination port for query message:53

```
> Frame 19: 71 bytes on wire (568 bits), 71 bytes captured (568 bits)
> Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-HSRP-routers_00 (00:00:0c:07:ac:00)
> Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.22
> User Datagram Protocol, Src Port: 3742, Dst Port: 53
> Domain Name System (query)
```

Source port for response message:53

- > Frame 20: 196 bytes on wire (1568 bits), 196 bytes captured (1568 bits)
- > Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:99 (00:09:6b:10:60:99)
- > Internet Protocol Version 4, Src: 128.238.29.22, Dst: 128.238.38.160
- > User Datagram Protocol, Src Port: 53, Dst Port: 3742
- > Domain Name System (response)

9. To what IP address is the DNS query message sent? Is this the IP address of your default local DNS server? Add screenshots in your answer.

128.238.29.22

DNS query send to this IP address

```
Wireless LAN adapter Wi-Fi:
Connection-specific DNS Suffix . : 
Description . . . . . : Intel(R) Wi-Fi 6 AX201 160MHz
Physical Address. . . . . : CC-15-31-86-8A-DA
DHCP Enabled. . . . . : Yes
Autoconfiguration Enabled . . . . : Yes
Link-local IPv6 Address . . . . . : fe80::2d6d:3e07:2186:f825%13(Preferred)
IPv4 Address. . . . . : 10.211.105.77(Preferred)
Subnet Mask . . . . . : 255.255.240.0
Lease Obtained. . . . . : Sunday, 27 October, 2024 6:53:33 PM
Lease Expires . . . . . : Sunday, 27 October, 2024 10:53:33 PM
Default Gateway . . . . . : 10.211.101.250
DHCP Server . . . . . : 161.139.100.238
DHCPv6 IAID . . . . . : 164369713
DHCPv6 Client DUID. . . . . : 00-01-00-01-2A-D6-FA-9E-CC-15-31-86-8A-DA
DNS Servers . . . . . : 161.139.250.2
                        161.139.168.168
NetBIOS over Tcpip. . . . . : Enabled
```

The destination IP address is different IP address with my default local DNS server.

10. Examine the DNS query message. What “Type” of DNS query is it? Does the query message contain any “answers”? Add screenshots in your answer.

19 4.953172 128.238.38.160 128.238.29.22 DNS 71 Standard query 0x0003 A www.mit.edu

20 4.969929 128.238.29.22 128.238.38.160 DNS 196 Standard query response 0x0003 A www.mit.edu A 18.7.22.83 NS BITSV.mit.edu NS STRAW8.mit.edu NS W20NS.mit.edu A 18.72.0.3 A 18.72.0.3

> Frame 19: 71 bytes on wire (568 bits), 71 bytes captured (568 bits) on interface 0

> Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-HSRP-routers_00 (00:00:0c:07:ac:00)

> Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.22

> User Datagram Protocol, Src Port: 3742, Dst Port: 53

> Domain Name System (query)

Transaction ID: 0x0003

Flags: 0x0100 Standard query

Questions: 1

Answer RRs: 0

Authority RRs: 0

Additional RRs: 0

Queries

> www.mit.edu: type A, class IN

[Response in 20]

Type A, 0 answer (No answer)

11. Examine the DNS response message. How many “answers” are provided? What do each of these answers contain? Add screenshots in your answer.

▼ Domain Name System (response)

Transaction ID: 0x0003

➤ Flags: 0x8580 Standard query response, No error

Questions: 1

Answer RRs: 1

Authority RRs: 3

Additional RRs: 3

▼ Queries

1 answer, Answer contained

▼ Answers

▼ www.mit.edu: type A, class IN, addr 18.7.22.83

Name: www.mit.edu

Type: A (1) (Host Address)

Class: IN (0x0001)

Time to live: 60 (1 minute)

Data length: 4

Address: 18.7.22.83