


Demo Board For RV1106G

RV1106G_UVC_DEMO_V1.1

Reference Design Main Functions Introduction

| | |
|-----------|---------------------------|
| Power | 3 DCDC + 4 LDO (default) |
| RAM | SPI FLASH |
| Interface | MIPI_CSI/USB/AUDIO |

Rockchip Confidential

| | | | | | |
|---|-------------------------|-------------------------------|---------|--------|---------|
|  | | Rockchip Electronics Co., Ltd | | | |
| Project: | RV1106G UVC DEMO | | | | |
| File: | 00.Cover Page | | | | |
| Date: | Saturday, July 15, 2023 | | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: | 1 of 15 |

| Catalogue | |
|-----------|--------------------------------|
| Page | Description |
| Page01 | 00.Cover Page |
| Page02 | 01.Index and Notes |
| Page03 | 02.Revision History |
| Page04 | 03.Block Diagram |
| Page05 | 04.Power Diagram and Sequence |
| Page06 | 06.IO Power Domain Map |
| Page07 | 10.RV1106G Power/Codec/ETH/USB |
| Page08 | 11.RV1106G OSC/RTC/PMU/VCCIO |
| Page09 | 12.RV1106G ADC/FLASH/SDMMC |
| Page10 | 13.RV1106G SDIO/LCD/VICAP/MIPI |
| Page11 | 20.Power-System |
| Page12 | 25.USB Port |
| Page13 | 47.VI-Camera-SC530AI |
| Page14 | 70.Audio Port/ALARM |
| Page15 | 99.Mark/Hole |
| Page16 | |
| Page17 | |
| Page18 | |

Index and Notes

Note

NOTE 1:

Component parameter description

1. DNP stands for component not mounted temporarily
2. If Value or option is DNP, which means the area is reserved without being mounted

NOTE 2:

Please use our recommended components to avoid too many changes.
For more informations about the second source,please refer to our AVL.

Generate Bill of Materials


Header:

`Item\tPart\tDescription\tPCB Footprint\tReference\tQuantity\tOption`


Combined property string:

`{Item}\t{Value}\t{Description}\t{PCB Footprint}\t{Reference}\t{Quantity}\t{Option}`

Graphic Description




Rockchip Confidential

| | | | |
|---|-------------------------|--------------|-----------|
|  Rockchip Electronics Co., Ltd | | | |
| Project: | RV1106G UVC DEMO | | |
| File: | 01.Index and Notes | | |
| Date: | Saturday, July 15, 2023 | | Rev: V1.1 |
| Designed by: | whb | Reviewed by: | Default |
| Sheet: | | 2 of 15 | |


Revision History

| Version | Date | Author | Change Note | Approved |
|---------|------------|--------|---|----------|
| V1.0 | 2022.05.09 | whb | First edition. | |
| V1.1 | 2023.07.15 | whb | 1.Modify the RC parameters of the nPOR. 2.Modify the default voltage of VDD_0V9 to 0.88V 3.Modify the voltage regulator circuit parameters for VDD_ARM. | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Rockchip Confidential


| | | | |
|---|-------------------------|-------------------------------|-----------|
|  | | Rockchip Electronics Co., Ltd | |
| Project: | RV1106G UVC DEMO | | |
| File: | 02.Revision History | | |
| Date: | Saturday, July 15, 2023 | | Rev: V1.1 |
| Designed by: | whb | Reviewed by: | Default |
| | | Sheet: | 3 of 15 |

Block Diagram



Power Diagram and Sequence

TYPE-C
5V/2A



RV1106G Power-on Sequence

| Power Name | PMIC Channel | Time Slot | Default voltage | Peak Current |
|------------|--|-----------|-----------------|--------------|
| VDD 0V9 | DC-DC BUCK | Slot: 1 | 0.93V | 1.6A |
| VDD ARM | DC-DC BUCK | Slot: 1 | 0.93V | 0.5A |
| VCC 1V8 | LDO | Slot: 2 | 1.8V | 0.1A |
| VCC DDR | DC-DC BUCK | Slot: 2 | 1.35V | 0.5A |
| VCC 3V3 | LDO | Slot: 3 | 3.3V | 0.2A |
| RESET | Finally , nPOR RESET 10ms after VCC 3V3 is ready | | | |

RESET

VDD_0V9

VDD_ARM

VCC_1V8

VCC_DDR

VCC_3V3

Rockchip Confidential




Rockchip Electronics Co., Ltd

| | | | | |
|--------------|-------------------------------|--------------|---------|----------------|
| Project: | RV1106G UVC DEMO | | | |
| File: | 04.Power Diagram and Sequence | | | |
| Date: | Saturday, July 15, 2023 | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: 5 of 15 |


IO Power Domain Map

| IO Domain | IO Group | Support of IO Voltage | | Default Actual assigned IO Domain Voltage | | | Remark |
|-----------|-----------------|-----------------------|------|---|--------------|----------|--------|
| | | 1.8V | 3.3V | Net Name of Power Supply | Power Source | Voltage | |
| PMU | Group GPIO0_A | | ✓ | VCC_3V3 | | 3.3V | |
| VCCIO1 | Group GPIO1_AB | | ✓ | VCC_3V3 | | 3.3V | |
| VCCIO2 | Group GPIO4_C | ✓ | | VCC_1V8 | | 1.8V | |
| VCCIO3 | Group GPIO4_AB | ✓ | ✓ | VCCIO_FLASH | | 1.8/3.3V | |
| VCCIO4 | Group GPIO3_A | ✓ | ✓ | VCCIO_SD | | 1.8/3.3V | |
| VCCIO5 | Group GPIO2_AB | ✓ | ✓ | | | | |
| VCCIO6 | Group GPIO1_CD | ✓ | ✓ | | | | |
| VCCIO7 | Group GPIO3_BCD | ✓ | | VCC_1V8 | | 1.8V | |






Rockchip Confidential

| | | | | | |
|---|-------------------------|-------------------------------|---------|--------|---------|
|  | | Rockchip Electronics Co., Ltd | | | |
| Project: | RV1106G UVC DEMO | | | | |
| File: | 06.IO Power Domain Map | | | | |
| Date: | Saturday, July 15, 2023 | | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: | 6 of 15 |

PART D



POWER



Rockchip Confidential




Rockchip Electronics Co., Ltd

| | | | | | |
|---------------------|---------------------------------------|---------------------|---------|---------------|---------|
| Project: | RV1106G UVC DEMO | | | | |
| File: | 10.RV1106G Power/Codec/ETH/USB | | | | |
| Date: | Saturday, July 15, 2023 | | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: | 7 of 15 |

A





PART B




SPI Flash

NOTE:
Refer to the latest AVL for parts selection.




RECOVERY Key




1


VCC5V0_SYS--->VDD_0V9 Setp 1




VCC5V0_SYS--->VDD_ARM Setp 1




VCC5V0_SYS--->VCC_1V8 Setp 2



VCC5V0_SYS--->VCC_DDR Setp 2



VCC5V0_SYS--->VCC_3V3 Setp 3



Rockchip Confidential

Rockchip Electronics Co., Ltd

Project: RV1106G UVC DEMO

File: 20.Power-System


Date: Saturday, July 15, 2023

Designed by: whb

Reviewed by: Default

Sheet: 11 of 15

USB Port




Rockchip Confidential




Rockchip Electronics Co., Ltd

| | | | | |
|--------------|-------------------------|--------------|---------|-----------------|
| Project: | RV1106G UVC DEMO | | | |
| File: | 25.USB Port | | | |
| Date: | Saturday, July 15, 2023 | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: 12 of 15 |


Sensor



VCC5V0_SYS--->VDD1V8_SENSOR




VCC5V0_SYS--->VDD1V5_SENSOR




Note:
Default power-on timing:
All three power on at the same time.
Or DOVDD (VCC_1V8) --> DVDD (VCC_1V5) --> AVDD (VCC_2V8)


VCC5V0_SYS--->AVDD2V8_SENSOR



Rockchip Confidential

| | | | |
|---|-------------------------|-------------------------------|-----------|
|  | | Rockchip Electronics Co., Ltd | |
| Project: | RV1106G UVC DEMO | | |
| File: | 47.VI-Camera | | |
| Date: | Thursday, July 27, 2023 | | Rev: V1.1 |
| Designed by: | whb | Reviewed by: | Default |
| Sheet: | 13 | | of 15 |

NOTE: If there is no EMI problem, the ferrite beads can be replaced by 0ohm resistors;



The image displays three circuit diagrams for the MIC2_4020 component, showing various electrical connections and component values.

Diagram 1 (Left): Shows the MIC2_4020 component connected to VCC1V8_MICBIAS (R7002, 100R 5%, R0402) and MICINO_P (R7005, 1.1K 5%, R0402). It includes a 1uF capacitor (C7007, X5R 6.3V, C0402) and a 10pF capacitor (C7009, C0G 50V, C0402, DNP). The output is connected to MICINO_N (R7010, 1.1K 5%, R0402) and MICIN1_P (R7011, 1.1K 5%, R0402). It also features two ESD protection diodes (ED7002, ED7003, ESD5451N, ESD0402) and a 3.3K resistor (R7018, 3.3K, R0402, DNP).

Diagram 2 (Middle): Shows the MIC2_4020 component connected to VCC1V8_MICBIAS (R7003, 100R 5%, R0402) and MICIN1_P (R7006, 1.1K 5%, R0402). It includes a 1uF capacitor (C7008, X5R 6.3V, C0402) and a 10pF capacitor (C7010, C0G 50V, C0402, DNP). The output is connected to MICIN1_N (R7011, 1.1K 5%, R0402) and MICIN1_P (R7012, 1.1K 5%, R0402). It also features two ESD protection diodes (ED7004, ED7005, ESD5451N, ESD0402) and a 3.3K resistor (R7018, 3.3K, R0402, DNP).

Diagram 3 (Right): Shows the MIC2_4020 component connected to MICIN1_P (R7014, 3.3K, R0402, DNP) and MICIN1_N (R7015, 2.2K 1%, R0402, DNP). It includes two 2.2nF capacitors (C7011, C7013, X5R 50V, C0402, DNP) and two 10nF capacitors (C7012, C7014, X5R 25V, C0402, DNP). The output is connected to MICIN1_P (R7016, 390R 1%, R0402, DNP) and MICIN1_N (R7017, 390R 1%, R0402, DNP). It also features two ESD protection diodes (ED7002, ED7003, ESD5451N, ESD0402) and a 3.3K resistor (R7018, 3.3K, R0402, DNP).



Rockchip Confidential




Rockchip Electronics Co., Ltd

| | | | | | |
|---------------------|-------------------------|---------------------|---------|---------------|----------|
| Project: | RV1106G UVC DEMO | | | | |
| File: | 70.Audio Port | | | | |
| Date: | Thursday, July 27, 2023 | | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: | 14 of 15 |

HOLE



Rockchip Confidential

| | | | | |
|---|-------------------------|-------------------------------|---------|-----------------|
|  | | Rockchip Electronics Co., Ltd | | |
| Project: | RV1106G UVC DEMO | | | |
| File: | 99.MARK/HOLE | | | |
| Date: | Saturday, July 15, 2023 | | Rev: | V1.1 |
| Designed by: | whb | Reviewed by: | Default | Sheet: 15 of 15 |