

Landmarks Detection by Applying Deep Networks

Van-Linh LE^{1,3}, Marie BEURTON-AIMAR¹,
Akka ZEMMARI¹, Nicolas PARISEY²

linhlv@dlu.edu.vn/van-linh.le@labri.fr, beurton@labri.fr
akka.zemmari@labri.fr, nicolas.parisey@inra.fr

¹LaBRI-CNRS 5800, Bordeaux University, France

²IGEPP, INRA 1349 Rennes, France

³ITDLU, Dalat University, Vietnam

MAPR Conference

Ho Chi Minh City, 5-6 April, 2018



Morphometry analysis

- ▶ Used to study the complex interaction between the evolution of insect and environmental factors.
- ▶ Characterize the common information of biological shape, such as, shape, sizes, or **landmarks**, . . .

Landmark

- ▶ A kind of **point of interest**
- ▶ A specific point defined by biologist. For example, intersection of viens on fly wing, the tip of beetle's mandible, . . .

Dataset



- ▶ Images have been taken from 293 **beetles**, separate into 5 parts (images),
- ▶ Format: 2D in RGB color,
- ▶ Focus on **pronotum** images.




(a) Left mandible



(b) Right mandible




(c) Body




(d) Head

With segmentable images:¹




¹ Van-Linh Le, Marie Beurton-Aimar, Adrien Krähenbühl, and Nicolas Parisey. "MAELab: a framework to automatize landmark estimation." WSCG 2017.

With segmentable images:¹




With un-segmentable images:




¹ Van-Linh Le, Marie Beurton-Aimar, Adrien Krähenbühl, and Nicolas Parisey. "MAELab: a framework to automatize landmark estimation." WSCG 2017.

With segmentable images:¹



With un-segmentable images:



How to predict the landmarks coordinates?

¹ Van-Linh Le, Marie Beurton-Aimar, Adrien Krähenbühl, and Nicolas Parisey. "MAELab: a framework to automatize landmark estimation." WSCG 2017.



Deep learning and Convolutional Neural Networks

- Deep learning

- Convolutional neural networks (CNNs)

Proposed method

- Network architectures

- Data augmentation

- Training

Result

Conclusion



Definition

- ▶ A class of machine learning¹,
- ▶ Use a cascade of multiple layers for feature extraction and transformation,
- ▶ Learn multiple levels of representation in supervised or unsupervised.

¹Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," Nature, vol. 521, no. 7553, pp. 436–444, 2015



Definition

- ▶ A class of machine learning¹,
- ▶ Use a cascade of multiple layers for feature extraction and transformation,
- ▶ Learn multiple levels of representation in supervised or unsupervised.

Applications

- ▶ Computer vision (image recognition and classification)²
- ▶ Speech recognition³
- ▶ Question answering⁴, language translation⁵

¹ Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," Nature, vol. 521, no. 7553, pp. 436–444, 2015

² A. Krizhevsky et al, "Imagenet classification with deep convolutional neural networks", 2012.


³ T. N. Sainath et al, "Deep convolutional neural networks for lvcsr", 2013.

⁴ A. Bordes et al, "Question answering with subgraph embeddings", 2014.

⁵ I. Sutskever et al, "Sequence to sequence learning with neural networks", 2014.



- ▶ Consists an input, an output and multiple hidden layers¹
- ▶ Arranges the data in 3 dimensions: *width, height and depth*
- ▶ Classical layers: convolutional layers (**CONV**), pooling layers (**POOLING**), dropout layers (**DROPOUT**), full-connected layers (**FC**), ...



¹ Y. LeCun et al, "Convolutional networks and applications in vision", 2010.




The first model includes:

- ▶ An gray-scale input,
- ▶ 3 CNN layers,
- ▶ 3 POOLING layers,
- ▶ 3 FC layers.

Problems:


- ▶ Output is not good enough,
- ▶ Overfitting.





The second model:


- ▶ Has the same architecture with the first one,
- ▶ Modify the output of FC layers,
- ▶ Result is not improved.





The **third** model includes:

- ▶ An gray-scale input,
- ▶ 3 CNN layers,
- ▶ 3 POOLING layers,
- ▶ 4 **DROPOUT** layers,
- ▶ 3 FC layers.






Dataset: 293 pronotum images in RGB format.


Augmentation methods:

- Increase the value of each channel,



Augmentation methods:

- Split the channels.



Proposed method

Data augmentation




Dataset: 293 pronotum images in RGB format.

Augmentation methods:


- ▶ Increase the value of each channel,
- ▶ Split the channels.

Total: $293 \times 7 = 2051$ images






- ▶ Model: the third model in 5000 epochs²
- ▶ Training dataset: 1820 images (260×7)
- ▶ Testing set: 33 images
- ▶ Images shows training and validation losses of the models.
Blue curves are training losses, green curves are validation losses.




(a) The first architecture




(b) The third architecture

² An epoch is a single pass through the full training set.

Images show the result on testing images.



(a)



(b)



- ▶ Run the trained model to predict the landmarks on testing images,
- ▶ Calculate the distance between predicted landmarks and corresponding manual landmarks,
- ▶ Compute the average distance of all images per landmark.

#Landmark	Distance (in pixels)
1	4.002
2	4.4831
3	4.2959
4	4.3865
5	4.2925
6	5.3631
7	4.636
8	4.9363


Result

Statistic on acceptable predicted landmarks



Chart shows the propotion of acceptable predicted landmarks

- ▶ Average accuracy: $\sim 75\%$
- ▶ Highest accuracy: 87.88%
- ▶ Lowest accuracy: 66.67%




Result

Distribution of distance on the first landmark



- ▶ Good prediction: 56.66%
- ▶ Acceptable prediction: 40.27%
- ▶ Bad prediction: 3.07%





Quality metrics: coefficient of determination (r^2), explained variance (EV), Pearson correlation.

Metric	r^2	EV	Pearson
Cintast et al. ³	0.884	0.951	0.976
Proposed architecture	0.9952	0.9951	0.9974

³Cintas, "Automatic ear detection and feature extraction using geometric morphometrics and convolutional neural networks," IET Biometrics, vol. 6, no. 3, pp. 211–223, 2016



Conclusion

- ▶ Proposed a CNN to predict the landmarks on pronotum images.
- ▶ Proposed procedure to augment the dataset.
- ▶ The location of the predicted landmarks are acceptable with high accuracy ($\sim 75\%$). It allows to replace manual landmarks.




Conclusion

- ▶ Proposed a CNN to predict the landmarks on pronotum images.
- ▶ Proposed procedure to augment the dataset.
- ▶ The location of the predicted landmarks are acceptable with high accuracy ($\sim 75\%$). It allows to replace manual landmarks.

Future works

Continue improving the landmarks coordinates by continuing on deep learning, *for example*, using transfer learning.



Thank you for attention!