Lecture 13: Initial guess for steady-state PDEs

Lecture 13: Initial guess for steady-state PDEs

COMP5930M Scientific Computation

Today

Time-dependent PDE models

Steady-state PDE models

Algorithms

Pseudo-timestepping Nested iteration Ad-hoc continuation

Summary

Time-dependent PDE models

- Always specified with appropriate initial conditions
- ▶ On each step $t^k \to t^{k+1}$, we can use the current solution \mathbf{U}^k as an initial guess to Newton
- For large time step sizes we may still face problems
- We can use forward Euler solution as an initial guess: $\mathbf{U}_0 = \mathbf{U}^k + \Delta t \mathbf{F}(\mathbf{U}^k)$
- ▶ In practice we may have to restrict Δt to ensure convergence

Steady PDE models

- No initial conditions, only boundary data
- Often difficult to guess an appropriate initial state
- We can employ some standard techniques to help

1. Pseudo-timestepping

Modify the nonlinear system $\mathbf{F}(\mathbf{U}) = \mathbf{0}$ to

$$\frac{\partial \mathbf{U}}{\partial \tau} + \mathbf{F}(\mathbf{U}) = \mathbf{0}$$

- ightharpoonup is a *pseudo*-time variable not physical time
- ► The steady-state solution satisfies the original nonlinear system
- Use standard time-stepping techniques to evolve to steady state from the initial state

Pseudo-timestepping

Pros/Cons

- Simple heuristic approach
 - use standard time-stepping algorithm
- Still requires some (pseudo)-initial conditions
 - should be less sensitive to a poor guess
- ▶ There will be some dependence on the step size $\Delta \tau$
 - as for real time stepping

Nested iteration


2. Nested iteration

- Convergence for PDE models is often faster (easier) for smaller problems
 - ▶ fewer grid points, ie. smaller *n*
- Solve a sequence of problems on successively finer grids
 - the coarse mesh solution is interpolated to the finer level as an initial guess

— Algorithms

Nested iteration


Example: Nested iteration method



— Algorithms

Nested iteration

Example: Multigrid method



Pros/Cons 2

- As we move to finer levels we should have an almost perfect initial state
 - Fast convergence
- Requires us to be able to solve from a poor guess at some coarse level
 - May not be possible
- ► In general will require experimentation

3. Continuation approaches



(less formal than Homotopy Continuation)

- Define a transformation, from a simple, easy-to-solve state to our desired nonlinear model
- Mathematically, we use a continuation parameter α to define the transformation
- Solve a sequence of nonlinear problems with the previous solution used as initial data for the next

A simple example

Find x such that

$$F(x) = -x^3 - 2x + 2$$
For $\alpha \in [0,1]$, define
$$G(\alpha,x) = -\alpha x^3 - 2x + 2$$

- For $\alpha = 0$, G(0, x) = -2x + 2we have a root at x = 1
- ▶ Define *k* steps from $\alpha = 0$ to $\alpha = 1$

A PDE example

Find u(x) on $x \in [0,1]$ that satisfies

$$u\frac{\partial u}{\partial x} - \epsilon \frac{\partial^2 u}{\partial x^2} = 0$$

with boundary conditions u(0) = 1 and u(1) = 0

For α ∈ [0, 1], define a modified PDE with the same domain and boundary conditions.

$$((1-\alpha)+\alpha u)\frac{\partial u}{\partial x}-\epsilon\frac{\partial^2 u}{\partial x^2}=0$$

 α = 0 is a linear PDE and hence the FDM leads to a linear system of equations

Pros/Cons

- ► We can start from an easily solvable state
 - generally linear
- ► Requires some <u>mathematical intuition</u> to define a workable sequence
 - focus on the nonlinear part of the problem
- ▶ We assume the path taken is well-defined
 - ▶ ie. that the sub-problems have a solution
- ▶ There may be some dependence on the step size $\Delta \alpha$
 - ▶ similar to pseudo-time stepping

Summary

- There are a variety of methods available if a good initial state is not known
- Knowledge of the context, or physics, of the model is a very useful starting point
- Formal, mathematical techniques are available as a last resort