

1.1 ./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp/CSharpToCppTransformer.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Linq;
4  using System.Text.RegularExpressions;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.RegularExpressions.Transformer.CSharpToCpp
9  {
10     public class CSharpToCppTransformer : TextTransformer
11     {
12         public static readonly IList

```

```

58 //
59 (new Regex(@"\r?\n[^\n]+bool operator !=\(((?<type>[^\n]+) (?<left>[a-zA-Z0-9]+),
    ↳ \k<type> (?<right>[a-zA-Z0-9]+)\) => !\((\k<left>|\k<right>) ==
    ↳ (\k<left>|\k<right>)\);"), "", 10),
60 // public override bool Equals(object obj) => obj is Range<T> range ? Equals(range)
    ↳ : false;
61 //
62 (new Regex(@"\r?\n[^\n]+override bool Equals\((System\.)?[Oo]bject
    ↳ (?<this>[a-zA-Z0-9]+)\) => \k<this> is [^\n]+ (?<other>[a-zA-Z0-9]+) \?
    ↳ Equals\(\k<other>\) : false;"), "", 10),
63 // out TProduct
64 // TProduct
65 (new Regex(@"(?<before><|, ))(in|out)
    ↳ (?<typeParameter>[a-zA-Z0-9]+)(?<after>>|,))"),
    ↳ "${before}${typeParameter}${after}", 10),
66 // public ...
67 // public: ...
68 (new Regex(@"(?<newLineAndIndent>\r?\n?[
    ↳ \t]*) (?<before>[^\{\\(\r\n)*) (?<access>private|protected|public) [ \t]+(?![^\{\\(\r\n
    ↳ \n]*((?<=\\s)|\\W) (interface|class|struct) (\\W) [^\{\\(\r\n)*[\\{\\(\r\n)]")",
    ↳ "${newLineAndIndent}${access}: ${before}", 0),
69 // public: static bool CollectExceptions { get; set; }
70 // public: inline static bool CollectExceptions;
71 (new Regex(@"(?<access>(private|protected|public): ) (?<before>(static )? [^\r\n]+
    ↳ ) (?<name>[a-zA-Z0-9]+) { [^;]* (?<=\\W) get; [^;]* (?<=\\W) set; [^;]* }"),
    ↳ "${access}inline ${before}${name};", 0),
72 // public abstract class
73 // class
74 (new Regex(@"((public|protected|private|internal|abstract|static)
    ↳ )*(?<category>interface|class|struct)", "${category}", 0),
75 //class GenericCollectionMethodsBase<TElement> {
76 // template <typename TElement> class GenericCollectionMethodsBase {
77 (new Regex(@"(?<before>\r?\n) (?<indent>[ \t]*) (?<type>class|struct)
    ↳ (?<typeName>[a-zA-Z0-9]+)<(?<typeParameters>[a-zA-Z0-9
    ↳ ,]+)> (?<typeDefinitionEnding>[^\{]+){", "${before}${indent}template <typename
    ↳ ...> ${type} ${typeName};" + Environment.NewLine + "${indent}template <typename
    ↳ ${typeParameters}> ${type}
    ↳ ${typeName}<${typeParameters}>${typeDefinitionEnding}{", 0),
78 // static void
    ↳ TestMultipleCreationsAndDeletions<TElement>(SizedBinaryTreeMethodsBase<TElement>
    ↳ tree, TElement* root)
79 // template<typename T> static void
    ↳ TestMultipleCreationsAndDeletions<TElement>(SizedBinaryTreeMethodsBase<TElement>
    ↳ tree, TElement* root)
80 (new Regex(@"static ([a-zA-Z0-9]+) ([a-zA-Z0-9]+)<([a-zA-Z0-9]+)>\\(((\\r\\n)+)\\)",
    ↳ "template <typename $3> static $1 $2($4)", 0),
81 // interface IFactory<out TProduct> {
82 // template <typename...> class IFactory; \ntemplate <typename TProduct> class
    ↳ IFactory<TProduct>
83 (new Regex(@"(?<before>\r?\n) (?<indent>[ \t]*) interface
    ↳ (?<interface>[a-zA-Z0-9]+)<(?<typeParameters>[a-zA-Z0-9
    ↳ ,]+)> (?<typeDefinitionEnding>[^\{]+){", "${before}${indent}template <typename
    ↳ ...> class ${interface};" + Environment.NewLine + "${indent}template <typename
    ↳ ${typeParameters}> class
    ↳ ${interface}<${typeParameters}>${typeDefinitionEnding}{", 0),
    ↳ "public:", 0),
84 // template <typename TObject, TProperty, TValue>
85 // template <typename TObject, typename TProperty, typename TValue>
86 (new Regex(@"(?<before>template <((, )?typename [a-zA-Z0-9]+)+,
    ↳ ) (?<typeParameter>[a-zA-Z0-9]+) (?<after>(,|>))", "${before}typename
    ↳ ${typeParameter}${after}", 10),
87 // Insert markers
88 // private: static void BuildExceptionString(this StringBuilder sb, Exception
    ↳ exception, int level)
89 // /*~extensionMethod~BuildExceptionString~*/private: static void
    ↳ BuildExceptionString(this StringBuilder sb, Exception exception, int level)
90 (new Regex(@"private: static [^\r\n]+ (?<name>[a-zA-Z0-9]+)\\(this [^\r\n]+\\)",
    ↳ "/*~extensionMethod~${name}~*/$0", 0),
91 // Move all markers to the beginning of the file.
92 (new Regex(@"\A(?<before>[^\r\n]+\r?\n(.|\n)+) (?<marker>\/\*~extensionMethod~(?<name>
    ↳ [a-zA-Z0-9]+)~\*/)", "${marker}${before}",
    ↳ 10),
93 // /*~extensionMethod~BuildExceptionString~*/...sb.BuildExceptionString(exception.In_
    ↳ nerException, level +
    ↳ 1);

```

```

94 // /*~extensionMethod~BuildExceptionString~*/...BuildExceptionString(sb,
    ↳ exception.InnerException, level + 1);
95 (new Regex(@"(?<before>/\/*~extensionMethod~(?<name>[a-zA-Z0-9]+)~\*/(.\|\\n)+\\W)(?<var_
    ↳ iable>[_a-zA-Z0-9]+)\\.\\k<name>\\(", "${before}${name}${{variable}}, ",
    ↳ 50),
96 // Remove markers
97 // /*~extensionMethod~BuildExceptionString~*/
98 //
99 (new Regex(@"/*~extensionMethod~[a-zA-Z0-9]+~\*/"), "", 0),
100 // (this
101 // (
102 (new Regex(@"\\(this ", "(", 0),
103 // private: static readonly Disposal _emptyDelegate = (manual, wasDisposed) => { };
104 // private: inline static std::function<Disposal> _emptyDelegate = [](auto manual,
    ↳ auto wasDisposed) { };
105 (new Regex(@"(?<access>(private|protected|public): )?static readonly
    ↳ (?<type>[a-zA-Z][a-zA-Z0-9]*) (?<name>[a-zA-Z_][a-zA-Z0-9_]*) =
    ↳ \\((?<firstArgument>[a-zA-Z_][a-zA-Z0-9_]*)
    ↳ (?<secondArgument>[a-zA-Z_][a-zA-Z0-9_]*)\\) => {\\s*};"), "${access}inline static
    ↳ std::function<${type}> ${name} = [](auto ${firstArgument}, auto
    ↳ ${secondArgument}) { };", 0),
106 // public: static readonly EnsureAlwaysExtensionRoot Always = new
    ↳ EnsureAlwaysExtensionRoot();
107 // public: inline static EnsureAlwaysExtensionRoot Always;
108 (new Regex(@"(?<access>(private|protected|public): )?static readonly
    ↳ (?<type>[a-zA-Z0-9]+(<[a-zA-Z0-9]+>?)) (?<name>[a-zA-Z0-9_]+) = new
    ↳ \\k<type>\\(\\);"), "${access}inline static ${type} ${name};", 0),
109 // public: static readonly Range<int> SByte = new
    ↳ Range<int>(std::numeric_limits<int>::min(), std::numeric_limits<int>::max());
110 // public: inline static Range<int> SByte =
    ↳ Range<int>(std::numeric_limits<int>::min(), std::numeric_limits<int>::max());
111 (new Regex(@"(?<access>(private|protected|public): )?static readonly
    ↳ (?<type>[a-zA-Z0-9]+(<[a-zA-Z0-9]+>?)) (?<name>[a-zA-Z0-9_]+) = new
    ↳ \\k<type>\\(\\((?<arguments>[\\n]+)\\);"), "${access}inline static ${type} ${name} =
    ↳ ${type}${{arguments}};", 0),
112 // public: static readonly string ExceptionContentsSeparator = "---";
113 // public: inline static std::string ExceptionContentsSeparator = "---";
114 (new Regex(@"(?<access>(private|protected|public): )?(const|static readonly) string
    ↳ (?<name>[a-zA-Z0-9_]+) = ""(?<string>(\\\\"|\\r\\n)+)"";"), "${access}inline
    ↳ static std::string ${name} = \\\"${string}\\\";", 0),
115 // private: const int MaxPath = 92;
116 // private: inline static const int MaxPath = 92;
117 (new Regex(@"(?<access>(private|protected|public): )?(const|static readonly)
    ↳ (?<type>[a-zA-Z0-9]+) (?<name>[_a-zA-Z0-9]+) = (?<value>[~;\\r\\n]+);"),
    ↳ "${access}inline static const ${type} ${name} = ${value};", 0),
118 // ArgumentNotNull(EnsureAlwaysExtensionRoot root, TArgument argument) where
    ↳ TArgument : class
119 // ArgumentNotNull(EnsureAlwaysExtensionRoot root, TArgument* argument)
120 (new Regex(@"(?<before> [a-zA-Z]+\\((([a-zA-Z *,]+, |))?(?<type>[a-zA-Z]+)(?<after>(\\
    ↳ [a-zA-Z *,]+)\\))\\[ \\r\\n]+where \\k<type> : class"), "${before}${type}*${after}",
    ↳ 0),
121 // protected: abstract TElement GetFirst();
122 // protected: virtual TElement GetFirst() = 0;
123 (new Regex(@"(?<access>(private|protected|public): )?abstract
    ↳ (?<method>[~;\\r\\n]+);"), "${access}virtual ${method} = 0;", 0),
124 // TElement GetFirst();
125 // virtual TElement GetFirst() = 0;
126 (new Regex(@"(?<before>[\\r\\n]+ [ ]+)(?<methodDeclaration>(?!return)[a-zA-Z0-9]+
    ↳ [a-zA-Z0-9]+\\(([^\\)\\r\\n]*\\))(?<after>;[ ]*[\\r\\n]+)"), "${before}virtual
    ↳ ${methodDeclaration} = 0${after}", 1),
127 // protected: readonly TreeElement[] _elements;
128 // protected: TreeElement _elements[N];
129 (new Regex(@"(?<access>(private|protected|public): )?readonly
    ↳ (?<type>[a-zA-Z<>0-9]+)(\\[\\]]+) (?<name>[_a-zA-Z0-9]+);"), "${access}${type}
    ↳ ${name}[N];", 0),
130 // protected: readonly TElement Zero;
131 // protected: TElement Zero;
132 (new Regex(@"(?<access>(private|protected|public): )?readonly
    ↳ (?<type>[a-zA-Z<>0-9]+) (?<name>[_a-zA-Z0-9]+);"), "${access}${type} ${name};",
    ↳ 0),
133 // internal
134 //
135 (new Regex(@"(\\W)internal\\s+"), "$1", 0),
136 // static void NotImplementedException(ThrowExtensionRoot root) => throw new
    ↳ NotImplementedException();

```

```

137 // static void NotImplementedException(ThrowExtensionRoot root) { return throw new
138     ↳ NotImplementedException(); }
139 (new Regex(@"(^s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
140     ↳ )?(override )?([a-zA-Z0-9]+
141     ↳ )([a-zA-Z0-9]+)\(((^\\(\\r\\n)*)\\)\s+=>\s+throw([~;\r\n]+);"),
142     ↳ "$1$2$3$4$5$6$7$8($9) { throw$10; }", 0),
143 // SizeBalancedTree(int capacity) => a = b;
144 // SizeBalancedTree(int capacity) { a = b; }
145 (new Regex(@"(^s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
146     ↳ )?(override )?(void )?([a-zA-Z0-9]+)\(((^\\(\\r\\n)*)\\)\s+=>\s+([~;\r\n]+);"),
147     ↳ "$1$2$3$4$5$6$7$8($9) { $10; }", 0),
148 // int SizeBalancedTree(int capacity) => a;
149 // int SizeBalancedTree(int capacity) { return a; }
150 (new Regex(@"(^s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
151     ↳ )?(override )?([a-zA-Z0-9]+
152     ↳ )([a-zA-Z0-9]+)\(((^\\(\\r\\n)*)\\)\s+=>\s+([~;\r\n]+);"), "$1$2$3$4$5$6$7$8($9) {
153     ↳ return $10; }", 0),
154 // OnDispose = (manual, wasDisposed) =>
155 // OnDispose = [&](auto manual, auto wasDisposed)
156 (new Regex(@"(?<variable>[a-zA-Z_][a-zA-Z0-9_]*) (?<operator>\s*[\+=\s*])\(((?<firstArg_
157     ↳ ument>[a-zA-Z_][a-zA-Z0-9_]*) ,
158     ↳ (?<secondArgument>[a-zA-Z_][a-zA-Z0-9_]*)\\)\s*=>"),
159     ↳ "$${variable}$${operator}&](auto ${firstArgument}, auto ${secondArgument})", 0),
160 // () => Integer<TElement>.Zero;
161 // () { return Integer<TElement>.Zero; },
162 (new Regex(@"\\(\\)\s+=>\s+(?<expression>[~() ;\r\n]+(\\(((?<parenthesis>\\()|(?<-parent_
163     ↳ hesis>\\))| [~() ;\r\n]*?)*)? [~() ;\r\n]* )(?<after>,|\\);)"), "() { return
164     ↳ ${expression}; }${after}", 0),
165 // ~DisposableBase() => Destruct();
166 // ~DisposableBase() { Destruct(); }
167 (new Regex(@"~(?<class>[a-zA-Z_][a-zA-Z0-9_]*)\\(\\)\s+=>\s+([~;\r\n]+?);"),
168     ↳ "~${class}() { $1; }", 0),
169 // => Integer<TElement>.Zero;
170 // { return Integer<TElement>.Zero; }
171 (new Regex(@"\\)\s+=>\s+([~;\r\n]+?);"), ") { return $1; }", 0),
172 // () { return avlTree.Count; }
173 // [&]() -> auto { return avlTree.Count; }
174 (new Regex(@"(?<before>, |\\()\\(\\) { return (?<expression>[~;\r\n]+); }"),
175     ↳ "$${before}&]() -> auto { return ${expression}; }", 0),
176 // Count => GetSizeOrZero(Root);
177 // Count() { return GetSizeOrZero(Root); }
178 (new Regex(@"(\\W)([A-Z][a-zA-Z]+)\\)\s+=>\s+([~;\r\n]+);"), "$1$2() { return $3; }", 0),
179 // Insert scope borders.
180 // interface IDisposable { ... }
181 // interface IDisposable { /*~start~interface~IDisposable~*/ ...
182     ↳ /*~end~interface~IDisposable~*/ }
183 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\\t ]*)interface[\\t
184     ↳ ]*(?<type>[a-zA-Z_][a-zA-Z0-9_]*(\\<[^>\\n]*\\)?) [~{]*{ }(?<middle>(\\.|\\n)*) (?<beforeE_
185     ↳ nd>(?<=\\r?\\n)\\k<indent>)(?<end>})"),
186     ↳ "$${classDeclarationBegin}/*~start~interface~${type}~*/${middle}${beforeEnd}/*~en_
187     ↳ d~interface~${type}~*/${end}",
188     ↳ 0),
189 // Inside scopes replace:
190 // /*~start~interface~IDisposable~*/ ... bool IsDisposed { get; } ...
191     ↳ /*~end~interface~IDisposable~*/
192 // /*~start~interface~IDisposable~*/ ... virtual bool IsDisposed() = 0;
193     ↳ /*~end~interface~IDisposable~*/
194 (new Regex(@"(?<before>(?<typeScopeStart>/\\*~start~interface~(?<type>[~\\n\\*]+)~\\*/)
195     ↳ (\\.|\\n)+?)(?<propertyDeclaration>(?(access>(private|protected|public):
196     ↳ )?(?<propertyType>[a-zA-Z_][a-zA-Z0-9_]*<\\>*) (?<property>[a-zA-Z_][a-zA-Z0-9_]* )
197     ↳ (?<blockOpen>[\\n\\s]*[\\n\\s]*)\\([\\[\\^\\n]+\\][\\n\\s]*?get; (?<blockClose>[\\n\\s]*)) (?<
198     ↳ after>(\\.|\\n)+?)(?<typeScopeEnd>/\\*~end~interface~\\k<type>~\\*/))"),
199     ↳ "$${before}virtual ${propertyType} ${property}() = 0;${after}", 20),
200 // Remove scope borders.
201 // /*~start~interface~IDisposable~*/
202 //
203 (new Regex(@"/*~[~\\*\\n]+(~[~\\*\\n]+)*~\\*/"), "", 0),
204 // public: T Object { get; }
205 // public: const T Object;
206 (new Regex(@"(?<before>[~\\r\\r?\\n[ \\t]*) (?<access>(private|protected|public):
207     ↳ )?(?<type>[a-zA-Z_][a-zA-Z0-9_]*<\\>*)
208     ↳ (?<property>[a-zA-Z_][a-zA-Z0-9_]*) (?<blockOpen>[\\n\\s]*[\\n\\s]*)\\([\\[\\^\\n]+\\][\\n\\s_
209     ↳ ]*)?get; (?<blockClose>[\\n\\s]*) (?<after>[\\n\\s]*)"), "$${before}${access}const
210     ↳ ${type} ${property};${after}", 2),
211 // public: bool IsDisposed { get => _disposed > 0; }
212 // public: bool IsDisposed() { return _disposed > 0; }

```

```

(new Regex(@"(?<before>[^\r]\r?\n[ \t]*) (?<access>(private|protected|public):
) ?(?<virtual>virtual )?bool
→ (?<property>[a-zA-Z_][a-zA-Z0-9_]*) (?<blockOpen>[\n\s]*{[\n\s]*} ([^\n]+\n) [\n\s]
→ ]*) ?get\s*=>\s*(?<expression>[^\n]+); (?<blockClose>[\n\s]*{[\n\s]*})",
→ "${before}${access}${virtual}bool ${property}() ${blockOpen}return
→ ${expression}; ${blockClose}", 2),
// protected: virtual std::string ObjectName { get => GetType().Name; }
// protected: virtual std::string ObjectName() { return GetType().Name; }
(new Regex(@"(?<before>[^\r]\r?\n[ \t]*) (?<access>(private|protected|public):
) ?(?<virtual>virtual ) ?(?<type>[a-zA-Z_][a-zA-Z0-9_<:;>]*)
→ (?<property>[a-zA-Z_][a-zA-Z0-9_]*) (?<blockOpen>[\n\s]*{[\n\s]*} ([^\n]+\n) [\n\s]
→ ]*) ?get\s*=>\s*(?<expression>[^\n]+); (?<blockClose>[\n\s]*{[\n\s]*})",
→ "${before}${access}${virtual}${type} ${property}() ${blockOpen}return
→ ${expression}; ${blockClose}", 2),
// ArgumentInRange(string message) { string messageBuilder() { return message; }
// ArgumentInRange(string message) { auto messageBuilder = [&]() -> string { return
→ message; };
(new Regex(@"(?<before>\W[_a-zA-Z0-9]+\n((^\n)\n)*[\s\n]*{[\s\n]*{[^\n]+\n)*?(\r?\n)
→ ?[ \t]*) (?<returnType>[_a-zA-Z0-9*:] +[_a-zA-Z0-9*:] *)
→ (?<methodName>[_a-zA-Z0-9+] +)\n((?<arguments>[^\n]\n)*)\n\s*{(?<body>("[^"\n]+"" |
→ [^}] | \n)+?) }"), "${before}auto ${methodName} = [&]() -> ${returnType}
→ {${body}};", 10),
// Func<TElement> treeCount
// std::function<TElement()> treeCount
(new Regex(@"Func<([a-zA-Z0-9+] +)> ([a-zA-Z0-9+] +)", "std::function<$1()> $2", 0),
// Action<TElement> free
// std::function<void(TElement)> free
(new Regex(@"Action<(?<typeParameters>[a-zA-Z0-9+] +,
→ ([a-zA-Z0-9+] +)*)> (?<after>| (?<variable>[a-zA-Z0-9+] +))"),
→ "std::function<void(${typeParameters})> ${after}", 0),
// Predicate<TArgument> predicate
// std::function<bool(TArgument)> predicate
(new Regex(@"Predicate<([a-zA-Z0-9+] +)> ([a-zA-Z0-9+] +)", "std::function<bool($1)>
→ $2", 0),
// var
// auto
(new Regex(@"(\W)var(\W)", "$1auto$2", 0),
// unchecked
//
(new Regex(@"[\r\n]{2}\s*?unchecked\s*?$"), "", 0),
// throw new
// throw
(new Regex(@"(\W)throw new(\W)", "$1throw$2", 0),
// void RaiseExceptionIgnoredEvent(Exception exception)
// void RaiseExceptionIgnoredEvent(const std::exception& exception)
(new Regex(@"(\\(| ) (System\\.Exception|Exception) (|\\))", "$1const
→ std::exception&$3", 0),
// EventHandler<Exception>
// EventHandler<std::exception>
(new Regex(@"(\W) (System\\.Exception|Exception) (\W)", "$1std::exception$3", 0),
// override void PrintNode(TElement node, StringBuilder sb, int level)
// void PrintNode(TElement node, StringBuilder sb, int level) override
(new Regex(@"override ([a-zA-Z0-9 \*+]+) \n((^\n)\r?\n)+?)"), "$1$2 override", 0),
// return {range.Minimum, range.Maximum}
// return {range.Minimum, range.Maximum}
(new Regex(@"(?<before>return\s*) \n((?<values>[^\n]\n)+) \n (?!\n) (?<after>\W)",
→ "${before}${values}${after}", 0),
// string
// std::string
(new Regex(@"(?<before>\W) (?<!:):) string (?<after>\W)",
→ "${before}std::string${after}", 0),
// System.ValueTuple
// std::tuple
(new Regex(@"(?<before>\W) (System\\.)?ValueTuple(?!\s*=\n) (?<after>\W)",
→ "${before}std::tuple${after}", 0),
// sbyte
// std::int8_t
(new Regex(@"(?<before>\W) ((System\\.)?SB|sb) yte(?!\s*=\n) (?<after>\W)",
→ "${before}std::int8_t${after}", 0),
// short
// std::int16_t
(new Regex(@"(?<before>\W) ((System\\.)?Int16|short) (?!\s*=\n) (?<after>\W)",
→ "${before}std::int16_t${after}", 0),
// int
// std::int32_t

```

```

231 (new Regex(@"(?<before>\W)((System\.)?I|i)nt(32)?(?!\s*=\|()\ (?<after>\W)"),
232     ↳ "${before}std::int32_t${after}", 0),
233 // long
234 (new Regex(@"(?<before>\W)((System\.)?Int64|long)(?! \s*=\|()\ (?<after>\W)"),
235     ↳ "${before}std::int64_t${after}", 0),
236 // byte
237 (new Regex(@"(?<before>\W)((System\.)?Byte|byte)(?! \s*=\|()\ (?<after>\W)"),
238     ↳ "${before}std::uint8_t${after}", 0),
239 // ushort
240 (new Regex(@"(?<before>\W)((System\.)?UInt16|ushort)(?! \s*=\|()\ (?<after>\W)"),
241     ↳ "${before}std::uint16_t${after}", 0),
242 // uint
243 (new Regex(@"(?<before>\W)((System\.)?UI|ui)nt(32)?(?!\s*=\|()\ (?<after>\W)"),
244     ↳ "${before}std::uint32_t${after}", 0),
245 // ulong
246 (new Regex(@"(?<before>\W)((System\.)?UInt64|ulong)(?! \s*=\|()\ (?<after>\W)"),
247     ↳ "${before}std::uint64_t${after}", 0),
248 // char*[] args
249 (new Regex(@"([_a-zA-Z0-9:\*]?)\[\] ([a-zA-Z0-9]+)", "$1 $2[]", 0),
250 // float.MinValue
251 (new Regex(@"(?<before>\W)(?<type>std::[a-z0-9_]+|float|double)\.MinValue(?<after>\W|
252     ↳ )"), "${before}std::numeric_limits<${type}>::lowest()${after}",
253     ↳ 0),
254 // double.MaxValue
255 (new Regex(@"(?<before>\W)(?<type>std::[a-z0-9_]+|float|double)\.MaxValue(?<after>\W|
256     ↳ )"), "${before}std::numeric_limits<${type}>::max()${after}",
257     ↳ 0),
258 // using Platform.Numbers;
259 //
260 (new Regex(@"([\r\n]{2}|^)\s*?using [\.a-zA-Z0-9]+;\s*?$)", "", 0),
261 // class SizedBinaryTreeMethodsBase : GenericCollectionMethodsBase
262 // class SizedBinaryTreeMethodsBase : public GenericCollectionMethodsBase
263 (new Regex(@"(struct|class) ([a-zA-Z0-9]+)(<[a-zA-Z0-9_ ,]+>)? : ([a-zA-Z0-9]+)",
264     ↳ "$1 $2$3 : public $4", 0),
265 // System.IDisposable
266 // System::IDisposable
267 (new Regex(@"(?<before>System(?:[a-zA-Z_]\w*)*)\. (?<after>[a-zA-Z_]\w*)"),
268     ↳ "${before}::${after}", 20),
269 // class IProperty : ISetter<TValue, TObjct>, IProvider<TValue, TObjct>
270 // class IProperty : public ISetter<TValue, TObjct>, public IProvider<TValue,
271     ↳ TObjct>
272 (new Regex(@"(?<before>(interface|struct|class) [a-zA-Z_]\w* : ((public
273     ↳ [a-zA-Z_]\w* : (<[a-zA-Z0-9_ ,]+>)?,
274     ↳ )+)? (?<inheritedType>(?!public) [a-zA-Z_]\w* (<[a-zA-Z0-9_ ,]+>)? (?<after>(,
275     ↳ [a-zA-Z_]\w* (?!>)| [ \r\n]+))", "${before}public ${inheritedType}${after}",
276     ↳ 10),
277 // interface IDisposable {
278 // class IDisposable { public:
279 (new Regex(@"(?<before>\r?\n)(?<indent>[ \t]*)interface
280     ↳ (?<interface>[a-zA-Z_]\w*) (?<typeDefinitionEnding>[^\{]+){",
281     ↳ "${before}${indent}class ${interface}${typeDefinitionEnding}{ " +
282     ↳ Environment.NewLine + "      public:", 0),
283 // struct TreeElement { }
284 // struct TreeElement { };
285 (new Regex(@"(struct|class) ([a-zA-Z0-9]+)(\s+){([\sa-zA-Z0-9;:_]+?)}([^\;])", "$1
286     ↳ $2$3{$4};$5", 0),
287 // class Program { }
288 // class Program { };
289 (new Regex(@"(?<type>struct|class)
290     ↳ (?<name>[a-zA-Z0-9_][^\r\n]*) (?<beforeBody>[\r\n]+(?<indentLevel>[ \t
291     ↳ ]*)?)\{(?<body>[ \S\s]+?[ \r\n]+\k<indentLevel>)\}(?<afterBody>[^\;]|$)", "${type}
292     ↳ ${name}${beforeBody}${body}};${afterBody}", 0),
293 // Insert scope borders.
294 // ref TElement root
295 // ~!root!~ref TElement root
296 (new Regex(@"(?<definition>(?!= \|()\ (ref [a-zA-Z0-9_]+|[a-zA-Z0-9_]+(?<ref>))
297     ↳ (?<variable>[a-zA-Z0-9_]+)(?=\|, \| =))", "~!${variable}!~${definition}", 0),
298 // Inside the scope of ~!root!~ replace:

```

```

282 // root
283 // *root
284 (new Regex(@"(?<definition>~!(?<pointer>[a-zA-Z0-9]+)!~ref [a-zA-Z0-9]+
→ \k<pointer>(=?\)|,| =)) (?<before>((?<!~!\k<pointer>!~)(.\|\\n))*?) (?<prefix>(\W
→ |\\())\k<pointer>(=?<suffix>( |\\)|;|,))"),
→ "$${definition}${before}${prefix}*${pointer}${suffix}", 70),
285 // Remove scope borders.
286 // ~!root!~
287 //
288 (new Regex(@"~!(?<pointer>[a-zA-Z0-9]+)!~"), "", 5),
289 // ref auto root = ref
290 // ref auto root =
291 (new Regex(@"ref ([a-zA-Z0-9]+) ([a-zA-Z0-9]+) = ref(\W)"), "$1* $2 =$3", 0),
292 // *root = ref left;
293 // root = left;
294 (new Regex(@"\*([a-zA-Z0-9]+) = ref ([a-zA-Z0-9]+)(\W)"), "$1 = $2$3", 0),
295 // (ref left)
296 // (left)
297 (new Regex(@"\ (ref ([a-zA-Z0-9]+)(\\|\\(|,))"), "($1$2", 0),
298 // ref TElement
299 // TElement*
300 (new Regex(@"( |\\())ref ([a-zA-Z0-9]+) "), "$1$2* ", 0),
301 // ref sizeBalancedTree.Root
302 // &sizeBalancedTree->Root
303 (new Regex(@"ref ([a-zA-Z0-9]+)\.([a-zA-Z0-9\*]+)"), "&$1->$2", 0),
304 // ref GetElement(node).Right
305 // &GetElement(node)->Right
306 (new Regex(@"ref ([a-zA-Z0-9]+)\((([a-zA-Z0-9\*]+)\\)\.([a-zA-Z0-9]+)"),
→ "&$1($2)->$3", 0),
307 // GetElement(node).Right
308 // GetElement(node)->Right
309 (new Regex(@"([a-zA-Z0-9]+)\((([a-zA-Z0-9\*]+)\\)\.([a-zA-Z0-9]+)"), "$1($2)->$3", 0),
310 // [Fact]npublic: static void SizeBalancedTreeMultipleAttachAndDetachTest()
311 // public: TEST_METHOD(SizeBalancedTreeMultipleAttachAndDetachTest)
312 (new Regex(@"\[Fact\\] \[s\\n\]+(public:)?(static)?void ([a-zA-Z0-9]+)\\(\\)"), "public:
→ TEST_METHOD($3)", 0),
313 // class TreesTests
314 // TEST_CLASS(TreesTests)
315 (new Regex(@"class ([a-zA-Z0-9]+Tests)"), "TEST_CLASS($1)", 0),
316 // Assert.Equal
317 // Assert::AreEqual
318 (new Regex(@"(?<type>Assert)\\. (?<method>(Not)?Equal)"), "${type}::Are${method}", 0),
319 // Assert.Throws
320 // Assert::ExpectException
321 (new Regex(@"(Assert)\\.Throws"), "$1::ExpectException", 0),
322 // Assert.True
323 // Assert::IsTrue
324 (new Regex(@"(Assert)\\. (True|False)"), "$1::Is$2", 0),
325 // $"Argument {argumentName} is null."
326 // std::string("Argument
→ ").append(Platform::Converters::To<std::string>(argumentName)).append(" is
→ null.")
327 (new Regex(@"\$""(?<left>(\\""| [^""\r\n])*){(?<expression>[_a-zA-Z0-9]+)}(?<right>(\\_
→ ""| [^""\r\n])*"""),
→ "std::string(\$\"${left}\").append(Platform::Converters::To<std::string>(${expres_
→ sion})).append(\$\"${right}\")",
→ 10),
328 // $"
329 // "
330 (new Regex(@"\$""""), "\"", 0),
331 // std::string(std::string("[").append(Platform::Converters::To<std::string>(Minimum)
→ )).append(",
→ ").append(Platform::Converters::To<std::string>(Maximum)).append("]")
332 // std::string("[").append(Platform::Converters::To<std::string>(Minimum)).append(",
→ ").append(Platform::Converters::To<std::string>(Maximum)).append("]")
333 (new Regex(@"std::string\\((?<begin>std::string\\(""(\\""| [^""])""\\)\\.append\\((Platf_
→ orm::Converters::To<std::string>\\([~]\\n\\+)| [~]\\n\\+))\\+\\)\\)\\.append"),
→ "${begin}.append", 10),
334 // Console.WriteLine("...")
335 // printf("...\\n")
336 (new Regex(@"Console\\.WriteLine\\(""([~""\r\n]+)""\\)"), "printf(\$\"$1\\n\\n\"", 0),
337 // TElement Root;
338 // TElement Root = 0;
339 (new Regex(@"(?<before>\r?\n[t ]+)(?<access>(private|protected|public)(:
→ )?)?(?<type>[a-zA-Z0-9:~]+(?<!return)) (?<name>[_a-zA-Z0-9~]+);"),
→ "${before}${access}${type} ${name} = 0;", 0),

```



```

340 // TreeElement _elements[N];
341 // TreeElement _elements[N] = { {0} };
342 (new Regex(@"(\\r?\\n[\\t ]+)(private|protected|public)?(: )?([a-zA-Z0-9]+)
    ↳ ([_a-zA-Z0-9]+)\\[([_a-zA-Z0-9]+)\\];\"", "$1$2$3$4 $5[$6] = { {0} };\"", 0),
343 // auto path = new TElement[MaxPath];
344 // TElement path[MaxPath] = { {0} };
345 (new Regex(@"(\\r?\\n[\\t ]+)[a-zA-Z0-9]+ ([a-zA-Z0-9]+) = new
    ↳ ([a-zA-Z0-9]+)\\[([_a-zA-Z0-9]+)\\];\"", "$1$3 $2[$4] = { {0} };\"", 0),
346 // bool Equals(Range<T> other) { ... }
347 // bool operator ==(const Key &other) const { ... }
348 (new Regex(@"(?<before>\\r?\\n[\\t ]+bool )Equals\\((?<type>[\\n]+)
    ↳ (?<variable>[a-zA-Z0-9]+)\\)(?<after>(\\s|\\n)*\\)", "${before}operator ==(const
    ↳ ${type} &${variable}) const${after}", 0),
349 // Insert scope borders.
350 // class Range { ... public: override std::string ToString() { return ...; }
351 // class Range { /*~Range<T>~*/ ... public: override std::string ToString() { return
    ↳ ...; }
352 (new Regex(@"(?<classDeclarationBegin>\\r?\\n(?<indent>[\\t ]*)template <typename
    ↳ (?<typeParameter>[~<>\\n]+> (struct|class)
    ↳ (?<type>[a-zA-Z0-9]+<\\k<typeParameter>>)(\\s*:\\s*[~{\\n]+)?[\\t ]*(\\r?\\n)?[\\t
    ↳ ]*(?<middle>((?!class|struct)\\.\\n)+?)?(?<toStringDeclaration>(?!<access>(private|
    ↳ |protected|public): )override std::string ToString\\(\\))\"",
    ↳ "${classDeclarationBegin}/*~${type}~*/${middle}${toStringDeclaration}", 0),
353 // Inside the scope of ~!Range!~ replace:
354 // public: override std::string ToString() { return ...; }
355 // public: operator std::string() const { return ...; }\\n\\npublic: friend
    ↳ std::ostream & operator <<(std::ostream &out, const A &obj) { return out <<
    ↳ (std::string)obj; }
356 (new Regex(@"(?<scope>/\\s*(?<type>[a-zA-Z0-9<>:]+)~\\s*/)(?<separator>\\.\\n)(?<before>
    ↳ ((?!/\\s*~\\k<type>~\\s*/)(\\.\\n)*)?(?<toStringDeclaration>\\r?\\n(?<indent>[
    ↳ \\t]*)?(?<access>(private|protected|public): )override std::string ToString\\(\\)
    ↳ (?<toStringMethodBody>[~}\\n]+))\"", "${scope}${separator}${before}" +
    ↳ Environment.NewLine + "${indent}${access}operator std::string() const
    ↳ ${toStringMethodBody}" + Environment.NewLine + Environment.NewLine +
    ↳ "${indent}${access}friend std::ostream & operator <<(std::ostream &out, const
    ↳ ${type} &obj) { return out << (std::string)obj; }\"", 0),
357 // Remove scope borders.
358 // /*~Range~*/
359 //
360 (new Regex(@"/\\s*~[_a-zA-Z0-9<>:]+~\\s*/", "", 0),
361 // private: inline static ConcurrentBag<std::exception> _exceptionsBag;
362 // private: inline static std::mutex _exceptionsBag_mutex; \\n\\n private: inline
    ↳ static std::vector<std::exception> _exceptionsBag;
363 (new Regex(@"(?<begin>\\r?\\n(?<indent>[\\t ]+))?(?<access>(private|protected|public):
    ↳ )?inline static ConcurrentBag<(?!<argumentType>[~;\\r\\n]+)>
    ↳ (?<name>[_a-zA-Z0-9]+);\"", "${begin}private: inline static std::mutex
    ↳ ${name}_mutex;" + Environment.NewLine + Environment.NewLine +
    ↳ "${indent}${access}inline static std::vector<${argumentType}> ${name};\"", 0),
364 // public: static IReadonlyCollection<std::exception> GetCollectedExceptions() {
    ↳ return _exceptionsBag; }
365 // public: static std::vector<std::exception> GetCollectedExceptions() { return
    ↳ std::vector<std::exception>(_exceptionsBag); }
366 (new Regex(@"(?<access>(private|protected|public): )?static
    ↳ IReadonlyCollection<(?!<argumentType>[~;\\r\\n]+)> (?<methodName>[_a-zA-Z0-9]+)\\(\\)
    ↳ { return (?<fieldName>[_a-zA-Z0-9]+); }\"", "${access}static
    ↳ std::vector<${argumentType}> ${methodName}() { return
    ↳ std::vector<${argumentType}>({${fieldName}}); }\"", 0),
367 // public: static event EventHandler<std::exception> ExceptionIgnored =
    ↳ OnExceptionIgnored; ... };
368 // ... public: static inline Platform::Delegates::MulticastDelegate<void(void*,
    ↳ const std::exception&> ExceptionIgnored = OnExceptionIgnored; };
369 (new Regex(@"(?<begin>\\r?\\n(\\r?\\n)?(?<halfIndent>[
    ↳ \\t]+)\\k<halfIndent>)(?<access>(private|protected|public): )?static event
    ↳ EventHandler<(?!<argumentType>[~;\\r\\n]+)> (?<name>[_a-zA-Z0-9]+) = (?<defaultDele
    ↳ gate>[_a-zA-Z0-9]+);(?<middle>(\\.\\n)+?)?(?<end>\\r?\\n\\k<halfIndent>});\"",
    ↳ "${middle}" + Environment.NewLine + Environment.NewLine +
    ↳ "${halfIndent}${halfIndent}${access}static inline
    ↳ Platform::Delegates::MulticastDelegate<void(void*, const ${argumentType}&>
    ↳ ${name} = ${defaultDelegate};${end}", 0),
370 // public: event Disposal OnDispose;
371 // public: Platform::Delegates::MulticastDelegate<Disposal> OnDispose;
372 (new Regex(@"(?<begin>(?!<access>(private|protected|public): )?(static )?)event
    ↳ (?<type>[a-zA-Z][:_a-zA-Z0-9]+) (?<name>[_a-zA-Z][_a-zA-Z0-9]+);\"",
    ↳ "${begin}Platform::Delegates::MulticastDelegate<${type}> ${name};\"", 0),
373 // Insert scope borders.

```



```

374 // class IgnoredExceptions { ... private: inline static std::vector<std::exception>
    ↳ _exceptionsBag;
375 // class IgnoredExceptions {/*~_exceptionsBag~*/ ... private: inline static
    ↳ std::vector<std::exception> _exceptionsBag;
376 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n}]+\r\n[\t
    ↳ ]*)(?<middle>((?!class)\.|\n)+?)(?<vectorFieldDeclaration>(?(<access>(private|pro
    ↳ tected|public): )inline static std::vector<(?(argumentType>[~;\r\n]+)>
    ↳ (?(fieldName>[_a-zA-Z0-9]+);)");
    ↳ "$${classDeclarationBegin}/*~${fieldName}~*/${middle}${vectorFieldDeclaration}",
    ↳ 0),
377 // Inside the scope of ~!_exceptionsBag!~ replace:
378 // _exceptionsBag.Add(exception);
379 // _exceptionsBag.push_back(exception);
380 (new Regex(@"(?<scope>/\s*(?<fieldName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ e>((?!/\s*\k<fieldName>~\s*/)(.\|\n))*?)\k<fieldName>\.Add"),
    ↳ "$${scope}${separator}${before}${fieldName}.push_back", 10),
381 // Remove scope borders.
382 // /*~_exceptionsBag~*/
383 //
384 (new Regex(@"/\s*~[_a-zA-Z0-9]+~\s*/"), "", 0),
385 // Insert scope borders.
386 // class IgnoredExceptions { ... private: static std::mutex _exceptionsBag_mutex;
387 // class IgnoredExceptions {/*~_exceptionsBag~*/ ... private: static std::mutex
    ↳ _exceptionsBag_mutex;
388 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n}]+\r\n[\t
    ↳ ]*)(?<middle>((?!class)\.|\n)+?)(?<mutexDeclaration>private: inline static
    ↳ std::mutex (?(fieldName>[_a-zA-Z0-9]+) _mutex;);"),
    ↳ "$${classDeclarationBegin}/*~${fieldName}~*/${middle}${mutexDeclaration}", 0),
389 // Inside the scope of ~!_exceptionsBag!~ replace:
390 // return std::vector<std::exception>(_exceptionsBag);
391 // std::lock_guard<std::mutex> guard(_exceptionsBag_mutex); return
    ↳ std::vector<std::exception>(_exceptionsBag);
392 (new Regex(@"(?<scope>/\s*(?<fieldName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ e>((?!/\s*\k<fieldName>~\s*/)(.\|\n))*?){(?<after>((?!lock_guard)[^{};\r\n])*\k<f
    ↳ ieldName>[~;}\r\n]*;);"), "$${scope}${separator}${before}{
    ↳ std::lock_guard<std::mutex> guard(${fieldName}_mutex);${after}", 10),
393 // Inside the scope of ~!_exceptionsBag!~ replace:
394 // _exceptionsBag.Add(exception);
395 // std::lock_guard<std::mutex> guard(_exceptionsBag_mutex); \r\n
    ↳ _exceptionsBag.Add(exception);
396 (new Regex(@"(?<scope>/\s*(?<fieldName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ e>((?!/\s*\k<fieldName>~\s*/)(.\|\n))*?){(?<after>((?!lock_guard)([~{};]\|\n))*?\r
    ↳ ?\n(?<indent>[\t ]*)\k<fieldName>[~;}\r\n]*;);"),
    ↳ "$${scope}${separator}${before}{\" + Environment.NewLine +
    ↳ \"$${indent}std::lock_guard<std::mutex> guard(${fieldName}_mutex);${after}", 10),
397 // Remove scope borders.
398 // /*~_exceptionsBag~*/
399 //
400 (new Regex(@"/\s*~[_a-zA-Z0-9]+~\s*/"), "", 0),
401 // Insert scope borders.
402 // class IgnoredExceptions { ... public: static inline
    ↳ Platform::Delegates::MulticastDelegate<void(void*, const std::exception&)>
    ↳ ExceptionIgnored = OnExceptionIgnored;
403 // class IgnoredExceptions {/*~ExceptionIgnored~*/ ... public: static inline
    ↳ Platform::Delegates::MulticastDelegate<void(void*, const std::exception&)>
    ↳ ExceptionIgnored = OnExceptionIgnored;
404 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n}]+\r\n[\t
    ↳ ]*)(?<middle>((?!class)\.|\n)+?)(?<eventDeclaration>(?(access>(private|protected
    ↳ |public): )static inline
    ↳ Platform::Delegates::MulticastDelegate<(?(argumentType>[~;\r\n]+)>
    ↳ (?(name>[_a-zA-Z0-9]+) = (?(defaultDelegate>[_a-zA-Z0-9]+);)");
    ↳ "$${classDeclarationBegin}/*~${name}~*/${middle}${eventDeclaration}", 0),
405 // Inside the scope of ~!ExceptionIgnored!~ replace:
406 // ExceptionIgnored.Invoke(NULL, exception);
407 // ExceptionIgnored(NULL, exception);
408 (new Regex(@"(?<scope>/\s*(?<eventName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ >((?!/\s*\k<eventName>~\s*/)(.\|\n))*?)\k<eventName>\.Invoke"),
    ↳ "$${scope}${separator}${before}${eventName}", 10),
409 // Remove scope borders.
410 // /*~ExceptionIgnored~*/
411 //
412 (new Regex(@"/\s*~[_a-zA-Z0-9]+~\s*/"), "", 0),
413 // Insert scope borders.
414 // auto added = new StringBuilder();
415 // /*~sb~*/std::string added;

```

```

416 (new Regex(@"(auto|(System\.Text\.)?StringBuilder) (?<variable>[a-zA-Z0-9]+) = new
    ↳ (System\.Text\.)?StringBuilder\(\);"), "/~*${variable}~/std::string
    ↳ ${variable};", 0),
417 // static void Indent(StringBuilder sb, int level)
418 // static void Indent(/*~sb~/StringBuilder sb, int level)
419 (new Regex(@"(?<start>, |\() (System\.Text\.)?StringBuilder
    ↳ (?<variable>[a-zA-Z0-9]+) (?<end>, |\))"), "${start}/*~*${variable}~/std::string&
    ↳ ${variable}${end}", 0),
420 // Inside the scope of ~!added!~ replace:
421 // sb.ToString()
422 // sb
423 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~/) (?<separator>.\|\\n) (?<before>
    ↳ ((?!/\~*~\k<variable>~\~/) (.\|\\n))*?) \k<variable>\.ToString\(\)"),
    ↳ "${scope}${separator}${before}${variable}", 10),
424 // sb.AppendLine(argument)
425 // sb.append(Platform::Converters::To<std::string>(argument)).append(1, '\\n')
426 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~/) (?<separator>.\|\\n) (?<before>
    ↳ ((?!/\~*~\k<variable>~\~/) (.\|\\n))*?) \k<variable>\.AppendLine\((?<argument>[^\|\\n], \\
    ↳ r\\n)+\\)"),
    ↳ "${scope}${separator}${before}${variable}.append(Platform::Converters::To<std::s
    ↳ tring>(${argument})).append(1, '\\n')",
    ↳ 10),
427 // sb.Append('\\t', level);
428 // sb.append(level, '\\t');
429 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~/) (?<separator>.\|\\n) (?<before>
    ↳ ((?!/\~*~\k<variable>~\~/) (.\|\\n))*?) \k<variable>\.Append\('( ?<character>[^\r\\n]
    ↳ +)', (?<count>[^\|\\n], \\r\\n)+\\)"),
    ↳ "${scope}${separator}${before}${variable}.append(${count}, '${character}')" , 10),
430 // sb.Append(argument)
431 // sb.append(Platform::Converters::To<std::string>(argument))
432 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~/) (?<separator>.\|\\n) (?<before>
    ↳ ((?!/\~*~\k<variable>~\~/) (.\|\\n))*?) \k<variable>\.Append\((?<argument>[^\|\\n], \\r\\n
    ↳ +)\\)"),
    ↳ "${scope}${separator}${before}${variable}.append(Platform::Converters::To<std::s
    ↳ tring>(${argument}))",
    ↳ 10),
433 // Remove scope borders.
434 // /*~sb~/
435 //
436 (new Regex(@"/*~*[a-zA-Z0-9]+~*/"), "", 0),
437 // Insert scope borders.
438 // auto added = new HashSet<TElement>();
439 // ~!added!~std::unordered_set<TElement> added;
440 (new Regex(@"auto (?<variable>[a-zA-Z0-9]+) = new
    ↳ HashSet<(?<element>[a-zA-Z0-9]+)>\(\);"),
    ↳ "~!${variable}!~std::unordered_set<${element}> ${variable};", 0),
441 // Inside the scope of ~!added!~ replace:
442 // added.Add(node)
443 // added.insert(node)
444 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~) (?<separator>.\|\\n) (?<before>((?<
    ↳ !~!\k<variable>!~) (.\|\\n))*?) \k<variable>\.Add\((?<argument>[a-zA-Z0-9]+)\\)"),
    ↳ "${scope}${separator}${before}${variable}.insert(${argument})", 10),
445 // Inside the scope of ~!added!~ replace:
446 // added.Remove(node)
447 // added.erase(node)
448 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~) (?<separator>.\|\\n) (?<before>((?<
    ↳ !~!\k<variable>!~) (.\|\\n))*?) \k<variable>\.Remove\((?<argument>[a-zA-Z0-9]+)\\)"),
    ↳ "${scope}${separator}${before}${variable}.erase(${argument})", 10),
449 // if (added.insert(node)) {
450 // if (!added.contains(node)) { added.insert(node);
451 (new Regex(@"if \\\((?<variable>[a-zA-Z0-9]+)\\.insert\\((?<argument>[a-zA-Z0-9]+)\\)\\) (?
    ↳ <separator>[\\t ]*[\\r\\n]+) (?<indent>[\\t ]*){"), "if
    ↳ (!${variable}.contains(${argument})) ${separator}${indent}{ " +
    ↳ Environment.NewLine + "${indent}    ${variable}.insert(${argument});", 0),
452 // Remove scope borders.
453 // ~!added!~
454 //
455 (new Regex(@"~![a-zA-Z0-9]+!~"), "", 5),
456 // Insert scope borders.
457 // auto random = new System::Random(0);
458 // std::srand(0);
459 (new Regex(@"[a-zA-Z0-9\\.]+ ([a-zA-Z0-9]+) = new
    ↳ (System::)?Random\\((([a-zA-Z0-9]+)\\)");), "~!$1!~std::srand($3);", 0),
460 // Inside the scope of ~!random!~ replace:
461 // random.Next(1, N)
462 // (std::rand() % N) + 1

```

```

463 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~)(?<separator>.\|\\n)(?<before>((?<
    ↳ !~!\k<variable>!~)(.\|\\n))*?)\k<variable>\.Next\\((?<from>[a-zA-Z0-9]+),
    ↳ (?<to>[a-zA-Z0-9]+)\\")", "${scope}${separator}${before}(std::rand() % ${to}) +
    ↳ ${from}", 10),
464 // Remove scope borders.
465 // ~!random!~
466 //
467 (new Regex(@"~![a-zA-Z0-9]+!~"), "", 5),
468 // Insert method body scope starts.
469 // void PrintNodes(TElement node, StringBuilder sb, int level) {
470 // void PrintNodes(TElement node, StringBuilder sb, int level) { /*method-start*/
471 (new Regex(@"(?<start>\r?\n[\\t ]+)(?<prefix>((private|protected|public): )?(virtual
    ↳ )?[a-zA-Z0-9:_]+
    ↳ )?(?<method>[a-zA-Z][a-zA-Z0-9]*\\(((?<arguments>[^\n])*)\\)(?<override>(
    ↳ override)?)(?<separator>[\\t\\r\\n]*)\\((?<end>[~])")", "${start}${prefix}${method}
    ↳ (${arguments})${override}${separator}{ /*method-start*/${end}",
    ↳ 0),
472 // Insert method body scope ends.
473 // { /*method-start*/...}
474 // { /*method-start*/... /*method-end*/}
475 (new Regex(@"{ /\*method-start\*/ (?<body>((?<bracket>\\{) | (?<-bracket>\\}) | [^\{\\}]*)+ )
    ↳ \\})", "{ /*method-start*/${body} /*method-end*/",
    ↳ 0),
476 // Inside method bodies replace:
477 // GetFirst(
478 // this->GetFirst(
479 (new
    ↳ Regex(@"(?<scope>\/\*method-start\*/)(?<before>((?!\/\*method-end\*/)(.\|\\n))*?) (?
    ↳ <separator>[\\W](?!(:|\\.|->|throw\\s+)))(?<method>(?!sizeof)[a-zA-Z0-9]+)\\((?!\\
    ↳ \\{)(?<after>(.\|\\n))*?) (?<scopeEnd>\/\*method-end\*/)",
    ↳ "${scope}${before}${separator}this->${method}(${after}${scopeEnd}", 100),
480 // Remove scope borders.
481 // /*method-start*/
482 //
483 (new Regex(@"\/\*method-(start|end)\\*/"), "", 0),
484 // Insert scope borders.
485 // const std::exception& ex
486 // const std::exception& ex/*~ex~*/
487 (new Regex(@"(?<before>\\(| )(?<variableDefinition>(const )?(std::)?exception&?
    ↳ (?<variable>[_a-zA-Z0-9]+)) (?<after>\\W)"),
    ↳ "${before}${variableDefinition}/*~${variable}~*/${after}", 0),
488 // Inside the scope of ~!ex!~ replace:
489 // ex.Message
490 // ex.what()
491 (new Regex(@"(?<scope>\/\*~(?<variable>[_a-zA-Z0-9]+)~\*/)(?<separator>.\|\\n)(?<before>
    ↳ >((?!\/\*~\k<variable>~\*/)(.\|\\n))*?) (Platform::Converters::To<std::string>\\(\k<
    ↳ variable>\\.Message\\) | \k<variable>\\.Message)"),
    ↳ "${scope}${separator}${before}${variable}.what()", 10),
492 // Remove scope borders.
493 // /*~ex~*/
494 //
495 (new Regex(@"\/\*~[_a-zA-Z0-9]+~\*/"), "", 0),
496 // throw ObjectDisposedException(objectName, message);
497 // throw std::runtime_error(std::string("Attempt to access disposed object
    ↳ ").append(objectName).append(": ").append(message).append("."));
498 (new Regex(@"throw ObjectDisposedException\\((?<objectName>[a-zA-Z_][a-zA-Z0-9_]*),
    ↳ (?<message>[a-zA-Z0-9_]*[Mm]essage[a-zA-Z0-9_]*\\(\\(\\)?| [a-zA-Z_][a-zA-Z0-9_]*)\\)
    ↳ ;");, "throw std::runtime_error(std::string("Attempt to access disposed object
    ↳ [\\").append(${objectName}).append("\\"): \").append(${message}).append("\\.\\"));";,
    ↳ 0),
499 // throw ArgumentNullException(argumentName, message);
500 // throw std::invalid_argument(std::string("Argument
    ↳ ").append(argumentName).append(" is null: ").append(message).append("."));
501 (new Regex(@"throw
    ↳ ArgumentNullException\\((?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]*),
    ↳ (?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*\\(\\(\\)?\\);");, "throw
    ↳ std::invalid_argument(std::string("Argument \").append(${argument}).append("\\
    ↳ is null: \").append(${message}).append("\\.\\"));";, 0),
502 // throw ArgumentException(message, argumentName);
503 // throw std::invalid_argument(std::string("Invalid ").append(argumentName).append("
    ↳ argument: ").append(message).append("."));
504 (new Regex(@"throw
    ↳ ArgumentException\\((?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*\\(\\(\\)?\\),
    ↳ (?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]*\\);");, "throw
    ↳ std::invalid_argument(std::string("Invalid \").append(${argument}).append("\\
    ↳ argument: \").append(${message}).append("\\.\\"));";, 0),

```

```

505 // throw ArgumentOutOfRangeException(argumentName, argumentValue, messageBuilder());
506 // throw std::invalid_argument(std::string("Value
    ↳ [").append(Platform::Converters::To<std::string>(argumentValue)).append("] of
    ↳ argument [").append(argumentName).append("] is out of range:
    ↳ ").append(messageBuilder()).append("."););
507 (new Regex(@"throw ArgumentOutOfRangeException\(((?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]
    ↳ A-Z)*([Nn]ame[a-zA-Z]*)?)",
    ↳ (?<argumentValue>[a-zA-Z]*[Aa]rgument[a-zA-Z]*([Vv]alue[a-zA-Z]*)?)",
    ↳ (?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*(\(\(\)?\)\);)", "throw
    ↳ std::invalid_argument(std::string("Value
    ↳ [").append(Platform::Converters::To<std::string>(${argumentValue})).append("\]
    ↳ of argument [").append(${argument}).append("\] is out of range:
    ↳ \").append(${message}).append("\.\");", 0),
508 // throw NotSupportedException();
509 // throw std::logic_error("Not supported exception.");
510 (new Regex(@"throw NotSupportedException\(\);)", "throw std::logic_error(\"Not
    ↳ supported exception.\");", 0),
511 // throw NotImplementedException();
512 // throw std::logic_error("Not implemented exception.");
513 (new Regex(@"throw NotImplementedException\(\);)", "throw std::logic_error(\"Not
    ↳ implemented exception.\");", 0),
514 // Insert scope borders.
515 // const std::string& message
516 // const std::string& message/*~message~/
517 (new Regex(@"(?<before>\(|\s)(?<variableDefinition>(const\s)?((std::)?string&?|char\*)
    ↳ (?<variable>[_a-zA-Z0-9]+)))(?<after>\W)",
    ↳ "${before}${variableDefinition}/*~${variable}~/${after}", 0),
518 // Inside the scope of /*~message~/ replace:
519 // Platform::Converters::To<std::string>(message)
520 // message
521 (new Regex(@"(?<scope>\/\s*(?<variable>[_a-zA-Z0-9]+)~\s*)(?<separator>.\|\n)(?<before>
    ↳ >((?!\/\s*\k<variable>~\s*)(.\|\n))*?)Platform::Converters::To<std::string>\(\k<v
    ↳ ariable>\)", "${scope}${separator}${before}${variable}",
    ↳ 10),
522 // Remove scope borders.
523 // /*~ex~/
524 //
525 (new Regex(@"\/\s*[_a-zA-Z0-9]+~\s\/", "", 0),
526 // Insert scope borders.
527 // std::tuple<T, T> tuple
528 // std::tuple<T, T> tuple/*~tuple~/
529 (new Regex(@"(?<before>\(|\s)(?<variableDefinition>(const\s)?(std::)?tuple<[^\n]+&?
    ↳ (?<variable>[_a-zA-Z0-9]+)))(?<after>\W)",
    ↳ "${before}${variableDefinition}/*~${variable}~/${after}", 0),
530 // Inside the scope of ~!ex!~ replace:
531 // tuple.Item1
532 // std::get<1-1>(tuple)
533 (new Regex(@"(?<scope>\/\s*(?<variable>[_a-zA-Z0-9]+)~\s*)(?<separator>.\|\n)(?<before>
    ↳ >((?!\/\s*\k<variable>~\s*)(.\|\n))*?)\k<variable>\.Item(?<itemNumber>\d+)(?<afte
    ↳ r>\W)",
    ↳ "${scope}${separator}${before}std::get<${itemNumber}-1>(${variable})${after}",
    ↳ 10),
534 // Remove scope borders.
535 // /*~ex~/
536 //
537 (new Regex(@"\/\s*[_a-zA-Z0-9]+~\s\/", "", 0),
538 // Insert scope borders.
539 // class Range<T> {
540 // class Range<T> {/~type~Range<T>~/
541 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)(template\s*<[^\<>\n]*>
    ↳ )?(struct|class)
    ↳ (?<fullType>(?(type)Name[a-zA-Z0-9]+)(<[^\n]*>)?)(\s*:\s*[^\n]+)?[\t
    ↳ ]*(\r?\n)?[\t ]*{)"),
    ↳ "${classDeclarationBegin}/*~type~${typeName}~${fullType}~/", 0),
542 // Inside the scope of /*~type~Range<T>~/ insert inner scope and replace:
543 // public: static implicit operator std::tuple<T, T>(Range<T> range)
544 // public: operator std::tuple<T, T>() const {/~variable~Range<T>~/
545 (new Regex(@"(?<scope>\/\s*~type~(?<typeName>[^\n]*)+~(?<fullType>[^\n]*+~\s\/)(?<
    ↳ separator>.\|\n)(?<before>((?!\/\s*~type~\k<typeName>~\k<fullType>~\s\/)(.\|\n))*?)
    ↳ (?<access>(private|protected|public): )static implicit operator
    ↳ (?<targetType>[^\n]*+)\(((?<argumentDeclaration>\k<fullType>
    ↳ (?<variable>[a-zA-Z0-9]+)))(?<after>\s*\n?\s*{)"),
    ↳ "${scope}${separator}${before}${access}operator ${targetType}()
    ↳ const${after}/*~variable~${variable}~/", 10),
    ↳ // Inside the scope of /*~type~Range<T>~/ replace:

```

```

547 // public: static implicit operator Range<T>(std::tuple<T, T> tuple) { return new
    ↳ Range<T>(std::get<1-1>(tuple), std::get<2-1>(tuple)); }
548 // public: Range(std::tuple<T, T> tuple) : Range(std::get<1-1>(tuple),
    ↳ std::get<2-1>(tuple)) { }
549 (new Regex(@"(?<scope>\/\~type~(?<typeName>[~\n\*]+)~(?<fullType>[~\n\*]+)~\*/)(?<
    ↳ separator>.\n)(?<before>((?!\/\~type~\k<typeName>~\k<fullType>~\*/)(.\n))*?) (
    ↳ ?<access>(private|protected|public): )static implicit operator
    ↳ (\k<fullType>|\k<typeName>)\((?<arguments>[~\n\*]+)\)(\s|\n)*{(\s|\n)*return
    ↳ (new )?(\k<fullType>|\k<typeName>)\((?<passedArguments>[~\n\*]+)\);(\s|\n)*"}),
    ↳ "${scope}${separator}${before}${access}${typeName}(${arguments}) :
    ↳ ${typeName}(${passedArguments}) { }", 10),
550 // Inside the scope of /*~variable~range~/ replace:
551 // range.Minimum
552 // this->Minimum
553 (new Regex(@"(?<scope>{\/\~variable~(?<variable>[~\n\*]+)~\*/)(?<separator>.\n)(?<be
    ↳ fore>(?(beforeExpression>(?(bracket>{)|(?(<-bracket>})|[\~{}]\n)*?)\k<variable>\.
    ↳ (?(field>[_a-zA-Z0-9]+)(?<after>(,|;|}|
    ↳ |\\))?(?<afterExpression>(?(bracket>{)|(?(<-bracket>})|[\~{}]\n)*?)")),
    ↳ "${scope}${separator}${before}this->${field}${after}", 10),
554 // Remove scope borders.
555 // /*~ex~/
556 //
557 (new Regex(@"\/\~[~\n\*]+[~\n\*]+~\*/"), "", 0),
558 // Insert scope borders.
559 // namespace Platform::Ranges { ... }
560 // namespace Platform::Ranges {/*~start~namespace~Platform::Ranges~/ ...
    ↳ /*~end~namespace~Platform::Ranges~/}
561 (new Regex(@"(?<namespaceDeclarationBegin>\r?\n(?<indent>[\t ]*)namespace
    ↳ (?<namespaceName>(?(namePart>[a-zA-Z][a-zA-Z0-9]+)(?(nextNamePart>:[a-zA-Z][a-z
    ↳ A-Z0-9]+))(\s|\n)*)(?(middle>(\n\*)?(?<end>(?(<=\r?\n)\k<indent>}{?!;))")",
    ↳ "${namespaceDeclarationBegin}/*~start~namespace~${namespaceName}~/${middle}/*~e
    ↳ nd~namespace~${namespaceName}~/${end}",
    ↳ 0),
562 // Insert scope borders.
563 // class Range<T> { ... };
564 // class Range<T> {/*~start~type~Range<T>~T~/ ... /*~end~type~Range<T>~T~/};
565 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)template <typename
    ↳ <?<typeParameter>[~\n\*]+> (struct|class)
    ↳ (?(type>[a-zA-Z0-9]+<\k<typeParameter>>)(\s*:\s*[~\n\*]+)?[\t ]*(\r?\n)?[\t
    ↳ ]*(?(middle>(\n\*)?(?<end>(?(<=\r?\n)\k<indent>){?!;}))")",
    ↳ "${classDeclarationBegin}/*~start~type~${type}~${typeParameter}~/${middle}${end}
    ↳ Indent}/*~end~type~${type}~${typeParameter}~/${end}",
    ↳ 0),
566 // Inside scopes replace:
567 // /*~start~namespace~Platform::Ranges~/ ... /*~start~type~Range<T>~T~/ ...
    ↳ public: override std::int32_t GetHashCode() { return {Minimum,
    ↳ Maximum}.GetHashCode(); } ... /*~end~type~Range<T>~T~/ ...
    ↳ /*~end~namespace~Platform::Ranges~/
568 // /*~start~namespace~Platform::Ranges~/ ... /*~start~type~Range<T>~T~/ ...
    ↳ /*~end~type~Range<T>~T~/ ... /*~end~namespace~Platform::Ranges~/ namespace std
    ↳ { template <typename T> struct hash<Platform::Ranges::Range<T>> { std::size_t
    ↳ operator()(const Platform::Ranges::Range<T> &obj) const { return {Minimum,
    ↳ Maximum}.GetHashCode(); } }; }
569 (new Regex(@"(?<namespaceScopeStart>\/\~start~namespace~(?<namespace>[~\n\*]+)~\*/)
    ↳ (?<betweenStartScopes>(\n\+)(?<typeScopeStart>\/\~start~type~(?<type>[~\n\*]+)
    ↳ )~(?<typeParameter>[~\n\*]+)~\*/)(?<before>(\n\+)?)(?<hashMethodDeclaration>\r
    ↳ ?\n[ \t]*(?<access>(private|protected|public): )override std::int32_t
    ↳ GetHashCode\(\)(\s|\n)*{\s*(?(methodBody>[~\n\*]+[~\n\*])\s*\s*)(?<after>(\n
    ↳ )+)?)(?<typeScopeEnd>\/\~end~type~\k<type>~\k<typeParameter>~\*/)(?<betweenEndSco
    ↳ pes>(\n\+)(?<namespaceScopeEnd>\/\~end~namespace~\k<namespace>~\*/)}\r?\n"),
    ↳ "${namespaceScopeStart}${betweenStartScopes}${typeScopeStart}${before}${after}${
    ↳ typeScopeEnd}${betweenEndScopes}${namespaceScopeEnd}} + Environment.NewLine +
    ↳ Environment.NewLine + "namespace std" + Environment.NewLine + "{" +
    ↳ Environment.NewLine + "    template <typename ${typeParameter}>" +
    ↳ Environment.NewLine + "        struct hash<${namespace}::${type}>" +
    ↳ Environment.NewLine + "            {" + Environment.NewLine + "                std::size_t
    ↳ operator()(const ${namespace}::${type} &obj) const" + Environment.NewLine + "
    ↳ {" + Environment.NewLine + "
    ↳ /*~start~method~/${methodBody}/*~end~method~/ + Environment.NewLine + "
    ↳ }" + Environment.NewLine + "    };" + Environment.NewLine + "}" +
    ↳ Environment.NewLine, 10),
570 // Inside scope of /*~start~method~/ replace:
571 // /*~start~method~/ ... Minimum ... /*~end~method~/
572 // /*~start~method~/ ... obj.Minimum ... /*~end~method~/

```

```

573 (new Regex(@"(?<methodScopeStart>/\~*start~method~\~/) (?<before>.+({|,
    ↳ )) (?<name>[a-zA-Z] [a-zA-Z0-9]+) (?<after>[\n\.\ (a-zA-Z0-9] ((?!/\~*end~method~\~/)
    ↳ ) [^\n]+) (?<methodScopeEnd>/\~*end~method~\~/)"),
    ↳ "$${methodScopeStart}${before}obj.${${name}}${after}${methodScopeEnd}", 10),
574 // Remove scope borders.
575 // /\~*start~type~Range<T>~*/
576 //
577 (new Regex(@"/*~[^\~*\n]+(~[^\~*\n]+)*~*/"), "", 0),
578 // class Disposable<T> : public Disposable
579 // class Disposable<T> : public Disposable<>
580 (new Regex(@"(?<before>(struct|class) (?<type>[a-zA-Z] [a-zA-Z0-9]*) (<[^\>\n]+> :
    ↳ (?<access>(private|protected|public) ) ?\k<type> (?<after>\b(?:<))"),
    ↳ "$${before}<>${after}", 0),
581 // Insert scope borders.
582 // class Disposable<T> : public Disposable<> { ... };
583 // class Disposable<T> : public Disposable<>
    ↳ {/\~*start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/ ...
    ↳ /\~*end~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/};
584 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)template[\t
    ↳ ]*<(?<typeParameters>[^\n]*)>[\t ]*(struct|class)[\t
    ↳ ]+(<?fullType>(?<type>[a-zA-Z] [a-zA-Z0-9]*) (<[^\>\n]+>?) [\t ]*:[\t
    ↳ ]*(?<access>(private|protected|public) [\t
    ↳ ]+)?(<?fullBaseType>(?<baseType>[a-zA-Z] [a-zA-Z0-9]*) (<[^\>\n]+>?) [\t
    ↳ ]*(\r?\n)?[\t
    ↳ ]*{) (?<middle>(.|\n)*) (?<beforeEnd>(?!<= \r?\n) \k<indent>) (?<end>};)"),
    ↳ "$${classDeclarationBegin}/*~start~type~${type}~${fullType}~${baseType}~${fullBas
    ↳ eType}~*/$${middle}${beforeEnd}/*~end~type~${type}~${fullType}~${baseType}~${full
    ↳ BaseType}~*/$${end}]",
    ↳ 0),
585 // Inside scopes replace:
586 // /\~*start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/ ... ) : base(
    ↳ ... /\~*end~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/
587 // /\~*start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/ ... ) :
    ↳ Disposable<> ( /\~*end~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/
588 (new Regex(@"(?<before>(?<typeScopeStart>/\~*start~type~(?<types>(?<type>[^\n\*]+)~
    ↳ (?<fullType>[^\n\*]+)~\k<type>~(?<fullBaseType>[^\n\*]+)~\k<types>~\*/) (.\n)+?) \s*:\s
    ↳ )*base(?<after>\(((.\n)+)?(?<typeScopeEnd>/\~*end~type~\k<types>~\*/)))"),
    ↳ "$${before}${fullBaseType}${after}", 20),
589 // Inside scopes replace:
590 // /\~*start~type~Disposable~Disposable<T>~X~X<>~*/ ... ) : base( ...
    ↳ ... /\~*end~type~Disposable~Disposable<T>~X~X<>~*/
591 // /\~*start~type~Disposable~Disposable<T>~X~X<>~*/ ... ) : X(
    ↳ ... /\~*end~type~Disposable~Disposable<T>~X~X<>~*/
592 (new Regex(@"(?<before>(?<typeScopeStart>/\~*start~type~(?<types>(?<type>[^\n\*]+)~
    ↳ (?<fullType>[^\n\*]+)~(?<baseType>[^\n\*]+)~(?<fullBaseType>[^\n\*]+)~\k<types>~\*/) (.\n)+?) \s*:\s
    ↳ )*base(?<after>\(((.\n)+)?(?<typeScopeEnd>/\~*end~type~\k<types>~\*/)))"),
    ↳ "$${before}${baseType}${after}",
    ↳ 20),
593 // Inside scopes replace:
594 // /\~*start~type~Disposable~Disposable<T>~X~X<>~*/ ... public: Disposable(T object)
    ↳ { Object = object; } ... public: Disposable(T object) : Disposable(object) { }
    ↳ ... /\~*end~type~Disposable~Disposable<T>~X~X<>~*/
595 // /\~*start~type~Disposable~Disposable<T>~X~X<>~*/ ... public: Disposable(T object)
    ↳ { Object = object; } /\~*end~type~Disposable~Disposable<T>~X~X<>~*/
596 (new Regex(@"(?<before>(?<typeScopeStart>/\~*start~type~(?<types>(?<type>[^\n\*]+)~
    ↳ (?<fullType>[^\n\*]+)~(?<baseType>[^\n\*]+)~(?<fullBaseType>[^\n\*]+)~\k<types>~\*/) (.\n)+?) \s*:\s
    ↳ )*base(?<after>\(((.\n)+)?(?<typeScopeEnd>/\~*end~type~\k<types>~\*/)))"),
    ↳ "$${before}${baseType}${after}",
    ↳ 20),
597 // Remove scope borders.
598 // /\~*start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/
599 //
600 (new Regex(@"/*~[^\~*\n]+(~[^\~*\n]+)*~*/"), "", 0),
601 }.Cast<ISubstitutionRule>().ToList();
602
603 public static readonly IList<ISubstitutionRule> LastStage = new List<SubstitutionRule>
604 {
605     // IDisposable disposable)
606     // IDisposable &disposable)
607     (new Regex(@"(?<argumentAbstractType>I[A-Z] [a-zA-Z0-9]+ (<[^\>\r\n]+>?)
    ↳ (?<argument>[_a-zA-Z0-9]+) (?<after>,|\))"), "$${argumentAbstractType}
    ↳ &${argument}${after}", 0),

```



```

608 // ICounter<int, int> c1;
609 // ICounter<int, int>* c1;
610 (new Regex(@"(?<abstractType>I[A-Z][a-zA-Z0-9]+(<[^\r\n]+>)?)
    → (?<variable>[_a-zA-Z0-9]+)(?<after> = null)?;"), "${abstractType}
    → *${variable}${after}", 0),
611 // (expression)
612 // expression
613 (new Regex(@"(\(|\)|)(([a-zA-Z0-9_]*:)+)\(|\)|;|\\\)"), "$1$2$3", 0),
614 // (method(expression))
615 // method(expression)
616 (new Regex(@"(?<firstSeparator>\(|\)|
    → )\((?<method>[a-zA-Z0-9_>]*:)+\((?<expression>((?<parenthesis>\(|\)|(?<-parent
    → hesis>\\)|[a-zA-Z0-9_>]*:)+)(?<parenthesis>(?!))\\)\)(?<lastSeparator>(<|
    → |;|\\))"), "${firstSeparator}${method}(${expression})${lastSeparator}", 0),
617 // .append(".")
618 // .append(1, '.');
619 (new Regex(@"\..append\\(\"\"([^\\""]|\\\"")\"\"\\\)"), ".append(1, '$1')", 0),
620 // return ref _elements[node];
621 // return &elements[node];
622 (new Regex(@"return ref ([_a-zA-Z0-9]+)\([([_a-zA-Z0-9]*)+\)\";"), "return &$1[$2];",
    → 0),
623 // ((1, 2))
624 // ({1, 2})
625 (new Regex(@"(?<before>\(|\)|\((?<first>[^\n()]+),
    → (?<second>[^\n()]+)\)(?<after>\(|\)|\))", "${before}${first},
    → ${second}${after}", 10),
626 // {1, 2}.GetHashCode()
627 // Platform::Hashing::Hash(1, 2)
628 (new Regex(@"{(?<first>[^\n{}]+), (?<second>[^\n{}]+)}\.GetHashCode\\(\|)"),
    → "Platform::Hashing::Hash(${first}, ${second})", 10),
629 // range.ToString()
630 // Platform::Converters::To<std::string>(range).data()
631 (new Regex(@"(?<before>\W)(?<variable>[_a-zA-Z][_a-zA-Z0-9]+)\.ToString\\(\|)"),
    → "${before}Platform::Converters::To<std::string>(${variable}).data()", 10),
632 // new
633 //
634 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)new\\_
    → s+\"), "${before}
    → 10),
635 // x == null
636 // x == nullptr
637 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)(?<v
    → ariable>[_a-zA-Z][_a-zA-Z0-9]+)(?<operator>s*(==|!=)\s*)null(?<after>\W)",
    → "${before}${variable}${operator}nullptr${after}", 10),
638 // null
639 // {}
640 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)null\\_
    → (?<after>\W)", "${before}-{}${after}
    → 10),
641 // default
642 // 0
643 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)defa
    → ult(?<after>\W)", "${before}0${after}
    → 10),
644 // object x
645 // void *x
646 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)(?!_
    → @)(object|System\.Object) (?<after>\w)", "${before}void *${after}
    → 10),
647 // <object>
648 // <void*>
649 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)(?!_
    → @)(object|System\.Object) (?<after>\W)", "${before}void*${after}
    → 10),
650 // @object
651 // object
652 (new Regex(@"@([_a-zA-Z0-9]+)"), "$1", 0),
653 // this->GetType().Name
654 // typeid(this).name()
655 (new Regex(@"(this)->GetType\\(\|)\.Name"), "typeid($1).name()", 0),
656 // ArgumentException
657 // std::invalid_argument
658 (new Regex(@"(?<before>\r?\n[^\r\n]*(\"\"(\\\"|\"\"[^\r\n])*\")\"\"[^\r\n]*)*(?<=\W)(Sys
    → tem\.)?ArgumentException(?<after>\W)",
    → "${before}std::invalid_argument${after}", 10),
659 // InvalidOperationException

```

```

660 // std::runtime_error
661 (new Regex(@"(\\W)(InvalidOperationException|Exception)(\\W)"),
    ↪ "$1std::runtime_error$3", 0),
662 // ArgumentException
663 // std::invalid_argument
664 (new Regex(@"(\\W)(ArgumentException|ArgumentOutOfRangeException)(\\W)"),
    ↪ "$1std::invalid_argument$3", 0),
665 // template <typename T> struct Range : IEquatable<Range<T>>
666 // template <typename T> struct Range {
667 (new Regex(@"(?<before>template <typename (?<typeParameter>[^\n]+)> (struct|class)
    ↪ (?<type>[a-zA-Z0-9]+[^\n]+)) : (public
    ↪ )?IEquatable<k<type>>(?(after)(\s|\n)*{)"), "${before}${after}", 0),
668 // public: delegate void Disposal(bool manual, bool wasDisposed);
669 // public: delegate void Disposal(bool, bool);
670 (new Regex(@"(?<before>(?(access>(private|protected|public): )delegate
    ↪ (?(returnType>[a-zA-Z][a-zA-Z0-9:]+)
    ↪ (?(delegate>[a-zA-Z][a-zA-Z0-9:]+)\(((?(leftArgumentType>[a-zA-Z][a-zA-Z0-9:]+),
    ↪ )*)?(argumentType>[a-zA-Z][a-zA-Z0-9:]+)
    ↪ (?(argumentName>[a-zA-Z][a-zA-Z0-9:]+)(?(after>(),
    ↪ (?(rightArgumentType>[a-zA-Z][a-zA-Z0-9:]+)
    ↪ (?(rightArgumentName>[a-zA-Z][a-zA-Z0-9:]+))*\);)"),
    ↪ "${before}${argumentType}${after}", 20),
671 // public: delegate void Disposal(bool, bool);
672 // using Disposal = void(bool, bool);
673 (new Regex(@"(?<access>(private|protected|public): )delegate
    ↪ (?(returnType>[a-zA-Z][a-zA-Z0-9:]+)
    ↪ (?(delegate>[a-zA-Z][a-zA-Z0-9:]+)\(((?<argumentTypes>[^\(\)\n]*\)\);)", "using
    ↪ ${delegate} = ${returnType}(${argumentTypes});", 20),
674 // <4-1>
675 // <3>
676 (new Regex(@"(?<before><)4-1(?(after>>)", "${before}3${after}", 0),
677 // <3-1>
678 // <2>
679 (new Regex(@"(?<before><)3-1(?(after>>)", "${before}2${after}", 0),
680 // <2-1>
681 // <1>
682 (new Regex(@"(?<before><)2-1(?(after>>)", "${before}1${after}", 0),
683 // <1-1>
684 // <0>
685 (new Regex(@"(?<before><)1-1(?(after>>)", "${before}0${after}", 0),
686 // #region Always
687 //
688 (new Regex(@"(^\r?\n)[ \t]*\#(region|endregion)[^\r\n]*(\r?\n|$)", "", 0),
689 // //define ENABLE_TREE_AUTO_DEBUG_AND_VALIDATION
690 //
691 (new Regex(@"\\[/\][ \t]*\#define[ \t]+[_a-zA-Z0-9]+[ \t]*"), "", 0),
692 // #if USEARRAYPOOL\r\n#endif
693 //
694 (new Regex(@"#if [a-zA-Z0-9]+\s+#endif"), "", 0),
695 // [Fact]
696 //
697 (new Regex(@"(?<firstNewLine>\r?\n|\\A)(?(indent>[ \t
    ↪ ]+)\[[a-zA-Z0-9]+\(((?(expression>((?(parenthesis>\\()|(?<-parenthesis>\\))|[^()\r\
    ↪ \n]*+)(?(parenthesis>?!))\))\)?\][ \t]*(\r?\n\k<indent>?)"",
    ↪ "${firstNewLine}${indent}", 5),
698 // \A \n ... namespace
699 // \Anamespace
700 (new Regex(@"(\\A)(\r?\n)+namespace"), "$1namespace", 0),
701 // \A \n ... class
702 // \Aclass
703 (new Regex(@"(\\A)(\r?\n)+class"), "$1class", 0),
704 // \n\n\n
705 // \n\n
706 (new Regex(@"\r?\n[ \t]*\r?\n[ \t]*\r?\n"), Environment.NewLine +
    ↪ Environment.NewLine, 50),
707 // {\n\n
708 // {\n
709 (new Regex(@"{[ \t]*\r?\n[ \t]*\r?\n"), "{" + Environment.NewLine, 10),
710 // \n\n}
711 // \n}
712 (new Regex(@"\r?\n[ \t]*\r?\n(?<end>[ \t]*}")), Environment.NewLine + "${end}", 10),
713 }.Cast<ISubstitutionRule>().ToList();
714
715 public CSharpToCppTransformer(IList<ISubstitutionRule> extraRules) :
    ↪ base(FirstStage.Concat(extraRules).Concat>LastStage).ToList()) { }
716

```

```

717         public CSharpToCppTransformer() : base(FirstStage.Concat(LastStage).ToList()) { }
718     }
719 }

```

1.2 ./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp.Tests/CSharpToCppTransformerTests.cs

```

1  using Xunit;
2
3  namespace Platform.RegularExpressions.Transformer.CSharpToCpp.Tests
4  {
5      public class CSharpToCppTransformerTests
6      {
7          [Fact]
8          public void EmptyLineTest()
9          {
10             // This test can help to test basic problems with regular expressions like incorrect
11             ↪ syntax
12             var transformer = new CSharpToCppTransformer();
13             var actualResult = transformer.Transform("");
14             Assert.Equal("", actualResult);
15         }
16
17         [Fact]
18         public void HelloWorldTest()
19         {
20             const string helloWorldCode = @"using System;
21             class Program
22             {
23                 public static void Main(string[] args)
24                 {
25                     Console.WriteLine("Hello, world!");
26                 }
27             };
28             const string expectedResult = @"class Program
29             {
30             public: static void Main(std::string args[])
31             {
32                 printf("Hello, world!\n");
33             }
34             };";
35             var transformer = new CSharpToCppTransformer();
36             var actualResult = transformer.Transform(helloWorldCode);
37             Assert.Equal(expectedResult, actualResult);
38         }
39     }

```

Index

./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp.Tests/CSharpToCppTransformerTests.cs, 17

./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp/CSharpToCppTransformer.cs, 1