

## 1.1 ./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp/CSharpToCppTransformer.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Linq;
4  using System.Text.RegularExpressions;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.RegularExpressions.Transformer.CSharpToCpp
9  {
10     public class CSharpToCppTransformer : TextTransformer
11     {
12         public static readonly IList

```

```

58 //
59 (new Regex(@"r?\n[^\n]+bool operator !=\(((?<type>[^\n]+) (?<left>[a-zA-Z0-9]+),
    ↳ \k<type> (?<right>[a-zA-Z0-9]+)\) => !\((\k<left>|\k<right>) ==
    ↳ (\k<left>|\k<right>)\);"), "", 10),
60 // public override bool Equals(object obj) => obj is Range<T> range ? Equals(range)
    ↳ : false;
61 //
62 (new Regex(@"r?\n[^\n]+override bool Equals\((System\.)?[Oo]bject
    ↳ (?<this>[a-zA-Z0-9]+)\) => \k<this> is [^\n]+ (?<other>[a-zA-Z0-9]+) \?
    ↳ Equals\(\k<other>\) : false;"), "", 10),
63 // out TProduct
64 // TProduct
65 (new Regex(@"(?<before><|, ))(in|out)
    ↳ (?<typeParameter>[a-zA-Z0-9]+)(?<after>>|,))"),
    ↳ "${before}${typeParameter}${after}", 10),
66 // public ...
67 // public: ...
68 (new Regex(@"(?<newLineAndIndent>r?\n?[
    ↳ \t]*) (?<before>[^\{\\(\r\n)*) (?<access>private|protected|public) [ \t]+(?![^\{\\(\r\n)
    ↳ \n]*((?<=\\s)|\\W) (interface|class|struct) (\\W) [^\{\\(\r\n)*[\\{\\(\r\n)]")",
    ↳ "${newLineAndIndent}${access}: ${before}", 0),
69 // public: static bool CollectExceptions { get; set; }
70 // public: inline static bool CollectExceptions;
71 (new Regex(@"(?<access>(private|protected|public): ) (?<before>(static )? [^\r\n]+
    ↳ ) (?<name>[a-zA-Z0-9]+) {[~;]}*(?<=\\W) get; [~;]}*(?<=\\W) set; [~;]}*"),
    ↳ "${access}inline ${before}${name}";", 0),
72 // public abstract class
73 // class
74 (new Regex(@"((public|protected|private|internal|abstract|static)
    ↳ )*(?<category>interface|class|struct)", "${category}", 0),
75 //class GenericCollectionMethodsBase<TElement> {
76 // template <typename TElement> class GenericCollectionMethodsBase {
77 (new Regex(@"(?<before>r?\n) (?<indent>[ \t]*) (?<type>class|struct)
    ↳ (?<typeName>[a-zA-Z0-9]+)<(?<typeParameters>[a-zA-Z0-9
    ↳ ,]+)> (?<typeDefinitionEnding>[^\{]+){", "${before}${indent}template <typename
    ↳ ...> ${type} ${typeName};" + Environment.NewLine + "${indent}template <typename
    ↳ ${typeParameters}> ${type}
    ↳ ${typeName}<${typeParameters}>${typeDefinitionEnding}{", 0),
78 // static void
    ↳ TestMultipleCreationsAndDeletions<TElement>(SizedBinaryTreeMethodsBase<TElement>
    ↳ tree, TElement* root)
79 // template<typename T> static void
    ↳ TestMultipleCreationsAndDeletions<TElement>(SizedBinaryTreeMethodsBase<TElement>
    ↳ tree, TElement* root)
80 (new Regex(@"static ([a-zA-Z0-9]+) ([a-zA-Z0-9]+)<([a-zA-Z0-9]+)>\\(((\\r\\n)+)\\)",
    ↳ "template <typename $3> static $1 $2($4)", 0),
81 // interface IFactory<out TProduct> {
82 // template <typename...> class IFactory; \ntemplate <typename TProduct> class
    ↳ IFactory<TProduct>
83 (new Regex(@"(?<before>r?\n) (?<indent>[ \t]*) interface
    ↳ (?<interface>[a-zA-Z0-9]+)<(?<typeParameters>[a-zA-Z0-9
    ↳ ,]+)> (?<typeDefinitionEnding>[^\{]+){", "${before}${indent}template <typename
    ↳ ...> class ${interface};" + Environment.NewLine + "${indent}template <typename
    ↳ ${typeParameters}> class
    ↳ ${interface}<${typeParameters}>${typeDefinitionEnding}{", 0),
    ↳ "public:", 0),
84 // template <typename TObject, TProperty, TValue>
85 // template <typename TObject, typename TProperty, typename TValue>
86 (new Regex(@"(?<before>template <((, )?typename [a-zA-Z0-9]+)+,
    ↳ ) (?<typeParameter>[a-zA-Z0-9]+) (?<after>(,|>))", "${before}typename
    ↳ ${typeParameter}${after}", 10),
87 // Insert markers
88 // private: static void BuildExceptionString(this StringBuilder sb, Exception
    ↳ exception, int level)
89 // /*~extensionMethod~BuildExceptionString~*/private: static void
    ↳ BuildExceptionString(this StringBuilder sb, Exception exception, int level)
90 (new Regex(@"private: static [^\r\n]+ (?<name>[a-zA-Z0-9]+)\\(this [^\r\n]+\\)",
    ↳ "/*~extensionMethod~${name}~*/$0", 0),
91 // Move all markers to the beginning of the file.
92 (new Regex(@"A(?<before>[^\r\n]+r?\n(.|\n) ) (?<marker>\/\~extensionMethod~(?<name>
    ↳ [a-zA-Z0-9]+)~\*/)", "${marker}${before}",
    ↳ 10),
93 // /*~extensionMethod~BuildExceptionString~*/...sb.BuildExceptionString(exception.In_
    ↳ nerException, level +
    ↳ 1);

```

```

94 // /*~extensionMethod~BuildExceptionString~*/...BuildExceptionString(sb,
95   ↳ exception.InnerException, level + 1);
96 (new Regex(@"(?<before>/\/*~extensionMethod~(?<name>[a-zA-Z0-9]+)~\*/(.\|\\n)+\\W)(?<var_
97   ↳ iable>[_a-zA-Z0-9]+)\\.\\k<name>\\("), "${before}${name}${{variable}}, ",
98   ↳ 50),
99 // Remove markers
100 // /*~extensionMethod~BuildExceptionString~*/
101 //
102 (new Regex(@"\/*~extensionMethod~[a-zA-Z0-9]+~\*/"), "", 0),
103 // (this
104 // (
105 (new Regex(@"\((this ", "(", 0),
106 // private: static readonly Disposal _emptyDelegate = (manual, wasDisposed) => { };
107 // private: inline static std::function<Disposal> _emptyDelegate = [](auto manual,
108   ↳ auto wasDisposed) { };
109 (new Regex(@"(?<access>(private|protected|public): )?static readonly
110   ↳ (?<type>[a-zA-Z][a-zA-Z0-9]*) (?<name>[a-zA-Z_][a-zA-Z0-9_]*) =
111   ↳ \((?<firstArgument>[a-zA-Z_][a-zA-Z0-9_]*)
112   ↳ (?<secondArgument>[a-zA-Z_][a-zA-Z0-9_]*)\)) => {\s*};"), "${access}inline static
113   ↳ std::function<${type}> ${name} = [](auto ${firstArgument}, auto
114   ↳ ${secondArgument}) { };", 0),
115 // public: static readonly EnsureAlwaysExtensionRoot Always = new
116   ↳ EnsureAlwaysExtensionRoot();
117 // public: inline static EnsureAlwaysExtensionRoot Always;
118 (new Regex(@"(?<access>(private|protected|public): )?static readonly
119   ↳ (?<type>[a-zA-Z0-9]+(<[a-zA-Z0-9]+>?)) (?<name>[a-zA-Z0-9_]+) = new
120   ↳ \\k<type>\\(\\);"), "${access}inline static ${type} ${name};", 0),
121 // public: static readonly Range<int> SByte = new
122   ↳ Range<int>(std::numeric_limits<int>::min(), std::numeric_limits<int>::max());
123 // public: inline static Range<int> SByte =
124   ↳ Range<int>(std::numeric_limits<int>::min(), std::numeric_limits<int>::max());
125 (new Regex(@"(?<access>(private|protected|public): )?static readonly
126   ↳ (?<type>[a-zA-Z0-9]+(<[a-zA-Z0-9]+>?)) (?<name>[a-zA-Z0-9_]+) = new
127   ↳ \\k<type>\\((?<arguments>[^\n]+)\\);"), "${access}inline static ${type} ${name} =
128   ↳ ${type}${{arguments}};", 0),
129 // public: static readonly string ExceptionContentsSeparator = "---";
130 // public: inline static std::string ExceptionContentsSeparator = "---";
131 (new Regex(@"(?<access>(private|protected|public): )?(const|static readonly) string
132   ↳ (?<name>[a-zA-Z0-9_]+) = ""(?<string>(\\\\"|\\r\\n)+)"";"), "${access}inline
133   ↳ static std::string ${name} = \\\"${string}\\\";", 0),
134 // private: const int MaxPath = 92;
135 // private: inline static const int MaxPath = 92;
136 (new Regex(@"(?<access>(private|protected|public): )?(const|static readonly)
137   ↳ (?<type>[a-zA-Z0-9]+) (?<name>[_a-zA-Z0-9]+) = (?<value>[^\r\n]+);"),
138   ↳ "${access}inline static const ${type} ${name} = ${value};", 0),
139 // ArgumentNotNull(EnsureAlwaysExtensionRoot root, TArgument argument) where
140   ↳ TArgument : class
141 // ArgumentNotNull(EnsureAlwaysExtensionRoot root, TArgument* argument)
142 (new Regex(@"(?<before> [a-zA-Z]+\\((([a-zA-Z *,]+, |)) (?<type>[a-zA-Z]+) (?<after>(\\
143   ↳ [a-zA-Z *,]+)\\)) [ \\r\\n]+where \\k<type> : class"), "${before}${type}*${after}",
144   ↳ 0),
145 // protected: abstract TElement GetFirst();
146 // protected: virtual TElement GetFirst() = 0;
147 (new Regex(@"(?<access>(private|protected|public): )?abstract
148   ↳ (?<method>[^\r\n]+);"), "${access}virtual ${method} = 0;", 0),
149 // TElement GetFirst();
150 // virtual TElement GetFirst() = 0;
151 (new Regex(@"(?<before>[\\r\\n]+ [ ]+)(?<methodDeclaration>(?!return) [a-zA-Z0-9]+
152   ↳ [a-zA-Z0-9]+\\(([^\\r\\n]*\\)) (?<after>;[ ]*[\\r\\n]+)"), "${before}virtual
153   ↳ ${methodDeclaration} = 0${after}", 1),
154 // protected: readonly TreeElement[] _elements;
155 // protected: TreeElement _elements[N];
156 (new Regex(@"(?<access>(private|protected|public): )?readonly
157   ↳ (?<type>[a-zA-Z<>0-9]+)(\\[\\]]+ ) (?<name>[_a-zA-Z0-9]+);"), "${access}${type}
158   ↳ ${name}[N];", 0),
159 // protected: readonly TElement Zero;
160 // protected: TElement Zero;
161 (new Regex(@"(?<access>(private|protected|public): )?readonly
162   ↳ (?<type>[a-zA-Z<>0-9]+) (?<name>[_a-zA-Z0-9]+);"), "${access}${type} ${name};",
163   ↳ 0),
164 // internal
165 //
166 (new Regex(@"(\\W)internal\\s+"), "$1", 0),
167 // static void NotImplementedException(ThrowExtensionRoot root) => throw new
168   ↳ NotImplementedException();

```

```

137 // static void NotImplementedException(ThrowExtensionRoot root) { return throw new
138     ↳ NotImplementedException(); }
139 (new Regex(@"(^s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
140     ↳ )?(override )?([a-zA-Z0-9]+
141     ↳ )([a-zA-Z0-9]+\(((^\\(\\r\\n)*)\\)\s+=>\s+throw([~;\r\n]+);"),
142     ↳ "$1$2$3$4$5$6$7$8($9) { throw$10; }", 0),
143 // SizeBalancedTree(int capacity) => a = b;
144 // SizeBalancedTree(int capacity) { a = b; }
145 (new Regex(@"(^s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
146     ↳ )?(override )?(void )?([a-zA-Z0-9]+\(((^\\(\\r\\n)*)\\)\s+=>\s+([~;\r\n]+);"),
147     ↳ "$1$2$3$4$5$6$7$8($9) { $10; }", 0),
148 // int SizeBalancedTree(int capacity) => a;
149 // int SizeBalancedTree(int capacity) { return a; }
150 (new Regex(@"(^s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
151     ↳ )?(override )?([a-zA-Z0-9]+
152     ↳ )([a-zA-Z0-9]+\(((^\\(\\r\\n)*)\\)\s+=>\s+([~;\r\n]+);"), "$1$2$3$4$5$6$7$8($9) {
153     ↳ return $10; }", 0),
154 // OnDispose = (manual, wasDisposed) =>
155 // OnDispose = [&](auto manual, auto wasDisposed)
156 (new Regex(@"(?<variable>[a-zA-Z_][a-zA-Z0-9_]*) (?<operator>\s*[\+=\s*])\(((?<firstArg_
157     ↳ ument>[a-zA-Z_][a-zA-Z0-9_]*) ,
158     ↳ (?<secondArgument>[a-zA-Z_][a-zA-Z0-9_]*)\\)\s*=>"),
159     ↳ "$${variable}${operator}[&](auto ${firstArgument}, auto ${secondArgument})", 0),
160 // () => Integer<TElement>.Zero;
161 // () { return Integer<TElement>.Zero; },
162 (new Regex(@"\\(\\)\s+=>\s+(?<expression>[^() ,;\\r\\n]+(\\(((?<parenthesis>\\(|(?<-parent_
163     ↳ hesis>\\)|[^() ,;\\r\\n]*)*?\\))?[~;\r\\n]*)(?<after>,|\\);)"), "() { return
164     ↳ ${expression}; }${after}", 0),
165 // ~DisposableBase() => Destruct();
166 // ~DisposableBase() { Destruct(); }
167 (new Regex(@"~(?<class>[a-zA-Z_][a-zA-Z0-9_]*)\\(\\)\s+=>\s+([~;\r\\n]+?);"),
168     ↳ "~${class}() { $1; }", 0),
169 // => Integer<TElement>.Zero;
170 // { return Integer<TElement>.Zero; }
171 (new Regex(@"\\)\s+=>\s+([~;\r\\n]+?);"), ") { return $1; }", 0),
172 // () { return avlTree.Count; }
173 // [&]()-> auto { return avlTree.Count; }
174 (new Regex(@"(?<before>, |\\(\\)\s+{ return (?<expression>[^;\r\\n]+); }"),
175     ↳ "$${before}[&]()-> auto { return ${expression}; }", 0),
176 // Count => GetSizeOrZero(Root);
177 // Count() { return GetSizeOrZero(Root); }
178 (new Regex(@"(\\W)([A-Z][a-zA-Z]+)\s+=>\s+([~;\r\\n]+);"), "$1$2() { return $3; }", 0),
179 // Insert scope borders.
180 // interface IDisposable { ... }
181 // interface IDisposable { /*~start~interface~IDisposable~*/ ...
182     ↳ /*~end~interface~IDisposable~*/ }
183 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\\t ]*)interface[\\t
184     ↳ ]*(?<type>[a-zA-Z_][a-zA-Z0-9_]*(<[~<>\\n]*?)[~{ }]*{ }(?<middle>(.|\\n)*)(?<beforeE_
185     ↳ nd>(?<=\\r?\\n)\\k<indent>)(?<end>})"),
186     ↳ "$${classDeclarationBegin}/*~start~interface~${type}~*/${middle}${beforeEnd}/*~en_
187     ↳ d~interface~${type}~*/${end}",
188     ↳ 0),
189 // Inside the scope replace:
190 // /*~start~interface~IDisposable~*/ ... bool IsDisposed { get; } ...
191     ↳ /*~end~interface~IDisposable~*/
192 // /*~start~interface~IDisposable~*/ ... virtual bool IsDisposed() = 0;
193     ↳ /*~end~interface~IDisposable~*/
194 (new Regex(@"(?<before>(?<typeScopeStart>/\\*~start~interface~(?<type>[~\\n\\*]+)~\\*/)_
195     ↳ (.|\\n)+?)(?<propertyDeclaration>(?<access>(private|protected|public):
196     ↳ )?(?<propertyType>[a-zA-Z_][a-zA-Z0-9_]*(<[~<>\\n]*?)) [~{ }]*{ }(?<middle>(.|\\n)*)(?<beforeE_
197     ↳ nd>(?<=\\r?\\n)\\k<indent>)(?<end>})"),
198     ↳ "$${classDeclarationBegin}/*~start~interface~${type}~*/${middle}${beforeEnd}/*~en_
199     ↳ d~interface~${type}~*/${end}",
200     ↳ 0),
201 // Remove scope borders.
202 // /*~start~interface~IDisposable~*/
203 //
204 (new Regex(@"/*~[~\\n\\*]+(~[~\\n\\*]+)*~\\*/"), "", 0),
205 // public: T Object { get; }
206 // public: const T Object;
207 (new Regex(@"(?<before>[~\\r\\r?\\n[ \\t ]*)(?<access>(private|protected|public):
208     ↳ )?(?<type>[a-zA-Z_][a-zA-Z0-9_]*(<[~<>\\n]*?))
209     ↳ (?<property>[a-zA-Z_][a-zA-Z0-9_]*)(?<blockOpen>[\\n\\s]*{[\\n\\s]*}\\(\\[~\\n\\n]+\\)[\\n\\s_
210     ↳ ]*)?get; (?<blockClose>[\\n\\s]*}) (?<after>[\\n\\s]*)", "${before}${access}const
211     ↳ ${type} ${property};${after}", 2),
212 // public: bool IsDisposed { get => _disposed > 0; }
213 // public: bool IsDisposed() { return _disposed > 0; }

```

```

(new Regex(@"(?<before>[^\r]\r?\n[ \t]*) (?<access>(private|protected|public):
) ?(?<virtual>virtual )?bool
→ (?<property>[a-zA-Z_][a-zA-Z0-9_]*) (?<blockOpen>[\n\s]*{[\n\s]*}(\[[^\n]+\][\n\s]
→ ]*)?get\s*=>\s*(?<expression>[^\n]+); (?<blockClose>[\n\s]*{[\n\s]*})",
→ "${before}${access}${virtual}bool ${property}() ${blockOpen}return
→ ${expression}; ${blockClose}", 2),
// protected: virtual std::string ObjectName { get => GetType().Name; }
// protected: virtual std::string ObjectName() { return GetType().Name; }
(new Regex(@"(?<before>[^\r]\r?\n[ \t]*) (?<access>(private|protected|public):
) ?(?<virtual>virtual ) ?(?<type>[a-zA-Z_][a-zA-Z0-9_<:;>]*)
→ (?<property>[a-zA-Z_][a-zA-Z0-9_]*) (?<blockOpen>[\n\s]*{[\n\s]*}(\[[^\n]+\][\n\s]
→ ]*)?get\s*=>\s*(?<expression>[^\n]+); (?<blockClose>[\n\s]*{[\n\s]*})",
→ "${before}${access}${virtual}${type} ${property}() ${blockOpen}return
→ ${expression}; ${blockClose}", 2),
// ArgumentInRange(string message) { string messageBuilder() { return message; }
// ArgumentInRange(string message) { auto messageBuilder = [&]() -> string { return
→ message; };
(new Regex(@"(?<before>\W[_a-zA-Z0-9]+\(([^\\]\n)*\)[\s\n]*{[\s\n]*{([~}]|\n)*?(\r?\n)
→ ?[ \t]*) (?<returnType>[_a-zA-Z0-9*:] +[_a-zA-Z0-9*:] *)
→ (?<methodName>[_a-zA-Z0-9+] +)\((?<arguments>[^\n]*\)[\s\n]*{(?<body>("[^""\n]+""|
→ [~}]|\n)+?)})", "${before}auto ${methodName} = [&]() -> ${returnType}
→ {${body}};", 10),
// Func<TElement> treeCount
// std::function<TElement()> treeCount
(new Regex(@"Func<([a-zA-Z0-9+] +)> ([a-zA-Z0-9+] +)", "std::function<$1()> $2", 0),
// Action<TElement> free
// std::function<void(TElement)> free
(new Regex(@"Action<([?<typeParameters>[a-zA-Z0-9+] +,
→ ([a-zA-Z0-9+] +)*)> (?<after>| (?<variable>[a-zA-Z0-9+] +))",
→ "std::function<void(${typeParameters})> ${after}", 0),
// Predicate<TArgument> predicate
// std::function<bool(TArgument)> predicate
(new Regex(@"Predicate<([a-zA-Z0-9+] +)> ([a-zA-Z0-9+] +)", "std::function<bool($1)>
→ $2", 0),
// var
// auto
(new Regex(@"(\W)var(\W)", "$1auto$2", 0),
// unchecked
//
(new Regex(@"[\r\n]{2}\s*?unchecked\s*?$)", "", 0),
// throw new
// throw
(new Regex(@"(\W)throw new(\W)", "$1throw$2", 0),
// void RaiseExceptionIgnoredEvent(Exception exception)
// void RaiseExceptionIgnoredEvent(const std::exception& exception)
(new Regex(@"(\\(| ) (System\\.Exception|Exception) (|\\))", "$1const
→ std::exception&$3", 0),
// EventHandler<Exception>
// EventHandler<std::exception>
(new Regex(@"(\W) (System\\.Exception|Exception) (\W)", "$1std::exception$3", 0),
// override void PrintNode(TElement node, StringBuilder sb, int level)
// void PrintNode(TElement node, StringBuilder sb, int level) override
(new Regex(@"override ([a-zA-Z0-9 \*+]+) \(([^\\]\r\n)+?)\"", "$1$2 override", 0),
// return {range.Minimum, range.Maximum}
// return {range.Minimum, range.Maximum}
(new Regex(@"(?<before>return\s*) \((?<values>[^\n]+\n)+\) (?!\() (?<after>\W)",
→ "${before}${values}${after}", 0),
// string
// std::string
(new Regex(@"(?<before>\W) (?<!:):)string(?<after>\W)",
→ "${before}std::string${after}", 0),
// System.ValueTuple
// std::tuple
(new Regex(@"(?<before>\W) (System\\.)?ValueTuple(?!\s*=\|\\() (?<after>\W)",
→ "${before}std::tuple${after}", 0),
// sbyte
// std::int8_t
(new Regex(@"(?<before>\W) ((System\\.)?SB|sb)yte(?!\s*=\|\\() (?<after>\W)",
→ "${before}std::int8_t${after}", 0),
// short
// std::int16_t
(new Regex(@"(?<before>\W) ((System\\.)?Int16|short) (?!\s*=\|\\() (?<after>\W)",
→ "${before}std::int16_t${after}", 0),
// int
// std::int32_t

```

```

231 (new Regex(@"(?<before>\W)((System\.)?I|i)nt(32)?(?!\s*=\|()\ (?<after>\W)"),
232     ↳ "${before}std::int32_t${after}", 0),
233 // long
234 (new Regex(@"(?<before>\W)((System\.)?Int64|long)(?! \s*=\|()\ (?<after>\W)"),
235     ↳ "${before}std::int64_t${after}", 0),
236 // byte
237 (new Regex(@"(?<before>\W)((System\.)?Byte|byte)(?! \s*=\|()\ (?<after>\W)"),
238     ↳ "${before}std::uint8_t${after}", 0),
239 // ushort
240 (new Regex(@"(?<before>\W)((System\.)?UInt16|ushort)(?! \s*=\|()\ (?<after>\W)"),
241     ↳ "${before}std::uint16_t${after}", 0),
242 // uint
243 (new Regex(@"(?<before>\W)((System\.)?UI|ui)nt(32)?(?!\s*=\|()\ (?<after>\W)"),
244     ↳ "${before}std::uint32_t${after}", 0),
245 // ulong
246 (new Regex(@"(?<before>\W)((System\.)?UInt64|ulong)(?! \s*=\|()\ (?<after>\W)"),
247     ↳ "${before}std::uint64_t${after}", 0),
248 // char*[] args
249 (new Regex(@"([_a-zA-Z0-9:\*]?)\[\] ([a-zA-Z0-9]+)", "$1 $2[]", 0),
250 // float.MinValue
251 (new Regex(@"(?<before>\W)(?<type>std::[a-z0-9_]+|float|double)\.MinValue(?<after>\W|
252     ↳ )"), "${before}std::numeric_limits<${type}>::lowest()${after}",
253     ↳ 0),
254 // double.MaxValue
255 (new Regex(@"(?<before>\W)(?<type>std::[a-z0-9_]+|float|double)\.MaxValue(?<after>\W|
256     ↳ )"), "${before}std::numeric_limits<${type}>::max()${after}",
257     ↳ 0),
258 // using Platform.Numbers;
259 //
260 (new Regex(@"([\r\n]{2}|^)\s*?using [\.a-zA-Z0-9]+;\s*?$)", "", 0),
261 // class SizedBinaryTreeMethodsBase : GenericCollectionMethodsBase
262 // class SizedBinaryTreeMethodsBase : public GenericCollectionMethodsBase
263 (new Regex(@"(struct|class) ([a-zA-Z0-9]+)(<[a-zA-Z0-9_ ,]+>)? : ([a-zA-Z0-9]+)",
264     ↳ "$1 $2$3 : public $4", 0),
265 // System.IDisposable
266 // System::IDisposable
267 (new Regex(@"(?<before>System(::[a-zA-Z_]\w*)*)\. (?<after>[a-zA-Z_]\w*)"),
268     ↳ "${before}::${after}", 20),
269 // class IProperty : ISetter<TValue, TObjct>, IProvider<TValue, TObjct>
270 // class IProperty : public ISetter<TValue, TObjct>, public IProvider<TValue,
271     ↳ TObjct>
272 (new Regex(@"(?<before>(interface|struct|class) [a-zA-Z_]\w* : ((public
273     ↳ [a-zA-Z_]\w*:(<[a-zA-Z0-9_ ,]+>)?,
274     ↳ )+)?(?<inheritedType>(?!public)[a-zA-Z_]\w*:(<[a-zA-Z0-9_ ,]+>)?(?<after>(,
275     ↳ [a-zA-Z_]\w*:(!>)|[\r\n]+)))", "${before}public ${inheritedType}${after}",
276     ↳ 10),
277 // interface IDisposable {
278 // class IDisposable { public:
279 (new Regex(@"(?<before>\r?\n)(?<indent>[ \t]*)interface
280     ↳ (?<interface>[a-zA-Z_]\w*)(?<typeDefinitionEnding>[~{]+){",
281     ↳ "${before}${indent}class ${interface}${typeDefinitionEnding}{", +
282     ↳ Environment.NewLine + "    public:", 0),
283 // struct TreeElement { }
284 // struct TreeElement { };
285 (new Regex(@"(struct|class) ([a-zA-Z0-9]+)(\s+){([\sa-zA-Z0-9;:_]+?)}([~;])", "$1
286     ↳ $2$3{$4};$5", 0),
287 // class Program { }
288 // class Program { };
289 (new Regex(@"(?<type>struct|class)
290     ↳ (?<name>[a-zA-Z0-9_][^r\n]*) (?<beforeBody>[\r\n]+(?<indentLevel>[ \t
291     ↳ ]*)?)\{(?<body>[ \S\s]+?[ \r\n]+\k<indentLevel>)\}(?<afterBody>[~;]|$)", "${type}
292     ↳ ${name}${beforeBody}${body}};${afterBody}", 0),
293 // Insert scope borders.
294 // ref TElement root
295 // ~!root!~ref TElement root
296 (new Regex(@"(?<definition>(?!<= \|()\ (ref [a-zA-Z0-9_]+|[a-zA-Z0-9_]+(?<ref>))
297     ↳ (?<variable>[a-zA-Z0-9_]+)(?<=\\|, |<=)")), "~!${variable}!~${definition}", 0),
298 // Inside the scope of ~!root!~ replace:

```

```

282 // root
283 // *root
284 (new Regex(@"(?<definition>~!(?<pointer>[a-zA-Z0-9]+)!~ref [a-zA-Z0-9]+
→ \k<pointer>(=?\)|,| =)) (?<before>((?<!~!\k<pointer>!~)(.\|\\n))*?) (?<prefix>(\W
→ |\\())\k<pointer>(=?<suffix>(\|\\|;|,))"),
→ "$${definition}${before}${prefix}*${pointer}${suffix}", 70),
285 // Remove scope borders.
286 // ~!root!~
287 //
288 (new Regex(@"~!(?<pointer>[a-zA-Z0-9]+)!~"), "", 5),
289 // ref auto root = ref
290 // ref auto root =
291 (new Regex(@"ref ([a-zA-Z0-9]+) ([a-zA-Z0-9]+) = ref(\W)"), "$1* $2 =$3", 0),
292 // *root = ref left;
293 // root = left;
294 (new Regex(@"\*([a-zA-Z0-9]+) = ref ([a-zA-Z0-9]+)(\W)"), "$1 = $2$3", 0),
295 // (ref left)
296 // (left)
297 (new Regex(@"\ (ref ([a-zA-Z0-9]+)(\\|\\(|,))"), "($1$2", 0),
298 // ref TElement
299 // TElement*
300 (new Regex(@"(\\|\\())ref ([a-zA-Z0-9]+) "), "$1$2* ", 0),
301 // ref sizeBalancedTree.Root
302 // &sizeBalancedTree->Root
303 (new Regex(@"ref ([a-zA-Z0-9]+)\\.([a-zA-Z0-9\\*]+)"), "&$1->$2", 0),
304 // ref GetElement(node).Right
305 // &GetElement(node)->Right
306 (new Regex(@"ref ([a-zA-Z0-9]+)\\((([a-zA-Z0-9\\*]+)\\)\\.([a-zA-Z0-9]+)"),
→ "&$1($2)->$3", 0),
307 // GetElement(node).Right
308 // GetElement(node)->Right
309 (new Regex(@"([a-zA-Z0-9]+)\\((([a-zA-Z0-9\\*]+)\\)\\.([a-zA-Z0-9]+)"), "$1($2)->$3", 0),
310 // [Fact]npublic: static void SizeBalancedTreeMultipleAttachAndDetachTest()
311 // public: TEST_METHOD(SizeBalancedTreeMultipleAttachAndDetachTest)
312 (new Regex(@"\\[Fact\\] \\s\\n+(public:)?(static)?void ([a-zA-Z0-9]+)\\(\\)"), "public:
→ TEST_METHOD($3)", 0),
313 // class TreesTests
314 // TEST_CLASS(TreesTests)
315 (new Regex(@"class ([a-zA-Z0-9]+Tests)"), "TEST_CLASS($1)", 0),
316 // Assert.Equal
317 // Assert::AreEqual
318 (new Regex(@"(?<type>Assert)\\. (?<method>(Not)?Equal)"), "${type}::Are${method}", 0),
319 // Assert.Throws
320 // Assert::ExpectException
321 (new Regex(@"(Assert)\\.Throws"), "$1::ExpectException", 0),
322 // Assert.True
323 // Assert::IsTrue
324 (new Regex(@"(Assert)\\. (True|False)"), "$1::Is$2", 0),
325 // $"Argument {argumentName} is null."
326 // std::string("Argument
→ ").append(Platform::Converters::To<std::string>(argumentName)).append(" is
→ null.")
327 (new Regex(@"\\$"" (?<left>(\\""| [^""\\r\\n])* ){(?<expression>[_a-zA-Z0-9]+)} (?<right>(\\_
→ ""| [^""\\r\\n])* )"""),
→ "std::string(\\$""${left}\\").append(Platform::Converters::To<std::string>(${expres_
→ sion})).append(\\$""${right}\\")",
→ 10),
328 // $"
329 // "
330 (new Regex(@"\\$"""), "\\\"", 0),
331 // std::string(std::string("[").append(Platform::Converters::To<std::string>(Minimum)
→ )).append(",
→ ").append(Platform::Converters::To<std::string>(Maximum)).append("]")
332 // std::string("[").append(Platform::Converters::To<std::string>(Minimum)).append(",
→ ").append(Platform::Converters::To<std::string>(Maximum)).append("]")
333 (new Regex(@"std::string\\((?<begin>std::string\\(""(\\""| [^""\\r\\n])*""\\)\\)\\.append\\((Platf_
→ orm::Converters::To<std::string>\\((\\^\\n)+\\| [^\\n]+\\)\\)\\)\\)\\.append\\)",
→ "${begin}.append", 10),
334 // Console.WriteLine("...")
335 // printf("...\\n")
336 (new Regex(@"Console\\.WriteLine\\(""([^""\\r\\n]+)""\\)"), "printf(\\$1\\n\\n)", 0),
337 // TElement Root;
338 // TElement Root = 0;
339 (new Regex(@"(?<before>\\r?\\n[\\t ]+)(?<access>(private|protected|public)(:
→ )?)?(?<type>[a-zA-Z0-9_]+(?<!return)) (?<name>[_a-zA-Z0-9]+);"),
→ "${before}${access}${type} ${name} = 0;", 0),

```



```

340 // TreeElement _elements[N];
341 // TreeElement _elements[N] = { {0} };
342 (new Regex(@"(\\r?\\n[\\t ]+)(private|protected|public)?(: )?([a-zA-Z0-9]+)
    ↳ ([_a-zA-Z0-9]+)\\[([_a-zA-Z0-9]+)\\];\"", "$1$2$3$4 $5[$6] = { {0} };\"", 0),
343 // auto path = new TElement[MaxPath];
344 // TElement path[MaxPath] = { {0} };
345 (new Regex(@"(\\r?\\n[\\t ]+)[a-zA-Z0-9]+ ([a-zA-Z0-9]+) = new
    ↳ ([a-zA-Z0-9]+)\\[([_a-zA-Z0-9]+)\\];\"", "$1$3 $2[$4] = { {0} };\"", 0),
346 // bool Equals(Range<T> other) { ... }
347 // bool operator ==(const Key &other) const { ... }
348 (new Regex(@"(?<before>\\r?\\n[\\t ]+bool )Equals\\((?<type>[\\n]+)
    ↳ (?<variable>[a-zA-Z0-9]+)\\)(?<after>(\\s|\\n)*\\)", "${before}operator ==(const
    ↳ ${type} &${variable}) const${after}", 0),
349 // Insert scope borders.
350 // class Range { ... public: override std::string ToString() { return ...; }
351 // class Range { /*~Range<T>~*/ ... public: override std::string ToString() { return
    ↳ ...; }
352 (new Regex(@"(?<classDeclarationBegin>\\r?\\n(?<indent>[\\t ]*)template <typename
    ↳ (?<typeParameter>[~<>\\n]+> (struct|class)
    ↳ (?<type>[a-zA-Z0-9]+<\\k<typeParameter>>)(\\s*:\\s*[~{\\n]+)?[\\t ]*(\\r?\\n)?[\\t
    ↳ ]*(?<middle>((?!class|struct)\\.\\n)+?)?(?<toStringDeclaration>(?!<access>(private|
    ↳ |protected|public): )override std::string ToString\\(\\))\"",
    ↳ "${classDeclarationBegin}/*~${type}~*/${middle}${toStringDeclaration}", 0),
353 // Inside the scope of ~!Range!~ replace:
354 // public: override std::string ToString() { return ...; }
355 // public: operator std::string() const { return ...; }\\n\\npublic: friend
    ↳ std::ostream & operator <<(std::ostream &out, const A &obj) { return out <<
    ↳ (std::string)obj; }
356 (new Regex(@"(?<scope>/\\s*(?<type>[a-zA-Z0-9<>:]+)~\\s*/)(?<separator>\\.\\n)(?<before>
    ↳ ((?!/\\s*~\\k<type>~\\s*/)(\\.\\n)*)?(?<toStringDeclaration>\\r?\\n(?<indent>[
    ↳ \\t]*)?(?<access>(private|protected|public): )override std::string ToString\\(\\)
    ↳ (?<toStringMethodBody>[~}\\n]+))\"", "${scope}${separator}${before}" +
    ↳ Environment.NewLine + "${indent}${access}operator std::string() const
    ↳ ${toStringMethodBody}" + Environment.NewLine + Environment.NewLine +
    ↳ "${indent}${access}friend std::ostream & operator <<(std::ostream &out, const
    ↳ ${type} &obj) { return out << (std::string)obj; }\"", 0),
357 // Remove scope borders.
358 // /*~Range~*/
359 //
360 (new Regex(@"/\\s*~[_a-zA-Z0-9<>:]+~\\s*/", "", 0),
361 // private: inline static ConcurrentBag<std::exception> _exceptionsBag;
362 // private: inline static std::mutex _exceptionsBag_mutex; \\n\\n private: inline
    ↳ static std::vector<std::exception> _exceptionsBag;
363 (new Regex(@"(?<begin>\\r?\\n(?<indent>[\\t ]+))?(?<access>(private|protected|public):
    ↳ )?inline static ConcurrentBag<(?!<argumentType>[~;\\r\\n]+)>
    ↳ (?<name>[_a-zA-Z0-9]+);\"", "${begin}private: inline static std::mutex
    ↳ ${name}_mutex;" + Environment.NewLine + Environment.NewLine +
    ↳ "${indent}${access}inline static std::vector<${argumentType}> ${name};\"", 0),
364 // public: static IReadonlyCollection<std::exception> GetCollectedExceptions() {
    ↳ return _exceptionsBag; }
365 // public: static std::vector<std::exception> GetCollectedExceptions() { return
    ↳ std::vector<std::exception>(_exceptionsBag); }
366 (new Regex(@"(?<access>(private|protected|public): )?static
    ↳ IReadonlyCollection<(?!<argumentType>[~;\\r\\n]+)> (?<methodName>[_a-zA-Z0-9]+)\\(\\)
    ↳ { return (?<fieldName>[_a-zA-Z0-9]+); }\"", "${access}static
    ↳ std::vector<${argumentType}> ${methodName}() { return
    ↳ std::vector<${argumentType}>({${fieldName}}); }\"", 0),
367 // public: static event EventHandler<std::exception> ExceptionIgnored =
    ↳ OnExceptionIgnored; ... };
368 // ... public: static inline Platform::Delegates::MulticastDelegate<void(void*,
    ↳ const std::exception&> ExceptionIgnored = OnExceptionIgnored; };
369 (new Regex(@"(?<begin>\\r?\\n(\\r?\\n)?(?<halfIndent>[
    ↳ \\t]+)\\k<halfIndent>)(?<access>(private|protected|public): )?static event
    ↳ EventHandler<(?!<argumentType>[~;\\r\\n]+)> (?<name>[_a-zA-Z0-9]+) = (?<defaultDele
    ↳ gate>[_a-zA-Z0-9]+);(?<middle>(\\.\\n)+?)?(?<end>\\r?\\n\\k<halfIndent>});\"",
    ↳ "${middle}" + Environment.NewLine + Environment.NewLine +
    ↳ "${halfIndent}${halfIndent}${access}static inline
    ↳ Platform::Delegates::MulticastDelegate<void(void*, const ${argumentType}&>
    ↳ ${name} = ${defaultDelegate};${end}", 0),
370 // public: event Disposal OnDispose;
371 // public: Platform::Delegates::MulticastDelegate<Disposal> OnDispose;
372 (new Regex(@"(?<begin>(?!<access>(private|protected|public): )?(static )?)event
    ↳ (?<type>[a-zA-Z][:_a-zA-Z0-9]+) (?<name>[a-zA-Z][_a-zA-Z0-9]+);\"",
    ↳ "${begin}Platform::Delegates::MulticastDelegate<${type}> ${name};\"", 0),
373 // Insert scope borders.

```



```

374 // class IgnoredExceptions { ... private: inline static std::vector<std::exception>
    ↳ _exceptionsBag;
375 // class IgnoredExceptions {/*~_exceptionsBag~*/ ... private: inline static
    ↳ std::vector<std::exception> _exceptionsBag;
376 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n}]+\r\n[\t
    ↳ ]*)(?<middle>((?!class)\.|\n)+?)(?<vectorFieldDeclaration>(?(access)(private|pro
    ↳ tected|public): )inline static std::vector<(?(argumentType)[^;\r\n]+)>
    ↳ (?(fieldName>[_a-zA-Z0-9]+);)"),
    ↳ "$${classDeclarationBegin}/*~${fieldName}~*/${middle}${vectorFieldDeclaration}",
    ↳ 0),
377 // Inside the scope of ~!_exceptionsBag!~ replace:
378 // _exceptionsBag.Add(exception);
379 // _exceptionsBag.push_back(exception);
380 (new Regex(@"(?<scope>/\s*(?<fieldName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ e>((?!/\s*\k<fieldName>~\s*/)(.\|\n))*?)\k<fieldName>\.Add"),
    ↳ "$${scope}${separator}${before}${fieldName}.push_back", 10),
381 // Remove scope borders.
382 // /*~_exceptionsBag~*/
383 //
384 (new Regex(@"/\s*~[_a-zA-Z0-9]+~\s*/"), "", 0),
385 // Insert scope borders.
386 // class IgnoredExceptions { ... private: static std::mutex _exceptionsBag_mutex;
387 // class IgnoredExceptions {/*~_exceptionsBag~*/ ... private: static std::mutex
    ↳ _exceptionsBag_mutex;
388 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n}]+\r\n[\t
    ↳ ]*)(?<middle>((?!class)\.|\n)+?)(?<mutexDeclaration>private: inline static
    ↳ std::mutex (?(fieldName>[_a-zA-Z0-9]+) _mutex;)",
    ↳ "$${classDeclarationBegin}/*~${fieldName}~*/${middle}${mutexDeclaration}", 0),
389 // Inside the scope of ~!_exceptionsBag!~ replace:
390 // return std::vector<std::exception>(_exceptionsBag);
391 // std::lock_guard<std::mutex> guard(_exceptionsBag_mutex); return
    ↳ std::vector<std::exception>(_exceptionsBag);
392 (new Regex(@"(?<scope>/\s*(?<fieldName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ e>((?!/\s*\k<fieldName>~\s*/)(.\|\n))*?){(?<after>((?!lock_guard)[^{};\r\n])*\k<f
    ↳ ieldName>[~;}\r\n]*;)", "$${scope}${separator}${before}{
    ↳ std::lock_guard<std::mutex> guard($${fieldName}_mutex);$${after}", 10),
393 // Inside the scope of ~!_exceptionsBag!~ replace:
394 // _exceptionsBag.Add(exception);
395 // std::lock_guard<std::mutex> guard(_exceptionsBag_mutex); \r\n
    ↳ _exceptionsBag.Add(exception);
396 (new Regex(@"(?<scope>/\s*(?<fieldName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ e>((?!/\s*\k<fieldName>~\s*/)(.\|\n))*?){(?<after>((?!lock_guard)([~{};]\|\n))*?\r
    ↳ ?\n(?<indent>[\t ]*)\k<fieldName>[~;}\r\n]*;)",
    ↳ "$${scope}${separator}${before}{\" + Environment.NewLine +
    ↳ \"$${indent}std::lock_guard<std::mutex> guard($${fieldName}_mutex);$${after}", 10),
397 // Remove scope borders.
398 // /*~_exceptionsBag~*/
399 //
400 (new Regex(@"/\s*~[_a-zA-Z0-9]+~\s*/"), "", 0),
401 // Insert scope borders.
402 // class IgnoredExceptions { ... public: static inline
    ↳ Platform::Delegates::MulticastDelegate<void(void*, const std::exception&)>
    ↳ ExceptionIgnored = OnExceptionIgnored;
403 // class IgnoredExceptions {/*~ExceptionIgnored~*/ ... public: static inline
    ↳ Platform::Delegates::MulticastDelegate<void(void*, const std::exception&)>
    ↳ ExceptionIgnored = OnExceptionIgnored;
404 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n}]+\r\n[\t
    ↳ ]*)(?<middle>((?!class)\.|\n)+?)(?<eventDeclaration>(?(access)(private|protected|
    ↳ public): )static inline
    ↳ Platform::Delegates::MulticastDelegate<(?(argumentType)[^;\r\n]+)>
    ↳ (?(name>[_a-zA-Z0-9]+) = (?(defaultDelegate>[_a-zA-Z0-9]+);)"),
    ↳ "$${classDeclarationBegin}/*~${name}~*/${middle}${eventDeclaration}", 0),
405 // Inside the scope of ~!ExceptionIgnored!~ replace:
406 // ExceptionIgnored.Invoke(NULL, exception);
407 // ExceptionIgnored(NULL, exception);
408 (new Regex(@"(?<scope>/\s*(?<eventName>[_a-zA-Z0-9]+)~\s*/)(?<separator>.\|\n)(?<before>
    ↳ >((?!/\s*\k<eventName>~\s*/)(.\|\n))*?)\k<eventName>\.Invoke"),
    ↳ "$${scope}${separator}${before}${eventName}", 10),
409 // Remove scope borders.
410 // /*~ExceptionIgnored~*/
411 //
412 (new Regex(@"/\s*~[_a-zA-Z0-9]+~\s*/"), "", 0),
413 // Insert scope borders.
414 // auto added = new StringBuilder();
415 // /*~sb~*/std::string added;

```

```

416 (new Regex(@"(auto|(System\.Text\.)?StringBuilder) (?<variable>[a-zA-Z0-9]+) = new
    ↳ (System\.Text\.)?StringBuilder\(\);"), "/~*${variable}~/std::string
    ↳ ${variable};", 0),
417 // static void Indent(StringBuilder sb, int level)
418 // static void Indent(/*~sb~/StringBuilder sb, int level)
419 (new Regex(@"(?<start>, |\() (System\.Text\.)?StringBuilder
    ↳ (?<variable>[a-zA-Z0-9]+) (?<end>, |\))"), "${start}/*~*${variable}~/std::string&
    ↳ ${variable}${end}", 0),
420 // Inside the scope of ~!added!~ replace:
421 // sb.ToString()
422 // sb
423 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~* /) (?<separator>.\| \n) (?<before>
    ↳ ((?!/\~* \k<variable> ~\~* /) (. \| \n) *)? \k<variable> \. ToString\(\)"),
    ↳ "${scope}${separator}${before}${variable}", 10),
424 // sb.AppendLine(argument)
425 // sb.append(Platform::Converters::To<std::string>(argument)).append(1, '\n')
426 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~* /) (?<separator>.\| \n) (?<before>
    ↳ ((?!/\~* \k<variable> ~\~* /) (. \| \n) *)? \k<variable> \. AppendLine\((?<argument>[^\], \
    ↳ r\n)+\) \)"),
    ↳ "${scope}${separator}${before}${variable}.append(Platform::Converters::To<std::s
    ↳ tring>(${argument})).append(1, '\n')",
    ↳ 10),
427 // sb.Append('\t', level);
428 // sb.append(level, '\t');
429 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~* /) (?<separator>.\| \n) (?<before>
    ↳ ((?!/\~* \k<variable> ~\~* /) (. \| \n) *)? \k<variable> \. Append\(' (?<character>[^\r\n]
    ↳ +)', (?<count>[^\], \r\n)+\) \)"),
    ↳ "${scope}${separator}${before}${variable}.append(${count}, '${character}')" , 10),
430 // sb.Append(argument)
431 // sb.append(Platform::Converters::To<std::string>(argument))
432 (new Regex(@"(?<scope>/\~* (?<variable>[a-zA-Z0-9]+) ~\~* /) (?<separator>.\| \n) (?<before>
    ↳ ((?!/\~* \k<variable> ~\~* /) (. \| \n) *)? \k<variable> \. Append\((?<argument>[^\], \r\n]
    ↳ +\) \)"),
    ↳ "${scope}${separator}${before}${variable}.append(Platform::Converters::To<std::s
    ↳ tring>(${argument}))",
    ↳ 10),
433 // Remove scope borders.
434 // /*~sb~/
435 //
436 (new Regex(@"/*~*[a-zA-Z0-9]+~\~*/"), "", 0),
437 // Insert scope borders.
438 // auto added = new HashSet<TElement>();
439 // ~!added!~std::unordered_set<TElement> added;
440 (new Regex(@"auto (?<variable>[a-zA-Z0-9]+) = new
    ↳ HashSet<(?<element>[a-zA-Z0-9]+)>\(\);"),
    ↳ "~!${variable}!~std::unordered_set<${element}> ${variable};", 0),
441 // Inside the scope of ~!added!~ replace:
442 // added.Add(node)
443 // added.insert(node)
444 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~) (?<separator>.\| \n) (?<before>((?<
    ↳ !~!\k<variable>!~) (. \| \n) *)? \k<variable> \. Add\((?<argument>[a-zA-Z0-9]+)\) \)"),
    ↳ "${scope}${separator}${before}${variable}.insert(${argument})", 10),
445 // Inside the scope of ~!added!~ replace:
446 // added.Remove(node)
447 // added.erase(node)
448 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~) (?<separator>.\| \n) (?<before>((?<
    ↳ !~!\k<variable>!~) (. \| \n) *)? \k<variable> \. Remove\((?<argument>[a-zA-Z0-9]+)\) \)"),
    ↳ "${scope}${separator}${before}${variable}.erase(${argument})", 10),
449 // if (added.insert(node)) {
450 // if (!added.contains(node)) { added.insert(node);
451 (new Regex(@"if \((?<variable>[a-zA-Z0-9]+)\.insert\((?<argument>[a-zA-Z0-9]+)\)\) \) (?
    ↳ <separator>[\t ]*\r\n)+ (?<indent>[\t ]*){", "if
    ↳ (!${variable}.contains(${argument})) ${separator}${indent}{ " +
    ↳ Environment.NewLine + "${indent} ${variable}.insert(${argument});", 0),
452 // Remove scope borders.
453 // ~!added!~
454 //
455 (new Regex(@"~![a-zA-Z0-9]+!~"), "", 5),
456 // Insert scope borders.
457 // auto random = new System::Random(0);
458 // std::srand(0);
459 (new Regex(@"[a-zA-Z0-9\.] + ([a-zA-Z0-9]+) = new
    ↳ (System::)?Random\((([a-zA-Z0-9]+)\) \);"), "~!$1!~std::srand($3);", 0),
460 // Inside the scope of ~!random!~ replace:
461 // random.Next(1, N)
462 // (std::rand() % N) + 1

```

```

463 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~)(?<separator>.\|\\n)(?<before>((?<
    ↳ !~!\k<variable>!~)(.\|\\n))*?)\k<variable>\.Next\\((?<from>[a-zA-Z0-9]+),
    ↳ (?<to>[a-zA-Z0-9]+)\\")", "${scope}${separator}${before}(std::rand() % ${to}) +
    ↳ ${from}", 10),
464 // Remove scope borders.
465 // ~!random!~
466 //
467 (new Regex(@"~![a-zA-Z0-9]+!~"), "", 5),
468 // Insert method body scope starts.
469 // void PrintNodes(TElement node, StringBuilder sb, int level) {
470 // void PrintNodes(TElement node, StringBuilder sb, int level) { /*method-start*/
471 (new Regex(@"(?<start>\r?\n[\\t ]+)(?<prefix>((private|protected|public): )?(virtual
    ↳ )?[a-zA-Z0-9:_]+
    ↳ )?(?<method>[a-zA-Z][a-zA-Z0-9]*\\(((?<arguments>[^\n])*)\\)(?<override>(
    ↳ override)?)(?<separator>[\\t\\r\\n]*)\\((?<end>[~])\\")", "${start}${prefix}${method}
    ↳ (${arguments})${override}${separator}{ /*method-start*/${end}]",
    ↳ 0),
472 // Insert method body scope ends.
473 // { /*method-start*/...}
474 // { /*method-start*/... /*method-end*/}
475 (new Regex(@"{ /\*method-start\*/ (?<body>((?<bracket>\\{) | (?<-bracket>\\}) | [^\{\\}]*)+ )
    ↳ \\}"), "{ /*method-start*/${body} /*method-end*/}",
    ↳ 0),
476 // Inside method bodies replace:
477 // GetFirst(
478 // this->GetFirst(
479 (new
    ↳ Regex(@"(?<scope> /\*method-start\*/)(?<before>((?! /\*method-end\*/)(.\|\\n))*?) (?
    ↳ <separator>[\\W] (?!(.:|\\.|->|throw\\s+))) (?<method>(?!sizeof)[a-zA-Z0-9]+)\\(((?!\\
    ↳ \\{) (?<after>(.\|\\n))*?) (?<scopeEnd> /\*method-end\*/)",
    ↳ "${scope}${before}${separator}this->${method} (${after}${scopeEnd}", 100),
480 // Remove scope borders.
481 // /*method-start*/
482 //
483 (new Regex(@" /\*method-(start|end)\*/"), "", 0),
484 // Insert scope borders.
485 // const std::exception& ex
486 // const std::exception& ex/*~ex~*/
487 (new Regex(@"(?<before>\\(| )(?<variableDefinition>(const )?(std::)?exception&?
    ↳ (?<variable>[_a-zA-Z0-9]+)) (?<after>\\W)"),
    ↳ "${before}${variableDefinition}/*~${variable}~*/${after}", 0),
488 // Inside the scope of ~!ex!~ replace:
489 // ex.Message
490 // ex.what()
491 (new Regex(@"(?<scope> /\*~(?<variable>[_a-zA-Z0-9]+)~\*/)(?<separator>.\|\\n)(?<before>
    ↳ >((?! /\*~\k<variable>~\*/)(.\|\\n))*?) (Platform::Converters::To<std::string>\\(\k<
    ↳ variable>\\.Message\\) | \k<variable>\\.Message)"),
    ↳ "${scope}${separator}${before}${variable}.what()", 10),
492 // Remove scope borders.
493 // /*~ex~*/
494 //
495 (new Regex(@" /\*~[_a-zA-Z0-9]+~\*/"), "", 0),
496 // throw ObjectDisposedException(objectName, message);
497 // throw std::runtime_error(std::string("Attempt to access disposed object
    ↳ ").append(objectName).append(": ").append(message).append("."));
498 (new Regex(@"throw ObjectDisposedException\\((?<objectName>[a-zA-Z_][a-zA-Z0-9_]*),
    ↳ (?<message>[a-zA-Z0-9_]*[Mm]essage[a-zA-Z0-9_]*\\(\\(\\)?| [a-zA-Z_][a-zA-Z0-9_]*\\)\\)
    ↳ ;");", "throw std::runtime_error(std::string("Attempt to access disposed object
    ↳ [\\").append("${objectName}").append("\\"): \").append("${message}").append("\\.\\");",
    ↳ 0),
499 // throw ArgumentNullException(argumentName, message);
500 // throw std::invalid_argument(std::string("Argument
    ↳ ").append(argumentName).append(" is null: ").append(message).append("."));
501 (new Regex(@"throw
    ↳ ArgumentNullException\\((?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]*),
    ↳ (?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*\\(\\(\\)?\\)\\);", "throw
    ↳ std::invalid_argument(std::string("Argument \").append("${argument}").append("\\
    ↳ is null: \").append("${message}").append("\\.\\");", 0),
502 // throw ArgumentException(message, argumentName);
503 // throw std::invalid_argument(std::string("Invalid ").append(argumentName).append("
    ↳ argument: ").append(message).append("."));
504 (new Regex(@"throw
    ↳ ArgumentException\\((?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*\\(\\(\\)?\\),
    ↳ (?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]*\\)\\);", "throw
    ↳ std::invalid_argument(std::string("Invalid \").append("${argument}").append("\\
    ↳ argument: \").append("${message}").append("\\.\\");", 0),

```

```

505 // throw ArgumentOutOfRangeException(argumentName, argumentValue, messageBuilder());
506 // throw std::invalid_argument(std::string("Value
    ↳ [").append(Platform::Converters::To<std::string>(argumentValue)).append("] of
    ↳ argument [").append(argumentName).append("] is out of range:
    ↳ ").append(messageBuilder()).append("."););
507 (new Regex(@"throw ArgumentOutOfRangeException\(((?<argument>[a-zA-Z]*[Aa]rgument[a-z]
    ↳ A-Z)*([Nn]ame[a-zA-Z]*)?)",
    ↳ (?<argumentValue>[a-zA-Z]*[Aa]rgument[a-zA-Z]*([Vv]alue[a-zA-Z]*)?)",
    ↳ (?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*(\(\(\)?\)\);)", "throw
    ↳ std::invalid_argument(std::string("Value
    ↳ [").append(Platform::Converters::To<std::string>(${argumentValue})).append("\]
    ↳ of argument [").append(${argument}).append("\] is out of range:
    ↳ \").append(${message}).append("\.\");", 0),
508 // throw NotSupportedException();
509 // throw std::logic_error("Not supported exception.");
510 (new Regex(@"throw NotSupportedException\(\);)", "throw std::logic_error(\"Not
    ↳ supported exception.\");", 0),
511 // throw NotImplementedException();
512 // throw std::logic_error("Not implemented exception.");
513 (new Regex(@"throw NotImplementedException\(\);)", "throw std::logic_error(\"Not
    ↳ implemented exception.\");", 0),
514 // Insert scope borders.
515 // const std::string& message
516 // const std::string& message/*~message~/
517 (new Regex(@"(?<before>\(|\s)(?<variableDefinition>(const\s)?((std::)?string&?|char\*)
    ↳ (?<variable>[_a-zA-Z0-9]+)))(?<after>\W)",
    ↳ "${before}${variableDefinition}/*~${variable}~/${after}", 0),
518 // Inside the scope of /*~message~/ replace:
519 // Platform::Converters::To<std::string>(message)
520 // message
521 (new Regex(@"(?<scope>\/\s*(?<variable>[_a-zA-Z0-9]+)~\s*)(?<separator>.\|\n)(?<before>
    ↳ >((?!\/\s*\k<variable>~\s*)(.\|\n))*?)Platform::Converters::To<std::string>\(\k<v
    ↳ ariable>\)", "${scope}${separator}${before}${variable}",
    ↳ 10),
522 // Remove scope borders.
523 // /*~ex~/
524 //
525 (new Regex(@"\/\s*[_a-zA-Z0-9]+~\s\/", "", 0),
526 // Insert scope borders.
527 // std::tuple<T, T> tuple
528 // std::tuple<T, T> tuple/*~tuple~/
529 (new Regex(@"(?<before>\(|\s)(?<variableDefinition>(const\s)?(std::)?tuple<[^\n]+&?
    ↳ (?<variable>[_a-zA-Z0-9]+)))(?<after>\W)",
    ↳ "${before}${variableDefinition}/*~${variable}~/${after}", 0),
530 // Inside the scope of ~!ex!~ replace:
531 // tuple.Item1
532 // std::get<1-1>(tuple)
533 (new Regex(@"(?<scope>\/\s*(?<variable>[_a-zA-Z0-9]+)~\s*)(?<separator>.\|\n)(?<before>
    ↳ >((?!\/\s*\k<variable>~\s*)(.\|\n))*?)\k<variable>\.Item(?<itemNumber>\d+)(?<afte
    ↳ r>\W)",
    ↳ "${scope}${separator}${before}std::get<${itemNumber}-1>(${variable})${after}",
    ↳ 10),
534 // Remove scope borders.
535 // /*~ex~/
536 //
537 (new Regex(@"\/\s*[_a-zA-Z0-9]+~\s\/", "", 0),
538 // Insert scope borders.
539 // class Range<T> {
540 // class Range<T> {/~type~Range<T>~/
541 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)(template\s*<[^\<>\n]*>
    ↳ )?(struct|class)
    ↳ (?<fullType>(?(typeName[a-zA-Z0-9]+)([^\n:]*))(\s*:\s*[^\n]+)?[\t
    ↳ ]*(\r?\n)?[\t ]*{)"),
    ↳ "${classDeclarationBegin}/*~type~${typeName}~${fullType}~/", 0),
542 // Inside the scope of /*~type~Range<T>~/ insert inner scope and replace:
543 // public: static implicit operator std::tuple<T, T>(Range<T> range)
544 // public: operator std::tuple<T, T>() const {/~variable~Range<T>~/
545 (new Regex(@"(?<scope>\/\s*~type~(?<typeName>[^\n\*]+)~(?<fullType>[^\n\*]+)~\s\/)(?<
    ↳ separator>.\|\n)(?<before>((?!\/\s*~type~\k<typeName>~\k<fullType>~\s\/)(.\|\n))*?)
    ↳ (?<access>(private|protected|public): )static implicit operator
    ↳ (?<targetType>[^\(\n]+)\(((?<argumentDeclaration>\k<fullType>
    ↳ (?<variable>[a-zA-Z0-9]+)))(?<after>\s*\n?\s*{)"),
    ↳ "${scope}${separator}${before}${access}operator ${targetType}()
    ↳ const${after}/*~variable~${variable}~/", 10),
    ↳ // Inside the scope of /*~type~Range<T>~/ replace:

```

```

547 // public: static implicit operator Range<T>(std::tuple<T, T> tuple) { return new
    ↳ Range<T>(std::get<1-1>(tuple), std::get<2-1>(tuple)); }
548 // public: Range(std::tuple<T, T> tuple) : Range(std::get<1-1>(tuple),
    ↳ std::get<2-1>(tuple)) { }
549 (new Regex(@"(?<scope>/\~*type~(?<typeName>[~\n\*]+)~(?<fullType>[~\n\*]+)~\*/)(?<
    ↳ separator>.\n)(?<before>((?!/\~*type~\k<typeName>~\k<fullType>~\*/)(.\n))*?) (
    ↳ ?<access>(private|protected|public): )static implicit operator
    ↳ (\k<fullType>|\k<typeName>)\((?<arguments>[~\n\*]+)\)(\s|\n)*{(\s|\n)*return
    ↳ (new )?(\k<fullType>|\k<typeName>)\((?<passedArguments>[~\n\*]+)\);(\s|\n)*"}),
    ↳ "${scope}${separator}${before}${access}${typeName}(${arguments}) :
    ↳ ${typeName}(${passedArguments}) { }", 10),
550 // Inside the scope of /*~variable~range~/ replace:
551 // range.Minimum
552 // this->Minimum
553 (new Regex(@"(?<scope>{/\~*variable~(?<variable>[~\n\*]+)~\*/)(?<separator>.\n)(?<be
    ↳ fore>(?(beforeExpression>(?(bracket>{)|(?(<-bracket>})|[\~{}]\n)*?)\k<variable>\.
    ↳ (?(field>[_a-zA-Z0-9]+)(?<after>(,|;|}|
    ↳ |\\))?(?<afterExpression>(?(bracket>{)|(?(<-bracket>})|[\~{}]\n)*?)") ,
    ↳ "${scope}${separator}${before}this->${field}${after}", 10),
554 // Remove scope borders.
555 // /*~ex~/
556 //
557 (new Regex(@"/*~[~\n\*]+[~\n\*]+~\*/"), "", 0),
558 // Insert scope borders.
559 // namespace Platform::Ranges { ... }
560 // namespace Platform::Ranges {/\~start~namespace~Platform::Ranges~/ ...
    ↳ /\~end~namespace~Platform::Ranges~/}
561 (new Regex(@"(?<namespaceDeclarationBegin>\r?\n(?<indent>[\t ]*)namespace
    ↳ (?<namespaceName>(?(namePart>[a-zA-Z][a-zA-Z0-9]+)(?(nextNamePart>:[a-zA-Z][a-z
    ↳ A-Z0-9]+))(\s|\n)*)(?(middle>(\.|\n)*)(?(end>(?(<=\r?\n)\k<indent>}{?!;))"),
    ↳ "${namespaceDeclarationBegin}/\~start~namespace~${namespaceName}~/${middle}/~e
    ↳ nd~namespace~${namespaceName}~/${end}",
    ↳ 0),
562 // Insert scope borders.
563 // class Range<T> { ... };
564 // class Range<T> {/\~start~type~Range<T>~T~/ ... /\~end~type~Range<T>~T~/};
565 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)template <typename
    ↳ (?<typeParameter>[~\n\*]+> (struct|class)
    ↳ (?<type>[a-zA-Z0-9]+<\k<typeParameter>>)(\s*:\s*[~\n\*]+)?[\t ]*(\r?\n)?[\t
    ↳ ]*(?(middle>(\.|\n)*)(?(endIndent>(?(<=\r?\n)\k<indent>){(?<end>};))"),
    ↳ "${classDeclarationBegin}/\~start~type~${type}~${typeParameter}~/${middle}${end}
    ↳ Indent}/\~end~type~${type}~${typeParameter}~/${end}",
    ↳ 0),
566 // Inside the scope replace:
567 // /\~start~namespace~Platform::Ranges~/ ... /\~start~type~Range<T>~T~/ ...
    ↳ public: override std::int32_t GetHashCode() { return {Minimum,
    ↳ Maximum}.GetHashCode(); } ... /\~end~type~Range<T>~T~/ ...
    ↳ /\~end~namespace~Platform::Ranges~/
568 // /\~start~namespace~Platform::Ranges~/ ... /\~start~type~Range<T>~T~/ ...
    ↳ /\~end~type~Range<T>~T~/ ... /\~end~namespace~Platform::Ranges~/ namespace std
    ↳ { template <typename T> struct hash<Platform::Ranges::Range<T>> { std::size_t
    ↳ operator()(const Platform::Ranges::Range<T> &obj) const { return {Minimum,
    ↳ Maximum}.GetHashCode(); } }; }
569 (new Regex(@"(?<namespaceScopeStart>/\~start~namespace~(?<namespace>[~\n\*]+)~\*/)
    ↳ (?<betweenStartScopes>(\.|\n)+)(?<typeScopeStart>/\~start~type~(?<type>[~\n\*]+)
    ↳ )~(?<typeParameter>[~\n\*]+)~\*/)(?<before>(\.|\n)+)?(?<hashMethodDeclaration>\r
    ↳ ?\n[\t ]*(?<access>(private|protected|public): )override std::int32_t
    ↳ GetHashCode\(\)(\s|\n)*{(\s*(?(methodBody>[~\n\*]+[~\n\*])\s*)\s*)?(?<after>(\.|\n
    ↳ )+)?)(?<typeScopeEnd>/\~end~type~\k<type>~\k<typeParameter>~\*/)(?<betweenEndSco
    ↳ pes>(\.|\n)+)(?<namespaceScopeEnd>/\~end~namespace~\k<namespace>~\*/)}\r?\n"),
    ↳ "${namespaceScopeStart}${betweenStartScopes}${typeScopeStart}${before}${after}${
    ↳ typeScopeEnd}${betweenEndScopes}${namespaceScopeEnd}} + Environment.NewLine +
    ↳ Environment.NewLine + "namespace std" + Environment.NewLine + "{" +
    ↳ Environment.NewLine + "    template <typename ${typeParameter}>" +
    ↳ Environment.NewLine + "        struct hash<${namespace}::${type}>" +
    ↳ Environment.NewLine + "            {" + Environment.NewLine + "                std::size_t
    ↳ operator()(const ${namespace}::${type} &obj) const" + Environment.NewLine + "
    ↳ {" + Environment.NewLine + "
    ↳ /\~start~method~/${methodBody}/\~end~method~/ + Environment.NewLine + "
    ↳ }" + Environment.NewLine + "    };" + Environment.NewLine + "}" +
    ↳ Environment.NewLine, 10),
570 // Inside scope of /\~start~method~/ replace:
571 // /\~start~method~/ ... Minimum ... /\~end~method~/
572 // /\~start~method~/ ... obj.Minimum ... /\~end~method~/

```

```

1  Regex(@"(?<methodScopeStart>/\*~start~method~*/)(?<before>.+({|,
2  ))(?<name>[a-zA-Z][a-zA-Z0-9]+)(?<after>[^\n\.\(a-zA-Z0-9)((?!/*~end~method~*/|
3  ) [^\n])+(?<methodScopeEnd>/\*~end~method~*/)"),
4  "${methodScopeStart}${before}obj.${name}${after}${methodScopeEnd}", 10),
5  // Remove scope borders.
6  // /*~start~type~Range<T>~*/
7  //
8  (new Regex(@"\/\*~[^\n]+([^\n]+)*~\/", "", 0),
9  // class Disposable<T> : public Disposable
10 // class Disposable<T> : public Disposable<>
11 (new Regex(@"(?<before>(struct|class) (?<type>[a-zA-Z][a-zA-Z0-9]*)<[^\<>\n]+> :
12   (?<access>(private|protected|public) )?\k<type>)(?<after>\b(?:\<|>))"),
13   "${before}<>${after}", 0),
14 // Insert scope borders.
15 // class Disposable<T> : public Disposable<> { ... };
16 // class Disposable<T> : public Disposable<>
17   { /*~start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/ ...
18   /*~end~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/};
19 (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)template[\t
20   ]*<(?<typeParameters>[^\n]*)>[\t ]*(struct|class) [\t
21   ]+<(?<fullType>(?<type>[a-zA-Z][a-zA-Z0-9]*)<[^\<>\n]+>?)>[\t ]*:[\t
22   ]*(?<access>(private|protected|public) [\t
23   ]+)?(?<fullBaseType>(?<baseType>[a-zA-Z][a-zA-Z0-9]*)<[^\<>\n]+>?)>[\t
24   ]*(\r?\n)?[\t
25   ]*{ } (?<middle>(.|\n)*)(?<beforeEnd>(?:\r?\n)\k<indent>)(?<end>};)"),
26   "${classDeclarationBegin}/*~start~type~${type}~${fullType}~${baseType}~${fullBas
27   eType}~*/${middle}${beforeEnd}/*~end~type~${type}~${fullType}~${baseType}~${full
28   BaseType}~*/${end}",
29   0),
30 // Inside the scope replace:
31 // /*~start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/ ... ) : base(
32   ... /*~end~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/
33 // /*~start~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/ ... ) :
34   Disposable<>( /*~end~type~Disposable~Disposable<T>~Disposable~Disposable<>~*/
35 (new Regex(@"(?<before>(?:<typeScopeStart>/\*~start~type~(?:<types>(?:<type>[^\n\*]+)~
36   )(?<fullType>[^\n\*]+)~\k<type>~(?:<fullBaseType>[^\n\*]+)~\k<types>~\k<type>~
37   )base(?<after>\((( |\n)+)?(?:<typeScopeEnd>/\*~end~type~\k<types>~\k<type>~
38   )\s*:\s
39   )\s*:\s
40   )\s*:\s
41   )\s*:\s
42   )\s*:\s
43   )\s*:\s
44   )\s*:\s
45   )\s*:\s
46   )\s*:\s
47   )\s*:\s
48   )\s*:\s
49   )\s*:\s
50   )\s*:\s
51   )\s*:\s
52   )\s*:\s
53   )\s*:\s
54   )\s*:\s
55   )\s*:\s
56   )\s*:\s
57   )\s*:\s
58   )\s*:\s
59   )\s*:\s
60   )\s*:\s
61   )\s*:\s
62   )\s*:\s
63   )\s*:\s
64   )\s*:\s
65   )\s*:\s
66   )\s*:\s
67   )\s*:\s
68   )\s*:\s
69   )\s*:\s
70   )\s*:\s
71   )\s*:\s
72   )\s*:\s
73   )\s*:\s
74   )\s*:\s
75   )\s*:\s
76   )\s*:\s
77   )\s*:\s
78   )\s*:\s
79   )\s*:\s
80   )\s*:\s
81   )\s*:\s
82   )\s*:\s
83   )\s*:\s
84   )\s*:\s
85   )\s*:\s
86   )\s*:\s
87   )\s*:\s
88   )\s*:\s
89   )\s*:\s
90   )\s*:\s
91   )\s*:\s
92   )\s*:\s
93   )\s*:\s
94   )\s*:\s
95   )\s*:\s
96   )\s*:\s
97   )\s*:\s
98   )\s*:\s
99   )\s*:\s
100  )\s*:\s
101  )\s*:\s
102  )\s*:\s
103  )\s*:\s
104  )\s*:\s
105  )\s*:\s
106  )\s*:\s
107  )\s*:\s
108  )\s*:\s
109  )\s*:\s
110  )\s*:\s
111  )\s*:\s
112  )\s*:\s
113  )\s*:\s
114  )\s*:\s
115  )\s*:\s
116  )\s*:\s
117  )\s*:\s
118  )\s*:\s
119  )\s*:\s
120  )\s*:\s
121  )\s*:\s
122  )\s*:\s
123  )\s*:\s
124  )\s*:\s
125  )\s*:\s
126  )\s*:\s
127  )\s*:\s
128  )\s*:\s
129  )\s*:\s
130  )\s*:\s
131  )\s*:\s
132  )\s*:\s
133  )\s*:\s
134  )\s*:\s
135  )\s*:\s
136  )\s*:\s
137  )\s*:\s
138  )\s*:\s
139  )\s*:\s
140  )\s*:\s
141  )\s*:\s
142  )\s*:\s
143  )\s*:\s
144  )\s*:\s
145  )\s*:\s
146  )\s*:\s
147  )\s*:\s
148  )\s*:\s
149  )\s*:\s
150  )\s*:\s
151  )\s*:\s
152  )\s*:\s
153  )\s*:\s
154  )\s*:\s
155  )\s*:\s
156  )\s*:\s
157  )\s*:\s
158  )\s*:\s
159  )\s*:\s
160  )\s*:\s
161  )\s*:\s
162  )\s*:\s
163  )\s*:\s
164  )\s*:\s
165  )\s*:\s
166  )\s*:\s
167  )\s*:\s
168  )\s*:\s
169  )\s*:\s
170  )\s*:\s
171  )\s*:\s
172  )\s*:\s
173  )\s*:\s
174  )\s*:\s
175  )\s*:\s
176  )\s*:\s
177  )\s*:\s
178  )\s*:\s
179  )\s*:\s
180  )\s*:\s
181  )\s*:\s
182  )\s*:\s
183  )\s*:\s
184  )\s*:\s
185  )\s*:\s
186  )\s*:\s
187  )\s*:\s
188  )\s*:\s
189  )\s*:\s
190  )\s*:\s
191  )\s*:\s
192  )\s*:\s
193  )\s*:\s
194  )\s*:\s
195  )\s*:\s
196  )\s*:\s
197  )\s*:\s
198  )\s*:\s
199  )\s*:\s
200  )\s*:\s
201  )\s*:\s
202  )\s*:\s
203  )\s*:\s
204  )\s*:\s
205  )\s*:\s
206  )\s*:\s
207  )\s*:\s
208  )\s*:\s
209  )\s*:\s
210  )\s*:\s
211  )\s*:\s
212  )\s*:\s
213  )\s*:\s
214  )\s*:\s
215  )\s*:\s
216  )\s*:\s
217  )\s*:\s
218  )\s*:\s
219  )\s*:\s
220  )\s*:\s
221  )\s*:\s
222  )\s*:\s
223  )\s*:\s
224  )\s*:\s
225  )\s*:\s
226  )\s*:\s
227  )\s*:\s
228  )\s*:\s
229  )\s*:\s
230  )\s*:\s
231  )\s*:\s
232  )\s*:\s
233  )\s*:\s
234  )\s*:\s
235  )\s*:\s
236  )\s*:\s
237  )\s*:\s
238  )\s*:\s
239  )\s*:\s
240  )\s*:\s
241  )\s*:\s
242  )\s*:\s
243  )\s*:\s
244  )\s*:\s
245  )\s*:\s
246  )\s*:\s
247  )\s*:\s
248  )\s*:\s
249  )\s*:\s
250  )\s*:\s
251  )\s*:\s
252  )\s*:\s
253  )\s*:\s
254  )\s*:\s
255  )\s*:\s
256  )\s*:\s
257  )\s*:\s
258  )\s*:\s
259  )\s*:\s
260  )\s*:\s
261  )\s*:\s
262  )\s*:\s
263  )\s*:\s
264  )\s*:\s
265  )\s*:\s
266  )\s*:\s
267  )\s*:\s
268  )\s*:\s
269  )\s*:\s
270  )\s*:\s
271  )\s*:\s
272  )\s*:\s
273  )\s*:\s
274  )\s*:\s
275  )\s*:\s
276  )\s*:\s
277  )\s*:\s
278  )\s*:\s
279  )\s*:\s
280  )\s*:\s
281  )\s*:\s
282  )\s*:\s
283  )\s*:\s
284  )\s*:\s
285  )\s*:\s
286  )\s*:\s
287  )\s*:\s
288  )\s*:\s
289  )\s*:\s
290  )\s*:\s
291  )\s*:\s
292  )\s*:\s
293  )\s*:\s
294  )\s*:\s
295  )\s*:\s
296  )\s*:\s
297  )\s*:\s
298  )\s*:\s
299  )\s*:\s
300  )\s*:\s
301  )\s*:\s
302  )\s*:\s
303  )\s*:\s
304  )\s*:\s
305  )\s*:\s
306  )\s*:\s
307  )\s*:\s
308  )\s*:\s
309  )\s*:\s
310  )\s*:\s
311  )\s*:\s
312  )\s*:\s
313  )\s*:\s
314  )\s*:\s
315 
```



```

605 // Inside the scope replace:
606 // /*~app-domain~_currentDomain~*/ ... _currentDomain.ProcessExit += OnProcessExit;
607 // /*~app-domain~_currentDomain~*/ ... std::atexit(OnProcessExit);
608 (new Regex(@"(?<before>(?<fieldScopeStart>/\*~app-domain~(?<field>[^\n\*]+)~\*/)(.|\n)+?)\k<field>\.ProcessExit[\t ]*\+=[\t ]*(?<eventHandler>[a-zA-Z_][a-zA-Z0-9_]*)");, "${before}std::atexit(${eventHandler});/*~process-exit-handler~${eventHandler}~*/", 20),
609 // Inside the scope replace:
610 // /*~app-domain~_currentDomain~*/ ... _currentDomain.ProcessExit -= OnProcessExit;
611 // /*~app-domain~_currentDomain~*/ ... /* No translation. It is not possible to
612   ↳ unsubscribe from std::atexit. */
613 (new Regex(@"(?<before>(?<fieldScopeStart>/\*~app-domain~(?<field>[^\n\*]+)~\*/)(.|\n)+?)\k<field>\.ProcessExit[\t ]*\-=[\t ]*(?<eventHandler>[a-zA-Z_][a-zA-Z0-9_]*)");, "${before}/* No translation. It is not possible to unsubscribe from std::atexit. */", 20),
614 // Inside the scope replace:
615 // /*~process-exit-handler~OnProcessExit~*/ ... static void OnProcessExit(void
616   ↳ *sender, EventArgs e)
617 // /*~process-exit-handler~OnProcessExit~*/ ... static void OnProcessExit()
618 (new Regex(@"(?<before>(?<fieldScopeStart>/\*~process-exit-handler~(?<handler>[^\n\*]+)~\*/)(.|\n)+?)static[\t ]+void[\t ]+\k<handler>\(\(\)\n\+\\")", "${before}", 20),
619 // Remove scope borders.
620 // /*~app-domain~_currentDomain~*/
621 (new Regex(@"/*~[^\n\*]+(\[^\n\*]+)*~\*/"), "", 0),
622 // AppDomain.CurrentDomain.ProcessExit -= OnProcessExit;
623 // /* No translation. It is not possible to unsubscribe from std::atexit. */
624 (new Regex(@"AppDomain\.CurrentDomain\.ProcessExit -= ([a-zA-Z_][a-zA-Z0-9_]*)");, "/* No translation. It is not possible to unsubscribe from std::atexit. */", 0),
625 }.Cast<ISubstitutionRule>().ToList();
626
627 public static readonly IList<ISubstitutionRule> LastStage = new List<SubstitutionRule>
628 {
629     // IDisposable disposable)
630     // IDisposable &disposable)
631     (new Regex(@"(?<argumentAbstractType>I[A-Z][a-zA-Z0-9]+(<[^\r\n]+>)?)(?<argument>[_a-zA-Z0-9]+)(?<after>,|\))");, "${argumentAbstractType}
632   ↳ &${argument}${after}", 0),
633     // ICounter<int, int> c1;
634     // ICounter<int, int>* c1;
635     (new Regex(@"(?<abstractType>I[A-Z][a-zA-Z0-9]+(<[^\r\n]+>)?)(?<variable>[_a-zA-Z0-9]+)(?<after> = null)?");, "${abstractType}
636   ↳ *${variable}${after}";, 0),
637     // (expression)
638     // expression
639     (new Regex(@"(\(|\)|\((([a-zA-Z0-9_\*:]*)\)|\(|\;|\)|)");, "$1$2$3", 0),
640     // method(expression)
641     // method(expression)
642     (new Regex(@"(?<firstSeparator>(\(|\)|\(((?<method>[a-zA-Z0-9_\*:]*)\)|\(((?<expression>((?<parenthesis>\(|(?<-parent_
643   ↳ hesis>)\)|[a-zA-Z0-9_\*:]*)\)|(?<parenthesis>(?!))\)|\)|\(((?<lastSeparator>(\(|\;|\)|)");, "${firstSeparator}${method}${expression}${lastSeparator}", 0),
644     // .append(".")
645     // .append(1, '.');
646     (new Regex(@"\.(append\("([^\"]|\\\"")*"")");, ".append(1, '$1')", 0),
647     // return ref _elements[node];
648     // return &elements[node];
649     (new Regex(@"return ref ([a-zA-Z0-9_\*:]*)\((([a-zA-Z0-9_\*:]*)\)|\);");, "return &$1[$2];", 0),
650     // ((1, 2))
651     // ({1, 2})
652     (new Regex(@"(?<before>\(|\)|\(((?<first>[^\n()]+),
653   ↳ (?<second>[^\n()]+)\)(?<after>\(|\)|\);");, "${before}${{first}},
654   ↳ ${{second}}${after}", 10),
655     // {1, 2}.GetHashCode()
656     // Platform::Hashing::Hash(1, 2)
657     (new Regex(@"{(?<first>[^\n{}]+), (?<second>[^\n{}]+)}\.GetHashCode\(\)");, "Platform::Hashing::Hash(${first}, ${second})", 10),
658     // range.ToString()
659     // Platform::Converters::To<std::string>(range).data()
660     (new Regex(@"(?<before>\W)(?<variable>[_a-zA-Z][a-zA-Z0-9_\*:]*)\.ToString\(\)");, "${before}Platform::Converters::To<std::string>(${variable}).data()", 10),
661     // new
662     //

```

```

657 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)new\
    ↪ s+)", "${before}",
    ↪ 10),
658 // x == null
659 // x == nullptr
660 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)(?<v
    ↪ ariable>[_a-zA-Z][_a-zA-Z0-9]+)(?<operator>\s*(==|!=)\s*)null(?<after>\W)",
    ↪ "${before}${variable}${operator}nullptr${after}", 10),
661 // null
662 // {}
663 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)null
    ↪ (?<after>\W)", "${before}{}${after}",
    ↪ 10),
664 // default
665 // 0
666 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)defa
    ↪ ult(?<after>\W)", "${before}0${after}",
    ↪ 10),
667 // object x
668 // void *x
669 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)(?!
    ↪ @)(object|System\.Object) (?<after>\w)", "${before}void *${after}",
    ↪ 10),
670 // <object>
671 // <void*>
672 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)(?!
    ↪ @)(object|System\.Object) (?<after>\W)", "${before}void*${after}",
    ↪ 10),
673 // @object
674 // object
675 (new Regex(@"@([_a-zA-Z0-9]+)", "$1", 0),
676 // this->GetType().Name
677 // typeid(this).name()
678 (new Regex(@"(this->GetType\(\)\.Name)", "typeid($1).name()", 0),
679 // ArgumentException
680 // std::invalid_argument
681 (new Regex(@"(?<before>\r?\n[~""\r\n]*("""\|~""\r\n))*""[~""\r\n]*)(?<=\W)(Sys
    ↪ tem\.)?ArgumentException(?<after>\W)",
    ↪ "${before}std::invalid_argument${after}", 10),
682 // InvalidOperationException
683 // std::runtime_error
684 (new Regex(@"(\W)(InvalidOperationException|Exception)(\W)",
    ↪ "$1std::runtime_error$3", 0),
685 // ArgumentException
686 // std::invalid_argument
687 (new Regex(@"(\W)(ArgumentException|ArgumentOutOfRangeException)(\W)",
    ↪ "$1std::invalid_argument$3", 0),
688 // template <typename T> struct Range : IEquatable<Range<T>>
689 // template <typename T> struct Range {
690 (new Regex(@"(?<before>template <typename (?<typeParameter>[~\n]+)> (struct|class)
    ↪ (?<type>[_a-zA-Z0-9]+<[~\n]+>)) : (public
    ↪ )?IEquatable<\k<type>>(?<after>(\s|\n)*{)\"", "${before}${after}", 0),
691 // public: delegate void Disposal(bool manual, bool wasDisposed);
692 // public: delegate void Disposal(bool, bool);
693 (new Regex(@"(?<before>(?<access>(private|protected|public): )delegate
    ↪ (?<returnType>[_a-zA-Z][_a-zA-Z0-9:]+)
    ↪ (?<delegate>[_a-zA-Z][_a-zA-Z0-9:]+)\(((?<leftArgumentType>[_a-zA-Z][_a-zA-Z0-9:]+)
    ↪ )*(?<argumentType>[_a-zA-Z][_a-zA-Z0-9:]+)
    ↪ (?<argumentName>[_a-zA-Z][_a-zA-Z0-9:]+)(?<after>(,
    ↪ (?<rightArgumentType>[_a-zA-Z][_a-zA-Z0-9:]+)
    ↪ (?<rightArgumentName>[_a-zA-Z][_a-zA-Z0-9:]+))*\);)\"",
    ↪ "${before}${argumentType}${after}", 20),
694 // public: delegate void Disposal(bool, bool);
695 // using Disposal = void(bool, bool);
696 (new Regex(@"(?<access>(private|protected|public): )delegate
    ↪ (?<returnType>[_a-zA-Z][_a-zA-Z0-9:]+)
    ↪ (?<delegate>[_a-zA-Z][_a-zA-Z0-9:]+)\(((?<argumentTypes>[~\(\)\n]*\)\);)", "using
    ↪ ${delegate} = ${returnType}(${argumentTypes});", 20),
697 // <4-1>
698 // <3>
699 (new Regex(@"(?<before><)4-1(?<after>>)", "${before}3${after}", 0),
700 // <3-1>
701 // <2>
702 (new Regex(@"(?<before><)3-1(?<after>>)", "${before}2${after}", 0),
703 // <2-1>
704 // <1>

```

```

705         (new Regex(@"(?<before><)2-1(?<after>>)", "${before}1${after}", 0),
706         // <1-1>
707         // <0>
708         (new Regex(@"(?<before><)1-1(?<after>>)", "${before}0${after}", 0),
709         // #region Always
710         //
711         (new Regex(@"(^\r?\n)[ \t]*#(region|endregion)[^\r\n]*(\r?\n|$)", "", 0),
712         // //define ENABLE_TREE_AUTO_DEBUG_AND_VALIDATION
713         //
714         (new Regex(@"\\\/[ \t]*#define[ \t]+[_a-zA-Z0-9]+[ \t]*"), "", 0),
715         // #if USEARRAYPOOL\r\n#endif
716         //
717         (new Regex(@"#if [a-zA-Z0-9]+\s+endif", "", 0),
718         // [Fact]
719         //
720         (new Regex(@"(?<firstNewLine>\r?\n|\A)(?<indent>[ \t
    ↪ ]+)\[[a-zA-Z0-9]+\((?<expression>((?<parenthesis>\(|(?<-parenthesis>))|[^()\r\
    ↪ \n]*)+)(?<parenthesis>(?!))\)?\][ \t]*(\r?\n\k<indent>)?"),
    ↪ "${firstNewLine}${indent}", 5),
721         // \A \n ... namespace
722         // \Anamespace
723         (new Regex(@"(\A)(\r?\n)+namespace", "$1namespace", 0),
724         // \A \n ... class
725         // \Aclass
726         (new Regex(@"(\A)(\r?\n)+class", "$1class", 0),
727         // \n\n\n
728         // \n\n
729         (new Regex(@"\r?\n[ \t]*\r?\n[ \t]*\r?\n"), Environment.NewLine +
    ↪ Environment.NewLine, 50),
730         // {\n\n
731         // {\n
732         (new Regex(@"{[ \t]*\r?\n[ \t]*\r?\n"), "{" + Environment.NewLine, 10),
733         // \n\n}
734         // \n}
735         (new Regex(@"\r?\n[ \t]*\r?\n(?<end>[ \t]*)"), Environment.NewLine + "${end}", 10),
736     }.Cast<ISubstitutionRule>().ToList();
737
738     public CSharpToCppTransformer(IList<ISubstitutionRule> extraRules) :
    ↪ base(FirstStage.Concat(extraRules).Concat(LastStage).ToList()) { }
739
740     public CSharpToCppTransformer() : base(FirstStage.Concat(LastStage).ToList()) { }
741 }
742 }

```

## 1.2 ./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp.Tests/CSharpToCppTransformerTests.cs

```

1  using Xunit;
2
3  namespace Platform.RegularExpressions.Transformer.CSharpToCpp.Tests
4  {
5      public class CSharpToCppTransformerTests
6      {
7          [Fact]
8          public void EmptyLineTest()
9          {
10             // This test can help to test basic problems with regular expressions like incorrect
    ↪ syntax
11             var transformer = new CSharpToCppTransformer();
12             var actualResult = transformer.Transform("");
13             Assert.Equal("", actualResult);
14         }
15
16         [Fact]
17         public void HelloWorldTest()
18         {
19             const string helloWorldCode = @"using System;
20 class Program
21 {
22     public static void Main(string[] args)
23     {
24         Console.WriteLine("Hello, world!");
25     }
26 }";
27             const string expectedResult = @"class Program
28 {
29     public: static void Main(std::string args[])
30     {
31         printf("Hello, world!\n");
32     }

```

```
33 };";
34
35     var transformer = new CSharpToCppTransformer();
36     var actualResult = transformer.Transform(helloWorldCode);
37     Assert.Equal(expectedResult, actualResult);
38 }
39 }
```

## Index

./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp.Tests/CSharpToCppTransformerTests.cs, 17

./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp/CSharpToCppTransformer.cs, 1