1.1 ./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp/CSharpToCppTransformer.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Text.RegularExpressions;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.RegularExpressions.Transformer.CSharpToCpp
{
    public class CSharpToCppTransformer : Transformer
    {
        public static readonly IList<ISubstitutionRule> FirstStage = new List<SubstitutionRule>
        {
            // // ...
            //
            (new Regex(@"(\r?\n)?[ \t]+//+.+"), "", null, 0),
            // #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
            //
            (new Regex(@"^\s*?\#pragma[\sa-zA-Z0-9]+$"), "", null, 0),
            // {\n\n\n
            // {
            (new Regex(@"{\s+[\r\n]+"), "{" + Environment.NewLine, null, 0),
            // Platform.Collections.Methods.Lists
            // Platform::Collections::Methods::Lists
            (new Regex(@"(namespace[^\r\n]+?)\.([^\r\n]+?)"), "$1::$2", null, 20),
            // out TProduct
            // TProduct
            (new Regex(@"(?<before>(<|, ))(in|out) (?<typeParameter>[a-zA-Z0-9]+)(?<after>(>|,))"), "${before}${typeParameter}${after}", null, 10),
            // public ...
            // public: ...
            (new Regex(@"(?<newLineAndIndent>\r?\n?[ \t]*)(?<before>[^\{\(\r\n]*)(?<access>private|protected|public)[ \t]+(?![^\{\(\r\n]*(interface|class|struct)[^\{\(\r\n]*[\{\(\r\n])"), "${newLineAndIndent}${access}: ${before}", null, 0),
            // public: static bool CollectExceptions { get; set; }
            // public: static bool CollectExceptions;
            (new Regex(@"(?<before>(private|protected|public): (static )?[^\r\n]+ )(?<name>[a-zA-Z0-9]+) {[^;}]*(?<=\W)get;[^;}]*(?<=\W)set;[^;}]*}"), "${before}${name};", null, 0),
            // public abstract class
            // class
            (new Regex(@"((public|protected|private|internal|abstract|static) )*(?<category>interface|class|struct)"), "${category}", null, 0),
            // class GenericCollectionMethodsBase<TElement> {
            // template <typename TElement> class GenericCollectionMethodsBase {
            (new Regex(@"class ([a-zA-Z0-9]+)<([a-zA-Z0-9]+)>([^{]+){"), "template <typename $2> class $1$3{", null, 0),
            // static void TestMultipleCreationsAndDeletions<TElement>(SizedBinaryTreeMethodsBase<TElement> tree, TElement* root)
            // template<typename T> static void TestMultipleCreationsAndDeletions<TElement>(SizedBinaryTreeMethodsBase<TElement> tree, TElement* root)
            (new Regex(@"static ([a-zA-Z0-9]+) ([a-zA-Z0-9]+)<([a-zA-Z0-9]+)>\(([^\)\r\n]+)\)"), "template <typename $3> static $1 $2($4)", null, 0),
            // interface IFactory<out TProduct> {
            // template <typename TProduct> class IFactory { public:
            (new Regex(@"interface (?<interface>[a-zA-Z0-9]+)<(?<typeParameters>[a-zA-Z0-9,]+)>(?<whitespace>[^{]+){"), "template <typename...> class ${interface}; template <typename ${typeParameters}> class ${interface}<${typeParameters}>${whitespace}{" + Environment.NewLine + "public:", null, 0),
            // template <typename TObject, TProperty, TValue>
            // template <typename TObject, typename TProperty, TValue>
            (new Regex(@"(?<before>template <(, )?typename [a-zA-Z0-9]+)+, )(?<typeParameter>[a-zA-Z0-9]+)(?<after>(,|>))"), "${before}typename ${typeParameter}${after}", null, 10),
            // Insert markers
            // private: static void BuildExceptionString(this StringBuilder sb, Exception exception, int level)
            // /*~extensionMethod~BuildExceptionString~*/private: static void BuildExceptionString(this StringBuilder sb, Exception exception, int level)
```

```
            (new Regex(@"private: static [^\r\n]+ (?<name>[a-zA-Z0-9]+)\(this [^\)\r\n]+\)"),
            ↪  "/*~extensionMethod~${name}~*/$0", null, 0),
            // Move all markers to the beginning of the file.
            (new Regex(@"\A(?<before>[^\r\n]+\r?\n(.|\n)+)(?<marker>/\*~extensionMethod~(?<name>
            ↪  [a-zA-Z0-9]+)~\*/)"), "${marker}${before}", null,
            ↪  10),
            // /*~extensionMethod~BuildExceptionString~*/...sb.BuildExceptionString(exception.In
            ↪  nerException, level +
            ↪  1);
            // /*~extensionMethod~BuildExceptionString~*/...BuildExceptionString(sb,
            ↪  exception.InnerException, level + 1);
            (new Regex(@"(?<before>/\*~extensionMethod~(?<name>[a-zA-Z0-9]+)~\*/(.|\n)+\W)(?<var
            ↪  iable>[_a-zA-Z0-9]+)\.\k<name>\("), "${before}${name}(${variable}, ", null,
            ↪  50),
            // Remove markers
            // /*~extensionMethod~BuildExceptionString~*/
            //
            (new Regex(@"/\*~extensionMethod~[a-zA-Z0-9]+~\*/"), "", null, 0),
            // (this
            // (
            (new Regex(@"\(this "), "(", null, 0),
            // public: static readonly EnsureAlwaysExtensionRoot Always = new
            ↪  EnsureAlwaysExtensionRoot();
            // public:inline static EnsureAlwaysExtensionRoot Always;
            (new Regex(@"(?<access>(private|protected|public): )?static readonly
            ↪  (?<type>[a-zA-Z0-9]+) (?<name>[a-zA-Z0-9_]+) = new \k<type>\(\);"),
            ↪  "${access}inline static ${type} ${name};", null, 0),
            // public: static readonly string ExceptionContentsSeparator = "---";
            // public: inline static const char* ExceptionContentsSeparator = "---";
            (new Regex(@"(?<access>(private|protected|public): )?static readonly string
            ↪  (?<name>[a-zA-Z0-9_]+) = ""(?<string>(\""|[^""\r\n])+)"";"), "${access}inline
            ↪  static const char* ${name} = \"${string}\";", null, 0),
            // private: const int MaxPath = 92;
            // private: static const int MaxPath = 92;
            (new Regex(@"(?<access>(private|protected|public): )?(const|static readonly)
            ↪  (?<type>[a-zA-Z0-9]+) (?<name>[_a-zA-Z0-9]+) = (?<value>[^;\r\n]+);"),
            ↪  "${access}static const ${type} ${name} = ${value};", null, 0),
            //  ArgumentNotNull(EnsureAlwaysExtensionRoot root, TArgument argument) where
            ↪  TArgument : class
            //  ArgumentNotNull(EnsureAlwaysExtensionRoot root, TArgument* argument)
            (new Regex(@"(?<before> [a-zA-Z]+\(([a-zA-Z *,]+, |))(?<type>[a-zA-Z]+)(?<after>(|
            ↪  [a-zA-Z *,]+)\))[ \r\n]+where \k<type> : class"), "${before}${type}*${after}",
            ↪  null, 0),
            // protected: abstract TElement GetFirst();
            // protected: virtual TElement GetFirst() = 0;
            (new Regex(@"(?<access>(private|protected|public): )?abstract
            ↪  (?<method>[^;\r\n]+);"), "${access}virtual ${method} = 0;", null, 0),
            // TElement GetFirst();
            // virtual TElement GetFirst() = 0;
            (new Regex(@"([\r\n]+[ ]+)((?!return)[a-zA-Z0-9]+ [a-zA-Z0-9]+\([^\)\r\n]*\))(;[
            ↪  ]*[\r\n]+)"), "$1virtual $2 = 0$3", null, 1),
            // protected: readonly TreeElement[] _elements;
            // protected: TreeElement _elements[N];
            (new Regex(@"(?<access>(private|protected|public): )?readonly
            ↪  (?<type>[a-zA-Z<>0-9]+)([\[\]]+) (?<name>[_a-zA-Z0-9]+);"), "${access}${type}
            ↪  ${name}[N];", null, 0),
            // protected: readonly TElement Zero;
            // protected: TElement Zero;
            (new Regex(@"(?<access>(private|protected|public): )?readonly
            ↪  (?<type>[a-zA-Z<>0-9]+) (?<name>[_a-zA-Z0-9]+);"), "${access}${type} ${name};",
            ↪  null, 0),
            // internal
            //
            (new Regex(@"(\W)internal\s+"), "$1", null, 0),
            // static void NotImplementedException(ThrowExtensionRoot root) => throw new
            ↪  NotImplementedException();
            // static void NotImplementedException(ThrowExtensionRoot root) { return throw new
            ↪  NotImplementedException(); }
            (new Regex(@"(^\s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
            ↪  )?(override )?([a-zA-Z0-9]+
            ↪  )([a-zA-Z0-9]+)\(([^\(\r\n]*)\)\s+=>\s+throw([^;\r\n]+);"),
            ↪  "$1$2$3$4$5$6$7$8($9) { throw$10; }", null, 0),
            // SizeBalancedTree(int capacity) => a = b;
            // SizeBalancedTree(int capacity) { a = b; }
```

```
98              (new Regex(@"(^\s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
                ↪  )?(override )?(void )?([a-zA-Z0-9]+)\(([^\(\r\n]*)\)\s+=>\s+([^;\r\n]+);"),
                ↪  "$1$2$3$4$5$6$7$8($9) { $10; }", null, 0),
99              // int SizeBalancedTree(int capacity) => a;
100             // int SizeBalancedTree(int capacity) { return a; }
101             (new Regex(@"(^\s+)(private|protected|public)?(: )?(template \<[^>\r\n]+\> )?(static
                ↪  )?(override )?([a-zA-Z0-9]+
                ↪  )([a-zA-Z0-9]+)\(([^\(\r\n]*)\)\s+=>\s+([^;\r\n]+);"), "$1$2$3$4$5$6$7$8($9) {
                ↪  return $10; }", null, 0),
102             // () => Integer<TElement>.Zero,
103             // () { return Integer<TElement>.Zero; },
104             (new Regex(@"\(\)\s+=>\s+(?<expression>[^(),;\r\n]+((?<parenthesis>\()|(?<-parenthes
                ↪  is>\))|[^();\r\n]*)*[^(),;\r\n]*)(?<after>,|\);)"), "() { return ${expression};
                ↪  }${after}", null, 0),
105             // => Integer<TElement>.Zero;
106             // { return Integer<TElement>.Zero; }
107             (new Regex(@"\)\s+=>\s+([^;\r\n]+?);"), ") { return $1; }", null, 0),
108             // () { return avlTree.Count; }
109             // [&]()-> auto { return avlTree.Count; }
110             (new Regex(@", \(\) { return ([^;\r\n]+); }"), ", [&]()-> auto { return $1; }",
                ↪  null, 0),
111             // Count => GetSizeOrZero(Root);
112             // GetCount() { return GetSizeOrZero(Root); }
113             (new Regex(@"(\W)([A-Z][a-zA-Z]+)\s+=>\s+([^;\r\n]+);"), "$1Get$2() { return $3; }",
                ↪  null, 0),
114             // Func<TElement> treeCount
115             // std::function<TElement()> treeCount
116             (new Regex(@"Func<([a-zA-Z0-9]+)> ([a-zA-Z0-9]+)"), "std::function<$1()> $2", null,
                ↪  0),
117             // Action<TElement> free
118             // std::function<void(TElement)> free
119             (new Regex(@"Action<([a-zA-Z0-9]+)> ([a-zA-Z0-9]+)"), "std::function<void($1)> $2",
                ↪  null, 0),
120             // Predicate<TArgument> predicate
121             // std::function<bool(TArgument)> predicate
122             (new Regex(@"Predicate<([a-zA-Z0-9]+)> ([a-zA-Z0-9]+)"), "std::function<bool($1)>
                ↪  $2", null, 0),
123             // var
124             // auto
125             (new Regex(@"(\W)var(\W)"), "$1auto$2", null, 0),
126             // unchecked
127             //
128             (new Regex(@"[\r\n]{2}\s*?unchecked\s*?$"), "", null, 0),
129             // throw new InvalidOperationException
130             // throw std::runtime_error
131             (new Regex(@"throw new (InvalidOperationException|Exception)"), "throw
                ↪  std::runtime_error", null, 0),
132             // void RaiseExceptionIgnoredEvent(Exception exception)
133             // void RaiseExceptionIgnoredEvent(const std::exception& exception)
134             (new Regex(@"(\(|, )(System\.Exception|Exception)( |\))"), "$1const
                ↪  std::exception&$3", null, 0),
135             // EventHandler<Exception>
136             // EventHandler<std::exception>
137             (new Regex(@"(\W)(System\.Exception|Exception)(\W)"), "$1std::exception$3", null, 0),
138             // override void PrintNode(TElement node, StringBuilder sb, int level)
139             // void PrintNode(TElement node, StringBuilder sb, int level) override
140             (new Regex(@"override ([a-zA-Z0-9 \*\+]+)(\([^\)\r\n]+?\))"), "$1$2 override", null,
                ↪  0),
141             // string
142             // const char*
143             (new Regex(@"(\W)string(\W)"), "$1const char*$2", null, 0),
144             // sbyte
145             // std::int8_t
146             (new Regex(@"(\W)sbyte(\W)"), "$1std::int8_t$2", null, 0),
147             // uint
148             // std::uint32_t
149             (new Regex(@"(\W)uint(\W)"), "$1std::uint32_t$2", null, 0),
150             // char*[] args
151             // char* args[]
152             (new Regex(@"([_a-zA-Z0-9:\*]?)\[\] ([a-zA-Z0-9]+)"), "$1 $2[]", null, 0),
153             // @object
154             // object
155             (new Regex(@"@([_a-zA-Z0-9]+)"), "$1", null, 0),
156             // using Platform.Numbers;
157             //
158             (new Regex(@"([\r\n]{2}|^)\s*?using [\.a-zA-Z0-9]+;\s*?$"), "", null, 0),
159             // struct TreeElement { }
```

```
160             // struct TreeElement { };
161             (new Regex(@"(struct|class) ([a-zA-Z0-9]+)(\s+){([\sa-zA-Z0-9;:_]+?)}([^;])"), "$1
                ↪  $2$3{$4};$5", null, 0),
162             // class Program { }
163             // class Program { };
164             (new Regex(@"(struct|class) ([a-zA-Z0-9]+[^\r\n]*)([\r\n]+(?<indentLevel>[\t
                ↪  ]*)?)\{([\S\s]+?[\r\n]+\k<indentLevel>)\}([^;]|$)"), "$1 $2$3{$4};$5", null, 0),
165             // class SizedBinaryTreeMethodsBase : GenericCollectionMethodsBase
166             // class SizedBinaryTreeMethodsBase : public GenericCollectionMethodsBase
167             (new Regex(@"class ([a-zA-Z0-9]+) : ([a-zA-Z0-9]+)"), "class $1 : public $2", null,
                ↪  0),
168             // class IProperty : ISetter<TValue, TObject>, IProvider<TValue, TObject>
169             // class IProperty : public ISetter<TValue, TObject>, IProvider<TValue, TObject>
170             (new Regex(@"(?<before>class [a-zA-Z0-9]+ : ((public [a-zA-Z0-9]+(<[a-zA-Z0-9
                ↪  ,]+>)?, )+)?)(?<inheritedType>(?!public)[a-zA-Z0-9]+(<[a-zA-Z0-9
                ↪  ,]+>)?)(?<after>(, [a-zA-Z0-9]+(?!>)|[ \r\n]+))"), "${before}public
                ↪  ${inheritedType}${after}", null, 10),
171             // Insert scope borders.
172             // ref TElement root
173             // ~!root!~ref TElement root
174             (new Regex(@"(?<definition>(?<= |\()(ref [a-zA-Z0-9]+|[a-zA-Z0-9]+(?<!ref))
                ↪  (?<variable>[a-zA-Z0-9]+)(?=\)|, | =))"), "~!${variable}!~${definition}", null,
                ↪  0),
175             // Inside the scope of ~!root!~ replace:
176             // root
177             // *root
178             (new Regex(@"(?<definition>~!(?<pointer>[a-zA-Z0-9]+)!~ref [a-zA-Z0-9]+
                ↪  \k<pointer>(?=\)|, | =))(?<before>((?<!~!\k<pointer>!~)(.|\n))*?)(?<prefix>(\W
                ↪  |\())\k<pointer>(?<suffix>( |\)|;|,))"),
                ↪  "${definition}${before}${prefix}*${pointer}${suffix}", null, 70),
179             // Remove scope borders.
180             // ~!root!~
181             //
182             (new Regex(@"~!(?<pointer>[a-zA-Z0-9]+)!~"), "", null, 5),
183             // ref auto root = ref
184             // ref auto root =
185             (new Regex(@"ref ([a-zA-Z0-9]+) ([a-zA-Z0-9]+) = ref(\W)"), "$1* $2 =$3", null, 0),
186             // *root = ref left;
187             // root = left;
188             (new Regex(@"\*([a-zA-Z0-9]+) = ref ([a-zA-Z0-9]+)(\W)"), "$1 = $2$3", null, 0),
189             // (ref left)
190             // (left)
191             (new Regex(@"\(ref ([a-zA-Z0-9]+)(\)|\(|,)"), "($1$2", null, 0),
192             //  ref TElement
193             //  TElement*
194             (new Regex(@"( |\()ref ([a-zA-Z0-9]+) "), "$1$2* ", null, 0),
195             // ref sizeBalancedTree.Root
196             // &sizeBalancedTree->Root
197             (new Regex(@"ref ([a-zA-Z0-9]+)\.([a-zA-Z0-9\*]+)"), "&$1->$2", null, 0),
198             // ref GetElement(node).Right
199             // &GetElement(node)->Right
200             (new Regex(@"ref ([a-zA-Z0-9]+)\(([a-zA-Z0-9\*]+)\)\.([a-zA-Z0-9]+)"),
                ↪  "&$1($2)->$3", null, 0),
201             // GetElement(node).Right
202             // GetElement(node)->Right
203             (new Regex(@"([a-zA-Z0-9]+)\(([a-zA-Z0-9\*]+)\)\.([a-zA-Z0-9]+)"), "$1($2)->$3",
                ↪  null, 0),
204             // [Fact]\npublic: static void SizeBalancedTreeMultipleAttachAndDetachTest()
205             // public: TEST_METHOD(SizeBalancedTreeMultipleAttachAndDetachTest)
206             (new Regex(@"\[Fact\][\s\n]+(public: )?(static )?void ([a-zA-Z0-9]+)\(\)"), "public:
                ↪  TEST_METHOD($3)", null, 0),
207             // class TreesTests
208             // TEST_CLASS(TreesTests)
209             (new Regex(@"class ([a-zA-Z0-9]+)Tests"), "TEST_CLASS($1)", null, 0),
210             // Assert.Equal
211             // Assert::AreEqual
212             (new Regex(@"Assert\.Equal"), "Assert::AreEqual", null, 0),
213             // $"Argument {argumentName} is null."
214             // ((std::string)"Argument ").append(argumentName).append(" is null.").data()
215             (new Regex(@"\$""(?<left>(\\""|[^""\r\n])*){(?<expression>[_a-zA-Z0-9]+)}(?<right>(\
                ↪  \""|[^""\r\n])*)"""),
                ↪  "((std::string)$\"${left}\").append(${expression}).append(\"${right}\").data()",
                ↪  null, 10),
216             // $"
217             // "
218             (new Regex(@"\$"""), "\"", null, 0),
```

```
            // Console.WriteLine("...")
            // printf("...\n")
            (new Regex(@"Console\.WriteLine\(""([^""\r\n]+)""\)"), "printf(\"$1\\n\")", null, 0),
            // TElement Root;
            // TElement Root = 0;
            (new Regex(@"(\r?\n[\t ]+)(private|protected|public)?(:
            ↪  )?([a-zA-Z0-9:_]+(?<!return)) ([_a-zA-Z0-9]+);"), "$1$2$3$4 $5 = 0;", null, 0),
            // TreeElement _elements[N];
            // TreeElement _elements[N] = { {0} };
            (new Regex(@"(\r?\n[\t ]+)(private|protected|public)?(: )?([a-zA-Z0-9]+)
            ↪  ([_a-zA-Z0-9]+)\[([_a-zA-Z0-9]+)\];"), "$1$2$3$4 $5[$6] = { {0} };", null, 0),
            // auto path = new TElement[MaxPath];
            // TElement path[MaxPath] = { {0} };
            (new Regex(@"(\r?\n[\t ]+)[a-zA-Z0-9]+ ([a-zA-Z0-9]+) = new
            ↪  ([a-zA-Z0-9]+)\[([_a-zA-Z0-9]+)\];"), "$1$3 $2[$4] = { {0} };", null, 0),
            // private: static readonly ConcurrentBag<std::exception> _exceptionsBag = new
            ↪  ConcurrentBag<std::exception>();
            // private: static std::mutex _exceptionsBag_mutex; \n\n private: static
            ↪  std::vector<std::exception> _exceptionsBag;
            (new Regex(@"(?<begin>\r?\n?(?<indent>[ \t]+))(?<access>(private|protected|public):
                )?static readonly ConcurrentBag<(?<argumentType>[^;\r\n]+)>
            ↪  (?<name>[_a-zA-Z0-9]+) = new ConcurrentBag<\k<argumentType>>\(\);"),
            ↪  "${begin}private: static std::mutex ${name}_mutex;" + Environment.NewLine +
            ↪  Environment.NewLine + "${indent}${access}static std::vector<${argumentType}>
            ↪  ${name};", null, 0),
            // public: static IReadOnlyCollection<std::exception> GetCollectedExceptions() {
            ↪  return _exceptionsBag; }
            // public: static std::vector<std::exception> GetCollectedExceptions() { return
            ↪  std::vector<std::exception>(_exceptionsBag); }
            (new Regex(@"(?<access>(private|protected|public): )?static
            ↪  IReadOnlyCollection<(?<argumentType>[^;\r\n]+)> (?<methodName>[_a-zA-Z0-9]+)\(\)
            ↪  { return (?<fieldName>[_a-zA-Z0-9]+); }"), "${access}static
            ↪  std::vector<${argumentType}> ${methodName}() { return
            ↪  std::vector<${argumentType}>(${fieldName}); }", null, 0),
            // public: static event EventHandler<std::exception> ExceptionIgnored =
            ↪  OnExceptionIgnored; ... };
            // ... public: static inline Platform::Delegates::MulticastDelegate<void(void*,
            ↪  const std::exception&)> ExceptionIgnored = OnExceptionIgnored; };
            (new Regex(@"(?<begin>\r?\n(\r?\n)?(?<halfIndent>[
                \t]+)\k<halfIndent>)(?<access>(private|protected|public): )?static event
            ↪  EventHandler<(?<argumentType>[^;\r\n]+)> (?<name>[_a-zA-Z0-9]+) = (?<defaultDele
            ↪  gate>[_a-zA-Z0-9]+);(?<middle>(.|\n)+?)(?<end>\r?\n\k<halfIndent>};)"),
            ↪  "${middle}" + Environment.NewLine + Environment.NewLine +
            ↪  "${halfIndent}${halfIndent}${access}static inline
            ↪  Platform::Delegates::MulticastDelegate<void(void*, const ${argumentType}&)>
            ↪  ${name} = ${defaultDelegate};${end}", null, 0),
            // Insert scope borders.
            // class IgnoredExceptions { ... private: static std::vector<std::exception>
            ↪  _exceptionsBag;
            // class IgnoredExceptions {/*~_exceptionsBag~*/ ... private: static
            ↪  std::vector<std::exception> _exceptionsBag;
            (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n]+\r\n[\t
                ]*{)(?<middle>((?!class).|\n)+?)(?<vectorFieldDeclaration>(?<access>(private|pro
            ↪  tected|public): )static std::vector<(?<argumentType>[^;\r\n]+)>
            ↪  (?<fieldName>[_a-zA-Z0-9]+);)"),
            ↪  "${classDeclarationBegin}/*~${fieldName}~*/${middle}${vectorFieldDeclaration}",
            ↪  null, 0),
            // Inside the scope of ~!_exceptionsBag!~ replace:
            // _exceptionsBag.Add(exception);
            // _exceptionsBag.push_back(exception);
            (new Regex(@"(?<scope>/\*~(?<fieldName>[_a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<befor
            ↪  e>((?<!/\*~\k<fieldName>~\*/)(.|\n))*?)\k<fieldName>\.Add"),
            ↪  "${scope}${separator}${before}${fieldName}.push_back", null, 10),
            // Remove scope borders.
            // /*~_exceptionsBag~*/
            //
            (new Regex(@"/\*~[_a-zA-Z0-9]+~\*/"), "", null, 0),
            // Insert scope borders.
            // class IgnoredExceptions { ... private: static std::mutex _exceptionsBag_mutex;
            // class IgnoredExceptions {/*~_exceptionsBag~*/ ... private: static std::mutex
            ↪  _exceptionsBag_mutex;
            (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n]+\r\n[\t
                ]*{)(?<middle>((?!class).|\n)+?)(?<mutexDeclaration>private: static std::mutex
            ↪  (?<fieldName>[_a-zA-Z0-9]+)_mutex;)"),
            ↪  "${classDeclarationBegin}/*~${fieldName}~*/${middle}${mutexDeclaration}", null,
            ↪  0),
```

```
256             // Inside the scope of ~!_exceptionsBag!~ replace:
257             // return std::vector<std::exception>(_exceptionsBag);
258             // std::lock_guard<std::mutex> guard(_exceptionsBag_mutex); return
                ↪  std::vector<std::exception>(_exceptionsBag);
259             (new Regex(@"(?<scope>/\*~(?<fieldName>[_a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<befor
                ↪  e>((?<!/\*~\k<fieldName>~\*/)(.|\n))*?){(?<after>((?!lock_guard)[^{};\r\n])*\k<f
                ↪  ieldName>[^;}\r\n]*;)"), "${scope}${separator}${before}{
                ↪  std::lock_guard<std::mutex> guard(${fieldName}_mutex);${after}", null, 10),
260             // Inside the scope of ~!_exceptionsBag!~ replace:
261             // _exceptionsBag.Add(exception);
262             // std::lock_guard<std::mutex> guard(_exceptionsBag_mutex); \r\n
                ↪  _exceptionsBag.Add(exception);
263             (new Regex(@"(?<scope>/\*~(?<fieldName>[_a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<befor
                ↪  e>((?<!/\*~\k<fieldName>~\*/)(.|\n))*?){(?<after>((?!lock_guard)([^{};]|\n))*?\r
                ↪  ?\n(?<indent>[ \t]*)\k<fieldName>[^;}\r\n]*;)"),
                ↪  "${scope}${separator}${before}{" + Environment.NewLine +
                ↪  "${indent}std::lock_guard<std::mutex> guard(${fieldName}_mutex);${after}", null,
                ↪  10),
264             // Remove scope borders.
265             // /*~_exceptionsBag~*/
266             //
267             (new Regex(@"/\*~[_a-zA-Z0-9]+~\*/"), "", null, 0),
268             // Insert scope borders.
269             // class IgnoredExceptions { ... public: static inline
                ↪  Platform::Delegates::MulticastDelegate<void(void*, const std::exception&)>
                ↪  ExceptionIgnored = OnExceptionIgnored;
270             // class IgnoredExceptions {/*~ExceptionIgnored~*/ ... public: static inline
                ↪  Platform::Delegates::MulticastDelegate<void(void*, const std::exception&)>
                ↪  ExceptionIgnored = OnExceptionIgnored;
271             (new Regex(@"(?<classDeclarationBegin>\r?\n(?<indent>[\t ]*)class [^{\r\n]+\r\n[\t
                ]*{)(?<middle>((?!class).|\n)+?)(?<eventDeclaration>(?<access>(private|protected
                ↪  |public): )static inline
                ↪  Platform::Delegates::MulticastDelegate<(?<argumentType>[^;\r\n]+)>
                ↪  (?<name>[_a-zA-Z0-9]+) = (?<defaultDelegate>[_a-zA-Z0-9]+);)"),
                ↪  "${classDeclarationBegin}/*~${name}~*/${middle}${eventDeclaration}", null, 0),
272             // Inside the scope of ~!ExceptionIgnored!~ replace:
273             // ExceptionIgnored.Invoke(NULL, exception);
274             // ExceptionIgnored(NULL, exception);
275             (new Regex(@"(?<scope>/\*~(?<eventName>[a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<before
                ↪  >((?<!/\*~\k<eventName>~\*/)(.|\n))*?)\k<eventName>\.Invoke"),
                ↪  "${scope}${separator}${before}${eventName}", null, 10),
276             // Remove scope borders.
277             // /*~ExceptionIgnored~*/
278             //
279             (new Regex(@"/\*~[a-zA-Z0-9]+~\*/"), "", null, 0),
280             // Insert scope borders.
281             // auto added = new StringBuilder();
282             // /*~sb~*/std::string added;
283             (new Regex(@"(auto|(System\.Text\.)?StringBuilder) (?<variable>[a-zA-Z0-9]+) = new
                ↪  (System\.Text\.)?StringBuilder\(\);"), "/*~${variable}~*/std::string
                ↪  ${variable};", null, 0),
284             // static void Indent(StringBuilder sb, int level)
285             // static void Indent(/*~sb~*/StringBuilder sb, int level)
286             (new Regex(@"(?<start>, |\()(System\.Text\.)?StringBuilder
                ↪  (?<variable>[a-zA-Z0-9]+)(?<end>,|\))"), "${start}/*~${variable}~*/std::string&
                ↪  ${variable}${end}", null, 0),
287             // Inside the scope of ~!added!~ replace:
288             // sb.ToString()
289             // sb.data()
290             (new Regex(@"(?<scope>/\*~(?<variable>[a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<before>
                ↪  ((?<!/\*~\k<variable>~\*/)(.|\n))*?)\k<variable>\.ToString\(\)"),
                ↪  "${scope}${separator}${before}${variable}.data()", null, 10),
291             // sb.AppendLine(argument)
292             // sb.append(argument).append('\n')
293             (new Regex(@"(?<scope>/\*~(?<variable>[a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<before>
                ↪  ((?<!/\*~\k<variable>~\*/)(.|\n))*?)\k<variable>\.AppendLine\((?<argument>[^\),\
                ↪  r\n]+)\)"),
                ↪  "${scope}${separator}${before}${variable}.append(${argument}).append(1, '\\n')",
                ↪  null, 10),
294             // sb.Append('\t', level);
295             // sb.append(level, '\t');
296             (new Regex(@"(?<scope>/\*~(?<variable>[a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<before>
                ↪  ((?<!/\*~\k<variable>~\*/)(.|\n))*?)\k<variable>\.Append\('(?<character>[^'\r\n]
                ↪  +)', (?<count>[^\),\r\n]+)\)"),
                ↪  "${scope}${separator}${before}${variable}.append(${count}, '${character}')",
                ↪  null, 10),
```

```
297                 // sb.Append(argument)
298                 // sb.append(argument)
299                 (new Regex(@"(?<scope>/\*~(?<variable>[a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<before>
                    ↪  ((?<!/\*~\k<variable>~\*/)(.|\n))*?)\k<variable>\.Append\((?<argument>[^\),\r\n]
                    ↪  +)\)"), "${scope}${separator}${before}${variable}.append(${argument})", null,
                    ↪  10),
300                 // Remove scope borders.
301                 // /*~sb~*/
302                 //
303                 (new Regex(@"/\*~[a-zA-Z0-9]+~\*/"), "", null, 0),
304                 // Insert scope borders.
305                 // auto added = new HashSet<TElement>();
306                 // ~!added!~std::unordered_set<TElement> added;
307                 (new Regex(@"auto (?<variable>[a-zA-Z0-9]+) = new
                    ↪  HashSet<(?<element>[a-zA-Z0-9]+)>\(\);"),
                    ↪  "~!${variable}!~std::unordered_set<${element}> ${variable};", null, 0),
308                 // Inside the scope of ~!added!~ replace:
309                 // added.Add(node)
310                 // added.insert(node)
311                 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~)(?<separator>.|\n)(?<before>((?<
                    ↪  !~!\k<variable>!~)(.|\n))*?)\k<variable>\.Add\((?<argument>[a-zA-Z0-9]+)\)"),
                    ↪  "${scope}${separator}${before}${variable}.insert(${argument})", null, 10),
312                 // Inside the scope of ~!added!~ replace:
313                 // added.Remove(node)
314                 // added.erase(node)
315                 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~)(?<separator>.|\n)(?<before>((?<
                    ↪  !~!\k<variable>!~)(.|\n))*?)\k<variable>\.Remove\((?<argument>[a-zA-Z0-9]+)\)"),
                    ↪  "${scope}${separator}${before}${variable}.erase(${argument})", null, 10),
316                 // if (added.insert(node)) {
317                 // if (!added.contains(node)) { added.insert(node);
318                 (new Regex(@"if \((?<variable>[a-zA-Z0-9]+)\.insert\((?<argument>[a-zA-Z0-9]+)\)\)(?
                    ↪  <separator>[\t ]*[\r\n]+)(?<indent>[\t ]*){"), "if
                    ↪  (!${variable}.contains(${argument}))${separator}${indent}{" +
                    ↪  Environment.NewLine + "${indent}    ${variable}.insert(${argument});", null, 0),
319                 // Remove scope borders.
320                 // ~!added!~
321                 //
322                 (new Regex(@"~![a-zA-Z0-9]+!~"), "", null, 5),
323                 // Insert scope borders.
324                 // auto random = new System.Random(0);
325                 // std::srand(0);
326                 (new Regex(@"[a-zA-Z0-9\.]+ ([a-zA-Z0-9]+) = new
                    ↪  (System\.)?Random\(([a-zA-Z0-9]+)\);"), "~!$1!~std::srand($3);", null, 0),
327                 // Inside the scope of ~!random!~ replace:
328                 // random.Next(1, N)
329                 // (std::rand() % N) + 1
330                 (new Regex(@"(?<scope>~!(?<variable>[a-zA-Z0-9]+)!~)(?<separator>.|\n)(?<before>((?<
                    ↪  !~!\k<variable>!~)(.|\n))*?)\k<variable>\.Next\((?<from>[a-zA-Z0-9]+),
                    ↪  (?<to>[a-zA-Z0-9]+)\)"), "${scope}${separator}${before}(std::rand() % ${to}) +
                    ↪  ${from}", null, 10),
331                 // Remove scope borders.
332                 // ~!random!~
333                 //
334                 (new Regex(@"~![a-zA-Z0-9]+!~"), "", null, 5),
335                 // Insert method body scope starts.
336                 // void PrintNodes(TElement node, StringBuilder sb, int level) {
337                 // void PrintNodes(TElement node, StringBuilder sb, int level) {/*method-start*/
338                 (new Regex(@"(?<start>\r?\n[\t ]+)(?<prefix>((private|protected|public): )?(virtual
                    ↪  )?[a-zA-Z0-9:_]+
                    ↪  )?(?<method>[a-zA-Z][a-zA-Z0-9]*)\((?<arguments>[^\)]*)\)(?<override>(
                    ↪  override)?)(?<separator>[ \t\r\n]*)\{(?<end>[^~])"), "${start}${prefix}${method}
                    ↪  (${arguments})${override}${separator}{/*method-start*/${end}", null,
                    ↪  0),
339                 // Insert method body scope ends.
340                 // {/*method-start*/...}
341                 // {/*method-start*/.../*method-end*/}
342                 (new Regex(@"\{/\*method-start\*/(?<body>((?<bracket>\{)|(?<-bracket>\})|[^\{\}]*)+)
                    ↪  \}"), "{/*method-start*/${body}/*method-end*/}", null,
                    ↪  0),
343                 // Inside method bodies replace:
344                 // GetFirst(
345                 // this->GetFirst(
346                 //(new Regex(@"(?<separator>(\(|, |([\W]) |return ))(?<!(->|\*
                    ↪  ))(?<method>(?!sizeof)[a-zA-Z0-9]+)\((?!\) \{)"),
                    ↪  "${separator}this->${method}(", null, 1),
```

```
347             (new Regex(@"(?<scope>/\*method-start\*/)(?<before>((?<!/\*method-end\*/)(.|\n))*?)(
                    ?<separator>[\W](?<!(::|\.|->)))(?<method>(?!sizeof)[a-zA-Z0-9]+)\((?!\)
                    \{)(?<after>(.|\n)*?)(?<scopeEnd>/\*method-end\*/)"),
                    "${scope}${before}${separator}this->${method}(${after}${scopeEnd}", null, 100),
348             // Remove scope borders.
349             // /*method-start*/
350             //
351             (new Regex(@"/\*method-(start|end)\*/"), "", null, 0),
352             // Insert scope borders.
353             // const std::exception& ex
354             // const std::exception& ex/*~ex~*/
355             (new Regex(@"(?<before>\(| )(?<variableDefinition>(const )?(std::)?exception&?
                    (?<variable>[_a-zA-Z0-9]+))(?<after>\W)"),
                    "${before}${variableDefinition}/*~${variable}~*/${after}", null, 0),
356             // Inside the scope of ~!ex!~ replace:
357             // ex.Message
358             // ex.what()
359             (new Regex(@"(?<scope>/\*~(?<variable>[_a-zA-Z0-9]+)~\*/)(?<separator>.|\n)(?<before
                    >((?<!/\*~\k<variable>~\*/)(.|\n))*?)\k<variable>\.Message"),
                    "${scope}${separator}${before}${variable}.what()", null, 10),
360             // Remove scope borders.
361             // /*~ex~*/
362             //
363             (new Regex(@"/\*~[_a-zA-Z0-9]+~\*/"), "", null, 0),
364             // throw new ArgumentNullException(argumentName, message);
365             // throw std::invalid_argument(((std::string)"Argument
                    ").append(argumentName).append(" is null: ").append(message).append("."));
366             (new Regex(@"throw new
                    ArgumentNullException\((?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]*),
                    (?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*)\);"), "throw
                    std::invalid_argument(((std::string)\"Argument \").append(${argument}).append(\"
                    is null: \").append(${message}).append(\".\"));", null, 0),
367             // throw new ArgumentException(message, argumentName);
368             // throw std::invalid_argument(((std::string)"Invalid
                    ").append(argumentName).append(" argument: ").append(message).append("."));
369             (new Regex(@"throw new ArgumentException\((?<message>[a-zA-Z]*[Mm]essage[a-zA-Z]*),
                    (?<argument>[a-zA-Z]*[Aa]rgument[a-zA-Z]*)\);"), "throw
                    std::invalid_argument(((std::string)\"Invalid \").append(${argument}).append(\"
                    argument: \").append(${message}).append(\".\"));", null, 0),
370             // throw new NotSupportedException();
371             // throw std::logic_error("Not supported exception.");
372             (new Regex(@"throw new NotSupportedException\(\);"), "throw std::logic_error(\"Not
                    supported exception.\");", null, 0),
373             // throw new NotImplementedException();
374             // throw std::logic_error("Not implemented exception.");
375             (new Regex(@"throw new NotImplementedException\(\);"), "throw std::logic_error(\"Not
                    implemented exception.\");", null, 0),
376         }.Cast<ISubstitutionRule>().ToList();
377
378         public static readonly IList<ISubstitutionRule> LastStage = new List<SubstitutionRule>
379         {
380             // ICounter<int, int> c1;
381             // ICounter<int, int>* c1;
382             (new Regex(@"(?<abstractType>I[A-Z][a-zA-Z0-9]+(<[^>\r\n]+>)?)
                    (?<variable>[_a-zA-Z0-9]+);"), "${abstractType}* ${variable};", null, 0),
383             // (expression)
384             // expression
385             (new Regex(@"(\(| )\(([a-zA-Z0-9_\*:]+)\)(,| |;|\))"), "$1$2$3", null, 0),
386             // (method(expression))
387             // method(expression)
388             (new Regex(@"(?<firstSeparator>(\(|
                    ))\((?<method>[a-zA-Z0-9_\->\*:]+)\((?<expression>((?<parenthesis>\()|(?<-parent
                    hesis>\))|[a-zA-Z0-9_\->\*:]*)+)(?(parenthesis)(?!))\)\)(?<lastSeparator>(,|
                    |;|\)))"), "${firstSeparator}${method}(${expression})${lastSeparator}", null, 0),
389             // return ref _elements[node];
390             // return &_elements[node];
391             (new Regex(@"return ref ([_a-zA-Z0-9]+)\[([_a-zA-Z0-9\*]+)\];"), "return &$1[$2];",
                    null, 0),
392             // null
393             // nullptr
394             (new Regex(@"(?<before>\r?\n[^""\r\n]*(""(\\""|[^""\r\n])*""[^""\r\n]*)*)(?<=\W)null
                    (?<after>\W)"), "${before}nullptr${after}", null,
                    10),
395             // default
396             // 0
```

```
            (new Regex(@"(?<before>\r?\n[^""\r\n]*(""(\\""|[^""\r\n])*""[^""\r\n]*)*)(?<=\W)defa
            ↪  ult(?<after>\W)"), "${before}0${after}", null,
            ↪  10),
            // object x
            // void *x
            (new Regex(@"(?<before>\r?\n[^""\r\n]*(""(\\""|[^""\r\n])*""[^""\r\n]*)*)(?<=\W)([O|
            ↪  o]bject|System\.Object) (?<after>\w)"), "${before}void *${after}", null,
            ↪  10),
            // #region Always
            //
            (new Regex(@"(^|\r?\n)[ \t]*\#(region|endregion)[^\r\n]*(\r?\n|$)"), "", null, 0),
            // //#define ENABLE_TREE_AUTO_DEBUG_AND_VALIDATION
            //
            (new Regex(@"\/\/[ \t]*\#define[ \t]+[_a-zA-Z0-9]+[ \t]*"), "", null, 0),
            // #if USEARRAYPOOL\r\n#endif
            //
            (new Regex(@"#if [a-zA-Z0-9]+\s+#endif"), "", null, 0),
            // [Fact]
            //
            (new Regex(@"(?<firstNewLine>\r?\n|\A)(?<indent>[\t
            ↪  ]+)\[[a-zA-Z0-9]+(\((?<expression>((?<parenthesis>\()|(?<-parenthesis>\))|[^()\r
            ↪  \n]*)+)(?(parenthesis)(?!))\))?\][ \t]*(\r?\n\k<indent>)?"),
            ↪  "${firstNewLine}${indent}", null, 5),
            // \n ... namespace
            // namespace
            (new Regex(@"(\S[\r\n]{1,2})?[\r\n]+namespace"), "$1namespace", null, 0),
            // \n ... class
            // class
            (new Regex(@"(\S[\r\n]{1,2})?[\r\n]+class"), "$1class", null, 0),
        }.Cast<ISubstitutionRule>().ToList();

        public CSharpToCppTransformer(IList<ISubstitutionRule> extraRules) :
        ↪  base(FirstStage.Concat(extraRules).Concat(LastStage).ToList()) { }

        public CSharpToCppTransformer() : base(FirstStage.Concat(LastStage).ToList()) { }
    }
}
```

1.2 ./csharp/Platform.RegularExpressions.Transformer.CSharpToCpp.Tests/CSharpToCppTransformerTests.cs

```
using Xunit;

namespace Platform.RegularExpressions.Transformer.CSharpToCpp.Tests
{
    public class CSharpToCppTransformerTests
    {
        [Fact]
        public void EmptyLineTest()
        {
            // This test can help to test basic problems with regular expressions like incorrect
            ↪  syntax
            var transformer = new CSharpToCppTransformer();
            var actualResult = transformer.Transform("", new Context(null));
            Assert.Equal("", actualResult);
        }

        [Fact]
        public void HelloWorldTest()
        {
            const string helloWorldCode = @"using System;
class Program
{
    public static void Main(string[] args)
    {
        Console.WriteLine(""Hello, world!"");
    }
}";
            const string expectedResult = @"class Program
{
    public: static void Main(const char* args[])
    {
        printf(""Hello, world!\n"");
    }
};";
            var transformer = new CSharpToCppTransformer();
            var actualResult = transformer.Transform(helloWorldCode, new Context(null));
            Assert.Equal(expectedResult, actualResult);
        }
    }
```

```
}
```

Index