

Introduction to R

Lino AA Notarantonio (lino@tec.mx)

30/07/2020

Timetable and material

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Day	hour
Thursday	16:00-19:00 hours
Friday	10:00-13:00 hours
Saturday	11:00-14:00 hours

There will a 30-minute break during each session.

The material of this workshop is [here](#)

**Introduction
to R**

Lino AA
Notarantonio
(lino@tec.mx)

**Introduction
to R(Studio)**

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Introduction to R(Studio)

R(Studio)

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- You should have defined a **project** (working directory) somewhere in your computer (e.g., Desktop).
- R is the actual programming language
- RStudio is an IDE (Integrated Development Environment) for R.
- R is **case sensitive**; e. g., **Mean** \neq **mean**
- R(Studio) may not work very well when files (or directory containing working files) have accented characters. If the locale language of your filesystem is not in English, then some errors may occur in those cases.

Basic calculations

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- R can be used as a calculator
- Mathematical constants:
 - $\pi = 3.142$
 - $\exp(1) = 2.718$
- Logarithms:
 - $\log(e) = 1$
 - $\log_{10}(100) = 2$
 - $\log(16, \text{base} = 4) = 2$

Display Information

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- Getting help: in the console, put a question mark before the function name; RStudio will display the documentation:

```
?cos
```

- Set the display of decimal digits to 3, for a better output:

```
options(digits = 3)
```

Installing packages

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

One of the strengths of R is the increasing number of available packages (more than 14,000 of them): [CRAN Packages](#)

To install and use a package we have

- firstly to **install** it;
- then, to **load** it in the current session.

To install a package (e.g., `tseries`), we can use the `install.packages("tseries")` function.

To load it in the current session, use `library(tseries)`

To install a package, we can also use the **Tools** option in the RStudio window and follow **Install Packages...**

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

**Data Types
and Data
Structure**

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Data Types and Data Structure

Data types

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

The data types used by R are

- numeric (double precision): 2.718, 1.4, ...
- integer: 1, -13, ...
- complex: $2 - 3i$, ...
- logical: TRUE, FALSE. Also NA is considered logical
- character: "one plus two", "Hello world!"

Data Structure

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

- Vector: basic data structure in R. Its components have the same data type.
- Matrix: think of linear algebra.
 - A matrix as a collection of vectors.
- Dataframe: similar to a matrix, except that it is not necessarily homogeneous.
 - A collection of vectors (of possible different types) with the same length.
- List: generic data structure containing other **objects** (vectors, other lists), **not necessarily of the same length.**

Assignment operator

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- In R, we assign a value, **value**, to an object **x** by means of
<-: `x <- value`
- To type it, you can use the shortcut ALT+"-" (ALT key and minus sign); it works with Windows, MacOS.
- It is also possible to use **=**, but the equal sign has lower priority than **<-**.
 - Check the discussion at [StackExchange](#).

Vectors

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

The easiest way to create a vector in R is to use the `c()` (concatenate) function:

```
v <- c(1, 3, 5, 7, 9)
```

```
v
```

```
## [1] 1 3 5 7 9
```

Vectors: coercion

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

If we define a vector with components of different data types, the result will be coerced to the same data type

```
w <- c(1.56, "Hello World", 4, TRUE)
```

```
typeof(w)
```

```
## [1] "character"
```

Notice that

```
u <- c(1.56, 4, TRUE)
```

```
typeof(u)
```

```
## [1] "double"
```

Vectors by sequences

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- Create a vector with the first 30 integer numbers:

```
(x <- 1:30)
```

```
## [1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15  
## [26] 26 27 28 29 30
```

- In reverse order:

```
(x <- 30:1)
```

```
## [1] 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16  
## [26] 5 4 3 2 1
```

Vectors by sequences

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

- Create a sequence of the first odd numbers, up to 11:

```
(y <- seq(1, 11, 2))
```

```
## [1] 1 3 5 7 9 11
```

- Repeat the character "Hello" 5 times:

```
(z <- rep("Hello", 5))
```

```
## [1] "Hello" "Hello" "Hello" "Hello" "Hello"
```

- Repeat the vector y, defined above, 2 times:

```
(rep(y,2))
```

```
## [1] 1 3 5 7 9 11 1 3 5 7 9 11
```

Length of a vector

The length of a vector (number of its components) is obtained with the function `length()`

```
x <- 1:30  
length(x)
```

```
## [1] 30
```

```
y <- seq(1, 11, 2)  
length(y)
```

```
## [1] 6
```

```
z <- rep("Hello", 5)  
length(z)
```

```
## [1] 5
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Subsetting

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Let `y <- seq(1,11,2)`: 1, 3, 5, 7, 9, 11.

- Select the third component: `y[3]` = 5
- Exclude the fourth component: `y[-4]`: 1, 3, 5, 9, 11.
- Select the first four components: `y[c(1:4)]`: 1, 3, 5, 7
- Select the first, fifth and last element:

```
y[c(1, 5, length(y))]
```

```
## [1] 1 9 11
```

or

```
y[c(1, length(y) - 1, length(y))]
```

```
## [1] 1 9 11
```

Subsetting

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- Remove the first four components: `y[-c(1:4)]`: 9, 11.
- Select the second, fifth and sixth components: `y[c(2, 5, 6)]`: 3, 9, 11.
- Select components by using a vector of logic type:

```
s <- c(TRUE, TRUE, FALSE, FALSE, TRUE, FALSE)
y[c(s)]
```

```
## [1] 1 3 9
```

Vectorization

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Consider the vector

```
x <- 1:100
```

Then,

- $x + 4 = 5, 6, 7, 8, 9, 10 \dots$
- $x^2 = 1, 4, 9, 16, 25, 36 \dots$
- $2*x+3 = 5, 7, 9, 11, 13, 15 \dots$
- $\text{sqrt}(x) = 1, 1.414, 1.732, 2, 2.236, 2.449 \dots$
- $\log(x) = 0, 0.693, 1.099, 1.386, 1.609, 1.792 \dots$

Vectorization

We can add up two vectors even when they have different lengths, provided that the length of one is an integer multiple of the other:

```
x <- seq(1,11,2)
y <- 1:12
x + y
```

```
## [1] 2 5 8 11 14 17 8 11 14 17 20 23
```

Check for identity

```
all(x + y == rep(x,2) + y)
```

```
## [1] TRUE
```

```
identical(x + y, rep(x,2) + y)
```

```
## [1] TRUE
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Logical operators

Each of the following operators returns either **TRUE** or **FALSE**.

- **==** (equality)
- **!=** (not equal to)
- **>** (greater than)
- **<** (less than)
- **>=** (greater than or equal to)
- **<=** (less than or equal to)
- **!x** (not **x**)
- **x | y** (**x** OR **y**)
- **x & y** (**x** AND **y**)

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Logical operators

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Examples

Let `x <- c(1,2,3,4,5,6)`

- `x > 4`: FALSE, FALSE, FALSE, FALSE, TRUE, TRUE
- `x == 4`: FALSE, FALSE, FALSE, TRUE, FALSE, FALSE
- `x != 3`: TRUE, TRUE, FALSE, TRUE, TRUE, TRUE
- `x == 4 | x != 3`: TRUE, TRUE, FALSE, TRUE, TRUE, TRUE
- `x == 4 & x != 3`: FALSE, FALSE, FALSE, TRUE, FALSE, FALSE
- `as.numeric(x == 4 | x != 3)`: 1, 1, 0, 1, 1, 1
- Arithmetically, **TRUE** is considered 1 and **FALSE** 0:
`sum(x == 4 | x != 3)`: 5

Logical operators

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Logical operators and subsetting

Subsetting will extract the values of the components that satisfy the given logical condition.

Let `x <- c(1,2,3,4,5,6)`

- `x[x > 3]`: 4, 5, 6
- `x[x != 3]`: 1, 2, 4, 5, 6
- `x[x <= 0]`: numeric(0) (empty set)
- `x[x <= 0 | x > 3]`: 4, 5, 6
- `x[x <= 0 & x > 3]`: numeric(0) (empty set)
- `sum(x[x <= 0 & x>3])`: 0

Logical operators

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Selection

```
y <- c(1, -2, 4, 6, 9, 2, 1)
```

- `which(y <= 4)`: 1, 2, 3, 6, 7
selects which **entries** satisfy the condition. Indexing of vectors starts from 1.
- `y[which(y <= 4)]`: 1, -2, 4, 2, 1
returns the **values** of the entries satisfying the condition.
- `which(y == max(y))`: 5
entry of the vector with the maximum value
- `y[which(y == max(y))]`: 9
maximum value of the vector

Matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

A matrix A is specified by the number of its rows and columns, $m \times n$.

The **order** of rows and columns is **important**.

Matrix can be created by means of the `matrix()` function:

```
x <- 1:8  
A <- matrix(x, nrow = 4, ncol = 2)  
B <- matrix(x, nrow = 2, ncol = 4)  
dim(A) # rows = 4; columns = 2
```

```
## [1] 4 2
```

```
dim(B) # rows = 2; columns = 4
```

```
## [1] 2 4
```

Matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

A

##		[,1]	[,2]
##	[1,]	1	5
##	[2,]	2	6
##	[3,]	3	7
##	[4,]	4	8

B

##		[,1]	[,2]	[,3]	[,4]
##	[1,]	1	3	5	7
##	[2,]	2	4	6	8

Matrices: Subsetting

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- Select the entry of the matrix A in the first row, second column:

```
A[1,2]
```

```
## [1] 5
```

- Select the third column of the matrix B

```
B[,3]
```

```
## [1] 5 6
```

- Select the third row of the matrix A

```
A[3,]
```

```
## [1] 3 7
```

Matrices: Subsetting

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- Select the first and fourth column of the matrix B

```
B[, c(1,4)]
```

```
##           [,1] [,2]  
## [1,]         1    7  
## [2,]         2    8
```

Binding vectors: by columns

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
u <- 1:4
v = rev(u)
w <- rep(1,4)
C <- cbind(u,v,w)
rownames(C) <- c("1st", "2nd", "3rd", "4th")
C
```

```
##      u v w
## 1st  1 4 1
## 2nd  2 3 1
## 3rd  3 2 1
## 4th  4 1 1
```

Binding vectors: by rows

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
u <- 1:4
v = rev(u)
w <- rep(1,4)
D <- rbind(u,v,w)
colnames(D) <- c("1st", "2nd", "3rd", "4th")
D
```

##		1st	2nd	3rd	4th
##	u	1	2	3	4
##	v	4	3	2	1
##	w	1	1	1	1

Matrix operations

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- The sum of two compatible matrices is $A + B$
- The subtraction of two compatible matrices is $A - B$
- The product of two compatible matrices is $A \%*\% B$
- The transpose of a matrix A is $t(A)$
- The inverse of a square matrix, A , if it exists, is $solve(A)$

Inverse matrix

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

```
x <- c(1,2,3,5, 4, 1, 2,2,1)
A <- matrix(x, nrow = 3, ncol = 3)
A1 <- solve(A)
A1 %*% A
```

```
##           [,1] [,2]      [,3]
## [1,] 1.00e+00  0 2.22e-16
## [2,] 8.88e-16  1 1.11e-15
## [3,] 0.00e+00  0 1.00e+00
```

The result is the identity matrix, up to round-off errors.

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- We can use the function `all.equal()` to compare the results of `solve(A)` and `A1 %*% A` with the identity matrix:

```
all.equal(A1 %*% A, diag(3))
```

```
## [1] TRUE
```

- The function `diag()` can also be used to extract the diagonal elements of a matrix

```
diag(A)
```

```
## [1] 1 4 1
```

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
diag((1:5)^(.5))
```

##		[,1]	[,2]	[,3]	[,4]	[,5]
##	[1,]	1	0.00	0.00	0	0.00
##	[2,]	0	1.41	0.00	0	0.00
##	[3,]	0	0.00	1.73	0	0.00
##	[4,]	0	0.00	0.00	2	0.00
##	[5,]	0	0.00	0.00	0	2.24

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
diag(log(1):log(5))
```

```
##           [,1] [,2]  
## [1,]         0  0  
## [2,]         0  1
```

```
diag(log(1:5))
```

```
##           [,1] [,2] [,3] [,4] [,5]  
## [1,]         0 0.000  0.0  0.00 0.00  
## [2,]         0 0.693  0.0  0.00 0.00  
## [3,]         0 0.000  1.1  0.00 0.00  
## [4,]         0 0.000  0.0  1.39 0.00  
## [5,]         0 0.000  0.0  0.00 1.61
```

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

R has some built-in functions to deal with matrices. Consider

A

```
##           [,1] [,2] [,3]
## [1,]         1     5     2
## [2,]         2     4     2
## [3,]         3     1     1
```

- `rowSums(A)` = 8, 8, 5
- `colSums(A)` = 6, 10, 5
- `rowMeans(A)` = 2.667, 2.667, 1.667
- `colMeans(A)` = 2, 3.333, 1.667

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

The operator %*%

The operator %*% works differently on vectors and matrices.

- On vectors it computes the **dot product**
- On matrices, the matrix multiplication (matrix multiplication is a form of ordered, vectorized dot product)

```
a <- c(1,2,3)
```

```
b <- c(4,5,6)
```

```
a %*% b
```

```
##      [,1]
```

```
## [1,]  32
```

- The dot product can also be implemented as

```
sum(a*b)
```

```
## [1] 32
```

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Vector can be coerced to work as matrices; in this case, columns matrices:

```
as.matrix(a)
```

```
##           [,1]
```

```
## [1,]      1
```

```
## [2,]      2
```

```
## [3,]      3
```

```
t(as.matrix(b)) %*% as.matrix(a) # dot product
```

```
##           [,1]
```

```
## [1,]    32
```

More matrices

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
as.matrix(a) %*% t(as.matrix(b))
```

##		[,1]	[,2]	[,3]
##	[1,]	4	5	6
##	[2,]	8	10	12
##	[3,]	12	15	18

Dataframes

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- Statistical analysis is done using datasets. A dataset contains a certain number of variables and observations.
- It is a good practice to have each variable set as a column vector and each observation as a row vector.
- A dataframe, in R, is the data structure of an observed dataset.
- A dataframe can be thought of as a matrix in which different columns may have different data types.

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

**Working with
a Dataframe**

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Working with a Dataframe

Preliminary analysis

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

When loading a dataset for analysis, there are some aspects to consider.

- 1 Understand the data: what the dataset is about; what are its variables; how many observation the dataset contains.
- 2 Determine whether there are missing observations; some functions will not work properly otherwise.
- 3 Visualize some of its variables.

Import the dataset with RStudio

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Information about the dataset

- The dataset is taken from the [UCI, Machine Learning Repository](#) website.
- The dataset can be found [here](#).
 - Download the file, change its name to **cleve.csv** and move it to the project (working directory).
 - The names of the variables will be assigned later.
- The dataset will be called **cleve** hereinafter in the presentation.
- The dataset format is **csv** (comma separated variables).

Import the dataset with RStudio

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

- 1 Open an **R script** and save it in the project.
- 2 Write in the script

```
cleve <- read.csv("cleve.csv", header = FALSE)
```

and hit **CTRL + Enter** (Windows); **CMD + Enter** (Mac OSX) to execute.
 - a. If you get an error in the console, you may be not in the project (working directory)
- 3 Type

```
head(cleve)
```

 in the script and execute the instruction. It will show in the console the first **six** observations.

Working with the dataset

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

- Set the names of the variables. Copy the instructions and paste it in the script:

```
cleve.names <- c("age", "sex", "cp", "trestbps",  
                 "chol", "fbs", "restcg", "thalac",  
                 "exang", "oldpeak", "slope", "ca",  
                 "thal", "diagnostic")  
names(cleve) <- cleve.names
```

- The documentation of the dataset is found [here](#)
- The gender variable **sex**: 0 for females, 1 for males.

Working with the dataset

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

- To work with only one variable from the dataset, e.g., *age*, we can **extract** it by means of `$`.

```
age <- cleve$age
```

- On the other hand, if we work with several variables in a dataset, it is better to use `attach(namedataset)` at the beginning; once done, use `detach(namedataset)`.

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

**Preliminary
analysis**

Statistical
Inference

Linear
regression
models

Logit models

Time series

Preliminary analysis

Properties of the dataset

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

The dataset is a dataframe

```
class(cleve)
```

```
## [1] "data.frame"
```

with

```
dim(cleve)
```

```
## [1] 303 14
```

$nrow(cleve) = 303$ observations and $ncol(cleve) = 14$ variables.

Properties of the dataset

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

The names of the variables can also be obtained by `colnames(cleve)`.

The first six observations can be displayed by

```
head(cleve)
```

(Output omitted because it does not fit the slide.)

Slicing

Introduction
to R

Lino AA
Notaran Antonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Display the first 3 observations of the first, third and seventh through ninth variables:

```
cleve[1:3,c(1,3,7:9)]
```

##	age	cp	restcg	thalac	exang
## 1	63	1	2	150	0
## 2	67	4	2	108	1
## 3	67	4	2	129	1

or with (omitted for space)

```
cleve[1:2, c("age", "cp", "restcg",  
            "thalac", "exang")]
```

Slicing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Examples

- 1 Compute the number of individuals whose age is greater than, or equal to, 50 years:

```
length(cleve$age[cleve$age >= 50])
```

```
## [1] 216
```

- 2 Compute the number of individuals without a diagnosis of heart disease:

```
length(cleve$sex[cleve$diagnostic == 0])
```

```
## [1] 164
```

Remark The variable `diagnostic` is strictly positive if there is indication of a heart condition.

Slicing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Examples

- ③ Compute the number of individuals with a diagnosis of heart disease **and** with fasting blood sugar > 120 mg/dl

```
length(cleve$sex[cleve$diagnostic > 0 &  
               cleve$fbs == 1])
```

```
## [1] 22
```

- ④ Compute the number of individuals with a diagnosis of heart disease **or** with fasting blood sugar > 120 mg/dl

```
length(cleve$sex[cleve$diagnostic > 0 |  
               cleve$fbs == 1])
```

```
## [1] 162
```

Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Consider, e.g., the variable *age*. Compute:

- 1 the mean (average)

```
mean(cleve$age)
```

```
## [1] 54.4
```

- 2 the median

```
median(cleve$age)
```

```
## [1] 56
```

- 3 the interquartile range

```
IQR(cleve$age) # Q3 - Q1
```

```
## [1] 13
```

Descriptive Statistics

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

- ④ the summary of the principal statistics

```
summary(cleve$age)
```

##	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
##	29.0	48.0	56.0	54.4	61.0	77.0

Remark The function `summary()` does not return neither the variance nor the standard deviation.

- ⑤ Quantile distribution

```
quantile(cleve$age, c(.1, .25, .40, .60, .80))
```

##	10%	25%	40%	60%	80%
##	42	48	53	58	62

Descriptive Statistics

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

It is possible to apply the `summary()` function to a full dataset, or to several variables of it

```
summary(cleve[,c(1,5,8)])
```

##	age	chol	thalac
##	Min. :29.0	Min. :126	Min. : 71
##	1st Qu.:48.0	1st Qu.:211	1st Qu.:134
##	Median :56.0	Median :241	Median :153
##	Mean :54.4	Mean :247	Mean :150
##	3rd Qu.:61.0	3rd Qu.:275	3rd Qu.:166
##	Max. :77.0	Max. :564	Max. :202

(Only three variables are selected for space.)

Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Variance and standard deviation

- The variance (resp., standard deviation) is computed by `var()` (resp., `sd()`).
- If the variable has `NA` (missing values), then `var()`, `sd()` return `NA`:

```
var(cleve$thal)
```

```
## [1] NA
```

```
sd(cleve$thal)
```

```
## [1] NA
```


Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Variance

We can apply the function `var()` to a single variable or several of them; in the latter case, we obtain the variance-covariance matrix of the selected variables:

```
var(cleve[, c(1, 3, 5, 6)])
```

##		age	cp	chol	fbs
##	age	81.697	0.9037	97.787	0.3816
##	cp	0.904	0.9218	3.595	-0.0137
##	chol	97.787	3.5951	2680.849	0.1815
##	fbs	0.382	-0.0137	0.181	0.1269

Descriptive Statistics

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Standard deviation

The standard deviation `sd()`, on the other hand, can only be applied to a single variable:

```
sd(cleve$age)
```

```
## [1] 9.04
```

```
sd(cleve$chol)
```

```
## [1] 51.8
```

Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Standard deviation of a set of variables

We have to vectorize the function `sd()` by means of `apply()`:

```
apply(cleve[,11:13], 2, sd)
```

- The value `2` in the second parameter of the function `apply()` computes the standard deviation, `sd`, of each variable (column).
- The value `1` would compute the standard deviation of each row (observation).

Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Standard deviation of a set of variables

```
apply(cleve[,11:13], 2, sd)
```

```
## slope      ca    thal
```

```
## 0.616      NA     NA
```

There are missing values in the dataset.

Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Count and remove NA's

Let's count them:

```
sum(is.na(cleve))
```

```
## [1] 6
```

We can eliminate them (less than 2% of the observed values)

```
cleve <- na.omit(cleve)
```

```
sum(is.na(cleve))
```

```
## [1] 0
```

Remark

R works in memory (RAM), so only the dataset **cleve** loaded in memory is changed. The file **cleve.csv** with the original observations is not changed (reproducibility in research).

Descriptive Statistics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Standard deviation of a set of variables

```
apply(cleve[,11:13], 2, sd)
```

```
## slope      ca    thal
```

```
## 0.618 0.939 1.939
```

The variable **slope** has a slightly larger standard deviation now.

Contingency Tables

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Write a contingency table of gender and diagnosis of heart disease:

```
table(cleve$sex, cleve$diagnostic)
```

```
##  
##      0  1  2  3  4  
##  0 71  9  7  7  2  
##  1 89 45 28 28 11
```

Using the `with()` function:

```
with(cleve, table(age, diagnostic))
```

(Same result; output omitted for space.)

Contingency Tables

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Alternative to `table`

Using the `xtabs()` function:

```
with(cleve, xtabs(~ sex + diagnostic))
```

```
##      diagnostic
## sex  0  1  2  3  4
##    0 71  9  7  7  2
##    1 89 45 28 28 11
```


Estimated Frequencies

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Redefine the variable **diagnostic** as dummy, with value 1 if some heart problem is observed:

```
cleve$diagnostic[cleve$diagnostic >0] <- 1
```

Table of estimated frequencies:

```
with(cleve, xtabs(~ sex + diagnostic)/nrow(cleve))
```

##		diagnostic	
##	sex	0	1
##	0	0.2391	0.0842
##	1	0.2997	0.3771

Visualization: Barplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

```
barplot(table(cleve$diagnostic),  
         main = "Diagnostic (observed)")
```

Visualization: Barplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Visualization: Barplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models


Time series

Barplot with observed frequencies

```
barplot(table(cleve$diagnostic)/nrow(cleve),  
        main = "Diagnostic (frequencies)")
```

Visualization: Barplot

Barplot with observed frequencies



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Barplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series


Barplot with a contingency table

```
barplot(table(cleve$cp,  
              cleve$sex)/nrow(cleve),  
        main = "Chest pain by gender")
```

Visualization: Barplot

Barplot with a contingency table

Chest pain by gender



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Barplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series


Grouped barplots

```
barplot(table(cleve$cp,  
              cleve$sex)/nrow(cleve),  
        main = "Diagnostic (frequencies)",  
        beside = TRUE)
```


Visualization: Barplot

Grouped barplots

Chest pain by gender



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Barplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series


Grouped barplots with colors

```
barplot(table(cleve$cp,  
              cleve$sex)/nrow(cleve),  
        main = "Chest pain by gender",  
        beside = TRUE,  
        col = c("blue", "green", "red", "cyan"))
```

Visualization: Barplot

Grouped barplots with colors

Chest pain by gender



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Boxplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models


Time series

Variable “age”

```
boxplot(cleve$age)
```

Visualization: Boxplot

Variable “age”



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Boxplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models


Time series

Age as a function of gender

```
boxplot(age ~ sex, data = cleve)
```

Visualization: Boxplot

Age as a function of gender



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Boxplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models


Time series

Age as a function of gender, with positive diagnosis

```
boxplot(age ~ sex, data = cleve,  
         subset = diagnostic == 1)
```


Visualization: Boxplot

Age as a function of gender, with positive diagnosis



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Boxplot with notch

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Age as a function of gender


```
boxplot(age ~ sex, data = cleve,  
        notch = TRUE)
```

Justification

See, e.g., John M. Chalmers, William S. Cleveland, Beat Kleiner, Paul A. Tukey, "Graphical Methods for Data Analysis", Wadsworth International Group, Duxbury Press, 1983, pp. 60-63.

Visualization: Boxplot with notch

Age as a function of gender



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Boxplot with notch

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models


Time series

Age as a function of gender with positive diagnosis

```
boxplot(age ~ sex, data = cleve,  
        notch = TRUE,  
        subset = diagnostic == 1)
```

Visualization: Boxplot with notch

Age as a function of gender with positive diagnosis



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Boxplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models



Time series

Two graphs side by side

```
par(mfrow=c(1,2))  
boxplot(age ~ sex, data = cleve,  
        notch = TRUE,  
        subset = diagnostic == 0)  
boxplot(age ~ sex, data = cleve,  
        notch = TRUE,  
        subset = diagnostic == 1)  
par(mfrow = c(1,1))
```

Visualization: Boxplot

Two graphs side by side



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Visualization: Mosaicplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
mosaicplot(cleve$sex ~ cleve$diagnostic,  
            shade=F, color=T,  
            main = "Diagnosis by gender", xlab="Gender",  
            ylab = "Diagnostic")
```


Visualization: Mosaicplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Visualization: Mosaicplot

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
mosaicplot(cleve$cp ~ cleve$diagnostic,  
            shade=F, color=T,  
            xlab = "Chest pain", ylab = "Diagnostic",  
            main = "Diagnostic by Chest Pain")
```

The variable **cp** has four levels.

Visualization: Mosaicplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Visualization: Mosaicplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

```
mosaicplot(cleve$exang ~ cleve$diagnostic,  
            shade=F, color=T,  
            xlab = "Exercise-induced angina",  
            ylab = "Diagnostic",  
            main = "Diagnostic by Angina")
```

The variable **exang** (exercise induced angina): 1 = yes; 0 = no

Visualization: Mosaicplot

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Visualization of continuous variables

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Consider the variable *age*.

```
plot(cleve$age)
```

gives the scatterplot of the variable.

Visualization of continuous variables

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe


Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series



Visualization of continuous variables

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

```
plot(cleve$age, cleve$chol)
```


Visualization of continuous variables

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Visualization of continuous variables

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

With regression line:

```
plot(cleve$age, cleve$chol)
abline(lm(chol ~ age, data = cleve), col = "red")
```

Visualization of continuous variables

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Classification by K-means clustering

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

See the script `classification.R`

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

**Statistical
Inference**

Linear
regression
models

Logit models

Time series

Statistical Inference

Hypothesis testing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

We want to determine whether there is a difference in age between individuals with no heart condition and those with an indication of a heart condition.

```
age.pos <- cleve$age[cleve$diagnostic == 1]  
age.neg <- cleve$age[cleve$diagnostic == 0]
```

Formally

$$H_0 : \text{age.pos} = \text{age.neg}$$

$$H_1 : \text{age.pos} \neq \text{age.neg}$$

(significance level: $\alpha = .05$)

Hypothesis testing

95% Confidence interval

```
t.test(age.pos, age.neg, mu = 0)
```

```
##
```

```
## Welch Two Sample t-test
```

```
##
```

```
## data: age.pos and age.neg
```

```
## t = 4, df = 295, p-value = 6e-05
```

```
## alternative hypothesis: true difference in means is not equal to 0
```

```
## 95 percent confidence interval:
```

```
## 2.12 6.11
```

```
## sample estimates:
```

```
## mean of x mean of y
```

```
## 56.8 52.6
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Hypothesis testing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

99% Confidence interval

```
t.test(age.pos, age.neg, mu = 0, conf.level = .99)

##
##  Welch Two Sample t-test
##
## data:  age.pos and age.neg
## t = 4, df = 295, p-value = 6e-05
## alternative hypothesis: true difference in means is not equal to 0
## 99 percent confidence interval:
##  1.49 6.74
## sample estimates:
## mean of x mean of y
##      56.8      52.6
```


Hypothesis testing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

- The function `t.test()` uses by default the Welch *t*.test, with Welch-Satterthwaite correction for degrees of freedom.
- When the variances are equal, we can use

```
t.test(age.pos, age.neg, mu = 0,  
       var.equal = TRUE)
```

- The test for equal variances is

```
var.test(age.pos, age.neg, mu = 0, ratio = 1)
```

Hypothesis testing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Power calculation

Having rejected the null hypothesis, we compute the power of the test under the alternative

$$H_1 : \text{age.pos} - \text{age.neg} = 2.5$$

A power calculation needs four parameters, α , sd , n (sample size), δ (true difference in mean). It must also specify whether the test is one sided or two sided.

Hypothesis testing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Power calculation

```
power.t.test(n = nrow(cleve), sd =  
  sqrt(var(age.pos)+var(age.neg)),  
  sig.level = .05, delta = 2.5,  
  alternative = "two.sided"  
)
```

Hypothesis testing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Power calculation

```
##  
##      Two-sample t test power calculation  
##  
##              n = 297  
##            delta = 2.5  
##             sd = 12.4  
##    sig.level = 0.05  
##         power = 0.689  
## alternative = two.sided  
##  
## NOTE: n is number in *each* group
```

Hypothesis testing

Power calculation

Compute the sample size needed so that the power of the test is .90, when $\delta = 2.5$; $sd = 12.395$, with $\alpha = .05$ in a two sided alternative:

```
##  
##           Two-sample t test power calculation  
##  
##               n = 518  
##             delta = 2.5  
##             sd = 12.4  
##           sig.level = 0.05  
##             power = 0.9  
##           alternative = two.sided  
##  
## NOTE: n is number in *each* group
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Power curve

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

```
curve(power.t.test(n=50,delta = x,  
  sd = sqrt(var(age.pos)+var(age.neg)),  
  type="two.sample",  
  alternative="two.sided")$power,  
  from=.1, to=10, xlab="delta",  
  ylab="power")
```

Power curve

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe


Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

**Linear
regression
models**


Logit models

Time series

Linear regression models

Simple linear regression model

```
attach(faithful)
plot(waiting, eruptions)
```



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference


**Linear
regression
models**

Logit models

Time series

Simple linear regression model

```
plot(waiting, eruptions)
abline(lm(eruptions ~ waiting), col = "red")
```



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Simple linear regression model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Let us consider the model

$$eruptions = \beta_0 + \beta_1 waiting + u$$

```
slrm <- lm(eruptions ~ waiting, data = faithful)
```

Simple linear regression model

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

```
slrm.summary <- summary(slrn)  
slrm.summary$coefficients
```

##	Estimate	Std. Error	t value	Pr(> t)
## (Intercept)	-1.8740	0.16014	-11.7	7.36e-26
## waiting	0.0756	0.00222	34.1	8.13e-100

Simple linear regression model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Estimation

Estimate *eruptions*, when *waiting* = 90.

```
eruptions.fit.coef <- coefficients(slrn)
```

```
c <- c(1,90)
```

```
eruptions.fit.coef %*% c
```

```
##      [,1]
```

```
## [1,] 4.93
```

Simple linear regression model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Confidence interval

Find a 99% confidence interval for *eruptions*, when *waiting* = 90.

```
predict.lm(slrn, data.frame(waiting = 90),  
           interval = "confidence",  
           level = .99)
```

```
##      fit lwr  upr  
## 1 4.93 4.8 5.07
```

Simple linear regression model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Prediction interval

Find a 99% confidence interval for a prediction of *eruptions*, when *waiting* = 90.

```
predict.lm(slm, data.frame(waiting = 90),  
           interval = "prediction",  
           level = .99)
```

```
##      fit  lwr  upr  
## 1 4.93 3.64 6.23
```

Remark

After using a dataset, detach it:

```
detach(faithful)
```

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Download and then load the library **openintro**

```
install.packages("openintro") # download the library  
library(openintro)  
# load the library in the current session
```

Load the dataset **hsb2**:

```
data(hsb2)  
attach(hsb2)
```

The description of the variables is obtained typing

```
?hsb2
```

or can be found [here](#).

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 1

Estimate the standardized math score by race:

$$math = \beta_0 + \beta_1 race + u.$$

The variable *race* is **categorical**.

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 1

Model estimation

```
hsb2 <- read.csv("hsb2.csv")  
hsb2$race <- factor(c("black",  
                      "asian", "hisp", "white"))  
  
attach(hsb2)  
m1 <- lm(math ~ factor(race))  
summary.m1 <- summary(m1)
```

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 1

Model estimation: Extraction of the estimated coefficients

```
summary.m1$coefficients
```

##	Estimate	Std. Error	t value	Pr(>
## (Intercept)	54.40	1.32	41.082	2.93
## factor(race)black	-1.34	1.87	-0.716	4.75
## factor(race)hisp	-2.98	1.87	-1.591	1.13
## factor(race)white	-2.70	1.87	-1.442	1.51

Multiple linear regression

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Example 1

Use of vectorization

```
summary.m1$coefficients[2,]
```

##	Estimate	Std. Error	t value	Pr(> t)
##	-1.340	1.873	-0.716	0.475

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 2

Factor interaction

Estimate the standardized math score by gender, race.

R code

```
m2 <- lm(math ~ female*factor(race))  
summary.m2 <- summary(m2)
```

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 2

Estimated model

```
summary(m2)$coefficients
```

##	Estimate	Std. Error	t val
## (Intercept)	55.91	1.99	28.0
## female	-2.69	2.66	-1.0
## factor(race)black	-3.21	2.78	-1.1
## factor(race)hisp	-2.39	2.78	-0.8
## factor(race)white	-6.13	2.78	-2.2
## female:factor(race)black	3.37	3.75	0.8
## female:factor(race)hisp	-1.20	3.75	-0.3
## female:factor(race)white	6.25	3.75	1.6

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 3

Estimate the effect of the scores of reading skills, *read*; social studies, *socst*, y science, *science* on the score of mathematics, *math*.

Model

$$math = \beta_0 + \beta_1 read + \beta_2 socst + \beta_3 science + u.$$

R code

```
m3 <- lm(math ~ read + socst + science)
m3.estim <- summary(m3)
m3.estim$coefficients
```

Multiple linear regression

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Example 3

Estimated model

##	Estimate	Std. Error	t value	Pr(> t)
## (Intercept)	11.887	2.7937	4.25	3.24e-05
## read	0.313	0.0654	4.79	3.24e-06
## socst	0.154	0.0548	2.82	5.37e-03
## science	0.315	0.0599	5.25	3.96e-07

In-sample and out-of-sample validation

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

We randomly split the data and use one set to estimate the model and the rest to estimate the goodness of fit. To ensure reproducibility, we set the RNG seed to `set.seed(13)`.

We shall validate firstly the second model, `m2`, with interaction of factors.

To validate other models, the only change needed is to change below the code where the actual model is specified,
`linmodel.Train.`

In-sample and out-of-sample validation

Example 2

```
set.seed(13)
TrainRows <- sample(1:nrow(hsb2),
                    .8*nrow(hsb2), replace = FALSE)
Train <- hsb2[TrainRows,]
Valid <- hsb2[-TrainRows, ]
linmodel.Train <-
  lm(math ~ female*factor(race), data = Train)
mathPredic <-
  predict(linmodel.Train, Valid)
actual.predic <-
  data.frame(cbind(actual = Valid$math,
                    predicted = mathPredic))
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

In-sample and out-of-sample validation

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Example 2

Correlation matrix

```
corr.accuracy <- cor(actual.predic)
corr.accuracy
```

##	actual	predicted
## actual	1.0000	0.0959
## predicted	0.0959	1.0000

In-sample and out-of-sample validation

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Accuracy: Min-Max

The Min-Max method compute the mean of the minimum over the mean of the maximum.

Values very close to 1 (Min-Max > .90) denotes excellent accuracy.

R code

```
min.max.accuracy <-  
  mean(apply(actual.predic,  
              1, min)/apply(actual.predic, 1, max))  
min.max.accuracy  
## [1] 0.854
```

In-sample and out-of-sample validation

Introduction
to R

Lino AA
Notaran Antonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Accuracy: Mean Absolute Error (MAE)

If A_i are the actual (observed) values of the response and F_i are the forecast ones, then

$$MAE = \frac{1}{T} \sum_{i=1}^T |A_i - F_i|;$$

T is the sample size.

R code

```
mae <- mean(abs((actual.predic$predicted -  
                actual.predic$actual)))  
  
mae  
  
## [1] 8.41
```

In-sample and out-of-sample validation

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Accuracy: Mean Absolute Percentage Error (MAPE)

The mean absolute percentage error (MAPE) is defined as

$$MAPE = \frac{1}{T} \sum_{i=1}^T \left| \frac{A_i - F_i}{A_i} \right|.$$

- MAPE can be interpreted as the average percentage error.
- Sometimes, MAPE can be very large, even though the forecast is reasonably good. If, e.g., $A_i \approx 10^{-3}$ and $|F_i - A_i| \approx 10^{-1}$, entonces

$$\left| \frac{A_i - F_i}{A_i} \right| \approx 10^2$$

- If the forecast is exact, then $MAPE = 0$.

In-sample and out-of-sample validation

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

MAPE: R code

```
mape <- mean(  
  abs((actual.predic$predicted -  
        actual.predic$actual))/actual.predic$actual)  
mape
```

```
## [1] 0.169
```

On the average, the error is 16.9%.

In-sample and out-of-sample validation

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

RMSE

$$RMSE = \sqrt{\frac{1}{T} \sum_{i=1}^T (y_i - \hat{y}_i)^2}$$

- RMSE is the square root of the variance of the residuals.
- It can be interpreted as the standard deviation of the unexplained variance of the model.
- It has the same units as the response variable.

In-sample and out-of-sample validation

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

RMSE: R code

```
rmse <- sqrt(  
  mean(((actual.predic$predicted -  
          actual.predic$actual))^2)  
)  
rmse  
## [1] 9.72
```

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

The library `lmtest` permits to run tests to determine

- normality of errors;
- heteroskedasticity;
- serial autocorrelation, and
- correct specification of the model (RESET)

The library `sandwich` permits to estimate HC, HAC¹ standard errors.

We shall run the diagnostics on the model `m3` (Example 3).

¹HC: Heteroskedastic Consistent standard errors; HAC: Heteroskedastic and Autocorrelation Consistent errors.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Normality

There are several normality test available.

- The Shapiro-Wilk test is available in the **base** library (loaded by default), but it cannot be applied to vectors with more than 5,000 observations. For this reason, we also present the Jarque-Bera test.
- The normality of errors is less of a concern when the sample size is sufficiently large.

Hyopthesis test

H_0 : errors are normal

H_1 : errors are not normal

$(\alpha = .05)$

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Normality: Shapiro-Wilk test

```
shapiro.test(m3$residuals)
```

```
##
```

```
## Shapiro-Wilk normality test
```

```
##
```

```
## data: m3$residuals
```

```
## W = 1, p-value = 0.5
```

Conclusion

There is no evidence of non-normality of errors.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Jarque-Bera test

The Jarque-Bera test is available in the library **tseries**:

```
library(tseries)
jarque.bera.test(m3$residuals)
```

```
##
## Jarque Bera Test
##
## data:  m3$residuals
## X-squared = 3, df = 2, p-value = 0.2
```

Conclusion

There is no evidence of non-normality of errors.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

QQ plot

The QQ plot compares the observed quantiles of the errors to the theoretical quantiles of the standard normal distribution.


```
qqnorm(m3$residuals)
qqline(m3$residuals, col = "red")
```

We can see that the distribution of the errors follows pretty closely the standard normal distribution.

Diagnostics

QQ plot

Normal Q-Q Plot



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Heteroskedasticity

The underlying hypothesis test is

H_0 : the model is homoskedastic

H_1 : the model is heteroskedastic

Function `bptest()`

Apply the function `bptest()` to the fitted model.

```
library(lmtest)  
bptest(m3)
```


Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Heteroskedasticity

```
bptest(m3)
```

```
##  
## studentized Breusch-Pagan test  
##  
## data: m3  
## BP = 9, df = 3, p-value = 0.03
```

Conclusion

- There is evidence of heteroskedasticity.
- If there is evidence of autocorrelation of errors, then neither OLS nor HC standard errors are correct.

Diagnostics

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Serial autocorrelation

The purpose of the test is to determine whether there is any linear dependence among terms of the innovations.

We can apply the Durbin-Watson test, `dwtest()`, and the Breusch-Godfrey test, `bgtest()`.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Serial autocorrelation

```
dwtest(m3, alternative = "two.sided")  
  
##  
## Durbin-Watson test  
##  
## data: m3  
## DW = 2, p-value = 0.3  
## alternative hypothesis: true autocorrelation is no
```

Result

There is no evidence that $\text{corr}(u_t, u_{t-1}) \neq 0$.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Serial autocorrelation

```
bgtest(m3, order = 10)
```

```
##
```

```
## Breusch-Godfrey test for serial correlation of order
```

```
##
```

```
## data: m3
```

```
## LM test = 12, df = 10, p-value = 0.3
```

Result

There is no evidence of linear dependence among the first 10 terms of the errors.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Heteroskedasticity

We have detected heteroskedasticity, but not autocorrelation of the errors, so HC standard errors are appropriate.

HC standard errors are obtained using the function `coeftest()` passing the parameter `vcov. = vcovHCa`

```
library(sandwich)  
coeftest(m3, vcov. = vcovHC)
```

All controls are still significant.

^aThere are several variants of HC standard errors.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Heteroskedasticity

```
##
```

```
## t test of coefficients:
```

```
##
```

##	Estimate	Std. Error	t value	Pr(> t)	
## (Intercept)	11.8865	2.4585	4.83	2.7e-06	*
## read	0.3134	0.0600	5.22	4.5e-07	*
## socst	0.1542	0.0572	2.70	0.0076	*
## science	0.3145	0.0567	5.54	9.5e-08	*
## ---					

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.'
```

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

RESET: Hypothesis test

H_0 : the model does not need nonlinear combination of controls

H_1 : the model needs nonlinear combination of controls

- Typically, quadratic and cubic powers are considered.
- The test statistics may need heteroskedastic (HC; HAC) corrections.

R code

```
resettest(m3, power = 2:3, vcov = vcovHC)
```

Diagnostics

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

RESET

```
##  
## RESET test  
##  
## data: m3  
## RESET = 1, df1 = 2, df2 = 196, p-value = 0.3
```

Conclusion

There is no need of nonlinear combinations of regressors.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Plots

We can also apply `plot()` to a `lm()` object to obtain these tests.

It is an interactive plot and it is convenient to do it in the console.

```
plot(m3)
```

Plots: documentation

It can be found [here](#) (check “Details”).

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Plots: Leverage and influential observations

The concepts of leverage and influential observations can be used as a proxy for finding whether a given observation is an outlier.

- Leverage is a measure of how far the independent variables of an observation are from those of other observations.
- An influential observation is one whose deletion will affect greatly the estimate.

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Plots: Leverage and influential observations

- The leverage in a linear regression can be computed using the projection matrix (F. Hayashi, 2000, *Econometrics*, Princeton University Press, pp. 21-23).
- The Cook's distance defined in the next slide can be often used as a measure of observations with high leverage; Cook's distance can also be used to detect highly influential observations.
- In R, the **residual-leverage** plot draws a red, dashed line identifying observations with Cook's distance greater than .5.
- In R, observations with leverage greater than 1 are omitted with a warning; check Residual-Leverage plot in "Details" [here](#),

Diagnostics

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Plots

Cook's distance

The Cook's distance is a tool that is used to check whether a single observation has a large influence on the estimate of the linear regression:

$$D_i = \frac{\sum_{j=1}^T (\hat{y}_j - \hat{y}_{j(i)})^2}{(k+1)TSS}$$

where $\hat{y}_{j(i)}$ is the fitted response value when excluding i ; TSS is the total sum of square (mean square error):

$$TSS = (1/T) \sum_{i=1}^T (y_i - \hat{y}_i)^2.$$

```
detach(hsb2)
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Logit models

Logit model

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Estimate the probability of a positive diagnosis of heart disease, controlling for cholesterol levels and age:

$$\text{logit}(\textit{diagnostic}) = \beta_0 + \beta_1 \textit{chol} + \beta_2 \textit{age},$$

where

$$\text{logit}(\textit{diagnostic}) = \log \left(\frac{\textit{diagnostic}}{1 - \textit{diagnostic}} \right)$$

is the **log-odds** of a positive diagnosis.

Thus, e.g., β_1 is the change of the log-odds of a positive diagnosis with respect to a unit increase of *chol*.

Logit model

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Estimation

```
modelo.logit <- glm(diagnostic ~ chol + age,  
                    data = cleve,  
                    family = "binomial")  
summary(modelo.logit)
```

Logit model

Estimation

```
##  
## Call:  
## glm(formula = diagnostic ~ chol + age, family = "b  
##  
## Deviance Residuals:  
##      Min        1Q      Median        3Q        Max   
## -1.593   -1.085   -0.815    1.158    1.729   
##  
## Coefficients:  
##              Estimate Std. Error z value Pr(>|z|)   
## (Intercept) -3.32713    0.89145  -3.73   0.00019 *   
## chol         0.00147    0.00237   0.62   0.53411   
## age          0.05129    0.01405   3.65   0.00026 *   
## ---  
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.'  
##
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Logit model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Goodness of fit

A measure of goodness of fit is a comparison of the estimated logit model to the null model

$$\text{logit}(\textit{diagnostic}) = \beta_0$$

The comparison is done by the hypothesis test

H_0 : The null model fits better the data

H_1 : The logit model fits better the data

($\alpha = .05.$)

Logit model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Goodness of fit

The test statistics is the **difference of deviations**, which has χ^2 distribution, with `df.null - df.residual` degrees of freedom:

```
with(modelo.logit,  
      pchisq(null.deviance - deviance,  
              df.null - df.residual,  
              lower.tail = FALSE))  
## [1] 0.000322
```

Conclusion

The logit model better fit the data.

Logit model

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

Diagnosis of heart disease ($diagnostic = 1$), if the estimated value of $diagnostic$ in the logit model is greater than $mean(diagnostic)$.

Validation

```
probs.predicted <- predict(modelo.logit,  
                           type = "response")  
mu <- mean(cleve$diagnostic)  
probs.predicted2 <-  
  ifelse(probs.predicted > mu, 1, 0)  
table(cleve$diagnostic,  
      probs.predicted2)/nrow(cleve)
```

Logit model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Off-diagonal terms are false positives and false negatives.

Validation

```
##      probs.predicted2
##           0         1
##  0 0.323 0.215
##  1 0.148 0.313
```

There is a 21.5% of false positives and a 14.8% of false negatives.

Logit model

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Diagnosis of heart disease ($diagnostic = 1$), if the estimated value of $diagnostic$ in the logit model is greater than .5.

Validation

```
probs.predicted3 <-  
  ifelse(probs.predicted > .5, 1, 0)  
table(cleve$diagnostic,  
      probs.predicted3)/nrow(cleve)
```

```
##      probs.predicted3  
##           0         1  
##  0 0.374 0.165  
##  1 0.226 0.236
```

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Time series

Libraries

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Needed libraries are `forecast`, `tseries`.

Download them,

```
install.packages("forecast", "tseries")
```


and then load them in your session

```
library(forecast)  
library(tseries)
```

Time series

Plots (Multiplicative model)

```
plot.ts(JohnsonJohnson)
```



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models


Logit models

Time series

Time series

Plots (Additive model)

```
plot.ts(log(JohnsonJohnson))
```



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Let y_t be a stochastic process.

The idea of exponential smoothing is to compute the *one-step ahead forecast*, $\hat{y}_{T+1|T}$, as a weighted mean of the previous observed terms:

$$\begin{aligned}\hat{y}_{T+1|T} &= \alpha y_T + \alpha(1 - \alpha)y_{T-1} + \cdots \\ &= \alpha y_T + (1 - \alpha)\hat{y}_{T|T-1}, \quad 0 \leq \alpha < 1;\end{aligned}$$

rearranging terms,

$$\hat{y}_{t+1|t} = \alpha y_t + (1 - \alpha)\hat{y}_{t|t-1},$$

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

which gives

$$\begin{aligned}\hat{y}_{t+1|t} &= \alpha y_t + (1 - \alpha)\hat{y}_{t|t-1} = \hat{y}_{t|t-1} + \alpha(y_t - \hat{y}_{t|t-1}) \\ &= \hat{y}_{t|t-1} + \alpha e_t,\end{aligned}$$

where $e_t = y_t - \hat{y}_{t|t-1}$ is the forecast error.

The value α is estimated optimizing the errors squared.

The work by Holt & Winters allowed the inclusion of seasonal, s_t , and trending, b_t , terms, beside the level term, ℓ_t .

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Holt-Winters Modeling (Additive model)

$$y_{t+h|t} = \ell_t + hb_t + s_{t-m+h_m^+}$$

$$\ell_t = \alpha(y_t - s_{t-m}) + (1 - \alpha)(\ell_{t-1} - b_{t-1})$$

$$b_t = \beta^*(\ell_t - \ell_{t-1}) + (1 - \beta^*)b_{t-1}$$

$$s_t = \gamma(y_t - \ell_{t-1} - b_{t-1}) + (1 - \gamma)s_{t-m}$$

where m denotes the seasonality period (per year)

The symbol

$$h_m^+ = \lfloor (h - 1) \bmod(m) \rfloor + 1$$

makes sure that the estimation of the seasonality is the last year of the sample.

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Estimation

```
logJJ.forecast <- HoltWinters(  
  log(JohnsonJohnson), beta = TRUE, gamma = TRUE)  
logJJ.forecast
```

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Estimation

```
logJJ.forecast$coefficients[1]
```

```
##      a
```

```
## 2.61
```

```
logJJ.forecast$SSE # measure of estimate error
```

```
## [1] 0.661
```

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Plots


```
plot(logJJ.forecast)
```

The original series is plotted in black and the forecast is in red.

Exponential smoothing

Plots

Holt-Winters filtering



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Estimate with an initial value

```
logJJ.forecast2 <- HoltWinters(  
  log(JohnsonJohnson), beta = TRUE, gamma =  
    TRUE, l.start = .91) # arbitrary initial value  
logJJ.forecast2
```

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Estimate with an initial value

```
logJJ.forecast2$coefficients[1]
```

```
##      a
```

```
## 2.68
```

```
logJJ.forecast$coefficients[1]
```

```
##      a
```

```
## 2.61
```

```
logJJ.forecast$SSE # measure of estimate error
```

```
## [1] 0.661
```

```
logJJ.forecast2$SSE
```

```
## [1] 6.01
```

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Comparing plots


```
plot(logJJ.forecast2)  
lines(logJJ.forecast$fitted[,1], col = "green")
```

The object is a matrix whose columns are, respectively, the fitted time series; its level part; its trend part and the seasonality. We select above the fitted part.

Exponential smoothing

Comparing plots

Holt-Winters filtering



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Forecast

Forecast can be performed using the library **forecast**

```
library(forecast)
```

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Forecast


```
logJJ.forecast8095 <-  
  forecast.HoltWinters(logJJ.forecast, h=8)
```

- We use the first estimate, `logJJ.forecast`, as it is proven to be the better.
- The parameter `h=8` will forecast the estimate **eight** periods in the future (two years).
- The forecast also plots a confidence interval (80%; 95% is the default).

Exponential smoothing

Forecast: Plot

Forecasts from HoltWinters



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series


Forecast: Plot

```
logJJ.forecast8599 <- forecast(  
  logJJ.forecast, h=8, level = c(85,99))  
plot(logJJ.forecast8599)
```


Exponential smoothing

Forecast: Plot

Forecasts from HoltWinters



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Diagnostics

```
library(tseries)
ts8095.fitted <- as.ts(logJJ.forecast8095$fitted)
ts8095.fitted <- na.omit(ts8095.fitted)
ts8095.residuals <-
  as.ts(logJJ.forecast8095$residuals)
ts8095.residuals <-
  na.omit(as.ts(logJJ.forecast8095$residuals))
```

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series


Diagnostics: ACF

```
acf(ts8095.residuals)
```

Exponential smoothing

Diagnostics: ACF

Series ts8095.residuals



Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Diagnostics: Ljung-Box Test

```
Box.test(ts8095.residuals, lag = 20)
```

```
##
```

```
## Box-Pierce test
```

```
##
```

```
## data: ts8095.residuals
```

```
## X-squared = 25, df = 20, p-value = 0.2
```

Conclusion

We do not reject the null hypothesis of no autocorrelation (for the first 20 lags).

Exponential smoothing

Introduction
to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction
to R(Studio)

Data Types
and Data
Structure

Working with
a Dataframe

Preliminary
analysis

Statistical
Inference

Linear
regression
models

Logit models

Time series

Diagnostics: Augmented Dickey-Fuller Test

```
adf.test(ts8095.fitted)
```

```
##
```

```
## Augmented Dickey-Fuller Test
```

```
##
```

```
## data: ts8095.fitted
```

```
## Dickey-Fuller = -1, Lag order = 4, p-value = 0.8
```

```
## alternative hypothesis: stationary
```

Conclusion

There is evidence that the errors are not white noise.

Box-Jenkins approach

Introduction to R

Lino AA
Notarantonio
(lino@tec.mx)

Introduction to R(Studio)

Data Types and Data Structure

Working with a Dataframe

Preliminary analysis

Statistical Inference

Linear regression models

Logit models

Time series

See the script `BoxJenkins.R`