Data wrangling with Pandas: statistics and reshaping

Lino Galiana
Version of November 2, 2026

After seeing how to associate datasets through joins, this chapter continues exploring the data scientist's toolbox with two classic operations: group descriptive statistics and data reshaping. It also introduces building communication-ready tables with `great_tables`.

⚠️ **Automatically generated PDF.** This document is produced from the course website and may contain formatting issues. For an up-to-date version adapted to your reading, visit the course page: pythonds.linogaliana.fr.

Table of contents

1 Introduction **1**
1.1 Data 2
2 Descriptive statistics by group **3**
2.1 Principle 3
2.2 Illustration 1: counting by group 4
2.3 Illustration 2: aggregates by group 6
3 Application **7**
4 Restructuring datasets **8**
4.1 Principle 8
4.2 Application 9
5 Formatting descriptive statistics tables **10**
Informations additionnelles 12
Bibliography **13**

Skills to be acquired by the end of this chapter

- How to construct fine aggregate statistics using `Pandas` methods;
- Know how to reshape your data from *long* to *wide* format (and vice versa);
- Create attractive tables to communicate aggregated results.

1 Introduction

The previous chapter showed how to enrich a dataset by associating it with another source through a join. We now have two datasets that have been made consistent with one another: the Ademe greenhouse gas emissions data (`emissions`) and the Insee Filosofi framing data (`filosofi`).

This chapter will use this association to deepen our understanding of the data through two complementary operations:

- group descriptive statistics;
- reshaping data between *long* and *wide* formats.

Finally, we will see how to build, from these statistics, polished communication tables using the `great_tables` package.

1.1 Data

We start again from the same datasets as in the chapter on joins: the Ademe municipal emissions data (`emissions`) and the Insee Filosofi data (`filosofi`), enriched with one another. The code below, already explained in detail in the previous chapter, retrieves these datasets again:

```
import requests
import pandas as pd

def get_melodi(dataset, dimension, code, value_name, time_period, geo_level="COM"):

  url = f"https://api.insee.fr/melodi/data/{dataset}"

  params = {
    "GEO": geo_level,
    dimension: code,
    "TIME_PERIOD": time_period,
    "maxResult": 40000,
  }

  response = requests.get(url, params=params, timeout=60)
  response.raise_for_status()
  observations = response.json()["observations"]

  return pd.DataFrame(
    {
      "CODGEO": obs["dimensions"]["GEO"].split("-")[-1],
      value_name: obs["measures"]["OBS_VALUE_NIVEAU"].get("value"),
    }
    for obs in observations
  )

niveau_vie = get_melodi("DS_FILOSOFI_CC", "FILOSOFI_MEASURE", "MED_SL", "NIVVIE_MEDIAN", 2023)
taux_pauvrete = get_melodi("DS_FILOSOFI_CC", "FILOSOFI_MEASURE", "PR_MD60", "TAUX_PAUVRETE",
2023)
population = get_melodi("DS_POPULATIONS_HISTORIQUES", "POPREF_MEASURE", "PMUN", "POPULATION",
2023)

url_cog_2023 = "https://www.insee.fr/fr/statistiques/fichier/6800675/v_commune_2023.csv"
url_backup = "https://minio.lab.sspcloud.fr/lgaliana/data/python-ENSAE/cog_2023.csv"

try:
  cog_2023 = pd.read_csv(url_cog_2023)
except requests.exceptions.Timeout:
  cog_2023 = pd.read_csv(url_backup)

noms_communes = (
  cog_2023
  .loc[cog_2023["TYPECOM"] == "COM", ["COM", "LIBELLE"]]
  .rename(columns={"COM": "CODGEO", "LIBELLE": "LIBGEO"})
)

filosofi = (
  niveau_vie
```

```
  .merge(taux_pauvrete, on="CODGEO", how="outer")
  .merge(population, on="CODGEO", how="outer")
  .merge(noms_communes, on="CODGEO", how="left")
  [["CODGEO", "LIBGEO", "POPULATION", "NIVVIE_MEDIAN", "TAUX_PAUVRETE"]]
)

filosofi["POPULATION"] = filosofi["POPULATION"].astype(int)
filosofi["dep"] = filosofi["CODGEO"].str[:2]
```

```
import pandas as pd

url   =   "https://data.ademe.fr/data-fair/api/v1/datasets/igt-pouvoir-de-rechauffement-global/
convert"
emissions = pd.read_csv(url)
emissions["dep"] = emissions["INSEE commune"].str[:2]

emissions.head(2)
```

	INSEE commune	Commune	Agriculture	Autres transports	Autres transports international	CO2 biomasse hors-total	Déchets	Energie	Industrie hors-énergie	Résidentiel	Routier	Tertiaire	dep
0	01001	L'ABERGEMENT-CLEMENCIAT	3711.425991	NaN	NaN	432.751835	101.430476	2.354558	6.911213	309.358195	793.156501	367.036172	01
1	01002	L'ABERGEMENT-DE-VAREY	475.330205	NaN	NaN	140.741660	140.675439	2.354558	6.911213	104.866444	348.997893	112.934207	01

We will also need the following *packages*

To obtain reproducible results, you can set the seed of the pseudo-random number generator.

```
import numpy as np
np.random.seed(123)
```

2 Descriptive statistics by group

2.1 Principle

In the introductory chapter, we saw how to obtain an aggregated statistic easily with `Pandas`. However, it is common to have data with intermediate analysis strata that are relevant: geographical variables, membership in socio-demographic groups related to recorded characteristics, temporal period indicators, etc. To better understand the structure of the data, data scientists are often led to construct descriptive statistics on sub-groups present in the data.

For example, we previously constructed emission statistics at the national level. But what about the emission profiles of different departments? To answer this question, it will be useful to aggregate our data at the departmental level. This will give us different information from the initial dataset (municipal level) and the most aggregated level (national level).

In `SQL`, it is very simple to segment data to perform operations on coherent blocks and recollect results in the appropriate dimension. The underlying logic is that of *split-apply-combine*, which is adopted by data manipulation languages, including `pandas` which is no exception.

The following image, from this site, well represents how the `split-apply-combine` approach works:




Figure 1: Split-apply-combine (Source: unlhcc.github.io)

In `Pandas`, we use `groupby` to segment the data according to one or more axes (this tutorial on the subject is particularly useful). All the aggregation operations (counting, averages, etc.) that we saw earlier can be applied by group.

Technically, this operation involves creating an association between labels (values of group variables) and observations. Using the `groupby` method does not trigger operations until a statistic is implemented; it simply creates a formal relationship between observations and groupings that will be used later:

```
filosofi.groupby('dep').__class__
```

```
pandas.api.typing.DataFrameGroupBy
```

As long as we do not call an action on a `DataFrame` by group, such as `head` or `display`, `pandas` performs no operations. This is called *lazy evaluation*. For example, the result of `df.groupby('dep')` is a transformation that has not yet been evaluated:

```
filosofi.groupby('dep')
```

```
<pandas.api.typing.DataFrameGroupBy object at 0x7f95cd301a90>
```

2.2 Illustration 1: counting by group

To illustrate the application of this principle to counting, we can count the number of municipalities by department in 2023 (this statistic changes every year due to municipal mergers). For this, we simply take the reference of French municipalities from the official geographical code (COG) and count by department using `count`:

With this dataset, without resorting to group statistics, we can already know how many municipalities, departments, and regions we have in France, respectively:

```
communes = cog_2023.loc[cog_2023['TYPECOM']=="COM"]
communes.loc[:, ['COM', 'DEP', 'REG']].nunique()
```

Line 1

We restrict to the status “Commune” because this file also contains Insee codes for other statuses, such as the “Municipal Arrondissements” of Paris, Lyon, and Marseille.

```
COM    34945
DEP      101
REG       18
dtype: int64
```

Now, let’s look at the departments with the most municipalities. It is the same counting function where we play, this time, on the group from which the statistic is calculated.

Calculating this statistic is quite straightforward when you understand the principle of calculating statistics with `Pandas`:

```
communes = cog_2023.loc[cog_2023['TYPECOM']=="COM"]
communes.groupby('DEP').agg({'COM': 'nunique'})
```

	COM
DEP	
01	392
02	798
03	317
04	198
05	162
...	...
971	32
972	34
973	22
974	24
976	17

In SQL, we would use the following query:

```
SELECT dep, COUNT DISTINCT "COM" AS COM
FROM communes
GROUP BY dep
WHERE TYPECOM == 'COM';
```

The output is an indexed `Series`. This is not very convenient as we mentioned in the previous chapter. It is more practical to transform this object into a `DataFrame` with `reset_index`. Finally, with `sort_values`, we obtain the desired statistic:

```
(
    communes
    .groupby('DEP')
    .agg({'COM': 'nunique'})
    .reset_index()
```

```
    .sort_values('COM', ascending = False)
)
```

	DEP	COM
62	62	890
1	02	798
80	80	772
57	57	725
76	76	708
...	...	...
96	971	32
99	974	24
98	973	22
100	976	17
75	75	1

2.3 Illustration 2: aggregates by group

To illustrate aggregates by group, we can use the Insee `filosofi` dataset and sum the `POPULATION` variable.

To calculate the total for the whole of France, we can do it in two ways:

```
filosofi['POPULATION'].sum()* 1e-6
```

```
np.float64(68.09428)
```

```
filosofi.agg({"POPULATION": "sum"}).div(1e6)
```

```
POPULATION    68.09428
dtype: float64
```

where the results are reported in millions of people. The logic is the same when doing group statistics, it's just a matter of replacing `filosofi` with `filosofi.groupby('dep')` to create a partitioned version of our dataset by department:

```
filosofi.groupby('dep')['POPULATION'].sum()
```

Line 1

With this approach, you need to pay attention to the order of operations: first, perform the `groupby` and then select the column of interest

```
dep
01     679344
02     523342
03     333298
04     168054
05     143467
```

```
      ...
92    1654712
93    1704316
94    1426929
95    1281653
97    1928465
Name: POPULATION, Length: 97, dtype: int64
```

```
filosofi.groupby('dep').agg({"POPULATION": "sum"})
```

	POPULATION
dep	
01	679344
02	523342
03	333298
04	168054
05	143467
...	...
92	1654712
93	1704316
94	1426929
95	1281653
97	1928465

The second approach is more practical because it directly gives a `Pandas` `DataFrame` and not an unnamed indexed series. From this, a few basic manipulations can suffice to have a shareable table on departmental demographics. However, this table would be somewhat rudimentary as we currently only have the department numbers. To get the names of the departments, we would need to use a second dataset and merge the common information between them (in this case, the department number): this is exactly the join principle we implemented in the previous chapter.

3 Application

This application exercise uses the `Ademe` dataset named `emissions` previously discussed.

Exercise 1: Group Aggregations

1. Calculate the total emissions of the “Residential” sector by department and compare the value to the most polluting department in this sector. Draw insights from the reality that this statistic reflects.
2. Calculate the total emissions for each sector in each department. For each department, calculate the proportion of total emissions coming from each sector.

Hint for this question

- *“Group by”* = `groupby`
- *“Total emissions”* = `agg({**: "sum"})`

In question 1, the result should be as follows:

	dep	Résidentiel	Résidentiel (% valeur max)
59	59	3.498347e+06	1.000000
75	75	1.934580e+06	0.552998
69	69	1.774653e+06	0.507283
62	62	1.738090e+06	0.496832
57	57	1.644192e+06	0.469991

This ranking may reflect demographics rather than the process we wish to measure. Without the addition of information on the population of each département to control for this factor, it is difficult to know whether there is a structural difference in behavior between the inhabitants of Nord (département 59) and Moselle (département 57).

At the end of question 2, let's take the share of emissions from agriculture and the tertiary sector in departmental emissions:

dep	Agriculture	Autres transports	Autres transports international	CO2 biomasse hors-total	Déchets	Energie	Industrie hors-énergie	Résidentiel	Routier	Tertiaire	...	Part Agriculture	Part Autres transports	Part Autres transports international	Part CO2 biomasse hors-total	Part Déchets	Part Energie	Part Industrie hors-énergie	Part Résidentiel	Part Routier	Part Tertiaire
23	1.430606e+06	5060.057601	0.000000	210196.604589	26550.858041	9752.578164	28626.245699	154197.515156	434767.869975	70733.245013	...	60.855172	0.215326	0.000000	8.944716	1.129846	0.415012	1.218163	5.710647	18.501132	3.009986
48	7.510594e+05	5697.938112	0.000000	70905.948092	26011.591018	6065.340741	17803.285591	61033.998305	253618.488432	43661.121359	...	60.772448	0.461052	0.000000	5.757238	2.104744	0.490781	1.440564	4.938605	20.521701	3.532867
15	1.539204e+06	8261.874450	18.804572	228415.892777	44814.875202	13138.432196	85214.659284	128315.601994	443832.903418	84564.615635	...	59.761414	0.320777	0.000730	8.868517	1.739990	0.510115	3.308560	4.982005	17.232356	3.275556
12	2.122331e+06	13796.608978	3124.844800	331420.983449	52412.681268	35495.484754	112897.690887	268862.654280	795413.985637	170211.845832	...	54.336847	0.353227	0.080004	8.485186	1.341893	0.906467	2.890457	6.883541	20.364540	4.357839
32	1.026604e+06	4599.824552	0.000000	201732.703762	50950.668326	16651.432546	53468.498055	158218.000190	446345.993580	105662.674213	...	49.732924	0.222835	0.000000	9.772766	2.468261	0.806644	2.590235	7.664734	21.622845	5.118737

dep	Agriculture	Autres transports	Autres transports international	CO2 biomasse hors-total	Déchets	Energie	Industrie hors-énergie	Résidentiel	Routier	Tertiaire	...	Part Agriculture	Part Autres transports	Part Autres transports international	Part CO2 biomasse hors-total	Part Déchets	Part Energie	Part Industrie hors-énergie	Part Résidentiel	Part Routier	Part Tertiaire
75	0.000000	42216.829025	1.837660e+02	1.186577e+06	27358.781206	147965.117571	434314.469384	1.934580e+06	1.625583e+06	1.331659e+06	...	0.000000	0.627255	0.002730	17.630092	0.406495	2.198457	6.453018	28.743870	24.152808	19.785275
94	2259.429643	218992.353559	3.146283e+05	6.914959e+05	213619.661516	763413.230740	467189.038927	1.356894e+06	1.169432e+06	7.636502e+05	...	0.043801	4.167781	5.987888	13.158562	4.065530	1.452898	8.891367	25.443275	22.256193	14.533505
92	91.408184	12360.794839	2.101194e+02	1.067889e+06	264497.880711	242842.018012	706597.424867	1.466794e+06	1.198420e+06	8.360132e+05	...	0.001577	0.212930	0.003625	18.425550	4.563695	4.190041	12.191761	25.308332	20.677765	14.424724
93	2018.470982	59617.086124	1.101400e+06	7.259516e+05	252166.943778	102837.663903	435216.360990	1.316452e+06	1.396911e+06	8.630178e+05	...	0.032277	0.953326	17.612287	11.608558	4.032555	1.644458	6.927483	21.051146	22.337751	13.800359
83	151715.557862	21772.374976	2.854770e+04	5.795888e+05	253522.964403	47044.063669	139710.930613	5.938382e+05	1.944266e+06	5.610549e+05	...	3.527399	0.506209	0.663736	13.475487	5.429428	1.093778	3.248291	13.806786	45.204334	13.044551

These results are quite logical; rural departments have a larger share of their emissions from agriculture, while urban departments have higher emissions from the tertiary sector, which is related to the higher density of these areas.

With these statistics, we progress in understanding our dataset and, consequently, the nature of CO2 emissions in France. Descriptive statistics by group help us better grasp the spatial heterogeneity of our phenomenon.

However, we would remain limited in our ability to interpret these statistics without additional information: a département could look like a low emitter simply because it is sparsely populated. This is exactly the kind of limitation we resolved thanks to enriching our data with a join against the Filosofi data (see in particular the computation of a carbon footprint per capita in the previous chapter).

4 Restructuring datasets

4.1 Principle

When we have multiple pieces of information for the same individual or group, we generally find two types of data structures:


- **Wide** format: the data contains repeated observations for the same individual (or group) in different columns.
- **Long** format: the data contains repeated observations for the same individual in different rows, with a column distinguishing the observation levels.

An example of the distinction between the two can be taken from Hadley Wickham's reference book, *R for Data Science*:



Figure 2: Wide and Long Data Formats (Source: *R for Data Science*)

The following cheat sheet will help remember the functions to apply if needed:



Switching from a *wide* format to a *long* format (or vice versa) can be extremely practical because certain functions are more suitable for one form of data than the other.

Generally, with `Python` as with `R`, **long formats are often preferable**. Wide formats are rather designed for spreadsheets like `Excel`, where we have a limited number of rows to create pivot tables from.

4.2 Application

The ADEME data, and the Insee data as well, are in the *wide* format. The next exercise illustrates the benefit of converting from *long* to *wide* before creating a plot with the `plot` method seen in the introductory chapter.

Exercice 2: Restructuring Data: Wide to Long

1. Create a copy of the ADEME data by doing `df_wide = emissions.copy()`
2. Restructure the data into the *long* format to have emission data by sector while keeping the commune as the level of analysis (pay attention to other identifying variables).
3. Sum the emissions by sector and represent it graphically.
4. For each department, identify the most polluting sector.

5 Formatting descriptive statistics tables

A `Pandas` DataFrame is automatically formatted when viewed from a notebook as a minimally styled HTML table. This formatting is convenient for viewing data, a necessary task for data scientists, but it doesn't go much beyond that.

In an exploratory phase, it can be useful to have a more complete table, including minimal visualizations, to better understand the data. In the final phase of a project, when communicating about it, having an attractive visualization is advantageous. The outputs of notebooks are not a satisfactory solution for these needs and require the medium of the notebook, which can deter some users.

Fortunately, the young package `great_tables` allows for the creation of tables programmatically that rival tedious manual productions in `Excel` and are difficult to replicate. This package is a `Python` port of the `GT` package. `great_tables` builds *HTML* tables, offering great formatting richness and excellent integration with `Quarto`, the reproducible publishing tool developed by RStudio.

The following exercise will propose building a table with this package, step by step. It requires installing the `great_tables` package beforehand:

```
!pip install great_tables --quiet
```

To focus on table construction, the necessary data preparations are provided directly. We will start from the `emissions_merged` dataset, built in the previous chapter when computing the carbon footprint per capita, which looks like this:

To ensure you are able to complete the next exercise, here is the dataframe required for it.

```
emissions_totales_commune = emissions.sum(axis = 1, numeric_only = True)

emissions_merged = (
    emissions.assign(emissions = emissions_totales_commune)
    .reset_index()
    .merge(filosofi, left_on = "INSEE commune", right_on = "CODGEO")
)
emissions_merged = emissions_merged.loc[emissions_merged['POPULATION'] > 0]
emissions_merged['empreinte'] = emissions_merged['emissions']/emissions_merged['POPULATION']
emissions_merged['empreinte'] = emissions_merged['empreinte'].astype(float)
```

```
emissions_table = (
    emissions_merged
    .rename(columns={"dep_y": "dep", "POPULATION": "population", "NIVVIE_MEDIAN": "revenu"})
    .groupby("dep")
    .agg({"empreinte": "sum", "revenu": "median", "population": "sum"}) #pas vraiment le revenu
médian
    .reset_index()
    .sort_values(by = "empreinte")
)
```

In this table, we will include horizontal bars, similar to the examples shown here. This is done by directly including the *HTML* code in the DataFrame column.

```
def create_bar(prop_fill: float, max_width: int, height: int, color: str = "green") -> str:
    """Create divs to represent prop_fill as a bar."""
    width = round(max_width * prop_fill, 2)
    px_width = f"{width}px"
    return f"""\
    <div style="width: {max_width}px; background-color: lightgrey;">\
```

```
        <div style="height:{height}px;width:{px_width};background-color:{color};"></div>\
    </div>\
    """

colors = {'empreinte': "green", 'revenu': "red", 'population': "blue"}

for variable in ['empreinte', 'revenu', 'population']:
                    emissions_table[f'raw_perc_{variable}']     =     emissions_table[variable]/
emissions_table[variable].max()
    emissions_table[f'bar_{variable}'] = emissions_table[f'raw_perc_{variable}'].map(
        lambda x: create_bar(x, max_width=75, height=20, color = colors[variable])
    )
```

We keep only the 5 smallest carbon footprints and the five largest.

```
emissions_min    =    emissions_table.head(5).assign(grp    =    "5    départements    les    moins
pollueurs").reset_index(drop=True)
emissions_max    =    emissions_table.tail(5).assign(grp    =    "5    départements    les    plus
pollueurs").reset_index(drop=True)

emissions_table = pd.concat([
    emissions_min,
    emissions_max
])
```

Finally, to use some practical functions for selecting columns based on patterns, we will convert the data to the `Polars` format.

```
import polars as pl
emissions_table = pl.from_pandas(emissions_table)
```

Exercise 5: A Beautiful Descriptive Statistics Table (Open Exercise)

Using this base table

```
GT(emissions_table, groupname_col="grp", rowname_col="dep")
```

construct a table in the style of the one below.

```
# Start from here
GT(emissions_table, groupname_col="grp", rowname_col="dep")
```

	empreinte	revenu	population	raw_perc_empreinte	bar_empreinte	raw_perc_revenu	bar_revenu	raw_perc_population	bar_population
5 départements les moins pollueurs									
92	142.01712816633915	36310.0	1654712	0.007765288087866 1455		1.0		0.63262343569 51262	
93	147.99110273881 74	21820.0	1704316	0.008009195624646505		0.600956381162243		0.651587853391433	
94	196.38841922398835	27940.0	1426929	0.010738239078515274		0.769404991603 7821		0.545338272 7330075	
90	895.5849355392521	29170.0	140255	0.048964856376 70511		0.803359953958041		0.055621775267795228	
83	922.1320421556788	26130.0	1119307	0.050492199946136078		0.719636463784 0815		0.427929555866931	
5 départements les plus pollueurs									
52	1306.8455197474397	24610.0	168331	0.714564018012 5334		0.677747177086202		0.064 0556918 3809097	
55	1365.0749781392267	25340.0	180290	0.746420760037646		0.697879372073899		0.068927312940361 17	
51	1440.1866868462248	28180.0	563076	0.787478390 3581239		0.776 0894739741 1182		0.215273155667028 08	
21	1540.5 932865409246	27090.0	540100	0.842373791792529		0.746075461305 4255		0.206 8905523 89764	
77	1828.7 1338371 6273	28910.0	1468108	1.0		0.796 1993941063068		0.561281677298469	

The table you should have :

Carbon Footprint

Initial descriptive statistics, by deciles

	Footprint			Median Income			Population		
	Carbon Footprint	(%)*		Income	(%)*		Population	(%)*	
5 départements les moins pollueurs									
92	14.20	0.8%		36.3K	100.0%		1.65M	63.3%	
93	14.80	0.8%		21.8K	60.1%		1.70M	65.2%	
94	19.64	1.1%		27.9K	76.9%		1.43M	54.6%	
90	89.55	4.9%		29.2K	80.3%		140.25K	5.4%	
83	92.22	5.0%		26.1K	72.0%		1.12M	42.8%	
5 départements les plus pollueurs									
52	1,306.85	71.5%		24.6K	67.8%		168.33K	6.4%	
55	1,365.11	74.6%		25.3K	69.8%		180.29K	6.9%	
51	1,440.20	78.7%		28.2K	77.6%		563.08K	21.5%	
21	1,540.59	84.2%		27.1K	74.6%		540.10K	20.6%	
77	1,828.87	100.0%		28.9K	79.6%		1.47M	56.1%	

Note: The median income presented here is an approximation of the department's median income.

Reading: The (%) columns presented above are scaled to the maximum value of the variable

Source: Calculations based on Ademe data

Thanks to this, we can already understand that our definition of the carbon footprint is certainly flawed. It seems unlikely that the inhabitants of the 77th department have a carbon footprint 500 times greater than that of intra-muros Paris. The main reason? We are not dealing with a concept of consumption emissions but production emissions, which penalizes industrial areas or areas with airports...

To learn more about constructing tables with `great_tables`, you can replicate this exercise on producing electoral tables that I proposed for an `R` course with `gt`, the equivalent of `great_tables` for `R`.

We have now covered the main features of `Pandas` for manipulating and reshaping data. The last chapter of this part takes a step back to look at the limitations of `Pandas` syntax and discover the alternative ecosystems that exist to go further.

Informations additionnelles

ℹ Python environment

This site was built automatically through a `Github` action using the `Quarto` reproducible publishing software (version 1.10.18).

The environment used to obtain the results is reproducible via uv. The `pyproject.toml` file used to build this environment is available on the `linogaliana/python-datascientist` repository

```
[project]
name = "python-datascientist"
version = "0.1.0"
description = "Source code for Lino Galiana's Python for data science course"
readme = "README.md"
requires-python = "≥3.13,<3.14"
dependencies = [
    "altair≥6.0.0",
    "cartiflette≥0.2",
    "contextily==1.6.2",
    "duckdb≥0.10.1",
    "folium≥0.19.6",
    "gdal==3.11.4",
    "graphviz==0.20.3",
    "great-tables≥0.12.0",
    "gt-extras≥0.0.8",
    "ipykernel≥6.29.5",
    "jupyter≥1.1.1",
    "jupyter-cache≥1.0.0",
    "kaleido≥0.2.1",
    "langchain-community≥0.3.27",
    "loguru==0.7.3",
    "markdown≥3.8",
    "nbclient≥0.10.0",
    "nbformat≥5.10.4",
    "nltk≥3.9.1",
    "openpyxl≥3.1.5",
    "pandas≥3.0",
    "pip≥25.1.1",
    "plotly≥6.1.2",
    "plotnine≥0.15",
    "polars≥1.8.2",
    "py7zr≥1.1.3",
    "pyarrow≥17.0.0",
```

```
    "pynsee>=0.1.8",
    "python-dotenv>=1.0.1",
    "python-frontmatter>=1.1.0",
    "pywaffle>=1.1.1",
    "requests>=2.32.3",
    "scikit-image>=0.24.0",
    "scikit-learn>=1.8.0",
    "scipy>=1.13.0",
    "seaborn>=0.13.2",
    "selenium<4.39.0",
    "spacy>=3.8.4",
    "webdriver-manager>=4.0.2",
    "wordcloud==1.9.3",
]

[tool.uv.sources]
gdal = [
  { index = "gdal-wheels", marker = "sys_platform == 'linux'" },
  { index = "geospatial_wheels", marker = "sys_platform == 'win32'" },
]

[[tool.uv.index]]
name = "geospatial_wheels"
url = "https://nathanjmcdougall.github.io/geospatial-wheels-index/"
explicit = true

[[tool.uv.index]]
name = "gdal-wheels"
url = "https://gitlab.com/api/v4/projects/61637378/packages/pypi/simple"
explicit = true

[dependency-groups]
dev = [
    "nb-clean>=4.0.1",
]
```

To use exactly the same environment (version of `Python` and *packages*), please refer to the documentation for `uv`.

Bibliography